

Prooflane configuration audit

example-branch-02

Audit 6f33550d-8207-4a50-8bf3-2f0880c2a43c · 2026-09-28T11:47:50.803257+00:00

Device	example-branch-02
Vendor	ios
Firmware	16.12
Serial	Unavailable
Snapshot SHA-256	c72dc9abaf1e589a10d51b564cb8795850381b3289545d0de43e32c858d01f49
Policy	Baseline technical evidence baseline / team-v1

Team-authored technical checks with illustrative framework crosswalks. Not a CIS/STIG benchmark release, an ISO certification assessment, or full NIST control coverage. Import a reviewed policy for your exact benchmark edition.

SYNTHETIC EXAMPLE — this configuration was authored for testing.

Coverage

Evaluated 55.0% of applicable checks. Counts: {'pass': 2, 'fail': 9, 'insufficient_evidence': 9, 'not_applicable': 0}. Insufficient evidence is not a pass.

AC-01 — Disable Telnet management

FAIL | high severity | Observed: False | Expected: True

Source lines: [14]. All declared VTY blocks in a user-declared complete snapshot. Mapping: native-v1

Team technical baseline v1. Candidate NIST crosswalk: AC-17 / SC-8.

Proposed remediation — review required

```
line vty <review all configured ranges>
  transport input ssh
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

AC-02 — Disable plaintext HTTP management

FAIL | high severity | Observed: False | Expected: True

Source lines: [4]. Explicit configuration. Mapping: native-v1

Team technical baseline v1. Candidate NIST crosswalk: SC-8.

Proposed remediation — review required

```
no ip http server
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

AC-03 — Configure HTTPS management

INSUFFICIENT EVIDENCE | medium severity | Observed: None | Expected: True

Team technical baseline v1. Candidate NIST crosswalk: SC-8.

AC-04 — Require SSH protocol version 2

FAIL | high severity | Observed: 1 | Expected: 2
Source lines: [5]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: SC-13.

Proposed remediation — review required

```
ip ssh version 2
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

AC-05 — Bound SSH negotiation timeout

FAIL | medium severity | Observed: 120 | Expected: 60
Source lines: [6]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: AC-12.

Proposed remediation — review required

```
ip ssh time-out 60
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

AC-06 — Limit idle administrative sessions

FAIL | medium severity | Observed: 0 | Expected: 600
Source lines: [15]. All declared VTY blocks in a user-declared complete snapshot. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: AC-12.

Proposed remediation — review required

```
line vty <review all configured ranges>  
  exec-timeout 10 0
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

AC-07 — Limit authentication retries

FAIL | medium severity | Observed: 8 | Expected: 3
Source lines: [7]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: AC-7.

Proposed remediation — review required

```
ip ssh authentication-retries 3
```

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.

IA-01 — Enable explicit authentication configuration

INSUFFICIENT EVIDENCE | high severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: IA-2.

IA-02 — Use stronger local account secret formats

FAIL | high severity | Observed: False | Expected: True
Source lines: [8]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: IA-5.

AU-01 — Configure remote audit logging

PASS | high severity | Observed: True | Expected: True
Source lines: [9]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: AU-9.

AU-02 — Include timestamps in audit logs

INSUFFICIENT EVIDENCE | medium severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: AU-8.

AU-03 — Log successful administrative logins

INSUFFICIENT EVIDENCE | low severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: AU-2.

AU-04 — Log failed administrative logins

INSUFFICIENT EVIDENCE | medium severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: AU-2.

AU-05 — Configure a reference time server

PASS | medium severity | Observed: True | Expected: True
Source lines: [10]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: AU-8.

AU-06 — Enable NTP authentication mode

INSUFFICIENT EVIDENCE | medium severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: SC-45.

SC-01 — Define an SNMPv3 privacy group

INSUFFICIENT EVIDENCE | high severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: SC-8.

SC-02 — Remove legacy SNMP communities

FAIL | high severity | Observed: False | Expected: True
Source lines: [11]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: SC-8.

AC-08 — Provide an administrative login notice

INSUFFICIENT EVIDENCE | low severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: AC-8.

AC-09 — Bind an inbound VTY access list

INSUFFICIENT EVIDENCE | high severity | Observed: None | Expected: True
Team technical baseline v1. Candidate NIST crosswalk: AC-3 / SC-7.

SC-03 — Disable IPv4 source routing

FAIL | high severity | Observed: False | Expected: True
Source lines: [12]. Explicit configuration. Mapping: native-v1
Team technical baseline v1. Candidate NIST crosswalk: SC-7.

Proposed remediation — review required

no ip source-route

Configuration proposal only. Validate device/firmware syntax, management reachability and rollback in a lab before use.