


B.M.S. COLLEGE OF ENGINEERING
Basavanagudi, Bengaluru- 560019
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING



LAB REPORT
On
Analysis and Design of Algorithms
(23CS4PCADA)


Submitted By:

AJAY N M
1BM22CS026

In partial fulfilment of
BACHELOR OF ENGINEERING
In
COMPUTER SCIENCE AND ENGINEERING
2023-24

Faculty-In-Charge
Vikranth B.M.
Assistant Professor
Department of Computer Science and Engineering

B.M.S. COLLEGE OF ENGINEERING
Basavanagudi, Bengaluru- 560019
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING



CERTIFICATE

This is to certify that the Lab work entitled “Analysis and Design of Algorithms (23CS4PCADA)” conducted by **AJAY N M (1BM22CS026)**, who is bonafide student at **B.M.S.College of Engineering**. It is in partial fulfilment for the award of **Bachelor of Engineering in Computer Science and Engineering** during the academic year 2023-24. The Lab report has been approved as it satisfies the academic requirements in respect of a Analysis and Design of Algorithms (23CS4PCADA) work prescribed for the said degree.

Mr. VIKRANTH. B. M
Assistant Professor
Dept of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Prof & Head of Dept of
CSE
BMSCE, Bengaluru

INDEX

Sl. No.	Experiment Title	Page No.
1	Topological ordering of vertices in a given digraph.	1-3
2	Merge Sort technique	4-5
3	Quick Sort technique	6-7
4	Bottom-up Heap Sort technique	8
5	Knapsack problem	9-10
6	Floyd's algorithm	11-12
7	Prim's algorithm Kruskal's algorithm	13-17
8	Dijkstra's algorithm	18-19
9	Fractional Knapsack problem using Greedy technique	20-21
10	N-Queens Problem using Backtracking	22-23

1. Write program to obtain the Topological ordering of vertices in a given digraph.

//C program to implement topological sort using DFS

```
#include <stdio.h>
```

```
int n, a[10][10], res[10], s[10], top = 0;
```

```
void dfs(int, int, int[][10]);
```

```
void dfs_top(int, int[][10]);
```

```
int main()
```

```
{
```

```
printf("Enter the no. of nodes");
```

```
scanf("%d", &n);
```

```
int i, j;
```

```
for (i = 0; i < n; i++) {
```

```
for (j = 0; j < n; j++) {
```

```
scanf("%d", &a[i][j]);
```

```
}
```

```
}
```

```
dfs_top(n, a);
```

```
printf("Solution: ");
```

```
for (i = n - 1; i >= 0; i--) {
```

```
printf("%d ", res[i]);
```

```
}
```

```
return 0;
```

```
}
```

```
void dfs_top(int n, int a[][10]) {
```

```
int i;
```

```
for (i = 0; i < n; i++) {
```

```
s[i] = 0;
```

```
}
```

```
for (i = 0; i < n; i++) {
```

```
if (s[i] == 0) {
```

```
dfs(i, n, a);
```

```
}
```

```
}
```

```
}
```

```
void dfs(int j, int n, int a[][10]) {
```

```
s[j] = 1;
```

```
1
```

```
int i;
```

```
for (i = 0; i < n; i++) {
```

```
if (a[j][i] == 1 && s[i] == 0) {
```

```
dfs(i, n, a);
```

```
}
```

```
}
```

```
res[top++] = j;
```

```
}
```

OUTPUT:

Enter the no. of nodes6

0 0 1 1 0 0

0 0 0 1 1 0

0 0 0 1 0 1

0 0 0 0 0 1

0 0 0 0 0 1

0 0 0 0 0 0

Solution: 1 4 0 2 3 5

//C program to implement topological sort using source removal method

```
#include<stdio.h>
```

```
int a[10][10],n,t[10],indegree[10];
```

```
int stack[10],top=-1;
```

```
void computeIndegree(int,int[][10]);
```

```
void tps_SourceRemoval(int,int[][10]);
```

```
int main(){
```

```
printf("Enter the no. of nodes: ");
```

```
scanf("%d",&n);
```

```
int i,j;
```

```
for(i=0;i<n;i++){
```

```
for(j=0;j<n;j++){
```

```
scanf("%d",&a[i][j]);
```

```
}
```

```
}
```

```
computeIndegree(n,a);
```

```
tps_SourceRemoval(n,a);
```

```
printf("Solution:");
```

```
for(i=0;i<n;i++){
```

```
printf("%d ",t[i]);
```

```
}
```

```
return 0;
```

```
2
```

```
}
```

```
3
```

```
void computeIndegree(int n,int a[][10]){
```

```
int i,j,sum=0;
```

```
for(i=0;i<n;i++){
```

```
sum=0;
```

```
for(j=0;j<n;j++){
```

```
sum=sum+a[j][i];
```

```
}
```

```
indegree[i]=sum;
```

```
}
```

```
}
```

```
void tps_SourceRemoval(int n,int a[][10]){
```

```
int i,j,v;
```

```

for(i=0;i<n;i++){
    if(indegree[i]==0){
        stack[++top]=i;
    }
}
int k=0;
while(top!=-1){
    v=stack[top--];
    t[k++]=v;
    for(i=0;i<n;i++){
        if(a[v][i]!=0){
            indegree[i]=indegree[i]-1;
            if(indegree[i]==0){
                stack[++top]=i;
            }
        }
    }
}
}
}

```

OUTPUT:

Enter the no. of nodes: 5

0 0 1 0 0

1 0 0 1 0

0 0 0 0 1

0 0 1 0 1

0 0 0 0 0

Solution:1 3 0 2 4

2. Sort a given set of N integer elements using Merge Sort technique and compute its time taken. Run the program for different values of N and record the time taken to sort.

```
//C program to implement merge sort
#include <stdio.h>
#include<time.h>
int a[20],n;
void simple_sort(int [],int,int,int);
void merge_sort(int[],int,int);
int main()
{
}
int i;
clock_t start, end;
double time_taken;
printf("Enter the no. of elements:");
scanf("%d", &n);
printf("Enter the array elements:");
for (i = 0; i < n; i++) {
scanf("%d", &a[i]);
}
start = clock();
merge_sort(a, 0, n - 1);
end = clock();
time_taken = (double)(end - start) / CLOCKS_PER_SEC;
printf("Sorted array:");
for (i = 0; i < n; i++) {
printf("%d ", a[i]);
}
printf("\n");
printf("Time taken to sort: %f seconds\n", time_taken);
return 0;
void merge_sort(int a[],int low, int high){
if(low<high){
6
int mid=(low+high)/2;
merge_sort(a,low,mid);
merge_sort(a,mid+1,high);
simple_sort(a,low,mid,high);
}
}
void simple_sort(int a[],int low, int mid, int high){
int i=low,j=mid+1,k=low;
int c[n];
while(i<=mid && j<=high){
if(a[i]<a[j]){
c[k++]=a[i];
```

```
i++;  
}else{  
c[k++]=a[j];  
j++;  
}  
}  
while(i<=mid){  
c[k++]=a[i];  
i++;  
}  
while(j<=high){  
c[k++]=a[j];  
j++;  
}  
for(i=low;i<=high;i++){  
a[i]=c[i];  
}  
}
```

OUTPUT:

Enter the no. of elements:10

Enter the array elements:8 96 32 75 62 78 63 48 56 100

Sorted array:8 32 48 56 62 63 75 78 96 100

Time taken to sort: 0.000002 seconds

3. Sort a given set of N integer elements using Quick Sort technique and compute its time taken.

```
//C program to implement quick sort
#include <stdio.h>
#include<time.h>
int a[20],n;
int partition(int [],int, int);
void quick_sort(int [],int,int);
void swap(int*,int*);
int main()
{
    int i;
    clock_t start, end;
    double time_taken;
    printf("Enter the no. of elements:");
    scanf("%d", &n);
    printf("Enter the array elements:");
    for (i = 0; i < n; i++) {
        scanf("%d", &a[i]);
    }
    start = clock();
    quick_sort(a, 0, n - 1);
    end = clock();
    time_taken = (double)(end - start) / CLOCKS_PER_SEC;
    printf("Sorted array:");
    for (i = 0; i < n; i++) {
        printf("%d ", a[i]);
    }
    printf("\n");
    printf("Time taken to sort: %f seconds\n", time_taken);
    return 0;
}
void swap(int *a,int *b){
    int temp=*a;
    *a=*b;
    *b=temp;
}
void quick_sort(int a[],int low,int high){
    if(low<high){
        int mid=partition(a,low,high);
        quick_sort(a,low,mid-1);
        quick_sort(a,mid+1,high);
    }
}
int partition(int a[],int low,int high){
    int pivot=a[low];
```

```
int i=low;
int j=high+1;
while(i<=j){
do{
i=i+1;
}while(a[i]<pivot && i<=high);
do{
j=j-1;
}while(a[j]>pivot && j>=low);
if(i<j){
swap(&a[i],&a[j]);
}
}
swap(&a[j],&a[low]);
return j;
}
```

OUTPUT:

Enter the no. of elements:10

Enter the array elements:96 53 26 78 12 63 85 12 06 95

Sorted array:6 12 12 26 53 63 78 85 95 96

Time taken to sort: 0.000002 seconds

4. Sort a given set of N integer elements using Heap Sort technique and compute its time taken.

```
//C program to implement heapify
#include<stdio.h>
int a[10],n;
void heapify(int[],int);
int main() {
printf("Enter the number of array elements:");
scanf("%d",&n);
int i;
printf("Enter array elements:");
for(i=0;i<n;i++){
scanf("%d",&a[i]);
}
heapify(a,n);
printf("Array elements:");
for(i=0;i<n;i++){
printf(" %d",a[i]);
}
return 0;
}
void heapify(int a[],int n){
int k;
for(k=1;k<n;k++){
int key=a[k];
int c=k;
int p=(c-1)/2;
while(c>0 && key>a[p]){
a[c]=a[p];
c=p;
p=(c-1)/2;
}
a[c]=key;
}
}
```

OUTPUT:

```
Enter the number of array elements:7
Enter array elements:50 25 30 75 100 45 80
Array elements: 100 75 80 25 50 30 45
```

5. Implement 0/1 Knapsack problem using dynamic programming.
//C program to implement knapsack problem in dynamic programming

```
#include <stdio.h>
int n,m,w[10],p[10],v[10][10];
void knapsack(int,int,int[],int[]);
int max(int,int);
int main()
{
    int i,j;
    printf("Enter the no. of items:");
    scanf("%d",&n);
    printf("Enter the capacity of knapsack:");
    scanf("%d",&m);
    printf("Enter weights:");
    for(i=0;i<n;i++){
        scanf("%d",&w[i]);
    }
    printf("Enter profits:");
    for(i=0;i<n;i++){
        scanf("%d",&p[i]);
    }
    knapsack(n,m,w,p);
    printf("Optimal Solution:\n");
    for(i=0;i<n;i++){
        for(j=0;j<m;j++){
            printf("%d ",v[i][j]);
        }
        printf("\n");
    }
    return 0;
}
void knapsack(int n, int m, int w[],int p[]){
    int i,j;
    for(i=0;i<n;i++){
        for(j=0;j<m;j++){
            if(i==0 || j==0){
                v[i][j]=0;
            }else if(w[i]>j){
                v[i][j]=v[i-1][j];
            }else{
                v[i][j]=max(v[i-1][j],((v[i-1][j]-w[i])+p[i]));
            }
        }
    }
}
int max(int a,int b){
```

```
if(a>b){  
return a;  
}else{  
return b;  
}  
}
```

OUTPUT:

Enter the no. of items:4

Enter the capacity of knapsack:5

Enter weights:2 1 3 2

Enter profits:12 10 20 15

Optimal Solution:

0 0 0 0

0 10 10 10

0 10 10 20

0 10 15 25

6. Implement All Pair Shortest paths problem using Floyd's algorithm.

```
//C program to implement floyd's algorithm
#include <stdio.h>
int a[10][10],D[10][10],n;
void floyd(int a[][10],int);
int min(int,int);
int main()
{
printf("Enter the no. of vertices:");
scanf("%d",&n);
printf("Enter the cost adjacency matrix:\n");
int i,j;
for(i=0;i<n;i++){
for(j=0;j<n;j++){
scanf("%d",&a[i][j]);
}
}
floyd(a,n);
printf("Distance Matrix:\n");
for(i=0;i<n;i++){
for(j=0;j<n;j++){
printf("%d ",D[i][j]);
}
printf("\n");
}
return 0;
}
void floyd(int a[][10],int n){
int i,j,k;
for(i=0;i<n;i++){
for(j=0;j<n;j++){
D[i][j]=a[i][j];
}
}
for(k=0;k<n;k++){
for(i=0;i<n;i++){
for(j=0;j<n;j++){
D[i][j]=min(D[i][j],(D[i][k]+D[k][j]));
}
}
}
13
}
14

}
```

```
int min(int a,int b){  
    if(a<b){  
        return a;  
    }else{  
        return b;  
    }  
}
```

OUTPUT:

Enter the no. of vertices:4

Enter the cost adjacency matrix:

0 99 3 99

2 0 99 99

99 6 0 1

7 99 99 0

Distance Matrix:

0 9 3 4

2 0 5 6

8 6 0 1

7 16 10 0

7. A. Find Minimum Cost Spanning Tree of a given undirected graph using Prim's algorithm.

```
//C program to implement prim's algorithm
#include <stdio.h>

int cost[10][10], n, t[10][2], sum;

void prims(int cost[10][10], int n);

int main() {
    int i, j;

    printf("Enter the number of vertices: ");
    scanf("%d", &n);

    printf("Enter the cost adjacency matrix:\n");
    for (i = 0; i < n; i++) {
        for (j = 0; j < n; j++) {
            scanf("%d", &cost[i][j]);
        }
    }

    prims(cost, n);

    printf("Edges of the minimal spanning tree:\n");
    for (i = 0; i < n - 1; i++) {
        printf("(%d, %d) ", t[i][0], t[i][1]);
    }
    printf("\nSum of minimal spanning tree: %d\n", sum);

    return 0;
}

void prims(int cost[10][10], int n) {
    int i, j, u, v;
    int min, source;
    int p[10], d[10], s[10];

    min = 999;
    source = 0;

    // Initialize arrays
    for (i = 0; i < n; i++) {
16
        d[i] = cost[source][i];
        s[i] = 0;
```



```

    p[i] = source;
}

s[source] = 1;
sum = 0;
int k = 0;

// Find MST
for (i = 0; i < n - 1; i++) {
    min = 999;
    u = -1;

    // Find the vertex with minimum distance to the MST
    for (j = 0; j < n; j++) {
        if (s[j] == 0 && d[j] < min) {
            min = d[j];
            u = j;
        }
    }

    if (u != -1) {
        // Add edge to MST
        t[k][0] = u;
        t[k][1] = p[u];
        k++;
        sum += cost[u][p[u]];
        s[u] = 1;

        // Update distances
        for (v = 0; v < n; v++) {
            if (s[v] == 0 && cost[u][v] < d[v]) {
                d[v] = cost[u][v];
                p[v] = u;
            }
        }
    }
}
}

```

OUTPUT:

Enter the number of vertices: 4

Enter the cost adjacency matrix:

17

0 1 5 2

1 0 99 99

5 99 0 3

2 99 3 0

Edges of the minimal spanning tree:

(1, 0) (3, 0) (2, 3)

Sum of minimal spanning tree: 6

B. Find Minimum Cost Spanning Tree of a given undirected graph using Kruskal's algorithm.

```
//C program to implement Kruskal's algorithm
#include <stdio.h>

int cost[10][10], n, t[10][2], sum;

void kruskal(int cost[10][10], int n);
int find(int parent[10], int i);

int main() {
    int i, j;

    printf("Enter the number of vertices: ");
    scanf("%d", &n);

    printf("Enter the cost adjacency matrix:\n");
    for (i = 0; i < n; i++) {
        for (j = 0; j < n; j++) {
            scanf("%d", &cost[i][j]);
        }
    }

    kruskal(cost, n);

    printf("Edges of the minimal spanning tree:\n");
    for (i = 0; i < n - 1; i++) {
        printf("(%d, %d) ", t[i][0], t[i][1]);
    }
    printf("\nSum of minimal spanning tree: %d\n", sum);

    return 0;
}

void kruskal(int cost[10][10], int n) {
    18

    int min, u, v, count, k;
    int parent[10];

    k = 0;
    sum = 0;

    // Initialize parent array for Union-Find
    for (int i = 0; i < n; i++) {
```

```

    parent[i] = i;
}

count = 0;
while (count < n - 1) {
    min = 999;
    u = -1;
    v = -1;

    // Find the minimum edge
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (find(parent, i) != find(parent, j) && cost[i][j] < min) {
                min = cost[i][j];
                u = i;
                v = j;
            }
        }
    }

    // Perform Union operation
    int root_u = find(parent, u);
    int root_v = find(parent, v);

    if (root_u != root_v) {
        parent[root_u] = root_v;
        t[k][0] = u;
        t[k][1] = v;
        sum += min;
        k++;
        count++;
    }
}

int find(int parent[10], int i) {
19
    while (parent[i] != i) {
        i = parent[i];
    }
    return i;
}

```

OUTPUT:

Enter the number of vertices: 4

Enter the cost adjacency matrix:

0 1 5 2

1 0 99 99

5 99 0 3

2 99 3 0

Edges of the minimal spanning tree:

(1, 0) (3, 0) (2, 3)

Sum of minimal spanning tree: 6

8. From a given vertex in a weighted connected graph, find shortest paths to other vertices using Dijkstra's algorithm.

```
// C program to implement Dijkstra's algorithm
#include <stdio.h>
int cost[10][10], n, result[10][2], weight[10];
void dijkstras(int[][10], int );
int main()
{
    int i, j, s;
    printf("Enter the number of vertices: ");
    scanf("%d", &n);
    printf("Enter the cost adjacency matrix:\n");
    for (i = 0; i < n; i++) {
        for (j = 0; j < n; j++) {
            scanf("%d", &cost[i][j]);
        }
    }
    printf("Enter the source vertex: ");
    scanf("%d", &s);
    dijkstras(cost, s);
    printf("Path:\n");
    for (i = 1; i < n; i++) {
        printf("(%d, %d) with weight %d ", result[i][0], result[i][1], weight[result[i][1]]);
    }
    return 0;
}

void dijkstras(int cost[][10], int s){
    int d[10], p[10], visited[10];
    int i, j, min, u, v, k;
    for(i = 0; i < 10; i++){
        d[i] = 999;
        visited[i] = 0;
        p[i] = s;
    }
    d[s] = 0;
    visited[s] = 1;
    for(i = 0; i < n; i++){
22
23
        min = 999;
        u = 0;
        for(j = 0; j < n; j++){
            if(visited[j] == 0){
                if(d[j] < min){
                    min = d[j];
                    u = j;
                }
            }
        }
    }
```

```

        }
    }
}
visited[u] = 1;

for(v = 0; v < n; v++){
    if(visited[v] == 0 && (d[u] + cost[u][v] < d[v])){
        d[v] = d[u] + cost[u][v];
        p[v] = u;
    }
}
}
for(i = 0; i < n; i++){
    result[i][0] = p[i];
    result[i][1] = i;
    weight[i] = d[i];
}
}

```

OUTPUT:

Enter the number of vertices: 4

Enter the cost adjacency matrix:

0 1 5 2

1 0 99 99

5 99 0 3

2 99 3 0

Enter the source vertex: 0

Path:

(0, 1) with weight 1 (0, 2) with weight 5 (0, 3) with weight 2

9. Implement fractional Knapsack problem using Greedy technique.

```
#include <stdio.h>
void knapsack(int n, int p[], int w[], int W) {
    int used[n];
    for (int i = 0; i < n; ++i)
        used[i] = 0;
    int cur_w = W;
    float tot_v = 0.0;
    int i, maxi;
    while (cur_w > 0) {
        maxi = -1;
        for (i = 0; i < n; ++i)
            if ((used[i] == 0) &&
                ((maxi == -1) || ((float)w[i]/p[i] > (float)w[maxi]/p[maxi])))
                maxi = i;
        used[maxi] = 1;
        if (w[maxi] <= cur_w) {
            cur_w -= w[maxi];
            tot_v += p[maxi];
            printf("Added object %d (%d, %d) completely in the bag. Space left: %d.\n", maxi + 1,
                w[maxi], p[maxi], cur_w);
        } else {
            int taken = cur_w;
            cur_w = 0;
            tot_v += (float)taken/p[maxi] * p[maxi];
            printf("Added %d%% (%d, %d) of object %d in the bag.\n", (int)((float)taken/w[maxi] *
                100), w[maxi], p[maxi], maxi + 1);
        }
    }
    printf("Filled the bag with objects worth %.2f.\n", tot_v);
}

int main() {
    int n, W;
    printf("Enter the number of objects: ");
    scanf("%d", &n);
    int p[n], w[n];
    printf("Enter the profits of the objects: ");
    for(int i = 0; i < n; i++){
        scanf("%d", &p[i]);
    }
    printf("Enter the weights of the objects: ");
    for(int i = 0; i < n; i++){
        scanf("%d", &w[i]);
    }
    printf("Enter the maximum weight of the bag: ");
    scanf("%d", &W);
}
```

```
knapsack(n, p, w, W);  
return 0;  
}
```

OUTPUT:

Enter the number of objects: 7

Enter the profits of the objects: 5 10 15 7 8 9 4

Enter the weights of the objects: 1 3 5 4 1 3 2

Enter the maximum weight of the bag: 15

Added object 4 (4, 7) completely in the bag. Space left: 11.

Added object 7 (2, 4) completely in the bag. Space left: 9.

Added object 3 (5, 15) completely in the bag. Space left: 4.

Added object 6 (3, 9) completely in the bag. Space left: 1.

Added 33% (3, 10) of object 2 in the bag.

Filled the bag with objects worth 36.00.

10. Implement “N-Queens Problem” using Backtracking.

```
#include <stdio.h>
#include <stdbool.h>
bool place(int[], int);
void printSolution(int[], int);
void nQueens(int);
int main()
{
    int n;
    printf("Enter the number of queens: ");
    scanf("%d",&n);
    nQueens(n);
    return 0;
}
void nQueens(int n){
    int x[10];
    int count=0;
    int k=1;
    while(k!=0){
        x[k]=x[k]+1;
        while(x[k]<=n && !place(x,k)){
            x[k]=x[k]+1;
        }
        if(x[k]<=n){
            if(k==n){
                printSolution(x, n);
                printf("Solution found\n");
                count++;
            }else{
                k++;
                x[k]=0;
            }
        }else{
            k--;
        }
    }
    printf("Total solutions: %d\n", count);
}
bool place(int x[10], int k){
    int i;
    for(i=1;i<k;i++){
        if((x[i]==x[k])||(i-x[i]==k-x[k])||(i+x[i]==k+x[k])){
        }
    }
    return false;
    return true;
}
```

```
}  
void printSolution(int x[10], int n){  
    int i;  
    for(i=1;i<=n;i++){  
        printf("%d ", x[i]);  
    }  
    printf("\n");  
}
```

OUTPUT:

Enter the number of queens: 4

2 4 1 3

Solution found

3 1 4 2

Solution found

Total solutions: 2