1945. Sum of Digits of String After Convert

**Problem Description** 

Simulation

String

Easy

# In this problem, you have a string s that is composed of lowercase English letters, and an integer k. You are required to perform

a series of transformations on the string to convert it into an integer using a specific set of rules, and then reduce it further by a process of digit summation. This reduction process is to be repeated k times. Here is what you need to do step by step:

Convert the string s into an integer by substituting each letter with its corresponding position in the English alphabet, where

- 'a' is replaced by 1, 'b' by 2, and so on until 'z' which is replaced by 26. **Transform** the resulting integer by summing its digits to create a new, smaller integer.
- Repeat the **transform** operation a total of k times.
- Your goal is to return the final integer after all the transformations are complete. For example, given the string s = "zbax" and k = 2, the process would look like this:

• Convert: "zbax" becomes "262124" because 'z'=26, 'b'=2, 'a'=1, and 'x'=24.

- Transform #1: 262124 becomes 17 since 2+6+2+1+2+4 = 17. • **Transform #2**: 17 becomes 8 since 1+7 = 8.
- At the end of these operations, you would return the integer 8.

# First, understand that each letter corresponds to a numeric value based on its position in the alphabet.

Intuition

value and then subtracting the ASCII value of the character 'a'. This will give a number between 0 and 25, to which we then add 1 to get the correct position in the alphabet (1-26).

each character back to an integer, and summing them.

**String to Integer Conversion:** 

The solution approach breaks down as follows:

As we convert the characters, concatenate their corresponding numeric strings to form a new string which represents the large integer.

Repeat Transformation:

**String to Integer Conversion:** 

**Sum of Digits Transformation:** 

- **Sum of Digits Transformation:** Now, we need to transform the integer by summing its digits. We do this by iterating over the string representation of the integer, converting
- The summation transformation is repeated k times as specified by the problem. Each time, the result of the previous transformation is used as the input for the next.

• The solution starts with an iteration over the input string s using a generator expression. It performs the conversion of each letter in the

Each mapped integer is converted to a string and joined together without delimiters to form the large integer as a string, which is assigned

The solution is implemented in Python with a straightforward approach. Let's dive deep into the algorithm, step by step:

• Iterate over each character in the string and convert it to the respective numeric value by using the built-in ord() function to get the ASCII

**Solution Approach** 

This sum is then converted back into a string so that we can repeat the process.

string to its corresponding position in the alphabet. • To achieve this, the ord() function is used, which takes a character and returns its ASCII encoding. Since ord('a') returns 97 (the ASCII value of 'a'), to map 'a' to 1, 'b' to 2, ..., 'z' to 26, we subtract ord('a') - 1 from ord(c), where c is the current character in the string.

## A loop is utilized to perform the transformation k times. Inside the loop, a temporary variable t is employed to accumulate the sum of digits

integers.

back to s.

of s. • The summation uses a list comprehension that iterates through each character in the string s, converts it to an integer, and sums all these

After the summation, s is updated to the string representation of t, preparing it for the next iteration (if any).

• The loop ensures that the sum of digits transformation is done k times as per the problem requirements.

return it as an integer.

an integer using int() and returned as the result.

Let's go through an example to illustrate the solution approach.

then reduce it k times by digit summation.

**Sum of Digits Transformation:** 

so we set s to "6" again.

**Repeat Transformation:** 

**Return the Result:** 

Solution Implementation

for in range(k):

Java

class Solution {

return int(numeric\_string)

public int getLucky(String s. int k) {

# where 'a' = 1, 'b' = 2, ... 'z' = 26.

# Repeat the transformation process k times.

numeric\_string = str(sum\_of\_digits)

# Return the final integer after k transformations.

numericalRepresentation.append(c - 'a' + 1);

s = numericalRepresentation.toString();

// Perform transformation k times

s = String.valueOf(sum);

the result.

After conversion, the string s becomes "123".

**Return the Result:** 

Repeat Transformation:

The entire implementation doesn't require any complex data structures or algorithms as it is a straightforward computational process. The use of Python's built-in functions like sum(), ord(), and comprehensions makes the code concise and efficient. The algorithm has a time complexity of O(nk), where n is the length of the input string, because it iterates over the string to

convert it to a numeric form, and then over the digits k times to compute the sum. The space complexity is O(n) due to holding

After the loop completes k iterations, s will have been transformed into a string representation of the final integer, at which point we can

o The loop naturally ends after the k iterations, and then the final string s, which is now representative of the last digit sum, is converted into

the numeric representation of the string as well as the intermediate sums during the transformation process. **Example Walkthrough** 

**Transform #1**: We sum the digits: 1 + 2 + 3 = 6. We then set s to "6" (the sum of the digits).

**Transform #3**: Again, we sum the digits: 6. Since s is already "6", it remains unchanged.

String to Integer Conversion: First, we convert each character of s into its corresponding position in the alphabet. • 'a' becomes "1" since 'a' is the first letter of the alphabet. ∘ 'b' becomes "2" since 'b' is the second letter. ∘ 'c' becomes "3" since 'c' is the third letter.

Transform #2: We sum the digits: 6 (since s is just "6" at this point). Nothing changes because s only contains one digit,

Assume we are given the string s = "abc" and k = 3. Our task is to transform s into an integer following the given rules and

We were required to perform the digit sum transformation a total of k (3) times, and now we have completed this process.

Now we start the process of summing the digits of the string "123".

representation into a single digit representing the sum of its parts, repeated k times.

numeric\_string = ''.join(str(ord(char) - ord('a') + 1) for char in s)

sum of digits = sum(int(digit) for digit in numeric string)

# Convert the sum back to string for the next iteration.

# Calculate the sum of digits in the numeric string.

**Python** class Solution: def getLucky(self, s: str, k: int) -> int: # Convert the string into its corresponding numerical string representation

After completing the k transformations, the final value of s is "6". We convert this string to an integer using int() and return

The returned integer after all transformations is 6. The process correctly reduces the initial string "abc" through an integer

// StringBuilder to create the initial numerical string representation StringBuilder numericalRepresentation = new StringBuilder(); // Convert each character in the string to its corresponding numerical value ('a' -> 1, 'b' -> 2, etc.) for (char c : s.toCharArray()) {

// Function to convert a string into a "lucky" number based on the specified rules and transformations.

// Append the numerical string equivalent of character to the StringBuilder

// Store the numerical string representation to s for further manipulation

// Convert the calculated sum back to string for the next iteration

// Convert the final string back to an integer and return it as the "lucky" number

int sum = 0; // Initialize sum to accumulate the digits

\* Converts a string into a transformed integer by a specific process.

\* @returns {number} - The resulting integer after k transformations.

let sum = 0; // Initialize the sum for this iteration.

// Convert the sum back to string for the next iteration.

for (const digit of numericRepresentation) {

// Calculate the sum of the digits in the numeric representation.

// Initialize an empty string to store the numeric representation.

\* @param  $\{number\}$  k - The number of transformations to perform.

function getLucky(s: string, k: number): number {

// Perform the transformation k times.

sum += Number(digit);

numericRepresentation = `\${sum}`;

def getLuckv(self, s: str, k: int) -> int:

for in range(k):

return int(numeric\_string)

**Time and Space Complexity** 

# where a' = 1, b' = 2, ... z' = 26.

# Repeat the transformation process k times.

numeric\_string = str(sum\_of\_digits)

# Return the final integer after k transformations.

let numericRepresentation = '';

for (const character of s) {

for (let i = 0; i < k; i++) {

\* @param {string} s - The input string consisting of lowercase English letters.

// Convert each character to its alphabetic position and concatenate to numericRepresentation.

numericRepresentation += character.charCodeAt(0) - 'a'.charCodeAt(0) + 1;

# Convert the string into its corresponding numerical string representation

numeric\_string = ''.join(str(ord(char) - ord('a') + 1) for char in s)

sum of digits = sum(int(digit) for digit in numeric string)

# Convert the sum back to string for the next iteration.

# Calculate the sum of digits in the numeric string.

### // Sum the digits of the string for (char c : s.toCharArray()) { sum += c - '0'; // Convert char digit to integer and add to sum

while (k-- > 0) {

return Integer.parseInt(s); C++ class Solution { public: // Converts a string s to its "transformed" value as per the problem statement // and performs the transformation k times. int getLucky(string s, int k) { string transformed; // Holds the numeric representation of the string 's' // Convert each character in string 's' to its corresponding number // 'a' -> 1, 'b' -> 2, ..., 'z' -> 26 for (char c : s) { transformed += to\_string(c - 'a' + 1); // Perform k transformations while (k--) { int sumDigits = 0; // Placeholder for the sum of digits // Calculate the sum of the digits in the transformed string for (char digitChar : transformed) { sumDigits += digitChar - '0'; // Convert char to int and add to sum // Update the transformed string to the new value transformed = to\_string(sumDigits); // Finally, convert the transformed string to an integer and return it return stoi(transformed); **}**;

### // Convert the final numeric representation to a number and return. return Number(numericRepresentation);

class Solution:

**TypeScript** 

where n is the length of the input string s. The concatenation of the string representations of these numerical values in the worst case can create a string of length

The time complexity of the function involves several parts:

Repeatedly summing the digits for k times. In each iteration, the length of the string s decreases roughly by a factor of 9 since we are summing the digits (except the first iteration which will operate on the concatenated string). Therefore, each

**Space Complexity** 

2n.

'26').

**Time Complexity** 

- Combining these, the total time complexity is 0(n + k \* m).
  - The space complexity is primarily affected by: The space required to store the numerical string equivalent to the input string which could be 0(n) in the worst case.
  - the first transformation.
- Since m is at most 2n, and the numerical string is overwritten in each iteration with a potentially shorter one, the total space
  - complexity is O(n). **Note**: The value of n here refers to the length of the initial input string, and the value of m is dynamic but starts off as at most

The space required to store the intermediate sum results, which is O(m) where m is the length of the numerical string after

Converting each character in the string s to its corresponding numerical value and then to a string. This takes O(n) time

0(n) because each character in the string s can at most add 2 digits to the new string ('z' being the 26th letter results in

subsequent summing operation will potentially work on a shorter string. The overall time for the summing part can be

approximated by 0(k \* m) where m represents the length of the numerical string after the first transformation.