1665. Minimum Initial Energy to Finish Tasks

Description

```
You are given an array tasks where tasks[i] = [actual i, minimum i]:
```

- actual i is the actual amount of energy you spend to finish the i th task.
- minimum i is the minimum amount of energy you require to begin the i th task.

For example, if the task is [10, 12] and your current energy is 11, you cannot start this task. However, if your current energy is 13, you can complete this task, and your energy will be 3 after finishing it.

You can finish the tasks in any order you like.

Return the minimum initial amount of energy you will need to finish all the tasks.

Example 1:

```
Input: tasks = [[1,2],[2,4],[4,8]]
Output: 8
Explanation:
Starting with 8 energy, we finish the tasks in the following order:
    - 3rd task. Now energy = 8 - 4 = 4.
    - 2nd task. Now energy = 4 - 2 = 2.
    - 1st task. Now energy = 2 - 1 = 1.
Notice that even though we have leftover energy, starting with 7 energy does not work because we cannot do the 3rd task.
```

Example 2:

```
Input: tasks = [[1,3],[2,4],[10,11],[10,12],[8,9]]
Output: 32
Explanation:
Starting with 32 energy, we finish the tasks in the following order:
    - 1st task. Now energy = 32 - 1 = 31.
    - 2nd task. Now energy = 31 - 2 = 29.
    - 3rd task. Now energy = 29 - 10 = 19.
    - 4th task. Now energy = 19 - 10 = 9.
    - 5th task. Now energy = 9 - 8 = 1.
```

Example 3:

```
Input: tasks = [[1,7],[2,8],[3,9],[4,10],[5,11],[6,12]]
Output: 27
Explanation:
Starting with 27 energy, we finish the tasks in the following order:
    - 5th task. Now energy = 27 - 5 = 22.
    - 2nd task. Now energy = 22 - 2 = 20.
    - 3rd task. Now energy = 20 - 3 = 17.
    - 1st task. Now energy = 17 - 1 = 16.
    - 4th task. Now energy = 16 - 4 = 12.
    - 6th task. Now energy = 12 - 6 = 6.
```

Constraints:

- 1 <= tasks.length <= 10 ⁵
- 1 <= actual $_i$ <= minimum $_i$ <= 10 4