The problem requires us to write a function that takes two non-negative integer numbers as strings, num1 and num2, and returns their

Problem Description

BigInteger, and we are not allowed to directly convert the input strings into integers. This is a common requirement when the numbers involved can exceed the typical integer limits of the programming language, which might lead to overflow issues.

sum, also as a string. We must achieve this without using any built-in library functions for handling large numbers, such as

Intuition To solve this problem, we need to mimic the way we perform addition by hand. We usually start adding the digits from the rightmost

side (the least significant digit) and carry over any overflow to the next digit to the left. This process is repeated until all digits are

into a string.

processed.

For the implementation: 1. We initialize pointers for both input strings at their respective ends (rightmost digits). We also initialize a variable c to keep track of the carryover during addition.

3. We iterate through both strings from right to left, digit by digit, adding corresponding digits along with any carryover from the

previous step.

- 4. If one string is shorter and we run out of digits, we simply treat the missing digits as 0. 5. As we add digits, we calculate both the digit that should be in the current position (v) and the new carryover (c) for the next
- position to the left. 6. We append the result of the current single-digit addition to an answer list.

7. After processing all digits (including the final carryover if it exists), we have our answer in reverse. We reverse it and join the list

- 8. That string is then returned as the result. With this approach, we can handle the addition of numbers of any size, as long as they fit into the computer's memory as strings.
- Solution Approach
- The implementation of the solution involves a few crucial steps and uses basic data structures like lists and strings. Here's a

indices will be used to traverse the strings from right to left.

7. Appending the Result: We append the value v as a string to our ans list.

breakdown of the approach: 1. Initialize Indices: We start by initializing two indices, i and j, to point to the last characters of num1 and num2 respectively. These

2. Result List: An empty list ans is created to store the digits of the result as we calculate them.

3. Carry Variable: A variable c is initialized to 0. This variable will be responsible for holding the carry that may come from the addition of two digits that sum more than 9.

4. Iterating Backwards: Using a while loop, we iterate over the digits of the numbers from right to left. This loop continues until both indices i and j have traversed all the digits in their respective strings and there is no carry leftover.

5. Adding Digits: Inside the loop, we add corresponding digits from num1 and num2. If one of the strings has been fully traversed

- (i.e., the index is less than 0), we treat the missing digit as 0. 6. Handling Carry and Value: We calculate both the carry and the value of the current digit we are processing using divmod.
- 8. **Updates**: We decrement both indices i and j by 1 to move to the next digits on the left. 9. Finalizing the Result: After processing all digits and the carry, we join the reversed ans list into a string and return it.

divmod(a + b + c, 10) gives us the carry for the next addition, and the digit to append to our result in this position.

overflow issues associated with large integer values. Example Walkthrough

By iterating in reverse and using a simple carry system, this algorithm efficiently mimics manual addition, avoiding any potential

1. Initialize Indices: Initialize i = 2 (the index of the last character '3' in num1) and j = 2 (the index of the last character '6' in num2). Result List: Create an empty list ans to store the result digits.

Let's walk through a simple example. Consider the input strings num1 = "123" and num2 = "456". We want to find their sum.

5. Adding Digits: Add the digits at i and j indices from num1 and num2. For the first iteration, these are 3 + 6 = 9. No carry here, so c remains 0.

7. **Updates**: Decrement i and j to 1.

making it ['9', '7'].

6. Appending the Result: Append '9' to ans, making it ['9'].

4. Iterating Backwards: Since i and j are both not less than 0, and c is 0, we enter the while loop.

- 8. Iterating Backwards Next Step: i and j are still not less than 0, we continue the loop. 9. Adding Digits - Next Step: Now i = 1 and j = 1, so we add '2' and '5' plus the carry (0). The sum is 7. We append '7' to ans,
- 12. Adding Digits Last Digit: Now i = 0 and j = 0, we add '1' and '4'. The sum is 5. We append '5' to ans, making it ['9', '7', '5'].

11. Iterating Backwards - Next Step: i and j are both 0, we continue the loop.

10. Updates - Next Step: Decrement i and j to 0.

3. Carry Variable: Initialize the carry variable c to 0.

Python Solution

def addStrings(self, num1: str, num2: str) -> str:

def subStrings(self, num1: str, num2: str) -> str:

Remove leading zeros from the result

while len(result) > 1 and result[-1] == "0":

public String subStrings(String num1, String num2) {

// Check if the result will be negative

// Pointers to the end of each string

if (isNegative) {

int borrow = 0;

while(i >= 0) {

--j;

num1 = num2;

num2 = temp;

String temp = num1;

// Initialize borrow to 0

// Swap numbers if the result is negative

int length1 = num1.length(), length2 = num2.length();

int i = num1.length() - 1, j = num2.length() - 1;

StringBuilder answer = new StringBuilder();

// Process the larger number from the end

answer.append((borrow + 10) % 10);

borrow = borrow < 0 ? 1 : 0;

// Move to the next digits

len1, len2 = len(num1), len(num2)

"""Add two non-negative numbers represented as strings."""

index1, index2 = len(num1) - 1, len(num2) - 1 # Start from the end of both strings

digit2 = 0 if index2 < 0 else int(num2[index2]) # Same for second number</pre>

return "".join(reversed(result)) # Reverse the result list and convert it to a string

index1, index2 = len(num1) - 1, len(num2) - 1 # Start from the end of both strings

temp = int(num1[index1]) - borrow - (0 if index2 < 0 else int(num2[index2]))

result.append(str(value)) # Append the computed digit to result

index1, index2 = index1 - 1, index2 - 1 # Move to next digits

"""Subtract two non-negative numbers represented as strings."""

result = [] # Result list for storing subtraction results

borrow = 0 # Initialize borrow to 0 for subtraction

13. Updates - Final Update: Decrement i and j to -1.

and join it into a string to return '579'.

Thus, the string sum of num1 and num2 is '579'.

result = [] # Result list to store the addition results carry = 0 # Initialize carry to 0 for addition 6 8 # Loop until both strings have been processed or there is a carry while index1 >= 0 or index2 >= 0 or carry: 9 digit1 = 0 if index1 < 0 else int(num1[index1]) # Get current digit or 0 if index is out of range 10

carry, value = divmod(digit1 + digit2 + carry, 10) # Add digits and carry, then divide by 10 for new carry and digit

14. Finalizing the Result: We exit the loop since i and j are both less than 0 and c is 0, so we reverse ans to get ['5', '7', '9'],

21 negative_result = len1 < len2 or (len1 == len2 and num1 < num2) # Determine if result should be negative 22 # Swap numbers if the result is going to be negative 23 if negative_result: num1, num2 = num2, num124

while index1 >= 0:

result.pop()

```
32
               digit = (temp + 10) % 10 # Normalize digit and possibly take a borrow
               result.append(str(digit)) # Append current digit to the result list
33
34
               borrow = 1 if temp < 0 else 0 # Update borrow
35
               index1, index2 = index1 - 1, index2 - 1 # Move to the next digits
36
```

class Solution:

11

12

13

14

15

16

17

18

19

20

25

26

27

28

29

30

31

37

38

39

```
40
 41
             # Append '-' if the result is negative
 42
             if negative_result:
                 result.append("-")
 43
 44
 45
             return "".join(reversed(result)) # Reverse and join the result list to form the final answer
 46
Java Solution
    class Solution {
         // Method to add two numeric strings
         public String addStrings(String num1, String num2) {
             // Pointers to the end of each string
             int i = num1.length() - 1;
             int j = num2.length() - 1;
  6
             StringBuilder answer = new StringBuilder();
  8
             // Initialize carry to 0
             int carry = 0;
  9
 10
 11
             // Process both strings from the end till both strings are processed or there is no carry left
             while(i >= 0 || j >= 0 || carry > 0) {
 12
                 // Get digit from string num1 if available, else use 0
 13
                 int digit1 = i < 0 ? 0 : num1.charAt(i) - '0';</pre>
 14
 15
                 // Get digit from string num2 if available, else use 0
 16
                 int digit2 = j < 0 ? 0 : num2.charAt(j) - '0';
                 // Calculate sum of digits and carry
 17
                 carry += digit1 + digit2;
 19
                 // Append the unit digit of sum to the answer
 20
                 answer.append(carry % 10);
 21
                 // Calculate new carry
 22
                 carry /= 10;
 23
                 // Move to the next digits in each string
 24
                 --i;
 25
                 --j;
 26
 27
 28
             // The answer is in reverse order, so reverse it to get the correct result
 29
             answer.reverse();
 30
             // Convert StringBuilder to String and return
 31
             return answer.toString();
 32
 33
 34
         // Method to subtract two numeric strings
```

boolean isNegative = length1 < length2 || (length1 == length2 && num1.compareTo(num2) < 0);</pre>

// Subtract borrow and digit from num2 if available, else use 0, from the digit from num1

borrow = (num1.charAt(i) - '0') - borrow - (j < 0 ? 0 : num2.charAt(j) - '0');

// Handle negative results and prepare the next borrow if necessary

62 63 64 65 66

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

```
// Remove leading zeros from the answer
             while(answer.length() > 1 && answer.charAt(answer.length() - 1) == '0') {
                 answer.deleteCharAt(answer.length() - 1);
 67
 68
             // Append the negative sign if the result is negative
             if (isNegative)
 69
                 answer.append('-');
 70
 71
 72
 73
             // The answer is in reverse order, so reverse it to get the correct result
 74
             answer.reverse();
 75
 76
             // Convert StringBuilder to String and return
             return answer.toString();
 77
 78
 79
 80
C++ Solution
  1 class Solution {
    public:
         // Adds two non-negative numbers represented as strings.
         string addStrings(string num1, string num2) {
             int i = num1.size() - 1;
             int j = num2.size() - 1;
             string result;
             int carry = 0; // Initialize the carry for addition to 0.
  8
  9
             // Loop until all digits are processed or there is a carry.
 10
             while (i >= 0 || j >= 0 || carry > 0) {
 11
 12
                 // Get the value of current digits and add to carry.
                 int digit1 = i >= 0 ? num1[i] - '0' : 0;
 13
                 int digit2 = j >= 0 ? num2[j] - '0' : 0;
 14
 15
                 carry += digit1 + digit2;
 16
 17
                 // Append the current digit to the result string.
                 result += to_string(carry % 10);
 18
                 carry /= 10; // Calculate carry for the next iteration.
 19
 20
 21
                 // Move to the next digits.
 22
                 --i;
 23
                 --j;
 24
 25
 26
             // Since we have added digits in reverse, reverse the string to get the final result.
 27
             reverse(result.begin(), result.end());
 28
 29
             return result;
 30
 31
 32
         // Subtracts the smaller number from the larger number represented as strings.
 33
         string subStrings(string num1, string num2) {
 34
             // Determine if the result will be negative.
 35
             bool isNegative = num1.size() < num2.size() || (num1.size() == num2.size() && num1 < num2);</pre>
 36
             if (isNegative) {
 37
                 // Ensure numl is always greater than num2 for direct subtraction.
 38
                 swap(num1, num2);
 39
 40
 41
             int i = num1.size() - 1;
             int j = num2.size() - 1;
 42
 43
             string result;
 44
             int borrow = 0; // Initialize the borrow for subtraction to 0.
 45
 46
             // Loop until all digits of numl are processed.
             while (i >= 0) {
 47
                 // Calculate current digits and subtract borrow.
 48
 49
                 int diff = (num1[i] - '0') - borrow - (j < 0 ? 0 : num2[j] - '0');
                 if (diff < 0) {
 50
 51
                     diff += 10; // If difference is negative, handle the borrow.
 52
                     borrow = 1; // Set borrow for the next iteration.
 53
                 } else {
                     borrow = 0; // No borrow if the difference is positive.
 54
 55
 56
 57
                 // Append the current digit to the result string.
 58
                 result += to_string(diff % 10);
 59
 60
                 // Move to the next digits.
 61
 62
                 --j;
 63
 64
 65
             // Remove any leading zeros from the result string.
```

const digit1 = index1 >= 0 ? Number(num1[index1--]) : 0; 10 // Get the current digit from num2 or 0 if index is out of bounds const digit2 = index2 >= 0 ? Number(num2[index2--]) : 0; // Calculate the sum of the two digits and the carry over, if any 13 const sum = digit1 + digit2 + (carryOver ? 1 : 0); 15 // If sum is greater or equal to 10, we have a new carry over

carryOver = sum >= 10;

result.push(sum % 10);

Time and Space Complexity

num2 respectively, the time complexity is $O(\max(m, n))$.

added. Hence, the space complexity is $O(\max(m, n))$.

return result.reverse().join('');

Typescript Solution

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

16

17

18

19

20

21

23

22 }

negative numbers.

};

while (result.length() > 1 && result.back() == '0') {

// If the result is negative, append the negative sign.

// Since we have subtracted digits in reverse, reverse the string to get the final result.

result.pop_back();

if (isNegative) {

return result;

result += '-';

reverse(result.begin(), result.end());

function addStrings(num1: string, num2: string): string {

while (index1 >= 0 || index2 >= 0 || carryOver) +

const result = []; // Array to store the result of addition

let index1 = num1.length - 1; // Start from the end of num1

let index2 = num2.length - 1; // Start from the end of num2

// Loop until both string indices go below zero or carry over is true

// Push the last digit of the sum into the result array

// Reverse the result array and join it to form the final result string

// Get the current digit from num1 or 0 if index is out of bounds

let carryOver = false; // Flag for the carry over value

addStrings Time Complexity

The function iterates over each digit of the longer input string (num1 or num2) at most once, and arithmetic computations of

The above Python code implements two functions, addStrings and subStrings, that operate on string representations of non-

addStrings Space Complexity

The space complexity is dominated by the space required for the ans array, which holds the result of the addition. The length of this array will be at most max(m, n) + 1. Therefore, the space complexity is 0(max(m, n)).

constant time complexity are carried out for the digits. No nested loops are present. Therefore, if m and n are the lengths of num1 and

Similar to addStrings, the subStrings function iterates over the digits of the inputs in a single pass. Comparisons and subtractions of constant time complexity are carried out. Thus, if m is the length of num1 and n is the length of num2, the time complexity is again

subStrings Time Complexity

O(max(m, n)). subStrings Space Complexity The space complexity is determined by the ans array here as well. In the worst case, this array's length is equal to the length of the

Overall, both functions exhibit linear time and space complexities relative to the sizes of the input strings.

longer input string since at most one additional digit (for a possible '-1' carried over or a leading '-' for a negative result) can be