556. Next Greater Element III

String

# **Problem Description**

Medium Math Two Pointers

Given a positive integer n, the goal is to find the smallest integer greater than n which contains exactly the same digits as n. This number is essentially the next permutation in a lexicographically greater order of the digits. If there is no such number that is greater than n with the same digits, the function returns -1. Additionally, the answer must fit within a signed 32-bit integer. If the smallest integer is greater than what a 32-bit integer can represent, the function should also return -1.

The intuition behind the solution involves thinking about what makes one number bigger than another when they have the same

digits. The key insight here is that for a number to be just bigger than the given number, the change must be made rightmost

# Intuition

such that the digits to the right of this change-point are reversed to form the smallest sequence possible, while creating a number that is bigger than the original number. Identify the rightmost digit that can be swapped to make the number bigger. We start from the right and look for the first digit that is smaller than the digit immediately to its right. If no such digit exists, the digits are in descending order and we cannot

- form a greater number, hence return -1. Swap the identified digit with the smallest digit to its right that is greater than itself. This guarantees that the increase in the number is as small as possible while still being greater than the original number.
- still in descending order. Reversing them will give us the smallest possible sequence to ensure that the overall number is the smallest possible number greater than n.

Implementing this approach, we can navigate through the digit sequence obtained from the integer n and incrementally build up

Reverse the sequence to the right of the original change point. After the swap, the digits to the right of the change point are

**Solution Approach** 

our solution step by step until we determine the next greatest element or lack thereof.

greater number can be formed, hence we return -1.

which would make the number larger than necessary.

2\*\*31 - 1, which is the maximum value for a 32-bit signed integer, return -1.

Let's use the integer n = 1423 as a small example to illustrate the solution approach.

Combine the characters to form the new integer ans = 1342.

# Convert the number to a list of characters for easy manipulation

# Now find an element which is greater than the found element at i

while i >= 0 and char\_list[i] >= char\_list[i + 1]:

char\_list[i], char\_list[j] = char\_list[j], char\_list[i]

return next\_greater if next\_greater <= 2\*\*31 - 1 else -1

char[] digits = String.valueOf(n).toCharArray();

// that is less than its immediate right digit.

while (i >= 0 && digits[i] >= digits[i + 1]) {

// that is greater than the digit found above.

// If no such digit is found, no greater permutation exists.

char list[i + 1 :] = char list[i + 1:][::-1]

# Convert the char list back to an integer

next\_greater = int(''.join(char\_list))

public int nextGreaterElement(int n) {

int length = digits.length;

int i = length - 2;

return -1;

int i = length - 1;

swap(digits, i, j);

while (digits[i] >= digits[j]) {

// Swap the two digits found above.

**if** (i < 0) {

j--;

The solution uses a single-pass approach and the concept of rearranging the digits to form the next permutation. To walk through the algorithm: Convert the integer n to a list of characters, cs, to facilitate the swapping of digits.

First, we iterate through cs from right to left, trying to find the first pair of digits where the left digit is less than the right digit.

# This step essentially finds the digit (cs[i]) that can be swapped to create a number larger than n. The loop variable i starts

from the second to last index (n-2) and decreases. If such a digit cs[i] can't be found and i becomes less than 0, it means that the digits are in descending order, and no

do this by iterating from the end of cs until we find a digit cs[j] that is greater. Swap cs[i] with cs[j] to form a larger number. However, the digits to the right of index i are still in descending order,

Now that we have found the swap position at index i, we need to find the smallest digit greater than cs[i] to its right. We

- Reverse the sublist cs[i+1:] so that we get the smallest possible number that is larger than n after the swap. Combine the characters back to form an integer ans and check if it is within the 32-bit integer range. If ans is larger than
- This solution uses the pattern of finding the next permutation which is a well-known technique that applies to not just numbers but also arrays and sequences where you want to find a lexicographically ordered element.

Finally, if ans is within the range, return it. This result is now the smallest integer larger than n using its digits.

Convert the integer n to a list of characters cs, so n = 1423 becomes cs = ['1', '4', '2', '3']. Iterate from right to left to find the first digit that is smaller than the digit immediately to its right. In our example, starting from

Swap cs[i] with cs[j] where cs[j] is '3'. The list cs now becomes ['1', '3', '2', '4']. The digits to the right of index i are ['2', '4']. We reverse this sublist to get the smallest sequence, which will result in

Check if ans fits within a signed 32-bit integer range. Since ans = 1342 is less than 2\*\*31 - 1, it is within the range.

The swap position is found at index i where cs[i] = '2'. Now, find the smallest digit greater than '2' to its right. This

the right, we compare 3 to 2, 2 to 4, and then 4 to 1. The first digit that is smaller than the digit to its right is 2.

### ['1', '3', '4', '2'].

would be '3'.

Solution Implementation

char list = list(str(num))

length = len(char\_list)

i = length - 2

return -1

if i < 0:

**Python** 

**Example Walkthrough** 

Following this algorithm provides a simple and efficient method to determine the next permutation of an integer with the same set of digits.

Return ans as the result. So the smallest integer greater than 1423 containing the same digits is 1342.

- class Solution: def nextGreaterElement(self, num: int) -> int:
- i -= 1 # If we can't find such an element, it means the number cannot be greater in its permutation

# Reverse the sublist after the index i to get the next greater element in terms of permutation

# If the next greater number is bigger than the largest 32-bit integer, return -1

// Convert the integer to a char array for easy manipulation of digits

// Start from the second last digit and move left until you find a digit

// Start from the end of the arrav and move left until you find a digit

// Return the answer if it's within the range of a 32-bit integer,

// TypeScript function to find the next greater permutation of a given integer.

// Convert the given integer 'n' to a string to manipulate individual digits.

// If no such digit is found, the number cannot be made greater, return -1.

// Swap the digits at index 'i' and 'i'. We create a character array for swapping.

[numChars[i], numChars[j]] = [numChars[j], numChars[i]]; // Perform the swap.

# Convert the number to a list of characters for easy manipulation

# Now find an element which is greater than the found element at i

numStr = numChars.join(''); // Convert the character array back to a string.

// Initialize 'i' for scanning the string from the right, starting at the second last digit.

// Find the first digit (scanning from right to left) that is smaller than the digit to its right.

// Find the rightmost digit that is greater than numStr[i], starting from the end of the string.

// Reverse the substring starting from the digit next to index 'i' to the end of the string.

// Return the answer if it's within the range of a 32-bit integer; otherwise, return -1.

numStr = numStr.substring(0, i + 1) + reversed; // Concatenate the non-reversed and reversed parts.

# If we can't find such an element, it means the number cannot be greater in its permutation

# Reverse the sublist after the index i to get the next greater element in terms of permutation

# If the next greater number is bigger than the largest 32-bit integer, return -1

return ans > INT\_MAX ? -1 : static\_cast<int>(ans);

while (i >= 0 && numStr.charAt(i) >= numStr.charAt(i + 1)) {

// Initialize 'i' to point at the last digit of the number.

let reversed: string = toReverse.split('').reverse().join('');

while i >= 0 and char\_list[i] >= char\_list[i + 1]:

char\_list[i], char\_list[j] = char\_list[j], char\_list[i]

return next\_greater if next\_greater <= 2\*\*31 - 1 else -1

entire list of digits from right to left, which is done in O(n) time.

4. Swapping cs[i] and cs[j]: This is done in constant time, 0(1).

char list[i + 1 :] = char list[i + 1:][::-1]

# Convert the char list back to an integer

next\_greater = int(''.join(char\_list))

// otherwise return -1.

let numStr: string = n.toString();

let i: number = numStr.length - 2;

let j: number = numStr.length - 1;

while (numStr.charAt(i) >= numStr.charAt(j)) {

let toReverse: string = numStr.substring(i + 1);

// Convert the modified string back to an integer.

let numChars: string[] = numStr.split('');

let ans: number = parseInt(numStr);

char list = list(str(num))

while char\_list[i] >= char\_list[j]:

# Swap these two elements

Time and Space Complexity

**Time Complexity** 

length = len(char\_list)

i = length - 2

i -= 1

return -1

i = length - 1

j -= 1

if i < 0:

function nextGreaterElement(n: number): number {

**}**;

**TypeScript** 

i--;

j--;

if (i < 0) return -1;

i = length - 1while char\_list[i] >= char\_list[j]: j -= 1 # Swap these two elements

# Start from the second last element and move backward to find the first element which is smaller than its next element

```
Java
```

class Solution {

```
// Reverse the digits to the right of the position where the swap was made
        // to get the next greater permutation with the smallest increase.
        reverse(digits, i + 1, length - 1);
        // Convert the resultant char array back to long to check for integer overflow.
        long result = Long.parseLong(new String(digits));
        // If the result is greater than the max value for int,
        // return -1, otherwise, cast to int and return.
        return result > Integer.MAX_VALUE ? -1 : (int) result;
    // Helper method to swap two elements in a char array.
    private void swap(char[] array, int i, int j) {
        char temp = array[i];
        arrav[i] = arrav[j];
        array[j] = temp;
    // Helper method to reverse a part of the char array between two indices.
    private void reverse(char[] array, int start, int end) {
        while (start < end) {</pre>
            swap(array, start, end);
            start++;
            end--;
C++
class Solution {
public:
    int nextGreaterElement(int n) {
        // Convert the given integer to a string to manipulate individual digits.
        string numStr = to_string(n);
       // Get the length of the string representation of the integer.
        int length = numStr.size();
        // Initialize i for scanning the string from the right, starting at the second last digit.
        int i = length - 2;
        // Initialize i to point at the last digit of the number.
        int j = length - 1;
       // Find the first digit (scanning from right to left) that is smaller than the digit to its right.
       while (i >= 0 && numStr[i] >= numStr[i + 1]) {
       // If no such digit is found, the number cannot be made greater, return -1.
        if (i < 0) return -1;
        // Find the rightmost digit that is greater than numStr[i], starting from the end of the string.
       while (numStr[i] >= numStr[j]) {
            --j;
        // Swap the digits at index i and j.
        swap(numStr[i], numStr[j]);
        // Reverse the substring starting from the digit next to index i to the end of the string.
        // This gives us the next greater permutation of the number.
        reverse(numStr.begin() + i + 1, numStr.end());
        // Convert the modified string back to a long integer.
        long ans = stol(numStr);
```

### return ans > 2\*\*31 - 1 ? -1 : ans;class Solution: def nextGreaterElement(self, num: int) -> int:

The time complexity of this code is O(n), where n is the number of digits in the given integer. Here's the breakdown of the time complexity: 1. Converting the integer to a list of characters: This is done in O(n) time.

2. Finding the pivot point (i) such that cs[i] is just less than the element to its right (cs[i + 1]): In the worst case, we may have to scan the

3. Finding the smallest digit greater than cs[i] to its right to swap with (j): Again, in the worst-case scenario, this is done in O(n) time.

# Start from the second last element and move backward to find the first element which is smaller than its next element

7. The final check to ensure the answer is within a 32-bit integer range is performed in constant time, 0(1). All other operations are constant with respect to the size of the input and, as such, do not change the overall 0(n) complexity.

5. Reversing the sublist after the pivot point: The sublist is at most n-1 elements long and reversing it is done in O(n).

6. Joining the list into a string and converting back to an integer: This operation is performed in O(n) time.

The space complexity of the code is also 0(n), where 'n' is the number of digits in the given integer. This is because:

1. We store the list of characters, cs, which takes 0(n) space. 2. The additional space used when creating the sublist and reversing it also does not exceed O(n).

There are no recursive calls or additional data structures that depend on the size of the input which would increase the space

complexity further.

**Space Complexity**