1275. Find Winner on a Tic Tac Toe Game

```
Hash Table
                                Matrix
                                          Simulation
Easy
       <u>Array</u>
```

Problem Description

own marks in a row either horizontally, vertically, or diagonally. In this LeetCode problem, we are given a list of moves where each move is represented by a pair of integers that correspond to a row and column on the grid. The task is to determine the outcome of the game based on the sequence of moves. The rules are as follows: • Player "A" uses the mark 'X' and makes the first move, while player "B" uses the mark 'O'.

Tic-tac-toe is a classic game for two players, "A" and "B", played on a 3×3 grid. The objective is to be the first to get three of their

 Players alternate turns, placing their mark on an empty cell. The game ends when a player has three of their marks in a row or all cells are filled.

- If a player wins, their identity ("A" or "B") should be returned.
- If all cells are filled without a winner, the game is a draw and "Draw" should be returned. If the game has not ended, "Pending" should be returned.
- The array moves represents the game sequence where moves $[i] = [row_i, col_i]$ is the i-th move played on the grid at the cell
- defined by the row and column indices.

Intuition The solution provided leverages a counting approach to keep track of the game's state without having to construct the entire grid

after each move. Here's the intuition behind the solution: • We create a count array cnt of length 8 to keep track of marks along the rows, columns, and diagonals. The first three positions are for the

rows, the next three positions for the columns, and the last two for the two diagonals. • We iterate over the moves inversely for both players, skipping moves alternatively (since players take turns). • Each player's move is analyzed with respect to the potential winning conditions: filling a row, column, or diagonal. We increment the respective

- counter for the move made. After each move, we check if any counters have reached 3, indicating a winning condition.
- If there's a winner, we identify which player's turn it was based on whether the number of moves made so far is odd or even, and return "A" or "B" accordingly.
- If no winner is detected and the total moves made are 9, we declare the game a draw. If the game is not won and not all moves are played, we return "Pending" indicating unfinished status.
- Solution Approach

 \circ Incrementing cnt [6] (the counter for the left-to-right diagonal) if i == j.

condition), the game ends in a Draw, and so we return "Draw".

implements an elegant solution to identify the game's status after each move is made.

Starting with the observation that a player wins if they achieve three of their symbols in a row, column, or diagonal, the code

Create a counter array cnt with 8 zeros, where cnt[0] to cnt[2] correspond to the three rows, cnt[3] to cnt[5] to the three

columns, and cnt[6] and cnt[7] to the two diagonals of the board. Iterate over the moves in reverse order using the range range(n-1, -1, -2), where n is the length of the moves list. This

iteration goes backwards and skips every other move to alternate between players A and B as they play. For each move, extract the row and column from moves [k]. Increment the respective counters in cnt for the row index i and

column index j+3. This update simulates placing the 'X' or 'O' on the board.

Check for a diagonal match by:

the code returns "Pending".

moves = [[0,0],[2,0],[1,1],[2,1],[2,2]]

simulate the alternating turns:

Here is a step-by-step approach to the implementation:

- \circ Incrementing cnt [7] (the counter for the right-to-left diagonal) if i + j == 2. After updating the cnt, check if any value in cnt has reached 3 using the condition any (v == 3 for v in cnt). This check is indicative of a winning condition.
- If there is a winner, return "B" if k is odd (since the moves list includes player A's moves first, odd indexes will belong to player B during reverse iteration), or "A" if k is even, indicating it was player A's turn during the move that secured the win.

If no winner is found and the total number of moves n is 9 (meaning every cell has been filled without achieving a winning

In the final case where no winner is found and n is less than 9, not all cells have been filled, thus the game is still ongoing, and

- This method is efficient because it works incrementally, only tracking the essentials for determining the game outcome and not reconstructing the entire board's state after each move. It effectively makes use of a single-pass and counter-based technique, which is ideal for this array-based simulation of the tic-tac-toe game.
- **Example Walkthrough** Let's consider an example game represented by the sequence of moves:

In this example, player A (using 'X') makes the first move at the top-left corner of the grid (0,0), followed by player B (using 'O') making a move at the bottom-left corner (2,0). The game proceeds with each player taking turns. Now, let's walk through the moves according to the solution approach:

The length of the moves list is 5, and we start iterating from the last move to the first move, skipping every other one to

For k = 4, which is the move [2,2] by player A: ■ The row index is 2, so we increment cnt [2].

■ The row index is 1, so we increment cnt [1]. ■ The column index is 1, so we increment cnt [4].

(Note: Player B does not contribute to diagonal counters in these moves.)

• Since the row and column indices are equal, indicating a diagonal, we increment cnt [6].

At this point, after the even-indexed moves by player A, cnt looks like this: [0,1,1,0,1,1,2,0].

■ The indices are the same, indicating the diagonal again, so we increment cnt[6].

We initialize a counter array cnt with 8 zeros: cnt = [0,0,0,0,0,0,0,0].

Then we iterate for player B: For k = 3, which is the move [2,1] by player B:

4. After these iterations, we check if any counters reached the value of 3, which would indicate a win. Since none have, we proceed.

5. Since only 5 moves are made and the total number of moves is less than 9, we cannot have a 'Draw', so we return 'Pending'.

As a result, the output for this sequence will be "Pending", as the game has not concluded yet.

The current state of cnt is [0,1,2,0,2,1,2,0]. No values are 3, so no winner yet.

Solution Implementation

def tictactoe(self, moves):

counters = [0] * 8

num_moves = len(moves)

Initialize the number of moves

row, col = moves[idx]

counters [col + 3] += 1

counters[row] += 1

if row + col == 2:

counters[7] += 1

public String tictactoe(int[][] moves) {

if any(value == 3 for value in counters):

return "B" if idx % 2 else "A"

for idx in range(num_moves - 1, -1, -2):

■ The row index is 2, so we increment cnt [2].

■ The column index is 1, so we increment cnt[4].

■ The column index is 2, so we increment cnt [5].

For k = 2, which is the move [1,1] by player A:

Python class Solution:

Get the row and column index from the last move

Increment the corresponding row and column counters

If the move is on the main diagonal, increment the corresponding counter if row == col: counters[6] += 1

If the move is on the anti-diagonal, increment the corresponding counter

Check if any counters reached 3, which would indicate a win

// Array to keep track of the count of marks for rows, columns, and diagonals

// We start checking the game status from the last move backwards

// Diagonals: index 6 (left-top to right-bottom), index 7 (left-bottom to right-top)

Start from the last move and check if there is a winner after every move

'\counters' is a list that holds the count of marks for each row, column and diagonals

indexes [0,1,2] are for rows, [3,4,5] are for columns, [6] is for diagonal, [7] is for anti-diagonal

Return 'B' if the current index is odd (indicating player "B"'s turn), otherwise 'A'

```
# After all moves, if no winner is found, check if the board is full. If yes, it's a draw
# Otherwise, the game is still pending
return "Draw" if num_moves == 9 else "Pending"
```

Java

class Solution {

```
int totalMoves = moves.length; // Total number of moves made.
        int[] counts = new int[8]; // Array to keep track of the counts across rows, columns, and diagonals.
       // Iterate from the last move to the first, decrementing by 2 to alternate between players.
        for (int moveIndex = totalMoves - 1; moveIndex >= 0; moveIndex -= 2) {
            int row = moves[moveIndex][0]; // Row of the current move.
            int col = moves[moveIndex][1]; // Column of the current move.
            // Increment the count for the current row and column.
            counts[row]++;
            counts[col + 3]++;
           // Check for diagonal win condition (top-left to bottom-right).
            if (row == col) {
                counts[6]++;
           // Check for anti-diagonal win condition (top-right to bottom-left).
            if (row + col == 2) {
                counts[7]++;
           // Check if the current player has won (if any count reaches 3).
            if (counts[row] == 3 || counts[col + 3] == 3 || counts[6] == 3 || counts[7] == 3) {
                return moveIndex % 2 == 0 ? "A" : "B"; // Return winner "A" or "B" based on move index.
       // If all 9 moves are made and no winner, it is a draw.
       return totalMoves == 9 ? "Draw" : "Pending"; // If not a draw, the game is still pending.
C++
class Solution {
public:
    string tictactoe(vector<vector<int>>& moves) {
        int movesCount = moves.size(); // Total number of moves made
```

```
// If all 9 moves are made and no winner, it is a draw. Otherwise, game is pending.
       return movesCount == 9 ? "Draw" : "Pending";
};
TypeScript
```

// Rows:

indices 0-2

int row = moves[k][0];

int col = moves[k][1];

if (row == col) {

count [6]++;

if (row + col == 2) {

count [7]++;

for (int $k = movesCount - 1; k >= 0; k -= 2) {$

count[row]++; // Increment row count

return k % 2 == 0 ? "A" : "B";

count[col + 3]++; // Increment column count

// Check for diagonal — top—left to bottom—right

// Check for anti-diagonal - bottom-left to top-right

// Check if player made 3 marks in a row, column, or diagonal

Start from the last move and check if there is a winner after every move

If the move is on the main diagonal, increment the corresponding counter

If the move is on the anti-diagonal, increment the corresponding counter

After all moves, if no winner is found, check if the board is full. If yes, it's a draw

Return 'B' if the current index is odd (indicating player "B"'s turn), otherwise 'A'

Check if any counters reached 3, which would indicate a win

if (count[row] == 3 || count[col + 3] == 3 || count[6] == 3 || count[7] == 3) {

// If the index is even, it is player A's move; if odd, player B's move.

// Columns: indices 3-5

int count $[8] = \{0\};$

```
function tictactoe(moves: number[][]): string {
      // Total number of moves made, corresponds to the number of turns played
      const totalMoves = moves.length;
      // An array to count the moves for rows, columns, and diagonals
      // Indices 0-2 for rows, 3-5 for columns, 6-7 for diagonals
      const moveCounters = new Array(8).fill(0);
      // Iterate through the moves in reverse, starting with the last move
      for (let moveIdx = totalMoves - 1; moveIdx >= 0; moveIdx -= 2) {
          const [row, col] = moves[moveIdx];
          // Increment the counters for the current row and column
          moveCounters[row]++;
          moveCounters[col + 3]++;
          // If the move is on the main diagonal, increment the counter
          if (row === col) {
              moveCounters[6]++;
          // If the move is on the secondary diagonal, increment the counter
          if (row + col === 2) {
              moveCounters[7]++;
          // Check if any counter has reached 3, indicating a win
          if (moveCounters[row] === 3 || moveCounters[col + 3] === 3 || moveCounters[6] === 3 || moveCounters[7] === 3) {
              // Determine the winner based on the index of the move
              return moveIdx % 2 === 0 ? 'A' : 'B';
      // If all 9 spaces were played and no winner, it's a draw
      return totalMoves === 9 ? 'Draw' : 'Pending';
class Solution:
   def tictactoe(self, moves):
       # Initialize the number of moves
       num_moves = len(moves)
       # '\counters' is a list that holds the count of marks for each row, column and diagonals
       # indexes [0,1,2] are for rows, [3,4,5] are for columns, [6] is for diagonal, [7] is for anti-diagonal
        counters = [0] * 8
```

```
Time and Space Complexity
  The time complexity of the given code is 0(1), as the function processes a fixed number (at most 9) of moves, regardless of the
```

Otherwise, the game is still pending

if any(value == 3 for value in counters):

return "B" if idx % 2 else "A"

return "Draw" if num_moves == 9 else "Pending"

for idx in range(num_moves -1, -1, -2):

row, col = moves[idx]

counters[col + 3] += 1

counters[6] += 1

counters[7] += 1

counters[row] += 1

if row + col == 2:

if row == col:

Get the row and column index from the last move

Increment the corresponding row and column counters

counters, and checking for a win condition), and thus does not grow with input size. The space complexity of the code is also 0(1) because the amount of memory used does not depend on the input size either. The cnt list has a constant size of 8, and no additional memory is allocated that would depend on the input.

input size. The logic within the loop has a constant number of operations (checking the status of the game board, incrementing