734. Sentence Similarity

Hash Table

String

dissimilarity, the overall similarity check fails, and we return False.

Problem Description

The problem asks to determine if two sentences are similar. Each sentence is represented as an array of words. For example, the sentence "I am happy with leetcode" can be represented as arr = ["I", "am", "happy", "with", "leetcode"]. The words within each sentence are considered similar based on a provided list of word pairs similarPairs, where each pair [xi, yi] indicates that xi and yi are similar words. Two sentences are similar if they have the same number of words and each word in a position in sentence1 is similar to the corresponding word in the same position in sentence2. A word is always considered similar to itself. It is important to note that the similarity between words is not transitive - just because word a is similar to word b and word b is similar to word c, it doesn't mean a is similar to c.

To determine if the two sentences are similar, there are two main checks that need to be carried out:

Intuition

return False as they can't be similar with different lengths.

Check Word Similarity: Then, we check each pair of corresponding words from sentence1 and sentence2. For each word pair (a, b) we check:

Check Length: First, we need to check if both sentences have the same number of words. If they don't, we can immediately

- If a is the same as b, they are automatically similar. ∘ If a and b are found as a pair in similarPairs, they are similar.
- As similarity is not directed (it is bidirectional), we should also check (b, a) in similarPairs.

If all word pairs pass these similarity checks, the sentences are similar, and we return True. Otherwise, at the first instance of

Solution Approach

Set Data Structure: A set is used to store the similarPairs for efficient O(1) average time complexity on lookups. This is

The nature of a set provides constant time membership testing, which is much faster compared to a list or array for this

Zip Function: The zip function is a built-in Python function that aggregates elements from two or more iterables (arrays,

lists, etc.) and returns an iterator of tuples. In this solution, zip is used to create pairs of corresponding words from

done by creating a set s using set comprehension to hold all given similar word pairs in both directions (e.g., (a, b) and (b, a)).

purpose.

The implemented solution takes advantage of the following algorithms, data structures, and programming constructs:

- sentence1 and sentence2. List Comprehension with all Function: A list comprehension is used in conjunction with the all function to check if all corresponding pairs of words between sentence1 and sentence2 are similar. The all function returns True if all elements of
- the given iterable are true (or if the iterable is empty). The list comprehension iterates through each word pair and uses a logical or | to evaluate if the words are identical, or if they exist as similar word pairs in the set s. Here is the step-by-step approach of the solution process:
- **Check Length Equality:** • Before iterating through the words, the solution checks if sentence1 and sentence2 have the same length using len(sentence1) != len(sentence2). If they don't match, it returns False, thereby optimizing the solution by eliminating non-matching sentences early on.

similarPairs.

s = {(a, b) for a, b in similarPairs}

Iterative Comparison with Early Exit:

If a == b, then the words are the same.

way to compare the sentences. This results in a concise and effective code:

Let's consider a small example to illustrate the solution approach.

If (a, b) in s, the pair exists in the similarity set, so they are similar. • If (b, a) in s, since similarity is not transitive but is bidirectional, this pair is also checked in case the reverse was provided in

return all(

• The all function wraps the list comprehension to ensure that every pair meets at least one of these conditions. If even one pair does not meet the similarity condition, all returns False.

By using this approach, the solution effectively breaks down the problem into small logical checks, ensuring an efficient and clear

• The solution iterates over each pair of words (a, b) from the zipped sentences using list comprehension and checks:

def areSentencesSimilar(self, sentence1: List[str], sentence2: List[str], similarPairs: List[List[str]]) -> bool: if len(sentence1) != len(sentence2): return False

a == b or (a, b) in s or (b, a) in s for a, b in zip(sentence1, sentence2)

Example Walkthrough

```
Suppose we have two sentences represented by the arrays below:
• sentence1 = ["I", "love", "to", "code"]
sentence2 = ["I", "adore", "to", "program"]
And let's say we are also given the list of similar word pairs:
similarPairs = [["love", "adore"], ["code", "program"]]
```

• We create an iterator of tuples by pairing up corresponding items from both sentences using zip(sentence1, sentence2), which gives us

• Both sentence1 and sentence2 have the same number of words (4 words each), so we move on to the next step. If they had a different

Check Length Equality:

[("I", "I"), ("love", "adore"), ("to", "to"), ("code", "program")]. • We create a set from similarPairs to store all given similar word pairs, including their bidirectional counterparts - that would give us a set

number of words, we would return False at this point.

Iterative Comparison with Early Exit:

Using list comprehension, we check each pair:

When we apply our solution, this is how it will proceed:

■ First pair is ("I", "I"): the words are identical, so this pair is similar. Second pair is ("love", "adore"): the pair exists in set s, so this pair is also similar. ■ Third pair is ("to", "to"): again, the words are identical, similar by default.

■ Fourth pair is ("code", "program"): the pair exists in set s, hence this pair is similar too.

First, check if both sentences have the same number of words

similar_set = {(first, second) for first, second in similar_pairs}

for word1, word2 in zip(sentence1, sentence2)

usually including test cases to demonstrate the implementation.

if (sentence1.length != sentence2.length) {

Set<String> similarPairSet = new HashSet<>();

// Iterate through the words in both sentences.

for (int i = 0; i < sentence1.length; i++) {</pre>

String word1 = sentence1[i]:

String word2 = sentence2[i];

for (List<String> pair : similarPairs) {

// Create a set to store the unique similar word pairs.

similarPairSet.add(pair.get(0) + "." + pair.get(1));

Below this point would be code that uses the Solution class and its method,

Since the class itself should only contain the method definition, usage of the

Check each pair of words from both sentences to see if they're the same

s containing [("love", "adore"), ("adore", "love"), ("code", "program"), ("program", "code")].

True because all corresponding word pairs are similar as per our rules. Solution Implementation **Python**

Using this approach with the given sentence1, sentence2, and similarPairs, our function areSentencesSimilar would return

Since every pair of words from both sentences have passed the similarity check, the all function will ultimately return True.

def areSentencesSimilar(self. sentence1: List[str]. sentence2: List[str], similar_pairs: List[List[str]]) -> bool:

Create a set of pairs that are considered similar from the given list of similar pairs

word1 == word2 or (word1, word2) in similar set or (word2, word1) in similar_set

// Method to determine whether two sentences are similar based on the provided similar word pairs.

String[] sentence1, String[] sentence2, List<List<String>> similarPairs) {

// Concatenate the two words with a delimiter and add to the set.

// does not exist in the set, the sentences are not similar.

// If the current words are not the same and the pair (both combinations)

if (!word1.equals(word2) && !similarPairSet.contains(word1 + "." + word2)

&& !similarPairSet.contains(word2 + "." + word1)) {

// If the sentences have different lengths, they cannot be similar.

If not, check if they are considered similar from the previously created set # We check for both (a, b) and (b, a) to account for the order in which the similar pair might have been given # If all pairs of words are either the same or similar (in any order), sentences are similar return all(

```
Java
class Solution {
```

public boolean areSentencesSimilar(

return false;

class is not included here.

from typing import List

If not, they cannot be similar

return False

if len(sentence1) != len(sentence2):

This allows for O(1) lookup time

class Solution:

```
return false;
        // If all word pairs are similar, return true.
        return true;
C++
#include <vector>
#include <string>
#include <unordered_set>
class Solution {
public:
    // Function to check if two sentences are similar based on the provided similar word pairs.
    bool areSentencesSimilar(std::vector<std::string>& sentence1, std::vector<std::string>& sentence2, std::vector<std::vector<std::s</pre>
        int sentenceLength = sentence1.size(); // Storing the length of the first sentence.
        // Check if the two sentences are of different lengths; if so, they can't be similar.
        if (sentenceLength != sentence2.size()) return false;
        // Create a set to hold the pairs as concatenated strings for quick lookup.
        std::unordered set<std::string> pairSet;
        // Insert each pair of similar words into the set as 'word1.word2'.
        for (const auto& pair : similarPairs) {
            pairSet.insert(pair[0] + "." + pair[1]);
        // Check every word in both sentences for similarity.
        for (int i = 0; i < sentenceLength; ++i) {</pre>
            const std::string& word1 = sentence1[i]; // Word from the first sentence.
            const std::string& word2 = sentence2[i]; // Corresponding word from the second sentence.
           // If words are not the same and neither composition of words exists in the similarity set, return false.
            if (word1 != word2 && pairSet.find(word1 + "." + word2) == pairSet.end() && pairSet.find(word2 + "." + word1) == pairSet.
                return false;
```

// If we make it through all word comparisons without returning false, the sentences are similar.

function areSentencesSimilar(sentence1: string[], sentence2: string[], similarPairs: StringPair[]): boolean {

// Function to check if two sentences are similar based on the provided similar word pairs.

// Check if the two sentences are of different lengths; if so, they can't be similar.

// Create a set to hold the pairs as concatenated strings for quick lookup.

const word1: string = sentence1[i]: // Word from the first sentence.

First, check if both sentences have the same number of words

similar_set = {(first, second) for first, second in similar_pairs}

Check each pair of words from both sentences to see if they're the same

If not, check if they are considered similar from the previously created set

const word2: string = sentence2[i]; // Corresponding word from the second sentence.

// If words are not the same and neither composition of words exists in the similarity set, return false.

def areSentencesSimilar(self. sentence1: List[str]. sentence2: List[str], similar_pairs: List[List[str]]) -> bool:

We check for both (a, b) and (b, a) to account for the order in which the similar pair might have been given

if (word1 !== word2 && !pairSet.has(word1 + "." + word2) && !pairSet.has(word2 + "." + word1)) {

// If we make it through all word comparisons without returning false, the sentences are similar.

Create a set of pairs that are considered similar from the given list of similar pairs

If all pairs of words are either the same or similar (in any order), sentences are similar

word1 == word2 or (word1, word2) in similar set or (word2, word1) in similar_set

// Insert each pair of similar words into the set as 'word1.word2'.

from typing import List class Solution:

return False

return all(

Time Complexity

the input.

return true;

return false;

return true;

type StringPair = [string, string];

// Global variables and function definitions in TypeScript

// Storing the length of the first sentence.

const pairSet: Set<string> = new Set();

pairSet.add(pair[0] + "." + pair[1]);

for (let i = 0; i < sentenceLength; i++) {</pre>

If not, they cannot be similar

if len(sentence1) != len(sentence2):

This allows for O(1) lookup time

for (const pair of similarPairs) {

const sentenceLength: number = sentence1.length;

if (sentenceLength !== sentence2.length) return false;

// Check every word in both sentences for similarity.

};

TypeScript

class is not included here. Time and Space Complexity

Below this point would be code that uses the Solution class and its method,

Since the class itself should only contain the method definition, usage of the

for word1, word2 in zip(sentence1, sentence2)

usually including test cases to demonstrate the implementation.

The time complexity of the given code can be broken down as follows: 1. Checking if len(sentence1) is equal to len(sentence2) takes 0(1) time, as it is simply comparing two integers. 2. Creating a set s from the similarPairs takes O(p) time, where p is the number of similar pairs.

words in each sentence (since we've previously established the sentences are of equal length to reach this point). 4. Each comparison within the list comprehension is 0(1) because checking equality of strings and checking for existence in a set are both

- constant-time operations. Thus, the time complexity is O(n + p), where n is the length of the sentences and p is the number of similar word pairs.
- **Space Complexity**
- The space complexity can be analyzed as follows: 1. The additional set s which stores the similar word pairs requires 0(p) space, where p is the number of similar pairs.

2. The space for input variables sentence1, sentence2, and similarPairs is not counted as extra space as per convention since they are part of

3. The list comprehension iterates over each pair of words from sentence1 and sentence2, which occurs in O(n) time, where n is the number of

As a result, the auxiliary space complexity of the code is O(p).