

# 2183. Count Array Pairs Divisible by K

## Problem Description

Given an array `nums` and an integer `k`, we have to find the number of pairs `(i,j)` such that the product of `nums[i]` and `nums[j]` is divisible by `k`. Note that `k` can be as large as `1e5`.

Here's a high-level approach to solving this problem:

- Calculate the greatest common divisor (gcd) of each value in `nums` with `k`.
- Then, for each pair `(nums[i], nums[j])`, check if their gcd values multiplied together are divisible by `k`. If yes, add them to the count.

Let's walk through an example to better understand the approach.

## Example

Suppose `nums = [1, 2, 3, 4, 5]` and `k = 6`. We first find the gcd values for each element in the array `nums` with `k`.

$1 \times 6 = 6$ ,  $\text{gcd}(1, 6) = 1$   $2 \times 3 = 6$ ,  $\text{gcd}(2, 6) = 2$   $3 \times 2 = 6$ ,  $\text{gcd}(3, 6) = 3$   $4 \times 1.5 = 6$ ,  $\text{gcd}(4, 6) = 2$   $5 \times 1.2 = 6$ ,  $\text{gcd}(5, 6) = 1$

Now the gcd values are `[1, 2, 3, 2, 1]`.

We go through each pair of gcd values and check if their product is divisible by `k`. In our example:

`(1, 2)` - No `(1, 3)` - No `(1, 2)` - No `(1, 1)` - No `(2, 3)` - Yes `(2, 2)` - No `(2, 1)` - No `(3, 2)` - Yes `(3, 1)` - No `(2, 1)` - No

We find two pairs that are divisible by `k`: `(2, 3)` and `(3, 2)`. So the final answer is `2`.

## Solution

### Python

```
python
from math import gcd
from typing import List

class Solution:
    def countPairs(self, nums: List[int], k: int) -> int:
        ans = 0
        gcds = {}

        for num in nums:
            gcd_num = gcd(num, k)
            for gcd_val, count in gcds.items():
                if gcd_num * gcd_val % k == 0:
                    ans += count
            gcds[gcd_num] = gcds.get(gcd_num, 0) + 1

        return ans
```

### Java

```
java
import java.util.HashMap;
import java.util.Map;

class Solution {
    public long countPairs(int[] nums, int k) {
        long ans = 0;
        Map<Integer, Integer> gcds = new HashMap<>();

        for (int num : nums) {
            int gcdNum = gcd(num, k);
            for (Map.Entry<Integer, Integer> entry : gcds.entrySet()) {
                if (gcdNum * entry.getKey() % k == 0) {
                    ans += entry.getValue();
                }
            }
            gcds.put(gcdNum, gcds.getOrDefault(gcdNum, 0) + 1);
        }

        return ans;
    }

    private int gcd(int a, int b) {
        if (b == 0) {
            return a;
        } else {
            return gcd(b, a % b);
        }
    }
}
```

### JavaScript

```
javascript
class Solution {
    countPairs(nums, k) {
        let ans = 0;
        const gcds = new Map();

        for (const num of nums) {
            const gcdNum = this.gcd(num, k);
            for (const [gcdVal, count] of gcds.entries()) {
                if (gcdNum * gcdVal % k === 0) {
                    ans += count;
                }
            }
            gcds.set(gcdNum, (gcds.get(gcdNum) || 0) + 1);
        }

        return ans;
    }

    gcd(a, b) {
        if (b === 0) {
            return a;
        } else {
            return this.gcd(b, a % b);
        }
    }
}
```

### C++

```
cpp
#include <unordered_map>

class Solution {
public:
    long long countPairs(vector<int>& nums, int k) {
        long ans = 0;
        unordered_map<int, int> gcds;

        for (const int num : nums) {
            const int gcdNum = gcd(num, k);
            for (const auto& [gcdVal, count] : gcds) {
                if (gcdNum * gcdVal % k == 0) {
                    ans += count;
                }
            }
            ++gcds[gcdNum];
        }

        return ans;
    }

private:
    int gcd(int a, int b) {
        if (b == 0) {
            return a;
        } else {
            return gcd(b, a % b);
        }
    }
};
```

### C#

```
csharp
using System.Collections.Generic;

public class Solution {
    public long CountPairs(int[] nums, int k) {
        long ans = 0;
        Dictionary<int, int> gcds = new Dictionary<int, int>();

        foreach (int num in nums) {
            int gcdNum = GCD(num, k);
            foreach (KeyValuePair<int, int> entry in gcds) {
                if (gcdNum * entry.Key % k == 0) {
                    ans += entry.Value;
                }
            }
            if (gcds.ContainsKey(gcdNum)) {
                gcds[gcdNum]++;
            } else {
                gcds[gcdNum] = 1;
            }
        }

        return ans;
    }

    private int GCD(int a, int b) {
        if (b == 0) {
            return a;
        } else {
            return GCD(b, a % b);
        }
    }
}
```