2451. Odd String Difference

String

Hash Table

## **Problem Description**

**Easy** 

In this problem, you are given an array of strings words, where all strings are of equal length n. We can imagine that each string is like a sequence of positions from a starting point in the alphabet. For example, "acd" could mean starting at 'a' (position 0), moving to 'c' (position 2), and then to 'd' (position 3).

For each string, we can calculate a difference integer array. This array represents the difference between each adjacent pairs of

characters in the alphabet. So, for a string words [i], we calculate difference[i][j] as the difference in the alphabet positions between words[i][j+1] and words[i][j], for all j from 0 up to n - 2. Example: For the string "acd", the difference integer array would be [2, 1] because that's the difference between 'c' and 'a' (2)

and 'd' and 'c' (1). The key point to remember is that we're only looking at the relative differences between neighboring characters, not absolute positions. All strings in the array words have the same difference integer array except for one string. Your task is to return the string whose

difference integer array does not match with the others.

Intuition

difference integer array, our job is to find which one doesn't fit with the others.

## The solution works on the principle of grouping and counting. Since we know that all strings except one will form the same

How can we find the odd one out? We can use a defaultdict from Python's collections module to group the strings based on their difference integer arrays. We calculate the difference integer array for each string, use it as a key, and append the string to the associate list in the dictionary. Since the difference integer array is used for grouping, we need it to be a hashable type,

hence we create a tuple (t) from it. For example, if "abc" and "def" both yield a difference integer array of [1, 1], they will be added to the same list in the dictionary under the key (1, 1). After we group all the strings, we look through the dictionary's values. The odd string out will be the only string in its group, so we

look for any list in the dictionary with a length of 1. This list contains our odd string, and that's the one we return.

Solution Approach The provided solution follows these steps to find the string that has a different difference integer array:

Importing Necessary Modules: The solution begins by importing defaultdict from the collections module, which allows for

## Compute the Difference Tuples: It iterates over each string s in the words array and computes the difference tuple t using a

generator expression. The expression ord(b) - ord(a) is used for each adjacent pair (a, b) of characters in the string,

easy grouping without having to initialize empty lists manually for each new key.

where ord() is a built-in Python function that returns the ASCII value (or position in the alphabet for lowercase letters) of the character.

Group Strings by their Difference Tuples: Using the difference tuple t as a key, the solution then appends the current string

s to a list in the dictionary d. This effectively groups all strings that produce the same difference tuple together. Find the Unique String: Finally, the solution uses a generator expression with a next() function to iterate over the dictionary's values. It searches for the first list ss that has a length of 1, indicating that it contains the unique string. Once it finds such a list, it retrieves the first (and only) string from that list, which is the string with a different difference integer array.

Notably, the code uses pairwise from the itertools module, which is not directly available in the provided code. If this function

were available or implemented, it would pair adjacent elements of s, facilitating the calculation of differences.

O(n) operations, where n is the length of the strings. The lookup and insertion times for a defaultdict are typically O(1). Here's a breakdown of the data structures and patterns used:

The algorithm complexity is primarily determined by the iteration over the strings and the difference calculation, which are both

• Next Function: A pythonic way to retrieve the first element of an iterator that satisfies a certain condition. The solution effectively uses these Python features to group strings and find the unique one in a concise and expressive manner.

**Example Walkthrough** 

Let's take a set of strings words = ["abc", "bcd", "ace", "xyz", "bbb"] as a small example to illustrate the solution approach.

group, we find that "ace" is the string with a different difference integer array.

• Generator Expressions: Used to efficiently compute difference tuples without needing intermediate lists.

• Tuples: Immutable and hashable, allowing them to be used as dictionary keys for grouping.

• Defaultdict: A convenient way to group strings without manual checks for the existence of dictionary keys.

• For "bcd": differences are (c-b, d-c), which is (1, 1). • For "ace": differences are (c-a, e-c), which is (2, 2).

1. First, we compute the difference integer arrays (which will be stored as tuples) for each string. These tuples represent the differences in

2. We then group the strings by difference tuples using a defaultdict, resulting in a dictionary with difference tuples as keys and lists of corresponding strings as values:

By inspecting the dictionary, we can see the group that contains only a single string is the one with the key (2, 2), which

Therefore, by using a generator expression with the next() function to search for the first occurrence of such a one-string

"ace" is returned as the odd one out string. So, using this grouping and counting strategy with efficient Python data structures and expressions, we identified that "ace" is the string whose difference integer array does not match with the others in a clear and concise way.

Solution Implementation

**Python** 

class Solution:

Each string has a length of n = 3.

position between each pair of adjacent characters:

• For "abc": differences are (b-a, c-b), which is (1, 1).

• For "xyz": differences are (y-x, z-y), which is (1, 1).

• For "bbb": differences are (b-b, b-b), which is (0, 0).

(1, 1): ["abc", "bcd", "xyz"],

corresponds to the string "ace".

(2, 2): ["ace"],

(0, 0): ["bbb"]

- from collections import defaultdict from itertools import pairwise
- # Compute the pattern of the word based on the pairwise differences # of the ASCII values of characters pattern = tuple(ord(second\_char) - ord(first\_char) for first\_char, second\_char in pairwise(word))

for word in words:

def oddString(self, words: List[str]) -> str:

pattern\_to\_words = defaultdict(list)

# Create a dictionary to map string patterns to strings

# Append the original word to the list of words for this pattern

# If a list contains only one word, return this word as it is the odd one out

# Iterate over each list of words associated with the same pattern

for words\_with\_same\_pattern in pattern\_to\_words.values():

# Iterate over each string in the list of words

pattern\_to\_words[pattern].append(word)

if len(words\_with\_same\_pattern) == 1:

// Iterate over the entries in the map.

if (wordsWithSameDifference.size() == 1) {

return wordsWithSamePattern[0];

// If no unique pattern is found, return an empty string

// Map to keep track of strings with the same character difference pattern

return wordsWithSameDifference.get(0);

// If no "odd" string is found, return an empty string.

for (List<String> wordsWithSameDifference : differenceMap.values()) {

// If a particular difference sequence is unique to one word, return that word.

return words\_with\_same\_pattern[0]

```
# If no word is found that satisfies the condition, i.e., being the only one
# of its pattern, (which theoretically shouldn't happen given the problem's constraints),
# an explicit return is not required as functions return None by default when no return is hit
```

Java

class Solution {

```
/**
* Method to find the "odd" string in a given array of words. The "odd" string is defined as the
* one which doesn't have any other string in the array with the same sequence of differences
* between consecutive characters.
* @param words An array of strings to process.
* @return The "odd" string if it exists, or an empty string otherwise.
*/
public String oddString(String[] words) {
   // Create a dictionary to map the difference sequence to a list of strings that share it.
   HashMap<String, List<String>> differenceMap = new HashMap<>();
   // Iterate over each word in the array.
    for (String word : words) {
        int length = word.length();
       // Create an array to store the differences in ASCII values between consecutive characters.
       char[] differenceArray = new char[length - 1];
        for (int i = 0; i < length - 1; ++i) {
            // Calculate the difference and store it in the array.
           differenceArray[i] = (char) (word.charAt(i + 1) - word.charAt(i));
       // Convert the difference array to a string to use as a key in the map.
       String differenceKey = String.valueOf(differenceArray);
       // If the key is not present in the map, create a new list for it.
       differenceMap.putIfAbsent(differenceKey, new ArrayList<>());
       // Add the current word to the list corresponding to its difference sequence.
        differenceMap.get(differenceKey).add(word);
```

C++

return "";

```
#include <vector>
#include <string>
#include <unordered_map>
class Solution {
public:
   // This function finds and returns the word from the given words vector that has no matching pattern
    string oddString(vector<string>& words) {
       // Dictionary to map a pattern to a list of words that share the same pattern
       unordered_map<string, vector<string>> patternToWords;
       // Process each word in the vector
        for (auto& word : words) {
            int length = word.size(); // Length of the current word
            string pattern(length - 1, 0); // Create a pattern string
           // Create a pattern based on the difference in ASCII values
           // between consecutive characters in the word
            for (int i = 0; i < length - 1; ++i) {
                // Subtract consecutive characters and store it in the pattern
                pattern[i] = word[i + 1] - word[i];
            // Add the word to the dictionary based on its pattern
            patternToWords[pattern].push_back(word);
        // Iterate through the mapped dictionary to find a unique pattern
        for (auto& kv : patternToWords) { // kv is a pair consisting of a pattern and a list of words
            auto& wordsWithSamePattern = kv.second; // Get the list of words with the same pattern
           // If there's only one word with this pattern, that's our "odd" word
            if (wordsWithSamePattern.size() == 1) {
```

return "";

function oddString(words: string[]): string {

**}**;

**TypeScript** 

```
const patternMap: Map<string, string[]> = new Map();
      // Iterate over each word
      for (const word of words) {
          // Array to hold the character difference pattern
          const charDifferences: number[] = [];
          // Compute consecutive character differences for the current word
          for (let i = 0; i < word.length - 1; ++i) {
              charDifferences.push(word.charCodeAt(i + 1) - word.charCodeAt(i));
          // Convert the character differences to a string, joining with commas
          const pattern = charDifferences.join(',');
          // If the pattern is not already in the map, initialize it with an empty array
          if (!patternMap.has(pattern)) {
              patternMap.set(pattern, []);
          // Add the current word to the array of words that match the same pattern
          patternMap.get(pattern)!.push(word);
      // Find the odd string out i.e., a string whose pattern is unique
      for (const wordGroup of patternMap.values()) {
          if (wordGroup.length === 1) { // The odd string will be the only one in its group
              return wordGroup[0];
      // If there's no odd string found, return an empty string
      return '';
from collections import defaultdict
from itertools import pairwise
class Solution:
   def oddString(self, words: List[str]) -> str:
       # Create a dictionary to map string patterns to strings
        pattern to words = defaultdict(list)
       # Iterate over each string in the list of words
        for word in words:
            # Compute the pattern of the word based on the pairwise differences
            # of the ASCII values of characters
            pattern = tuple(ord(second_char) - ord(first_char) for first_char, second_char in pairwise(word))
            # Append the original word to the list of words for this pattern
            pattern_to_words[pattern].append(word)
```

## Time and Space Complexity **Time Complexity**

The given code block consists of the following operations:

if len(words\_with\_same\_pattern) == 1:

return words\_with\_same\_pattern[0]

# Iterate over each list of words associated with the same pattern

# If a list contains only one word, return this word as it is the odd one out

# of its pattern, (which theoretically shouldn't happen given the problem's constraints),

# an explicit return is not required as functions return None by default when no return is hit

# If no word is found that satisfies the condition, i.e., being the only one

for words\_with\_same\_pattern in pattern\_to\_words.values():

consecutive pair of characters in the word. If the average length of the words is M, this part has a complexity of O(M). Therefore, the loop overall has a complexity of O(N \* M). • A next function is then used with a generator expression to find the first tuple t with only one associated word in the dictionary d. In the worst

case scenario, this operation will go through all the tuples generated, with a complexity of O(N), since there could be up to N unique tuples if all words are distinct. As a result, the total time complexity of this code block would be 0(N \* M) + 0(N), which simplifies to 0(N \* M) since M (the

• A loop that iterates through each word in the input list words: This will have an O(N) complexity, where N is the total number of words in words.

• Inside the loop, for each word, it calculates the tuple t using the pairwise function and a list comprehension, which iterates through each

- average length of a single word) is usually much smaller than N or at least M is considered constant for relatively short strings compared to the number of words.
- **Space Complexity** The space complexity is affected by:

difference tuples, the space used would be O(N \* M), where M is the average length of word lists associated with each tuple. However, the

• The dictionary d which stores tuples of integers as keys and lists of strings as values. In the worst-case scenario, if all words have unique

tuples and words themselves just keep references to already existing strings and characters, so we can consider that storing the tuples would at worst be O(N). • The space used by the list comprehension inside the loop does not add to the space complexity since it's used and discarded at each iteration.

Thus, the space complexity would be dominated by the dictionary d storing elements. So the space complexity of the code is O(N).