Problem Description

new index in one of three ways. They can jump to the next index (i + 1), jump back to the previous index (i - 1), or jump to any index j that contains the same value as the current index (arr[i] == arr[j] and i != j). The goal is to determine the minimum number of steps required to reach the last index of the array. It is important to note that jumps can only occur within the bounds of the array, meaning that the character cannot jump to an index outside of the array.

The problem involves an array of integers arr and a character that starts at the first index of the array. This character can jump to a

Intuition

steps. BFS is suitable for this kind of problem because it explores the nearest neighbors first and only goes deeper once there are no more neighbors to explore. Given this approach, we start from the first index and explore all possible jumps. To avoid revisiting indices and getting stuck in loops, we use a visited set (vis) to keep track of which indices have already been explored. Also, to avoid repeatedly performing the same jumps, we use a dictionary (idx) that maps each value to its indices in the array. As we progress, we store in a queue (a) each index we can jump to, along with the number of steps taken to reach there. Once the jump to the last index is made, we return the number of steps that led to it as the result. To make the BFS efficient, after checking all

To arrive at the solution, we use breadth-first search (BFS) as the main strategy since the goal is to find the minimum number of

indices that have the same value as the current index, we delete the entry from the idx dictionary to prevent redundant jumps in the future. This speeds up the BFS process significantly, as it reduces the number of potential jumps that are not helpful in reaching the end of the array quickly. Solution Approach

To solve this problem, the code uses the Breadth-First Search (BFS) algorithm, which is a standard approach for finding the shortest

path in an unweighted graph or the fewest number of steps to reach a certain point.

Here's a walkthrough of the implementation:

1. Index Dictionary (idx): A defaultdict from Python's collections module is used to create a dictionary where each value in the array is a key, and the corresponding value is a list of all indices in the array with that value.

```
idx[v].append(i)
```

1 idx = defaultdict(list)

2 for i, v in enumerate(arr):

2. Queue (q): A queue is implemented with deque from the collections module, and it's initialized with a tuple containing the starting index (0) and the initial step count (0). 1 q = deque([(0, 0)])

```
3. Visited Set (vis): A set is used to keep track of the indices that have been visited. This prevents the algorithm from processing
```

an index more than once and ensures not to get caught in an infinite loop. 1 $vis = \{0\}$

4. BFS Loop: The algorithm processes the queue q until it's empty, doing the following: It dequeues an element, which is a tuple of the current index (i) and the number of steps taken to reach this index (step).

All indices j in the array where arr[i] == arr[j] are added to the queue, with the number of steps incremented by 1, and

After processing all jumps to the same value, that value is deleted from idx to prevent future unnecessary jumps to those

□ The algorithm then looks to add the neighbor indices 1 + 1 and 1 - 1 to the queue (if they haven't been visited yet).

```
If the dequeued index is the last index of the array, the number of steps is immediately returned.
```

indices.

marked as visited.

1 while q: i, step = q.popleft() **if** i == len(arr) - 1:

```
return step
           v = arr[i]
           step += 1
           for j in idx[v]:
                if j not in vis:
                    vis.add(j)
                    q.append((j, step))
    10
            del idx[v]
    11
            if i + 1 < len(arr) and (i + 1) not in vis:
    12
    13
               vis.add(i + 1)
           q.append((i + 1, step))
if i - 1 \ge 0 and (i - 1) not in vis:
    14
    15
                vis.add(i - 1)
    16
                q.append((i - 1, step))
    17
By employing BFS, which explores all possible paths breadthwise and visits each node exactly once, the solution finds the minimum
number of steps needed to reach the last index of the array.
Example Walkthrough
Let's walk through a small example to illustrate the solution approach for the array arr = [100, 23, 23, 100, 23, 100].
```

2. Initialize the Queue (q): We start with the first index and 0 steps as we haven't yet taken any steps. \circ q = deque([(0, 0)])

1. Initialize the Index Dictionary (idx): We create a dictionary mapping each value in the array to a list of all indices in the array

Dequeue (0, 0). Current index i = 0, steps taken step = 0.

 \circ vis = {0}

4. Begin the BFS Loop:

with that value.

 \circ idx[100] = [0, 3, 5]

 \circ idx[23] = [1, 2, 4]

■ We found the value 100 at index 0. Indices with value 100 are [0, 3, 5].

■ Remove 100 from the idx dictionary to prevent future jumps to these indices: del idx[100].

3. Initialize the Visited Set (vis): To begin, we've only visited the start index 0.

Queue up index 3 and 5 with step+1 since 0 is already visited.

Value at index 3 is 100, but we've already deleted it from idx.

Dequeue (3, 1). Current index i = 3, steps taken step = 1.

from collections import defaultdict, deque

def min jumps(self, arr: List[int]) -> int:

for index, value in enumerate(arr):

index_map[value].append(index)

if position == len(arr) - 1:

return step_count

Set to keep track of visited nodes to avoid cycles

Increment the count of steps for the next jump

// Increment step count for next potential moves.

queue.offer(new int[] {index, stepCount});

// We remove this value from the map to prevent revisiting.

// Check and add unseen next and previous indices to the queue.

queue.offer(new int[] {currentIndex + 1, stepCount});

queue.offer(new int[] {currentIndex - 1, stepCount});

if (currentIndex + 1 < n && !visited.contains(currentIndex + 1)) {</pre>

if (currentIndex - 1 >= 0 && !visited.contains(currentIndex - 1)) {

// If we've exhausted all options and haven't reached the end, return -1.

if (!visited.contains(index)) {

visited.add(index);

indexMap.remove(arr[currentIndex]);

visited.add(currentIndex + 1);

visited.add(currentIndex - 1);

// Function to find the minimum number of jumps required to reach

// Populate the index map with the indices for each value.

bfsQueue.emplace(0, 0); // Start from the first element.

// Set to keep track of visited indices to avoid revisits.

// Queue to perform BFS, holding pairs of the index in arr and the number of steps taken.

// length of jump we can make from that position.

indexMap[arr[i]].push_back(i);

std::queue<std::pair<int, int>> bfsQueue;

// Map to hold the indices for each value in arr.

std::unordered_map<int, std::vector<int>> indexMap;

int minJumps(std::vector<int>& arr) {

for (int i = 0; i < n; ++i) {

std::unordered set<int> visited;

while (!bfsQueue.empty()) {

int n = arr.size();

visited.insert(0);

// Perform BFS.

// the last index of the array where each element indicates the maximum

// Get all indices with the same value and add unseen ones to the queue.

for (int index : indexMap.getOrDefault(arr[currentIndex], new ArrayList<>())) {

stepCount++;

return -1;

index_map = defaultdict(list)

queue = deque([(0, 0)])

step_count += 1

visited = set([0])

from typing import List

class Solution:

9

10

11

12

13

14

15

16

21

22

23

24

25

26

31

32

33

34

35

37

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

C++ Solution

#include <vector>

#include <queue>

class Solution {

public:

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

2 #include <unordered_map>

#include <unordered_set>

• Update queue: q = deque([(3, 1), (5, 1)]) and $vis = \{0, 3, 5\}$.

```
    We check the neighbors, and 4 has not been visited, so we queue it up.

          • Update queue: q = deque([(5, 1), (4, 2)]) and vis = \{0, 3, 4, 5\}.

    Dequeue (5, 1). Current index i = 5, steps taken step = 1.

    We've reached the last index of the array, so we return the number of steps: 1.

In this example, by using BFS and our optimizations, we've found that we can reach the end of the array arr in just 1 step through
the value jumps. We can jump directly from the first index to the last index since they share the same value of 100.
Python Solution
```

Initialize a dictionary to keep track of indices for each value in the array

If the end of the array is reached, return the count of steps

Initialize a queue with a tuple containing the start index and initial step count

17 # Process the queue until empty while queue: 18 19 position, step_count = queue.popleft() 20

```
27
28
                # Jump to all indexes with the same value as the current position
                value = arr[position]
29
                for next_position in index_map[value]:
30
```

```
if next_position not in visited:
 31
 32
                         visited.add(next_position)
 33
                         queue.append((next_position, step_count))
 34
 35
                 # Since all jumps for this value are done, clear the index list to prevent future jumps to the same value
 36
                 del index_map[value]
 37
 38
                 # Add the next consecutive index to the queue if it hasn't been visited
 39
                 if position + 1 < len(arr) and (position + 1) not in visited:</pre>
 40
                     visited.add(position + 1)
 41
                     queue.append((position + 1, step_count))
 42
 43
                 # Add the previous index to the queue if it hasn't been visited and it's within bounds
                 if position - 1 >= 0 and (position - 1) not in visited:
 44
 45
                     visited.add(position - 1)
 46
                     queue.append((position - 1, step_count))
 47
 48
             return -1 # If end is not reached, return -1 (this part of code should not be reached).
 49
 50 # Example usage:
 51 # sol = Solution()
    # print(sol.min_jumps([100, -23, -23, 404, 100, 23, 23, 23, 3, 404]))
 53
Java Solution
  1 class Solution {
  3
         // Finds minimum number of jumps to reach the end of the array.
         public int minJumps(int[] arr) {
  4
             // Hash map to store indices of values in the array.
             Map<Integer, List<Integer>> indexMap = new HashMap<>();
             int n = arr.length;
  8
             // Populate the hash map with indices for each value.
  9
             for (int i = 0; i < n; ++i) {
 10
                 indexMap.computeIfAbsent(arr[i], k -> new ArrayList<>()).add(i);
 11
 12
 13
 14
             // Queue for BFS, each element is a pair: [current index, current step count].
 15
             Deque<int[]> queue = new LinkedList<>();
 16
             // Set to keep track of visited indices.
 17
             Set<Integer> visited = new HashSet<>();
 18
 19
             // Start BFS with the first index.
             visited.add(0);
 20
 21
             queue.offer(new int[] {0, 0});
 22
 23
             // BFS to find minimum steps.
             while (!queue.isEmpty()) {
 24
                 int[] element = queue.pollFirst();
 25
                 int currentIndex = element[0], stepCount = element[1];
 26
 27
 28
                 // If we've reached the end of the array, return the step count.
                 if (currentIndex == n - 1) {
 29
 30
                     return stepCount;
```

34 35 36 37

```
31
                 auto current = bfsQueue.front();
 32
                 bfsQueue.pop();
 33
                 int currentIndex = current.first, steps = current.second;
                 // If we have reached the last index, return the number of steps.
                 if (currentIndex == n - 1) return steps;
 38
                 // Number of steps to reach the next index.
 39
                 ++steps;
                 int currentValue = arr[currentIndex];
 40
 41
                 // If we can jump to any index with the same value as currentValue.
 42
 43
                 if (indexMap.count(currentValue)) {
 44
                     for (int nextIndex : indexMap[currentValue]) {
 45
                         if (!visited.count(nextIndex)) {
 46
                             visited.insert(nextIndex);
 47
                             bfsQueue.emplace(nextIndex, steps);
 48
 49
 50
                     // To avoid unnecessary iterations in the future, erase the value from the map.
                     indexMap.erase(currentValue);
 51
 52
 53
                 // Check the possibilities of jumping to adjacent indices.
 54
 55
                 if (currentIndex + 1 < n && !visited.count(currentIndex + 1)) {</pre>
 56
                     visited.insert(currentIndex + 1);
 57
                     bfsQueue.emplace(currentIndex + 1, steps);
 58
                 if (currentIndex - 1 >= 0 && !visited.count(currentIndex - 1)) {
 59
                     visited.insert(currentIndex - 1);
 60
                     bfsQueue.emplace(currentIndex - 1, steps);
 61
 62
 63
 64
 65
             return -1; // If it's not possible to reach the end, return -1.
 66
 67 };
 68
Typescript Solution
     type IndexStepsPair = { index: number; steps: number };
     function minJumps(arr: number[]): number {
       // Map to hold the indices for each value in arr.
       const indexMap: Record<number, number[]> = {};
       const n: number = arr.length;
       // Populate the index map with the indices for each value.
       for (let i = 0; i < n; i++) {
  9
         if (!(arr[i] in indexMap)) {
 10
 11
           indexMap[arr[i]] = [];
 12
 13
         indexMap[arr[i]].push(i);
 14
 15
 16
       // Queue to perform BFS, holding pairs of the index in arr and the number of steps taken.
       const bfsQueue: IndexStepsPair[] = [{ index: 0, steps: 0 }];
 17
 18
       // Set to keep track of visited indices to avoid revisits.
 19
       const visited: Set<number> = new Set();
 20
 21
       visited.add(0);
 22
 23
       // Perform BFS.
       while (bfsQueue.length > 0) {
 24
 25
         const current = bfsQueue.shift()!; // Assumed to not be undefined
 26
         const currentIndex = current.index;
 27
         let steps = current.steps;
 28
 29
         // If we have reached the last index, return the number of steps.
 30
         if (currentIndex === n - 1) {
 31
           return steps;
 32
 33
```

59 60 return -1; 61 62

Time and Space Complexity

// Number of steps to reach the next index.

for (const nextIndex of indexMap[arr[currentIndex]]) {

// Check the possibilities of jumping to adjacent indices.

bfsQueue.push({ index: nextIndex, steps: steps });

// To avoid unnecessary iterations in the future, delete the value from the map.

dictionary ensures that each value's list is iterated over at most once, hence, contributing to E.

if (indexMap[arr[currentIndex]]) {

visited.add(nextIndex);

if (!visited.has(nextIndex)) {

delete indexMap[arr[currentIndex]];

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

steps++;

if (currentIndex + 1 < n && !visited.has(currentIndex + 1)) {</pre> 49 visited.add(currentIndex + 1); 50 bfsQueue.push({ index: currentIndex + 1, steps: steps }); 51 52 53 if (currentIndex - 1 >= 0 && !visited.has(currentIndex - 1)) { 54 visited.add(currentIndex - 1); bfsQueue.push({ index: currentIndex - 1, steps: steps }); 55 56 57 58 // If it's not possible to reach the end, return -1.

The space complexity is O(N) as we need to store the indices in the idx dictionary, which in the worst case will store all indices, and the vis set, which also could potentially store all indices if they are visited. The queue could also hold up to N-1 elements in the

The time complexity of the provided code is O(N + E) where N is the number of elements in arr and E is the total number of edges in

the graph constructed where each value in arr has edges to indices with the same value. The while loop runs for each index in arr

once, and each index is added to the queue at most once. The inner loops contribute to the edges. Deletion of keys in the idx

worst case scenario.