

81. Search in Rotated Sorted Array II

Description

There is an integer array `nums` sorted in non-decreasing order (not necessarily with **distinct** values).

Before being passed to your function, `nums` is **rotated** at an unknown pivot index `k` ($0 \leq k < \text{nums.length}$) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1], nums[0], nums[1], ..., nums[k-1]]` (**0-indexed**). For example, `[0,1,2,4,4,4,5,6,6,7]` might be rotated at pivot index `5` and become `[4,5,6,6,7,0,1,2,4,4]`.

Given the array `nums` **after** the rotation and an integer `target`, return `true` *if* `target` *is in* `nums`, *or* `false` *if it is not in* `nums`.

You must decrease the overall operation steps as much as possible.

Example 1:

Input: `nums = [2,5,6,0,0,1,2]`, `target = 0`

Output: `true`

Example 2:

Input: `nums = [2,5,6,0,0,1,2]`, `target = 3`

Output: `false`

Constraints:

- $1 \leq \text{nums.length} \leq 5000$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- `nums` is guaranteed to be rotated at some pivot.
- $-10^4 \leq \text{target} \leq 10^4$

Follow up: This problem is similar to [Search in Rotated Sorted Array](#), but `nums` may contain **duplicates**. Would this affect the runtime complexity? How and why?

