2375. Construct Smallest Number From DI String

String] Medium Stack Backtracking Greedy

In this problem, you're given a string pattern consisting of characters 'I' and 'D'. The 'I' stands for "increasing" and 'D' for "decreasing". Based on this pattern, you need to create another string num that follows these rules:

Leetcode Link

- 1. String num is formed by the digits '1' to '9', each digit can only be used once. 2. If pattern[i] == 'I', then the ith element of num must be less than the (i+1)th element.
- 3. If pattern[i] == 'D', then the ith element of num must be greater than the (i+1)th element.
- The goal is to find the lexicographically smallest string num that satisfies the given pattern.
- Intuition

Problem Description

When we are at index u in the num string, we have some options to consider for num[u]. We can choose any digit from '1' to '9', but only if that digit has not been used before (because each digit should appear at most once), and it must also satisfy the increasing or decreasing conditions as per the pattern.

To solve this problem, we can use a backtracking approach which is a type of depth-first search (DFS). The main idea is to build the

string num one digit at a time, choosing the smallest possible digit at each step that satisfies the pattern requirement.

As soon as we place a digit at index u, we recursively call the function to handle index u+1. If we reach the end of the pattern and have built a valid num string, we store the result and stop the search.

step. If at any step, no digit satisfies the condition, we backtrack, which means we undo the last step and try a different digit.

This process continues until all the possibilities are explored, or we find the answer. As soon as the answer is found, we stop the search to ensure we have the lexicographically smallest solution.

The reason why this generates the lexicographically smallest num is that we always try to place the smallest possible digit at each

The solution approach uses a backtracking algorithm, which is implemented through a recursive function named dfs. It explores all possible combinations of the digits from '1' to '9' to build the string num. Here's a run-down of the key aspects of the backtracking approach:

1. The recursion is controlled by the function dfs(u), where u represents the current index in num that we are trying to fill.

2. A list vis of length 10 is used to keep track of the digits that have been used so far. vis[i] is True if the digit i is already used in the string.

last placed digit t [-1].

the solution is found.

smallest num that follows this pattern.

Solution Approach

3. The t list is used to construct the num string in progress. When a digit is placed at index u, it is appended to t. 4. The base case of the recursion occurs when u == len(pattern) + 1. This means we have filled all the positions in num and we have a candidate solution. We then join all the characters in t to form the string ans, and the search is halted since we only want

the lexicographically smallest solution.

Similarly, if the pattern at u−1 is 'D', the digit i should be less than t[-1].

available digit, '1'. Before we move on to the next index, we mark '1' as used in vis.

If either condition is not satisfied, it skips the current digit.

from t (backtracking) so that future recursive calls can consider it.

5. Within the recursive function, a for-loop iterates through digits i from 1 to 9 to try each as the next character of num. For each digit, there are two main conditions to check:

∘ If the current index u is not zero and the pattern at u-1 is 'I', the current digit i should only be placed if it is greater than the

6. If the digit i satisfies the condition, it is marked as visited (vis[i] = True), added to the temporary list t, and the function recursively calls itself with the next index (dfs(u + 1)).

7. After the recursive call returns, whether it found a solution or not, the chosen digit is unmarked (vis[i] = False) and removed

8. The recursion and backtracking continue until all valid digit permutations that meet the pattern conditions are explored or until

Example Walkthrough

Let's consider a small example to illustrate the solution approach using the pattern "IDID". Our aim is to find the lexicographically

The ans variable is used to store the lexicographically smallest number that is formed. Since the algorithm always tries the smallest

digit first and goes in increasing order, it ensures that the first complete number that is formed will be the lexicographically smallest.

1. Start with an empty num string and vis list initializing all elements to 'False' indicating that no digits have been used yet. 2. Call dfs(0) to fill num[0]. At this stage, our num string and the pattern look like this: num = "", pattern = "IDID".

3. Since u is 0, we don't have any previous digits in num. We can choose any digit from 1 to 9. We start by choosing the smallest

4. Now, we recursively call dfs(1). The pattern at u - 1 (pattern[0]) is 'l', which means we need num[1] to be greater than '1'. The smallest available digit that satisfies this is '2'. num now looks like this: num = "12".

5. Next, we call dfs(2). The pattern at u - 1 (pattern[1]) is 'D'. Hence, num[2] needs to be less than '2'. We choose the smallest

6. With num = "121", we recursively call dfs(3). The pattern at u - 1 (pattern[2]) is 'l', so num[3] should be greater than '1'. The

smallest available digit is '2', but it's already used. The next smallest available is '3', so we choose '3' and num becomes "1213".

8. Since we attempt to place the digits in increasing order and stop once the valid num is completed, we guarantee that our solution

available digit that is less than '2', which is '1', but since '1' is already used, our next available smallest option is '3', this does not

satisfy the condition so we move to the next digit which is not used that satisfies the 'D', which is '1'.

class Solution:

6

12

13

14

15

16

17

18

19

20

21

22

23

27

28

29

30

31

32

33

34

35

36

37

5

6

8

9

10

11

53

54

55

57

4

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

38

6

8

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

};

37 };

56 }

C++ Solution

public:

1 class Solution {

string pattern;

dfs(0);

void dfs(int index) {

return;

string smallestNumber = "";

vector<bool> visited;

string tempNumber = "";

return smallestNumber;

string smallestNumber(string pattern) {

visited[i] = true;

tempNumber.pop_back();

dfs(index + 1);

2 function smallestNumber(pattern: string): string {

const patternLength = pattern.length;

tempNumber += to_string(i);

visited[i] = false;

const result = new Array(patternLength + 1).fill('');

const visited = new Array(patternLength + 1).fill(false);

// If no valid number is found, backtrack

// Once the DFS is complete, fill in the last available number in the result

result[patternLength] = i; // The last number in the result should be the unvisited number

depthFirstSearch(i, currentNum + 1);

// Convert the result array to a string and return it

of the pattern string (n) and the branching factor at each step of the recursion.

visited[currentNum] = false;

// Start the DFS with the first number being 1

for (let i = 1; i <= patternLength + 1; i++) {</pre>

// Visited array to keep track of used digits

// To store the answer

// Entry function to find the smallest number satisfying the pattern

for (int i = 1; i < 10; ++i) { // Loop through digits 1 to 9

// Result array to hold the sequence of digits forming the smallest number

if (!visited[i]) { // If digit i has not been used

// Recursive function to perform DFS and find the solution

visited.assign(10, false); // All digits are initially not visited

// To store the input pattern

this->pattern = pattern; // Initialize the class member with the input pattern

if (smallestNumber != "") return; // If already found the solution, exit the function

if (index == pattern.size() + 1) { // If the size of tempNumber is correct

smallestNumber = tempNumber; // Assign tempNumber to smallestNumber

// To keep track of visited digits

// Temporary number for DFS traversal

// Start the Depth-First Search (DFS) from index 0

// Return the smallest number that satisfies the pattern

// Skip if current pattern requires increase and the last digit in tempNumber is not less than i

// Skip if current pattern requires decrease and the last digit in tempNumber is not greater than i

// Append digit i to the tempNumber

// Backtrack: mark digit i as not visited

// Backtrack: remove the last digit from tempNumber

if (index > 0 && pattern[index - 1] == 'I' && tempNumber.back() - '0' >= i) continue;

if (index > 0 && pattern[index - 1] == 'D' && tempNumber.back() - '0' <= i) continue;</pre>

// Mark digit i as visited

// Recur for the next index

is the lexicographically smallest possible num.

def dfs(position):

if smallest:

return

visited = [False] * 10

Start DFS from the first digit

// Array to keep track of visited digits

// String to store the given pattern

private String pattern;

private String answer;

private boolean[] visited = new boolean[10];

// String to store the final answer sequence

public String smallestNumber(String pattern) {

// StringBuilder to construct the sequence incrementally

private StringBuilder sequence = new StringBuilder();

current_number = []

smallest = None

for digit in range(1, 10):

if not visited[digit]:

continue

continue

nonlocal smallest

In summary, the smallest num that follows the pattern "IDID" is "1213".

def smallest_number(self, pattern: str) -> str:

Helper function for depth-first search to build valid numbers

Try all possible digits from 1 to 9 for the next character

If a valid number is found, stop further search

7. Finally, we call dfs(4). Since we're at the end of the pattern, we've generated a valid num that adheres to the rules. The recursion base case is reached and we store num = "1213" as ans.

- **Python Solution**
- 8 return # Check if all positions are filled satisfying the pattern 9 if position == len(pattern) + 1: 10 smallest = ''.join(current_number) 11

If 'I' is encountered, the digit must be greater than the previous digit

If 'D' is encountered, the digit must be smaller than the previous digit

Backtrack: unmark the digit and remove it from the current number

Mark the digit as used and add it to the current number

if position and pattern[position - 1] == 'I' and int(current_number[-1]) >= digit:

if position and pattern[position - 1] == 'D' and int(current_number[-1]) <= digit:</pre>

24 current_number.append(str(digit)) 25 # Recursively continue to the next position 26 dfs(position + 1)

visited[digit] = False

Initialize the list to keep track of visited digits

Initialize the list to construct the current number

Variable to keep track of the smallest number found

current_number.pop()

visited[digit] = True

```
38
           dfs(0)
           # Return the smallest number that fits the given pattern
39
40
           return smallest
41
```

Java Solution

1 class Solution {

```
12
            this.pattern = pattern;
13
           // Starting the depth-first search (DFS)
           dfs(0);
14
15
           // Return the final answer sequence
16
            return answer;
17
18
19
       // Helper method for the DFS
20
       private void dfs(int position) {
           // If an answer is already found, stop the recursion
21
           if (answer != null) {
22
23
                return;
24
25
            // If the length of sequence equals the length of pattern + 1, we have a complete sequence
26
            if (position == pattern.length() + 1) {
27
                // Set the current sequence as the answer
28
                answer = sequence.toString();
29
                return; // Stop further recursion
30
31
           // Iterate through all possible digits (1 to 9)
32
            for (int i = 1; i < 10; ++i) {
                // If the current digit i has not been used yet
33
34
                if (!visited[i]) {
35
                    // If the last added digit should be less according to the pattern 'I'
36
                    if (position > 0 && pattern.charAt(position - 1) == 'I' && sequence.charAt(position - 1) - '0' >= i) {
37
                        continue; // Skip this digit since it would break the pattern
38
                    // If the last added digit should be more according to the pattern 'D'
39
40
                    if (position > 0 && pattern.charAt(position - 1) == 'D' && sequence.charAt(position - 1) - '0' <= i) {</pre>
                        continue; // Skip this digit since it would break the pattern
41
42
43
                    // Mark the digit as used
44
                    visited[i] = true;
45
                    // Add the digit to the sequence
                    sequence.append(i);
46
                    // Recurse to the next position with updated sequence and visited digits
47
48
                    dfs(position + 1);
49
                    // Backtrack: remove the last digit from the sequence
50
                    sequence.deleteCharAt(sequence.length() - 1);
51
                    // Mark the digit as not used (undo the previous marking)
52
                    visited[i] = false;
```

Typescript Solution 1 // Function to find the smallest number that matches the given pattern

```
// Depth-first search function to build the result sequence
 9
10
       // i: current position in the pattern, currentNum: current digit to consider
11
        const depthFirstSearch = (i: number, currentNum: number) => {
12
           // Base case: if we've reached the end of the pattern, return
13
            if (i === patternLength) {
14
                return;
15
16
17
            // If currentNum has been used, backtrack and try a different number
18
           if (visited[currentNum]) {
19
                visited[currentNum] = false;
20
                if (pattern[i] === 'I') { // 'I' means increasing; we go backwards with a smaller number
                    depthFirstSearch(i - 1, currentNum - 1);
21
22
                } else { // 'D' means decreasing; we go backwards with a larger number
23
                    depthFirstSearch(i - 1, currentNum + 1);
24
25
               return;
26
27
28
            // Mark the current number as used
29
            visited[currentNum] = true;
30
            // Assign current number to the result array at position i
            result[i] = currentNum;
31
32
33
           // If the current pattern character is 'I', explore the next numbers in increasing order
34
            if (pattern[i] === 'I') {
35
                for (let j = result[i] + 1; j <= patternLength + 1; j++) {</pre>
36
                    if (!visited[j]) { // If the number has not been used
37
                        depthFirstSearch(i + 1, j); // Recur with the next position and the current number
38
40
41
                // If no valid number is found, backtrack
42
                visited[currentNum] = false;
43
                depthFirstSearch(i, currentNum - 1);
            } else { // If the current pattern character is 'D', explore numbers in decreasing order
44
                for (let j = result[i] - 1; j > 0; j--) {
45
                    if (!visited[j]) { // If the number has not been used
46
47
                        depthFirstSearch(i + 1, j); // Recur with the next position and the current number
48
                        return;
49
50
```

Time Complexity The time complexity of the code is determined by the number of recursive calls to the dfs function, which is dependent on the length

depthFirstSearch(0, 1);

break;

return result.join('');

Time and Space Complexity

if (!visited[i]) {

resulting in a factorial time complexity.

Let's denote the length of the pattern as n. The number of recursive calls can be bounded by 9! (factorial) for small patterns, since we have at most 9 digits to use, and it decreases for each level of the recursion. However, for longer patterns, the maximum branching factor will diminish as the pattern increases beyond 9, so it will be less than 9! for patterns longer than 9.

With each recursive call to dfs, the function tries to append each number from 1 to 9 that hasn't already been used to the temporary

array t. This means that in the worst case, the first recursive call will have 9 options, the second will have 8 options, and so on,

Space Complexity The space complexity is determined by the depth of the recursion (which impacts the call stack size) and the additional data

Combining the contributions, the total space complexity is O(n) due also to the recursive call stack size being at most n for patterns

structures used (such as the vis array and the t list). Since the maximum depth of the recursion is equal to the length of the pattern plus one (n + 1), the contribution to the space

Therefore, the time complexity can be approximated as 0(9!) for patterns up to length 9. For patterns longer than 9, the time

complexity is still bounded by 0(9!) due to the early termination of the recursion once all digits are used.

The vis array is always of size 10, representing the digits 1 through 9. The size of t corresponds to the depth of the recursion, which is O(n). Therefore, the space requirements for vis are O(1) whereas for t are O(n).

longer than 9.

To summarize:

complexity from the call stack is O(n).

- The time complexity is 0(9!). The space complexity is O(n).