2896. Apply Operations to Make Two Strings Equal String] Medium Dynamic Programming

Leetcode Link

In this problem, we are given two binary strings of equal length, \$1 and \$2, as well as an integer cost x. Our goal is to transform \$1

Problem Description

into 52 through a series of operations, each of which incurs some cost. There are two types of operations we can perform: 1. We can flip (change from 0 to 1 or from 1 to 0) the bits at two chosen indices 1 and 1 in s1. This operation has a fixed cost of x.

2. We can flip the bits at consecutive indices i and i+1 in s1, provided i < n - 1. This operation has a cost of 1.

- Our objective is to calculate the minimum cost required to make \$1 identical to \$2. If it's not possible to make the strings identical, we should return -1.
- An important observation is that an even number of differences between \$1 and \$2 is required to make the transformation feasible because each flip operation changes the state of exactly two bits.

Intuition

an odd number of differing characters between s1 and s2, it's impossible to achieve equality, and the function returns -1. When the

The intuition behind the solution begins with the understanding that we are only able to change two characters at a time. If there is

number of differing characters is even, there is potential to reach the goal.

We use an array idx to store the indices of s1 where the characters differ from those in s2. The first step in our approach is a quick check of the length of idx: if it is odd, we return -1 right away as it would be impossible to make the strings equal. Next, we define a function dfs(i, j) to represent the minimum cost needed to flip the characters in the sub-array idx[i...j]. We're

The calculation for dfs(i, j) considers three possible scenarios: 1. Flipping endpoints (i and j): We flip characters at the two endpoints, using the first operation type at a cost of x. Then we

recursively call dfs to handle the sub-problem for idx[i+1] to idx[j-1]. 2. Flipping near i: We flip the characters at idx[i] and idx[i+1] using the second operation type. We add the distance between idx[i] and idx[i+1] to the cost of the recursive dfs call from idx[i+2] to idx[j].

3. Flipping near j: We flip the characters at idx[j-1] and idx[j] in similar fashion, adding the distance between these indices to

the cost of the recursive dfs call for idx[i] to idx[j-2]. We seek the minimum cost of these three approaches to be the result for dfs(i, j).

looking for the answer to dfs(0, len(idx) - 1).

- Memoization is used to cache the results of dfs(i, j) to avoid recomputing sub-problems. This is done by storing previously calculated results of dfs(i, j) and retrieving them instead of recalculating when they are requested again.
- This solution approach uses depth-first search combined with memoization (caching) to efficiently solve the problem.
- Solution Approach The given solution utilizes Depth-First Search (DFS) with memoization as its core algorithm. The DFS explores all combinations of

pairs that can be flipped to transform \$1 into \$2, while memoization ensures that the minimum cost for any given range of indices is

idx[i...j], identical. The Python @cache decorator is used to store the results of dfs(i, j) calls, so identical sub-problems are not

calculated only once and then reused. The use of memoization is a common pattern when there is a possibility of computing the

The code defines a recursive function dfs(i, j), which calculates the minimum cost of making subarrays of idx, specifically

same values repeatedly, as seen in many dynamic programming problems.

re-calculated from scratch—a typical memoization pattern.

There are three potential scenarios covered by the recursive function: 1. Flipping endpoints (i and j): The cost is calculated by flipping the characters at i and j, which consumes a fixed cost of x.

Example Walkthrough

4 a = 3

3 b = 0 + 2

into another efficiently.

class Solution:

6

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

33

34

35

36

37

38

39

44

4 b = 2

i.

idx[0], which is 3 - 1 = 2.

1 b = dfs(0 + 2, 1) + idx[1] - idx[0]

a total minimum cost of 2 to transform s1 into s2.

2 b = dfs(2, 1) # Out of bounds, but assume dfs(2, 1) = 0

1 = dfs(i + 1, j - 1) + x

2. Flipping near the start index (i and i + 1): The cost is the cost of flipping consecutive characters starting from i which costs 1. However, since 1 unit cost is specific to two adjacent characters, the actual cost is the distance between idx[i] and idx[i + 1]. This distance is then added to the cost of the recursive call starting from 1 + 2. 1 b = dfs(i + 2, j) + idx[i + 1] - idx[i]

3. Flipping near the end index (j - 1 and j): This is similar to the previous case, but here we start flipping from j.

1 c = dfs(i, j - 2) + idx[j] - idx[j - 1] In each call of dfs(i, j), the function computes the minimum cost among the three scenarios (a, b, and c). The index array idx helps to keep track of the indices where the two strings differ, emphasizing that we only care about the positions

This method provides a balance between the brute force approach (which would be too slow) and a more optimized approach that

that need transformation. This can be seen as a space optimization over considering the entire string for each recursive call.

The condition if m & 1 checks whether we have an odd number of differing bits by using bitwise AND with 1. If m is odd, it

immediately returns -1, as an odd number of differing bits cannot be solved with the given operations.

Lastly, return dfs(0, m - 1) kicks off the recursive calls with the full range of differing indices.

keeps the time complexity in check by only re-calculating necessary sub-problems when needed. Exploring all combinations through DFS ensures that all possibilities are considered, while memoization prevents unnecessary work, thus optimizing the solution.

Let's walk through a small example to illustrate the solution approach:

the minimum cost using the operations described.

thus, the problem is solvable. Let's apply the Depth-First Search (DFS) approach with memoization step by step:

Suppose we have the binary strings s1 = "1101" and s2 = "1000" with an integer cost x = 3. We want to transform s1 into s2 with

First, we identify the indices where s1 and s2 differ, which are idx = [1, 3]. There are two bits different, so it's an even number, and

3. Then we compute the cost of flipping near i (i = 0 and i + 1 = 1). The cost of flipping idx[0] and idx[1] is distance idx[1] -

4. Since there are only two indices, there's no distinct cost computation for flipping near j, as it would be the same as flipping near

However, we realize that since we used a hypothetical out-of-bounds result for the recursive dfs(0, 2) and dfs(2, 1), in a real

situation, the actual function would need to check for boundaries and return appropriate values (usually 0 if there are no more

1. The function dfs(0, 1) is called to solve the entire range of differing indices. 2. Inside dfs(0, 1), we calculate the cost of flipping endpoints (i = 0, j = 1). The cost for flipping idx[0] and idx[1] is x = 3. 1 a = dfs(1 - 1, 1 + 1) + x2 a = dfs(0, 2) + 3 # Out of bounds, but assume dfs(0, 2) = 0

characters to flip). This is handled in the implementation where each recursive call checks for the validity of the indices. In this case, only the operation of flipping bits at consecutive indices i and i+1 (the second type of operation) is applied, resulting in

def min_operations(self, s1: str, s2: str, x: int) -> int:

necessary to make substrings equal.

 $swap_with_x = dfs(i + 1, j - 1) + x$

 $skip_left = dfs(i + 2, j) + idx[i + 1] - idx[i]$

 $skip_right = dfs(i, j - 2) + idx[j] - idx[j - 1]$

40 # If intending to use, the Solution class is meant to be instantiated first

42 # and then the min_operations method can be called with the appropriate parameters:

def dfs(i: int, j: int) -> int:

Recurrence relation:

if i > j:

return 0

if num_diff_indices % 2:

43 # result = solution.min_operations(s1, s2, x)

return dfs(0, num_diff_indices - 1)

return -1

Helper function to recursively determine the minimum operations

@lru_cache(maxsize=None) # Cache results to avoid recomputation

The minimum cost among the scenarios is min(a, b), which is min(3, 2). Thus, the minimum cost is 2.

Python Solution from functools import lru_cache # Remember to import the necessary caching decorator

Base case: If the pointers cross each other, return 0 since we don't need to make operations.

2. Move the first pointer by two and add the difference between current and previous indices.

3. Move the second pointer by two and add the difference between current and previous indices.

1. Swap any character in s1 with 'x' and solve for the smaller substring.

This essentially skips one element that doesn't need changes.

This skips one element from the end that doesn't need changes.

Step 3: Apply the dfs function to the entire range of different indices.

This example demonstrates how the algorithm applies DFS with memoization to find the minimum cost to transform one binary string

24 25 # Return the minimum operations among the three alternatives. 26 return min(swap_with_x, skip_left, skip_right) 27 # Step 1: Identify indices where the characters in s1 and s2 differ.

Step 2: If there is an odd number of different indices, it's impossible to make s1 equal to s2, return -1.

```
28
            idx = [i for i in range(len(s1)) if s1[i] != s2[i]]
29
30
            # Number of indices that are different in s1 and s2.
31
            num_diff_indices = len(idx)
32
```

41 # solution = Solution()

```
Java Solution
  1 class Solution {
         private List<Integer> mismatchIndices = new ArrayList<>(); // Store indices of mismatched characters
         private Integer[][] memoization; // Memoization array for dynamic programming
         private int operationCost; // Cost of a swap operation
  6
         // Calculate the minimum number of operations to make s1 equal to s2 given the operation cost
         public int minOperations(String s1, String s2, int operationCost) {
             int length = s1.length();
  8
  9
 10
             // Identify all mismatched character positions and add them to the list
             for (int i = 0; i < length; ++i) {</pre>
 11
                 if (s1.charAt(i) != s2.charAt(i)) {
 12
 13
                     mismatchIndices.add(i);
 14
 15
 16
             int mismatches = mismatchIndices.size();
 17
 18
 19
             // If the number of mismatches is odd, return -1 since they cannot be paired
 20
             if (mismatches % 2 == 1) {
 21
                 return -1;
 22
 23
 24
             this.operationCost = operationCost;
             memoization = new Integer[mismatches][mismatches];
 25
 26
 27
             // Initiate dynamic programming with a depth-first search
 28
             return depthFirstSearch(0, mismatches - 1);
 29
 30
 31
         // Recursive depth-first search to find the minimum operation cost
 32
         private int depthFirstSearch(int left, int right) {
 33
             // When left > right, all characters are matched
 34
             if (left > right) {
 35
                 return 0;
 36
 37
             // Return the already computed value if available
 38
             if (memoization[left][right] != null) {
 39
                 return memoization[left][right];
 40
 41
             // Calculate the cost by swapping adjacent indices
 42
 43
             int cost = depthFirstSearch(left + 1, right - 1) + operationCost;
 44
 45
             // Calculate the cost by changing the left-most mismatched character
             if (left + 1 <= right) {
 46
 47
                 int leftSwapCost = mismatchIndices.get(left + 1) - mismatchIndices.get(left);
 48
                 cost = Math.min(cost, depthFirstSearch(left + 2, right) + leftSwapCost);
 49
 50
             // Calculate the cost by changing the right-most mismatched character
 51
```

int rightSwapCost = mismatchIndices.get(right) - mismatchIndices.get(right - 1);

cost = Math.min(cost, depthFirstSearch(left, right - 2) + rightSwapCost);

// Store the computed value in the memoization array

int minOperations(std::string s1, std::string s2, int swapCost) {

// Collect indices where characters from s1 and s2 differ

30 31 32 33

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

52

53

54

55

56

57

58

59

60

62

10

11

12

13

14

15

C++ Solution

#include <vector>

#include <cstring>

#include <functional>

2 #include <string>

6 class Solution {

public:

if (right - 1 >= left) {

return cost;

memoization[left][right] = cost;

std::vector<int> mismatchedIndices;

if (s1[i] != s2[i]) {

for (int i = 0; i < s1.size(); ++i) {

mismatchedIndices.push_back(i);

// If strings are already equal, no operations are needed

// Initialize a memoization array for dynamic programming

Array.from({ length: numDiffering }, () => -1));

if (memo[leftIndex][rightIndex] !== -1) {

return memo[leftIndex][rightIndex];

// Case 1: Swap a pair of differing characters

const memo: number[][] = Array.from({ length: numDiffering }, () =>

const dfs = (leftIndex: number, rightIndex: number): number => {

// Recursive depth-first search function to find the minimum operations

```
16
 17
             int mismatchCount = mismatchedIndices.size();
 18
 19
             // If there's an odd number of mismatches, it's impossible to make strings equal
             if (mismatchCount % 2 != 0) {
 20
 21
                 return -1;
 22
 23
 24
             // If there are no mismatches, no operations are required
 25
             if (mismatchCount == 0) {
 26
                 return 0;
 27
 28
 29
             int dp[mismatchCount][mismatchCount];
             // Initialize the dynamic programming table with -1 (uncomputed state)
             memset(dp, -1, sizeof(dp));
 34
             // Depth-First Search (DFS) to find minimum cost through dynamic programming
 35
             std::function<int(int, int)> dfs = [&](int left, int right) {
 36
                 // Base case: if left index greater than right, no operations needed
 37
                 if (left > right) {
 38
                     return 0;
 39
 40
                 // If already computed, just return the value
 41
                 if (dp[left][right] != -1) {
                     return dp[left][right];
 42
 43
                 // Calculate the minimum cost among three choices
 44
                 dp[left][right] = std::min({
 45
 46
                     dfs(left + 1, right - 1) + swapCost,
                                                                                     // Swap the outer characters
                     dfs(left + 2, right) + mismatchedIndices[left + 1] - mismatchedIndices[left], // Resolve leftmost pair
 47
 48
                     dfs(left, right - 2) + mismatchedIndices[right] - mismatchedIndices[right - 1] // Resolve rightmost pair
                 });
 49
                 return dp[left][right];
 50
             };
 51
 52
 53
             // Perform DFS and return the minimal operation cost
 54
             return dfs(0, mismatchCount - 1);
 55
 56
    };
 57
Typescript Solution
  1 // Function to calculate the minimum operations needed to make s1 equal to s2
    function minOperations(s1: string, s2: string, x: number): number {
         // Array to hold indices where characters in s1 and s2 differ
         const differingIndices: number[] = [];
  6
         // Populate the differingIndices array with the positions at which s1 and s2 differ
         for (let i = 0; i < s1.length; ++i) {
             if (s1[i] !== s2[i]) {
                 differingIndices.push(i);
 11
 12
 13
 14
        // The number of differing positions
 15
         const numDiffering = differingIndices.length;
 16
 17
        // If number of differing positions is odd, return -1 (not possible to make strings equal)
         if (numDiffering % 2 === 1) {
 18
 19
             return -1;
 20
```

57 58

Time and Space Complexity

if (numDiffering === 0) {

return 0;

if (leftIndex > rightIndex) {

// Compute the minimum operations

return 0;

42 memo[leftIndex][rightIndex] = dfs(leftIndex + 1, rightIndex - 1) + x; 43 44 // Case 2: Change one character and move to the next pair memo[leftIndex][rightIndex] = Math.min(memo[leftIndex][rightIndex], 45 46 dfs(leftIndex + 2, rightIndex) + differingIndices[leftIndex + 1] - differingIndices[leftIndex]); 47 48 // Case 3: Change the other character and move to the previous pair memo[leftIndex][rightIndex] = Math.min(memo[leftIndex][rightIndex], 49 50 dfs(leftIndex, rightIndex - 2) + differingIndices[rightIndex] - differingIndices[rightIndex - 1]); 51 return memo[leftIndex][rightIndex]; 52 53 }; 54 55 // Call the dfs function starting from the first and last index of the differing positions 56 return dfs(0, numDiffering - 1);

The time complexity of the given code is $0(n^2)$ where n is the length of idx, which derives from the number of mismatched

the @cache decorator. This ensures that each possible state (i, j) is calculated only once. The state (i, j) represents a

characters between \$1 and \$2. For each call to dfs(i, j), there are up to three recursive calls, but the function is memoized using

subproblem of finding the minimum operations for the substring from idx[i] to idx[j], and there are 0(n^2) such states because i

can range from 0 to n-1 and j can range from i to n-1. The space complexity of the code is also 0(n^2) due to the memoization cache that stores the computed result for each unique (i, j) pair. Each entry in the cache takes constant space, and since there are 0(n^2) pairs, the overall space used by the cache is O(n^2), plus the space used for the idx list and the recursion stack.