1188. Design Bounded Blocking Queue

Medium Concurrency

should block the calling thread until there is space available to add the new element.

## Problem Description

queue is a queue with a fixed maximum size, and it has the capability to block or wait when operations like enqueue (adding to the queue) and dequeue (removing from the queue) cannot be performed because the queue is full or empty, respectively. The queue supports three main operations: • enqueue(int element): This method adds an element to the end of the queue. If the queue has reached its capacity, the method

The problem is about creating a data structure which is a bounded blocking queue with thread-safety in mind. A bounded blocking

Leetcode Link

- dequeue(): This removes and returns the element at the front of the queue. If the queue is empty, this operation should block until there is an element available to dequeue.
- size(): This returns the current number of elements in the queue. It is especially noted that the implementation will be tested in a multithreaded environment, where multiple threads could be calling

these methods simultaneously. Therefore, it is crucial that the implementation ensures that all operations on the bounded blocking

queue are thread-safe (i.e., function correctly when accessed from multiple threads).

that could lead to incorrect behavior or data corruption.

Lastly, the use of any built-in bounded blocking queue implementations is prohibited as the goal is to understand how to create such a data structure from scratch, potentially in a job interview. Intuition

The solution to the problem involves coordinating access to the queue to ensure that only one thread can perform an enqueue or dequeue operation at a time to maintain thread safety. This means protecting the internal state of the queue from race conditions

## To achieve this, we employ two synchronization primitives called Semaphores. A semaphore maintains a set of permits, and a thread

that wants to perform an operation must first acquire a permit. If no permit is available, the thread blocks until a permit is released by another thread. This behavior fits perfectly for our problem's requirements. We use two semaphores in the solution:

1. s1, which starts with a number of permits equal to the capacity of the queue. This semaphore controls access to enqueue

operation. A thread can enqueue if it can acquire a permit from \$1, which signifies that there is room in the queue. After the enqueue operation, the thread releases a permit to \$2, signaling that there is an item available to be dequeued. 2. s2, which starts with zero permits as the queue is initially empty. This semaphore controls access to the dequeue operation. For

a thread to dequeue, it must acquire a permit from \$2, which signifies that there is at least one item in the queue to be

dequeued. After the dequeue operation, the thread releases a permit to \$1, indicating that there is now additional space

available in the queue.

appending and popping from both ends. Note that accessing len(q) to get the size of the queue does not need to be serialized by semaphores, as it is not modifying the queue. This approach enables us to limit the number of elements in the queue to the defined capacity, and to ensure that enqueue and

The queue itself (q) is represented by a deque (double-ended queue) from Python's collections module, which allows for fast

dequeue operations wait for the queue to be not full or not empty, respectively, before proceeding, fulfilling the conditions for a bounded blocking queue in a thread-safe manner. Solution Approach

In the provided solution, the implementation of the BoundedBlockingQueue class is done with two semaphores and a deque. Here's a

• Semaphores: Two instances of the Semaphore class are used, \$1 and \$2, each serving a distinct purpose. \$1 governs the ability

available to be dequeued and starts with no permits. This is a classic application of the "producer-consumer" problem's solution,

to insert an item into the queue, and begins with permits equal to the capacity. \$2 reflects the number of items in the queue

where one semaphore is used to signal "empty slots" and another semaphore is used to signal "available items". • Deque: A deque (double-ended queue) from the collections module is used to represent the queue's data structure. This provides efficient FIFO (first-in-first-out) operations needed for enqueueing (append) and dequeueing (popleft).

2. self.q.append(element): Once a permit has been acquired (meaning there is space in the queue), the element is safely

1. self.s2.acquire(): This acquires a permit from s2, which signifies that there is at least one element in the queue to be

dequeued. If the queue is empty, this call will block until a thread calls enqueue and releases a permit on \$2.

1. self.sl.acquire(): Attempt to acquire a permit from s1, which represents a free slot in the queue. If there are no free slots, this

enqueued into the queue. 3. self.s2.release(): Releasing a permit on s2 to signal that an element has been enqueued and is now available for dequeuing.

For dequeue(), the steps are the mirror image:

When enqueue(element: int) is called, the following steps are performed:

1. It acquires a permit from s1, which now has 1 permit left.

2. It then appends 1 to the deque, and the queue state becomes [1].

1. It acquires the remaining permit from \$1, and \$1 now has 0 permits.

2. It appends 2 to the deque, so the queue state becomes [1,2].

1. It acquires the permit from s1, and again s1 has 0 permits.

dequeuing operations using semaphores to manage its capacity and state.

from collections import deque # Ensure deque is imported

self.semaphore\_filled\_slots = Semaphore(0)

# Add an element to the end of the queue.

self.queue.append(element) # Add the element to the queue

// This class represents a thread-safe bounded blocking queue with a fixed capacity.

// Constructor initializes the semaphores and queue with specified capacity.

// Semaphore to control the number of elements that can be added (based on capacity).

// Semaphore to control the number of elements that can be removed (starts at 0).

# Remove and return an element from the front of the queue.

# Get the current number of elements in the queue.

def enqueue(self, element: int) -> None:

element = self.queue.popleft()

call will block until another thread calls dequeue and releases a permit on s1.

walkthrough of the pattern and algorithms used:

not empty. 3. self.sl.release(): Releasing a permit on s1 to signal that an element has been dequeued and there is now a free slot in the queue.

2. ans = self.q.popleft(): Removes the oldest (front) element from the queue safely because it's been ensured that the queue is

size() is a straightforward operation as it simply returns the current number of items in the queue, len(self.q). It does not modify the queue, so it does not require interaction with semaphores.

coordinate enqueue and dequeue actions. This guarantees that the queue never exceeds its capacity and avoids dequeue

operations being called on an empty queue, thus satisfying thread safety and other requirements of the problem.

Let's consider a small example to illustrate the solution approach for a BoundedBlockingQueue with a capacity of 2.

The solution effectively serializes access to the mutable shared state (self.q), preventing race conditions by using semaphores to

 Initially, we create the queue with a capacity of 2, initializing semaphore s1 with 2 permits and semaphore s2 with 0 permits. Imagine thread A calls enqueue(1):

3. Finally, it releases a permit to \$2, indicating that there is one item available for dequeuing. Now, thread B calls enqueue(2):

• At this state, the queue is full. If another thread, say thread C, tries to enqueue(3), it will be blocked as \$1 has no permits left,

3. It releases another permit to \$2, now \$2 has 2 permits indicating there are two items available to be dequeued.

the queue.

needing to acquire a permit.

signifying the queue is at full capacity.

Meanwhile, if thread D calls dequeue():

Example Walkthrough

1. It acquires a permit from \$2 (which has 2 permits at this point), leaving 1 permit left in \$2. 2. It dequeues an element from the deque which is 1 (FIFO order), leaving the queue state as [2].

If thread C is still waiting to enqueue (3), it can now proceed as a permit became available in s1.

2. It appends 3 to the deque, so the queue state becomes [2,3]. 3. It releases a permit to \$2, which now has 2 permits, reflecting the two items in the queue.

At any time, calling size() returns the number of items currently in the queue, which can be accessed by any thread without

# Semaphore to track empty slots

# Semaphore to track filled slots

# Use deque for queue operations

This example demonstrates how the BoundedBlockingQueue enforces its bounds and provides thread-safe enqueueing and

3. It releases a permit to \$1, increasing the number of permits back to 1, signaling that there is now space for one more item in

class BoundedBlockingQueue: def \_\_init\_\_(self, capacity: int): # Initialize the queue with given capacity.

self.semaphore\_empty\_slots.acquire() # Decrease the counter of empty slots, wait if no empty slots

self.semaphore\_filled\_slots.acquire() # Decrease the counter of filled slots, wait if no filled slots

# Return the size of the queue

# Return the dequeued element

self.semaphore\_filled\_slots.release() # Increase the counter of filled slots, signaling dequeue if slots are filled

# Remove the element from the queue

self.semaphore\_empty\_slots.release() # Increase the counter of empty slots, signaling enqueue if slots are available

Java Solution 1 import java.util.ArrayDeque;

```
self.semaphore_empty_slots = Semaphore(capacity)
```

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

26

27

9

10

11

12

13

14

15

16

54 }

55

1 from threading import Semaphore

self.queue = deque()

def dequeue(self) -> int:

return element

def size(self) -> int:

2 import java.util.Deque;

return len(self.queue)

import java.util.concurrent.Semaphore;

// The queue to store elements.

private final Deque<Integer> queue;

private final Semaphore enqueueSemaphore;

private final Semaphore dequeueSemaphore;

public BoundedBlockingQueue(int capacity) {

public class BoundedBlockingQueue {

Python Solution

```
enqueueSemaphore = new Semaphore(capacity);
17
           dequeueSemaphore = new Semaphore(0);
           queue = new ArrayDeque<>();
18
19
20
21
       // Enqueues an element into the queue if there's available capacity.
22
       public void enqueue(int element) throws InterruptedException {
           // Acquire a permit from enqueueSemaphore discarding it, if available capacity is 0 waits.
23
24
           enqueueSemaphore.acquire();
           synchronized (this) {
               // Adds the element to the end of the queue.
26
27
               queue.offer(element);
28
29
           // Release a permit to dequeueSemaphore, increasing the number of available elements to dequeue.
           dequeueSemaphore.release();
30
31
33
       // Dequeues an element from the front of the queue.
34
       public int dequeue() throws InterruptedException {
35
           // Acquire a permit from dequeueSemaphore, waiting if necessary until an element is available.
36
           dequeueSemaphore.acquire();
           int element;
37
           synchronized (this) {
               // Remove and return the front element of the queue.
39
40
               element = queue.poll();
41
           // Release a permit to enqueueSemaphore, increasing the available capacity.
           enqueueSemaphore.release();
43
           return element;
45
46
47
       // Returns the current number of elements in the queue.
       public int size() {
48
           synchronized (this) {
49
               // The size of the queue is returned.
51
               return queue.size();
52
53
```

### 21 22 23 24

C++ Solution

public:

11

12

13

14

15

16

17

#include <queue>

#include <mutex>

#include <condition\_variable>

void enqueue(int element) {

queue\_.push(element);

// Constructor initializes the queue with a capacity limit.

std::unique\_lock<std::mutex> lock(mutex\_);

// Wait until there is space in the queue

BoundedBlockingQueue(int capacity): capacity\_(capacity), count\_(0) {

not\_full\_condition\_.wait(lock, [this] { return count\_ < capacity\_; });</pre>

// No need to initialize semaphores since we will use condition\_variable and mutex

// Enqueue adds an element to the queue. If the queue is full, blocks until space is available.

class BoundedBlockingQueue {

```
18
             ++count_;
 19
             // Notify one waiting thread (if any) that an item was dequeued
 20
             not_empty_condition_.notify_one();
         // Dequeue removes and returns an element from the queue. If the queue is empty, blocks until an element is available.
         int dequeue() {
 25
             std::unique_lock<std::mutex> lock(mutex_);
 26
             // Wait until there is an item to dequeue
 27
             not_empty_condition_.wait(lock, [this] { return count_ > 0; });
 28
             int value = queue_.front();
 29
             queue_.pop();
 30
             --count_;
 31
             // Notify one waiting thread (if any) that space is now available
 32
             not_full_condition_.notify_one();
 33
             return value;
 34
 35
 36
         // Get the current size of the queue.
 37
         int size() {
 38
             std::lock_guard<std::mutex> lock(mutex_);
 39
             return count_;
 40
 41
    private:
         std::queue<int> queue_; // The queue that holds the elements
 43
         std::mutex mutex_; // Mutex to protect access to the queue
 44
 45
         std::condition_variable not_full_condition_; // Condition variable to block enqueue when queue is full
 46
         std::condition_variable not_empty_condition_; // Condition variable to block dequeue when queue is empty
 47
         int capacity_; // Maximum number of items in the queue
 48
         int count_; // Current number of items in the queue
 49 };
 50
Typescript Solution
   const queue: number[] = []; // The queue that holds the elements
  2 let capacity: number; // Maximum number of items in the queue
    let count: number = 0; // Current number of items in the queue
    // Utilizing these for synchronization could be complex without encapsulation
  6 const mutex = new Mutex(); // A pretend Mutex since JavaScript/TypeScript doesn't have one
    const notFullCondition = new ConditionVariable(); // A pretend condition variable for when the queue is not full
    const notEmptyCondition = new ConditionVariable(); // A pretend condition variable for when the gueue is not empty
    // Initialization of the queue with a capacity limit.
    function initializeQueue(initialCapacity: number): void {
 12
         capacity = initialCapacity;
 13
 14
    // Adds an element to the queue. If the queue is full, it is supposed to block until space is available.
    async function enqueue(element: number): Promise<void> {
         await mutex.lock();
 17
 18
         try {
 19
            // Wait until there is space in the queue
 20
             while (count >= capacity) {
                 await notFullCondition.wait(mutex);
 22
 23
             queue.push(element);
 24
             count++;
 25
             // Notify one waiting thread (if any) that an item was enqueued
             notEmptyCondition.notifyOne();
 26
 27
         } finally {
 28
             mutex.unlock();
 29
 30 }
```

// Removes and returns an element from the queue. If the queue is empty, it is supposed to block until an element is available.

# Time and Space Complexity

async function dequeue(): Promise<number> {

const value = queue.shift();

notFullCondition.notifyOne();

// Returns the current size of the queue.

while (count === 0) {

// Wait until there is an item to dequeue

await notEmptyCondition.wait(mutex);

// Notify one waiting thread (if any) that space is now available

return count; // No need for synchronization in a single-threaded environment

// These would need to be implemented or a library would have to be used to simulate them.

0(1), as it involves only a fixed number of operations, regardless of the capacity of the queue.

space complexity is O(capacity) based on the fixed maximum size of the underlying deque.

// Note that Mutex and ConditionVariable are not native JS/TS classes.

await mutex.lock();

count--;

function size(): number {

} finally {

return value;

mutex.unlock();

31

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

52

53

54

57

• enqueue: The enqueue operation involves two semaphore operations (acquire and release) and an append operation on a deque. The semaphore operations are generally 0(1) assuming they don't block; if they do block, the time complexity is dependent on

For this BoundedBlockingQueue implementation using semaphores, we will analyze the time and space complexities of its operations.

• \_\_init\_\_: Initializing the queue involves setting up two semaphores and the underlying deque. This operation is constant time,

## external factors such as contention from other threads. Appending to the deque is an 0(1) operation. Therefore, the combined time complexity is 0(1) per call in the absence of blocking. • dequeue: Like enqueue, dequeue also has two semaphore operations and a popleft operation on the deque. Since deque's

**Space Complexity** 

**Time Complexity** 

- popleft is designed to be 0(1) and semaphore operations are 0(1) without blocking, the overall time complexity for dequeue is again 0(1) per call in the absence of blocking. • size: This simply returns the number of items in the deque, which is maintained internally and is thus an O(1) operation.
- The space complexity revolves around the deque that stores elements. Since the capacity of the queue is fixed, the maximum space it will use is O(capacity), corresponding to the maximum number of elements that can be enqueued at any given time. In summary, except for the potential blocking on semaphores (which can't be quantified in standard complexity analysis), all fundamental operations (\_\_init\_\_, enqueue, dequeue, size) on the BoundedBlockingQueue class have a time complexity of 0(1). The