1440. Evaluate Boolean Expression

Description

Table `Variables` :

```
+---------------+---------+
| Column Name   | Type    |
+---------------+---------+
| name          | varchar |
| value         | int     |
+---------------+---------+
```

In SQL, name is the primary key for this table.
This table contains the stored variables and their values.

Table `Expressions` :

```
+---------------+---------+
| Column Name   | Type    |
+---------------+---------+
| left_operand  | varchar |
| operator      | enum    |
| right_operand | varchar |
+---------------+---------+
```

In SQL, (left_operand, operator, right_operand) is the primary key for this table.
This table contains a boolean expression that should be evaluated.
operator is an enum that takes one of the values ('<', '>', '=')
The values of left_operand and right_operand are guaranteed to be in the Variables table.

Evaluate the boolean expressions in `Expressions` table.

Return the result table in **any order** .

The result format is in the following example.

Example 1:

```
Input:
Variables table:
+------+-------+
| name | value |
+------+-------+
| x    | 66    |
| y    | 77    |
+------+-------+
Expressions table:
+--------------+----------+---------------+
| left_operand | operator | right_operand |
+--------------+----------+---------------+
| x            | >        | y             |
| x            | <        | y             |
| x            | =        | y             |
| y            | >        | x             |
| y            | <        | x             |
| x            | =        | x             |
+--------------+----------+---------------+
Output:
+--------------+----------+---------------+-------+
| left_operand | operator | right_operand | value |
+--------------+----------+---------------+-------+
| x            | >        | y             | false |
| x            | <        | y             | true  |
| x            | =        | y             | false |
| y            | >        | x             | true  |
| y            | <        | x             | false |
| x            | =        | x             | true  |
+--------------+----------+---------------+-------+
Explanation:
As shown, you need to find the value of each boolean expression in the table using the variables table.
```