

1048. Longest String Chain

Leetcode Link

You are given an array of `words` where each word consists of lowercase English letters.

$word_A$ {" "} is a **predecessor** of{" "} $word_B$ {" "} if and only if we can insert **exactly one** letter anywhere in{" "} $word_A$ {" "} **without changing the order of the other characters** to make it equal to{" "} $word_B$.

- For example, "abc" is a **predecessor** of{" "} "abac" , while "cba" is not a **predecessor** of{" "} "bcad".

A **word chain** is a sequence of words{" "} $\{word_1, word_2, \dots, word_k\}$ {" "} with $k \geq 1$, where{" "} $word_1$ {" "} is a **predecessor** of{" "} $word_2$,{" "} $word_2$ {" "} is a **predecessor** of{" "} $word_3$, and so on. A single word is trivially a **word chain** with{" "} $k = 1$.

Return{" "} k {" "} the **length of the{" "} k {" "} **longest possible word chain** with words chosen from the given list of{" "} k {" } words.**

Example 1:

Input: words = ["a","b","ba","bca","bda","bdca"] {"\n"}
Output: 4 {"\n"}
Explanation: One of the longest word chains is ["a","ba","bda","bdca"]. {"\n"}

Example 2:

Input: words = ["xbc","pcxbcf","xb","cxbc","pcxbc"] {"\n"}
Output: 5 {"\n"}
Explanation: All the words can be put in a word chain ["xb", "xbc", "cxbc", "pcxbc", "pcxbcf"]. {"\n"}

Example 3:

Input: words = ["abcd","dbqca"] {"\n"}
Output: 1 {"\n"}
Explanation: The trivial word chain ["abcd"] is one of the longest word chains. {"\n"} ["abcd","dbqca"] is not a valid word chain because the ordering of the letters is changed. {"\n"}

Constraints:

- $1 \leq words.length \leq 1000$
- $1 \leq words[i].length \leq 16$
- `words[i]` only consists of lowercase English letters.

Solution

Naive Solutions

We could go through all possible chains and check if each works, or we could use a recursive function that adds one character every time, but these solutions are too slow.

$\mathcal{O}(n^2L^2)$ Dynamic Programming Solution

Let's build a chain from the shortest string to the longest string. Say we currently have the chain $(w_1, w_2, \dots, w_{k-1}, w_k)$. We see that it doesn't matter what any of the words before w_k are, only that there are k of them. This suggests a dynamic programming solution, where $dp[i]$ = the length of the longest chain that ends with the string `words[i]`.

First sort words by increasing length. An outer loop will loop `current_word_index`. For each `current_word_index`, we have an inner loop to check every word before it to see if it can be a predecessor. We'll call this index `previous_word_index`. If so, we update `dp[current_word_index]` to `max(dp[current_word_index], dp[previous_word_index] + 1)` because we can extend the chain ending in `previous_word` by appending `current_word`.

For example, when words = ["a", "ab", "cb", "cab"], `current_word_index` = 3, and `previous_word_index` = 1, we find that removing "c" from `words[current_word_index]` = "cab" yields "ab" = `words[previous_word_index]`.

Time complexity

Let $n = words.length$ and $L = \max\{words[i].length\}$.

Sorting takes $\mathcal{O}(n \log n)$.

Our nested loops take $\mathcal{O}(n^2)$ and call `isPredecessor()` that runs in $\mathcal{O}(L^2)$, so this part takes $\mathcal{O}(n^2L^2)$.

The total time complexity of this algorithm is therefore $\mathcal{O}(n \log n + n^2L^2) = \mathcal{O}(n^2L^2)$.

Space complexity

The `dp` array consumes $\mathcal{O}(n)$ memory.

$\mathcal{O}(n^2L^2)$ Solutions below

C++ Solution

```
1 class Solution {
2     public:
3         bool isPredecessor(string &previous_word, string &current_word) {
4             if (previous_word.size() + 1 == current_word.size()) {
5                 for (int k = 0; k < current_word.size(); k++) {
6                     if (previous_word == current_word.substr(0, k) + current_word.substr(k + 1))
7                         return true;
8                 }
9             }
10            return false;
11        }
12        int longestStrChain(vector<string> &words) {
13            // sort words by length
14            sort(words.begin(), words.end(), [](auto x, auto y) { return x.size() < y.size(); });
15            int n = words.size();
16            vector<int> dp(n, 1);
17            for (int current_word_index = 0; current_word_index < n; current_word_index++) {
18                for (int previous_word_index = 0; previous_word_index < current_word_index; previous_word_index++) {
19                    if (isPredecessor(words[j], words[current_word_index])) {
20                        dp[current_word_index] = max(dp[current_word_index], dp[previous_word_index] + 1);
21                    }
22                }
23            }
24            return *max_element(dp.begin(), dp.end());
25        }
26    };
27 }
```

Java Solution

```
1 class Solution {
2     public static boolean isPredecessor(String previous_word, String current_word) {
3         if (previous_word.length() + 1 == current_word.length()) {
4             for (int k = 0; k < current_word.length(); k++) {
5                 if (previous_word.equals(current_word.substring(0, k) + current_word.substring(k+1)))
6                     return true;
7             }
8         }
9         return false;
10    }
11    public int longestStrChain(String[] words) {
12        // sort words by length
13        Arrays.sort(words, (a, b) -> Integer.compare(a.length(), b.length()));
14        int n = words.length;
15
16        // add padding to words to avoid index out of bounds errors
17        for (int i = 0; i < n; i++) {
18            words[i] = "#" + words[i];
19        }
20
21        int ans = 1;
22        int[] dp = new int[n];
23        Arrays.fill(dp, 1);
24        for (int current_word_index = 0; current_word_index < n; current_word_index++) {
25            for (int previous_word_index = 0; previous_word_index < current_word_index; previous_word_index++) {
26                if (isPredecessor(words[previous_word_index], words[current_word_index])) {
27                    dp[current_word_index] = Math.max(dp[current_word_index], dp[previous_word_index] + 1);
28                    ans = Math.max(ans, dp[current_word_index]);
29                }
30            }
31        }
32        return ans;
33    }
34 }
35 }
```

Python Solution

```
1 class Solution:
2     def isPredecessor(self, previous_word, current_word):
3         if len(previous_word) + 1 == len(current_word):
4             for k in range(len(current_word)):
5                 if previous_word == current_word[0:k] + current_word[k+1:]:
6                     return True
7         return False
8
9     def longestStrChain(self, words: List[str]) -> int:
10        words.sort(key=len)
11        n = len(words)
12        dp = [1 for _ in range(n)]
13        for current_word_index in range(n):
14            for previous_word_index in range(current_word_index):
15                if self.isPredecessor(words[previous_word_index], words[current_word_index]):
16                    dp[current_word_index] = max(dp[current_word_index], dp[previous_word_index] + 1)
17        return max(dp)
```

JavaScript Solution

```
1 var isPredecessor = function (previous_word, current_word) {
2     if (previous_word.length + 1 == current_word.length) {
3         for (let k = 0; k < current_word.length; k++) {
4             if (
5                 previous_word ==
6                 current_word.slice(0, k) + current_word.slice(k + 1)
7             )
8                 return true;
9         }
10    }
11    return false;
12 };
13
14 /**
15  * @param {string[]} words
16  * @return {number}
17  */
18 var longestStrChain = function (words) {
19     // sort words by length
20     words.sort((a, b) => a.length - b.length);
21     n = words.length;
22     dp = new Array(n).fill(1);
23
24     for (
25         let current_word_index = 0;
26         current_word_index < n;
27         current_word_index++
28     ) {
29         for (
30             let previous_word_index = 0;
31             previous_word_index < current_word_index;
32             previous_word_index++
33         ) {
34             if (
35                 isPredecessor(words[previous_word_index], words[current_word_index])
36             ) {
37                 dp[current_word_index] = Math.max(
38                     dp[current_word_index],
39                     dp[previous_word_index] + 1
40                 );
41             }
42         }
43     }
44     return Math.max(...dp);
45 };
```

$\mathcal{O}(nL^2)$ Dynamic Programming Solution (requires HashMap)

In our last solution, checking all previous words for predecessors was slow.

Observe that each word can only have $\mathcal{O}(L)$ predecessors, so we can generate them all (in $\mathcal{O}(L^2)$) and check the best `dp` value we can get from them.

Let `dp[str]` = the length of the longest chain that ends with the string `str`. `dp` will be a hashmap to allow for $\mathcal{O}(1)$ retrieval by key.

As we did before, sort words by increasing length. Loop through the current string `current_word`. Then for each index j , let `previous_wordj` be `current_word` with its j th character removed. Set `dp[current_word]` to `max{dp[previous_wordj] + 1}`. Our answer is the max of all entries in `dp`.

Time complexity

Let $n = words.length$ and $L = \max\{words[i].length\}$.

Sorting takes $\mathcal{O}(n \log n)$.

For every string (there are $\mathcal{O}(n)$ of them), create each of its predecessors in $\mathcal{O}(L^2)$ and check for their value in `dp` in $\mathcal{O}(1)$. This comes together to $\mathcal{O}(nL^2)$.

The total time complexity is therefore $\mathcal{O}(n \log n + nL^2)$.

Space complexity

The `dp` hashmap consumes $\mathcal{O}(n)$ memory.

Bonus:

We can perform [counting sort](#) in $\mathcal{O}(n + L)$, giving a total time complexity of $\mathcal{O}((n + L) + nL^2) = \mathcal{O}(nL^2)$.

$\mathcal{O}(n \log n + nL^2)$ Solutions below

C++ Solution

```
1 class Solution {
2     public:
3         int longestStrChain(vector<string> &words) {
4             // sort words by length
5             sort(words.begin(), words.end(), [](auto x, auto y) { return x.size() < y.size(); });
6             int n = words.size(); ans = 1;
7             unordered_map<string, int> dp;
8             for (auto &current_word: words) {
9                 for (int j = 0; j < current_word.size(); j++) {
10                     string previous_word = current_word.substr(0, j) + current_word.substr(j + 1);
11                     dp[current_word] = max(dp[current_word], dp[previous_word] + 1);
12                 }
13                 ans = max(ans, dp[current_word]);
14             }
15             return ans;
16        }
17    };
18 }
```

Java Solution

```
1 class Solution {
2     public int longestStrChain(String[] words) {
3         // sort words by length
4         Arrays.sort(words, (a, b) -> Integer.compare(a.length(), b.length()));
5         int n = words.length;
6         // add padding to words so that we don't have to do s.substring(0, -1).
7         // which would throw an index out of bounds error
8         for (int i = 0; i < n; i++) {
9             words[i] = "#" + words[i];
10        }
11        TreeMap<String, Integer> dp = new TreeMap<>();
12        int ans = 1;
13        for (String current_word: words) {
14            dp.put(current_word, 1);
15            for (int j = 0; j < current_word.length(); j++) {
16                String previous_word = current_word.substring(0, j) + current_word.substring(j + 1);
17                dp.put(current_word, Math.max(dp.getOrDefault(previous_word, 0) + 1));
18            }
19            ans = Math.max(ans, dp.get(current_word));
20        }
21        return ans;
22    }
23 }
```

Python Solution

```
1 class Solution:
2     def longestStrChain(self, words: List[str]) -> int:
3         # sort words by length
4         words.sort(key=len)
5         n = len(words)
6         ans = 0
7         dp = defaultdict(lambda: 0)
8         for current_word in words:
9             for j in range(len(current_word)):
10                 previous_word = current_word[0:j] + current_word[j+1:]
11                 dp[current_word] = max(dp[current_word], dp[previous_word] + 1)
12         ans = max(ans, dp[current_word])
13     return ans
```

JavaScript Solution

```
1 /**
2  * @param {string[]} words
3  * @return {number}
4  */
5 var longestStrChain = function (words) {
6     words.sort((a, b) => a.length - b.length);
7     n = words.length;
8     dp = new Map();
9     ans = 0;
10    for (current_word of words) {
11        dp[current_word] = 1;
12        for (let j = 0; j < s.length; j++) {
13            // We need (dp[previous_word] || 0) to get 0 if dp does not contain previous_word, otherwise we'd get Nan,
14            // which is larger than any integer
15            dp[current_word] = Math.max(
16                dp[current_word],
17                (dp[previous_word] || 0) + 1
18            );
19        }
20        ans = Math.max(ans, dp[current_word]);
21    }
22    return ans;
23 };
```

Got a question? [Ask the Teaching Assistant](#) anything you don't understand.