1161. Maximum Level Sum of a Binary Tree Medium Tree Depth-First Search Breadth-First Search Binary Tree

Leetcode Link

The problem provides us with the root of a binary tree and asks us to find the level with the maximum sum of node values. In a binary

Problem Description

tree, each node has at most two children. The root of the tree is at level 1, its children are at level 2, and this pattern continues for subsequent levels. We need to determine the smallest level number x, which has the maximum sum compared to sums of nodes at

other levels.

To solve this problem, we can use breadth-first search (BFS), which is an algorithm that starts at the tree root and explores all nodes

at the present depth level before moving on to nodes at the next depth level. This approach is suitable because it naturally

Intuition

processes nodes level by level. Here's how we can use BFS to solve the problem: Initialize a queue that will hold the nodes to be processed, and start with the root node. Initialize variables to keep track of the maximum sum (mx), the current level (1), and the level with the maximum sum (ans).

After processing all nodes at the current level, we compare the sum with mx. If the sum of the current level exceeds mx, we

update mx to this sum and record the current level number as ans since it's the smallest level with this new maximum sum so far.

- Continue the process for all levels until all nodes have been processed.
- Return the level number ans, which corresponds to the smallest level with the maximal sum.

For each level, we process all nodes on that level to calculate the sum of values at the current level (s).

- The provided solution implements this BFS approach efficiently.
- Solution Approach The Reference Solution Approach applies the breadth-first search (BFS) pattern using a queue to traverse the binary tree level by

2. We track the maximum sum encountered so far with mx, set initially to negative infinity (-inf), since we want to be able to

level. Here is the walk-through of the implementation steps: 1. Start by initializing a queue q with the root node of the tree. This queue will store the nodes to be processed for each level.

compare it with sums that can be potentially zero or positive.

If the current node has a left child, enqueue the left child.

effectively and keeping track of the level with the greatest sum.

7. Finally, return the variable ans, which holds the smallest level number with the greatest sum.

2. The maximum sum mx is initialized to negative infinity, and the current level i is set to 0.

3. Enter the while loop to begin processing since the queue is not empty.

There is only one node, which is the root node with value 3.

Enqueue its children (nodes with values 9 and 20) to the queue.

4. Increment i to 1 since we are now on level 1, and initialize the sum s to 0.

3. The current level i is set to 0 at the beginning. It will be incremented as we start processing each level to keep track of the level number.

the max sum mx.

Example Walkthrough

15 7

further has two children with values 15 and 7.

Add this value to s, so now s = 3.

4. We enter a while loop that continues as long as there are nodes left in the queue q.

- Increment the level i by one as we are beginning to process a new level. Initialize a sum s for the current level which will be used to add up all node values at this level.
- the start of the level (len(q)). Dequeue the front node of the queue and add its value to s.

Use a for loop to process each node at the current level. The range is determined by the number of elements in the queue at

- Similarly, if the current node has a right child, enqueue the right child. 5. After the for loop ends, all nodes at the current level have been processed. We now compare the sum s of the current level to
- o If s is greater than mx, we update mx to s and record the current level as ans because it's currently the level with the highest sum. 6. Once the queue is empty, meaning all levels have been processed, we exit the while loop.

By using a queue alongside the BFS pattern, the solution ensures that the tree is traversed level by level, summing node values

- Let's consider a small binary tree as an example to illustrate the solution approach:
- Here is how the BFS algorithm would process this tree to find the level with the maximum sum: We start by initializing the queue q with the root node (value 3).

In this tree, the root node has a value of 3, the root's left child has a value of 9, and the root's right child has a value of 20 which

5. Process all nodes at level 1:

o Increment i to 2.

The sum s is reset to 0.

 \circ s is now 9 + 20 = 29.

9. Move to the next level (level 3):

The sum s is reset to 0.

 \circ s is now 15 + 7 = 22.

Increment i to 3.

Python Solution

from math import inf

class TreeNode:

10

14

16

17

18

19

20

21

22

23

24

25

26

33

41

43

44

45

9

10

11

12

13

14

15

16

17

18

19

20

21

23

24

25

26

27

28

29

30

32

33

34

35

36

43

44

37

38

39

40

41

42

43

44

45

46 47

48

49

50

51

52

54

6 }

12

14

16

17

18

19

20

21

22

23

24

25

26 27

34

35

36

37

38

40

41

42

43

45

46

47

48

49

50

51

52

53

54

55

57

56 }

/**

*/

53 };

1 from collections import deque

self.val = val

 $\max sum = -inf$

level = 0

answer = 0

while queue:

return answer

level += 1

current_sum = 0

self.left = left

self.right = right

queue = deque([root])

Initialize level counter to 0

for _ in range(len(queue)):

if node.left:

answer = level

public int maxLevelSum(TreeNode root) {

queue.offer(root);

int level = 0;

int maxLevel = 0;

while (!queue.isEmpty()) {

Return the level that had the maximum sum

// Queue to store nodes of tree level-wise

Deque<TreeNode> queue = new ArrayDeque<>();

// Loop through each level of the tree

levelSum += node.val;

if (node.left != null) {

if (node.right != null) {

// Node's value

TreeNode left; // Reference to the left child node

if (maxSum < levelSum) {</pre>

maxSum = levelSum;

maxLevel = level;

// Definition for a binary tree node.

queue.offer(node.left);

queue.offer(node.right);

level++; // Increment the level counter

// Adding the root to the queue as the starting point

Definition for a binary tree node.

6. Now, s is compared to mx. Since s (3) is greater than mx (-∞), update mx to 3 and mark the current level ans as 1. 7. Move to the next level (level 2):

There are two nodes at this level, with values 9 and 20. Process each by dequeuing and adding their values to s.

There are two nodes at this level, with values 15 and 7. Process each by dequeuing and adding their values to s.

Using the BFS approach outlined above, we traversed the given binary tree level by level, efficiently calculating the sum of node

- Enqueue the children of these nodes (values 15 and 7) to the queue. 8. Now, s (29) is compared to mx (3). s is larger so we update mx to 29 and ans to 2 because this level has the new maximum sum.
- 12. Return ans, which is 2, as level 2 has the maximum sum of 29.

11. Since the queue is now empty, we have processed all levels.

values at each level and identifying the level with the maximum sum.

10. Now, s (22) is compared to mx (29). Since s is less than mx, we do not update mx or ans.

Initialize max_sum to negative infinity to ensure any level's sum will be larger

class Solution: 12 def maxLevelSum(self, root: Optional[TreeNode]) -> int: # Initialize the queue with the root node 13

Initialize answer to store the level with the maximum sum

Traverse the tree level by level using breadth-first search

// Function to find the level of the binary tree with the maximum sum

int maxSum = Integer.MIN_VALUE; // Initialized to minimum value

// Calculate the sum of all nodes at the current level

// Add child nodes to the queue for the next level

for (int count = queue.size(); count > 0; count--) {

// Variables to keep track of the maximum level sum and corresponding level

int levelSum = 0; // Reset the level sum for the current level

// Level counter

// Level with max sum

TreeNode node = queue.pollFirst(); // Get the next node from the queue

// Update max sum and corresponding level if the current level has a greater sum

// Add the node's value to the level sum

Process all the nodes at the current level

def __init__(self, val=0, left=None, right=None):

Pop the leftmost node from the queue 28 29 node = queue.popleft() 30 # Add the node's value to the current level's sum 31 current_sum += node.val 32 # If the node has a left child, add it to the queue

34 queue.append(node.left) 35 # If the node has a right child, add it to the queue 36 if node.right: 37 queue.append(node.right) 38 # Update max_sum and answer if the current level's sum is greater than max_sum 39 if max_sum < current_sum:</pre> max_sum = current_sum

Java Solution

1 class Solution {

```
37
38
39
           // Return the level with the maximum sum
            return maxLevel;
42
```

class TreeNode {

int val;

TreeNode right; // Reference to the right child node 50 51 // Constructors for TreeNode 52 TreeNode() {} TreeNode(int val) { this.val = val; } 54 TreeNode(int val, TreeNode left, TreeNode right) { 55 this.val = val; 56 this.left = left; 57 this.right = right; 58 59 60 C++ Solution #include <queue> #include <climits> // Include necessary headers // Definition for a binary tree node. 5 struct TreeNode { int val; TreeNode *left; TreeNode *right; 8 9 10 // Constructors 11 TreeNode() : val(0), left(nullptr), right(nullptr) {} 12 TreeNode(int x) : val(x), left(nullptr), right(nullptr) {} TreeNode(int x, TreeNode *left, TreeNode *right) : val(x), left(left), right(right) {} 13 14 }; 15 16 class Solution { 17 public: 18 // Function to find the level that has the maximum sum in a binary tree. 19 int maxLevelSum(TreeNode* root) { 20 // Using a queue to perform level order traversal 21 std::queue<TreeNode*> nodeQueue{ {root} }; 22 23 int maxSum = INT_MIN; // Initialize maxSum to the smallest possible integer 24 int resultLevel = 0; // The level with the max sum 25 int currentLevel = 0; // Current level during level order traversal 26 27 // Continue while there are nodes in the queue 28 while (!nodeQueue.empty()) { ++currentLevel; // Increment level counter 29 30 int levelSum = 0; // Sum of nodes at the current level 31 32 // Process all nodes of the current level 33 for (int remaining = nodeQueue.size(); remaining > 0; --remaining) { 34 TreeNode* currentNode = nodeQueue.front(); // Get the next node 35 nodeQueue.pop(); // Remove the node from the queue 36 levelSum += currentNode->val; // Update the level's sum

// Add child nodes to the queue for the next level

// Update the max sum and result level

resultLevel = currentLevel;

if (maxSum < levelSum) {</pre>

maxSum = levelSum;

// Return the level with the max sum

* Calculates the maximum level sum of a binary tree.

function maxLevelSum(root: TreeNode | null): number {

// Variable to store the level with the maximum sum

// Variable to keep track of the current maximum sum

// Get the number of nodes in the current level

// Add the node's value to the level sum

if (node.left) queue.push(node.left);

if (node.right) queue.push(node.right);

// Check if the current level has the maximum sum so far

// Update the maximum sum and the corresponding level

// If the left child exists, add it to the queue

// If the right child exists, add it to the queue

const queue: (TreeNode | null)[] = [root];

let maximumSum = Number.NEGATIVE_INFINITY;

// Loop until the queue is empty

let levelSize = queue.length;

while (queue.length !== 0) {

if (node) {

// Height starts at 1, as levels are 1-indexed

// Initialize sum for the current level

levelSum += node.val;

if (levelSum > maximumSum) {

maximumSum = levelSum;

maximumLevel = height;

// Return the level that has the maximum sum

The while loop will run once for each level of the tree.

// Move to the next level

Time and Space Complexity

height++;

return maximumLevel;

* @param {TreeNode | null} root - The root node of the binary tree.

* @returns {number} The level (1-indexed) with the maximum sum.

// Queue to hold nodes to visit using breadth-first search

return resultLevel;

// Definition for a binary tree node.

left: TreeNode | null;

let maximumLevel = 1;

let height = 1;

right: TreeNode | null;

Typescript Solution

interface TreeNode {

val: number;

if (currentNode->left) nodeQueue.push(currentNode->left);

if (currentNode->right) nodeQueue.push(currentNode->right);

28 let levelSum = 0; 29 30 // Process all nodes for the current level 31 for (let i = 0; i < levelSize; i++) {</pre> // Remove the first node from the queue 33 const node = queue.shift();

The given code block is designed to find the level of a binary tree that has the maximum sum of values of its nodes.

The time complexity of the code can be determined by analyzing the operations performed for each node in the tree:

Inside this loop, a for loop iterates through all nodes at the current level. Since each node is visited exactly once during the BFS traversal, all the nodes in the tree will be accounted for. Thus, if there are N nodes in the tree, the code has a time complexity of O(N) as each node is processed once.

Time complexity

Space complexity The space complexity is dependent on the storage used throughout the algorithm:

• The queue q holds the nodes at the current level being processed. In the worst case, this is equal to the maximum width of the

- tree, which occurs at the level with the most nodes. The maximum number of nodes at any level of a binary tree could be up to N/2 (in a complete binary tree).
- Therefore, the space complexity is O(N) in the worst case, because of the queue.