

2520. Count the Digits That Divide a Number

EasyMath

Problem Description

Given an integer `num`, the task is to find out how many of its own digits can divide the number itself without leaving a remainder. To clarify, for a digit `d` in `num` to be a valid divisor, the number `num` divided by this digit `d` should result in a whole number, meaning that `num % d` should equal `0`. It is important to note that the integer `num` will not contain the digit `0`, ensuring we avoid division by zero. You're expected to count all such digits that divide `num` and return this count as your answer.

Intuition

The basic idea for solving this problem is straightforward: go through each digit in the integer `num` and check if `num` can be divided by that digit without any remainder. We keep a count of all such digits that meet the criteria.

To implement this, we can use a while loop to iterate over the digits of `num`. In each iteration, we:

- Obtain the last digit of `num` by using the `divmod` operation with `10`, which gives us both the quotient and the remainder. The remainder here is the last digit which we will check for divisibility.
- If `num` is divisible by this digit (checked by `num % val == 0`), we increment our answer count.
- We continue this process until we've checked all digits of `num`.

By following this process, we can count and return the number of digits in `num` that divide `num` itself.

Solution Approach

The implementation of the provided solution makes use of a simple while loop and basic arithmetic operations to solve the problem. This approach does not require additional data structures, thus maintaining a low space complexity. Here's how the solution is implemented, step-by-step:

- Initialize `ans` as `0` which will hold our count of valid digits and `x` as `num` to begin processing the digits.
- Use a while loop that continues as long as `x` is greater than `0`. This loop will help us process each digit from right to left until we have iterated through all the digits of `num`.
- Inside the loop, the `divmod(x, 10)` function is used to divide `x` by `10`. `divmod` returns two values: the quotient and the remainder. The quotient is stored back in `x` for the next iteration, effectively removing the last digit from `x`. The remainder, which is the last digit of `x`, is stored in `val`.
- An inline conditional statement checks if the current digit `val` divides `num` evenly (`num % val == 0`). If the condition is true, it increments the `ans` counter by `1`.
- Once all digits have been processed and the loop ends, the function returns the value of `ans`, which now represents the total count of digits in `num` that can divide it without a remainder.

By iterating through each digit and checking divisibility, the algorithm ensures that all possible divisors are considered. This approach is an example of enumeration, where every element in a set (in this case, every digit of an integer) is counted for its validity against a specific condition (divisibility). Hence, every digit is enumerated to determine whether it divides the original number.

This solution is efficient as it processes each digit once and performs a constant number of operations per digit, leading to a time complexity that is linear with respect to the number of digits in `num`.

Example Walkthrough

Let's walk through a concrete example to illustrate the solution approach. Consider the integer `num = 252`. We need to find out how many of its digits can divide the number itself without leaving a remainder.

Following the solution approach step by step:

- Initialize `ans = 0` as the count of valid digits that divide `num` and `x = num` which in our case is `x = 252`.
- Set up a while loop that continues while `x > 0`. Beginning with `x = 252`, we will iterate through each digit.

The first iteration goes as follows:

- We use `divmod(x, 10)` to divide `x` by `10`. For the first iteration, `divmod(252, 10)` returns `(25, 2)`. We update `x` to `25` and `val` to `2`.
- We check if `num % val == 0`. Since `252 % 2 == 0`, the condition is true, and we increment `ans` to `1`.

The second iteration:

- `x` has been updated to `25`, and we perform `divmod(25, 10)` which gives us `(2, 5)`. Now, `x = 2` and `val = 5`.
- Again, we check `num % val`. Here, `252 % 5 == 2`, leaving a remainder. Therefore, we do not increment `ans`.

The third iteration:

- Now with `x = 2`, when we use `divmod(2, 10)` we get `(0, 2)`. We update `x` to `0` for the next iteration (which won't happen since `x` is now `0`), and `val = 2`.
- Checking `num % val` one last time, we find that `252 % 2 == 0`. Since it divides evenly, we increment `ans` to `2`.

The while loop ends because `x` is now `0`, and we have processed all digits. We return the final count `ans`, which is `2`.

In this example, two of the digits (`2` and `2`) can divide `252` without a remainder. So the function would return `2`.

Solution Implementation

Python

```
class Solution:
    def countDigits(self, num: int) -> int:
        # Initialize 'count' to keep track of the count of digits
        count = 0

        # Make a copy of the input number for manipulation
        temp_num = num

        # Iterate until the copied number is reduced to 0
        while temp_num:
            # Divide 'temp_num' by 10 to isolate the rightmost digit ('digit')
            # and reduce 'temp_num' for the next iteration
            temp_num, digit = divmod(temp_num, 10)

            # Avoid a division by zero and check if the digit divides 'num' without a remainder
            if digit != 0 and num % digit == 0:
                # If the digit divides 'num', increment the 'count'
                count += 1

        # Finally, return the count of such digits
        return count
```

Java

```
class Solution {
    public int countDigits(int num) {
        int count = 0; // Initialize count of digits

        // Loop through each digit of the number
        for (int current = num; current > 0; current /= 10) {
            int digit = current % 10; // Get the last digit

            // Check if digit is non-zero and perfectly divides the num
            if (digit != 0 && num % digit == 0) {
                count++; // Increment count if condition is met
            }
        }

        return count; // Return the final count
    }
}
```

C++

```
class Solution {
public:
    // Function to count the number of digits in 'num' that are divisors of 'num'
    int countDigits(int num) {
        int count = 0; // Variable to store the count of digits that are divisors of 'num'
        for (int current = num; current > 0; current /= 10) {
            int digit = current % 10; // Extract the rightmost digit of 'current'

            // Avoid division by zero error when the digit is 0
            if (digit == 0) continue;

            // Check if 'num' is divisible by 'digit'
            if (num % digit == 0) {
                ++count; // Increment the count if 'digit' is a divisor of 'num'
            }
        }
        return count; // Return the final count of divisor digits
    }
};
```

TypeScript

```
function countDigits(num: number): number {
    let count = 0; // Initialize a variable to count the digits that meet the criteria
    for (let current = num; current; current = Math.floor(current / 10)) { // Iterate over each digit of the number
        let digit = current % 10; // Extract the current digit

        // Check if the original number is divisible by the current digit
        // and ensure not to divide by 0
        if (digit !== 0 && num % digit === 0) {
            count++; // Increment count if the number is divisible by the digit
        }
    }
    return count; // Return the total count of divisible digits
}
```

class Solution:
 def countDigits(self, num: int) -> int:
 # Initialize 'count' to keep track of the count of digits
 count = 0

 # Make a copy of the input number for manipulation
 temp_num = num

 # Iterate until the copied number is reduced to 0
 while temp_num:
 # Divide 'temp_num' by 10 to isolate the rightmost digit ('digit')
 # and reduce 'temp_num' for the next iteration
 temp_num, digit = divmod(temp_num, 10)

 # Avoid a division by zero and check if the digit divides 'num' without a remainder
 if digit != 0 and num % digit == 0:
 # If the digit divides 'num', increment the 'count'
 count += 1

 # Finally, return the count of such digits
 return count

Time and Space Complexity

The time complexity of the code is $O(\log \text{ num})$. This is because the while loop runs as many times as there are digits in `num`. The number of digits in a number increases with the logarithm of the number, hence the logarithmic complexity.

The space complexity of the code is $O(1)$. The space used by the algorithm does not depend on the size of the input number `num`, as it only uses a fixed number of integer variables (`ans`, `x`, and `val`) regardless of the input size.