2746. Decremental String Concatenation

String Medium Array Dynamic Programming

Leetcode Link

Problem Description In this problem, we are given an array called words, which contains 'n' strings, each indexed from 0 to n-1. We need to combine these

the same as the first character of the second string, we have to remove one of these matching characters while joining them. The goal is to perform n - 1 join operations to generate a single string in such a way that the final string's length is as small as possible. Here's what we are allowed to do during each join operation:

strings using a special 'join' operation which merges two strings together. But there's a twist: if the last character of the first string is

Alternatively, we can prepend the next string in the array words to the current string str_i.

We can append the next string in the array words to the current string str_i.

Intuition

word. The impact of this choice on the final string length can vary depending on the matching characters at the edges of the strings

being joined.

We aim to minimize the overall length each time we make a join. To do this for n - 1 operations, an intuition may lead us to dynamic programming or recursion to check every possibility, remembering the results of sub-problems to avoid redundant calculations. Since the problem is about making choices at each step and optimizing for the 'smallest length', and considering that each choice might impact the subsequent ones, we can visualize the decision-making process as a tree. This is a common characteristic of

To arrive at the solution approach, consider that at every step of joining, we have two choices: either append or prepend the next

problems where backtracking or dynamic programming is a fit. The solution uses recursion with memoization (notice the use of the @cache decorator) to explore all possible concatenations and

record the results for sub-problems, thus avoiding the recalculation of the same state. The dfs function takes into account the current position i, as well as the potential characters at the beginning and end of the current concatenated string (a and b) to make decisions leading towards the minimum length of the final string.

Each call to the dfs function considers the effect of performing a join operation via appending or prepending the current word to the string being built so far and tracks which operation gives the shorter result. The use of a recursive function with memoization allows the efficient solving of this optimization problem by making the complexity feasible for larger input sizes. Solution Approach

The implementation relies on Depth-First Search (DFS) recursion with memoization to efficiently explore all possible concatenation sequences. The @cache decorator is used to memoize the results. Let's examine how the solution works by breaking down the key components of the implementation:

The base case for the recursion is when i exceeds the number of words we have. At that point, there are no more words to join,

Example Walkthrough

these strings to minimize the overall length.

appending or prepending the next word "dac".

from.

6

8

9

10

11

12

13

20

21

22

23

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

24 # Example usage:

25 # solution = Solution()

from typing import List

import functools

chosen by the DFS algorithm.

@functools.lru_cache(None)

if i >= len(words):

Python Solution

class Solution:

string up to this point.

the starting character of s.

 When inside dfs, we consider the next word s to be joined with the current string. We have two choices resembling a binary tree's branches:

Append: Where we consider adding s to the end of the current string, so we call dfs(i + 1, a, s[-1]), passing s[-1] as

the new ending character since we're appending. We subtract 1 from the length if the current ending character b matches

and the function returns 0 because there is no extra length to add from additional words.

- Prepend: Where we consider adding s at the beginning, so we call dfs(i + 1, s[0], b), passing s[0] as the new starting character. We subtract 1 from the length if the ending character s [-1] matches the current beginning character a. • The recursive calls return the sum of the length of the current word s and the minimum length from the two choices (append or prepend). The subtraction of 1 accounts for the removed character when there is a match.
- The final return statement return len(words[0]) + dfs(1, words[0][0], words[0][-1]) initiates the process with the first word, taking its length and appending the result of the recursive call starting from the second word with the first word's beginning and ending characters.
- recursive calls, especially for large arrays with many possible combinations. Overall, this solution showcases a classic recursive problem-solving strategy enhanced with memoization, a powerful way to optimize recursive depth-first search algorithms.

Let's take an example array of words: ["abc", "cda", "dac"]. We will walk through the process to understand how we might join

Firstly, starting with the first word "abc", we initiate the recursive process. There are no characters on either side, so a and b are 'a'

Now, we look at the next word "cda". We have two choices: 1. Append: If we append "cda" to "abc", the resulting string would be "abccda" because the last character of "abc" is the same as

the first of "cda", we can combine them by removing one 'c'. So, the string becomes "abcdac". We then call dfs(2, 'a', 'a')

Continuing with the recursion, we now have the third word "dac" and the choices described above for the second word:

since we have moved on to the next word and the end character has been updated to 'a' from "cda".

and 'c' respectively, which represent the first and last characters of the current string.

1. If we chose to append during the previous operation, we now have "abcdac":

2. If we chose to prepend in the previous operation, our string would be "cdabc":

def minimize_concatenated_length(self, words: List[str]) -> int:

Base case: all words have been considered

return 0 # No extra length is added

def search(i: int, first_char: str, last_char: str) -> int:

current_word = words[i] # Current word at index i

return len(words[0]) + search(1, words[0][0], words[0][-1])

26 # result = solution.minimize_concatenated_length(["abc", "bcd", "cde"])

Introduce caching to avoid recomputing overlapping subproblems

Recursive case for appending the current word to the first string

Start the search with the first word and its first and last characters

 Append: Append "dac" leading to "abcdacdac", and after removing the duplicate 'a', we have "abcdacdc". The recursive call would be dfs(3, 'a', 'c'). Prepend: Prepend "dac" leading to "dacabcdac", and after removing the duplicate 'd', it remains the same as prepending will not benefit us this time. The recursive call would be dfs(3, 'd', 'c').

Append: Append "dac" leading to "cdabcdac", with no character removed. The recursive call would be dfs(3, 'c', 'c').

Prepend: Prepend "dac" to "cdabc" leading to "daccdabc" and after removing the duplicate 'c', we have "dacdabc". The

- For each of these calls, we consider the removal of a duplicate character if there's a match at any end.
- In our example, assuming optimal choices were made, the solution might deduce that calling dfs(3, 'a', 'c') results in the smallest final string length. Ending with an efficient concatenated string "abcdacdc" or "dacdabc", depending on the sequence of operations

The memoization stores the results of each recursive call like dfs(2, 'a', 'a'), dfs(2, 'c', 'c'), dfs(3, 'a', 'c'), etc., so if the

function with the same set of parameters is called again, it doesn't recalculate but retrieves the value from the cache, saving time.

Recursive case for appending the current word to the second string 14 15 # Subtract 1 if the last character of current word matches the first character of the first string append_to_second = search(i + 1, current_word[0], last_char) - int(current_word[-1] == first_char) 16 17 # Add the length of the current word to the minimum of both scenarios 18 return len(current_word) + min(append_to_first, append_to_second) 19

Subtract 1 if the first character of current word matches the last character of the second string

append_to_first = search(i + 1, first_char, current_word[-1]) - int(current_word[0] == last_char)

Lines added include functools.lru_cache(None) to cache results of subproblems, explanatory comments, and better-named

variables for readability. The List type also should be imported from typing at the beginning of the file, as follows:

 The function dfs is the core of this solution. It takes three parameters: the current index i in the words array, a character a representing the beginning character of the string up to this point, and a character b representing the ending character of the

The @cache decorator on dfs ensures that for each unique set of inputs to the function (combinations of i, a, and b), the result is stored. If the same inputs are ever called again, the stored result is returned immediately, which significantly reduces the number of

2. Prepend: If we prepend "cda" to "abc", the resulting string would be "cdabc". There is no matching character in this case, so no character is removed. We then call dfs(2, 'c', 'c'), updating the start character to 'c'. The return value for each of these choices would be the length of "cda" (which is 3) plus the minimum of the lengths obtained from

recursive call would be dfs(3, 'd', 'c'). When i becomes equal to n, the recursion has considered all words, and we return o since there are no more words to add length

```
Java Solution
  1 class Solution {
        private Integer[][][] memoization; // 3D array for memoization to save calculated values
        private String[] words;
                                       // array of words
                                      // number of words
        private int wordCount;
  5
  6
        // The entry method that initiates the process
        public int minimizeConcatenatedLength(String[] words) {
  7
            this.wordCount = words.length; // store the number of words
  8
            this.words = words;
                                          // store the array of words
  9
            memoization = new Integer[wordCount][26][26]; // initialize the 3D array for memoization
 10
 11
            // Start the recursion with the first word, and use the first and last characters to track the state
 12
            return words[0].length() + dfs(1, words[0].charAt(0) - 'a',
 13
                                         words[0].charAt(words[0].length() - 1) - 'a');
 14
 15
 16
        // Recursive method to find the minimum concatenated length of words
 17
        private int dfs(int currentIndex, int firstCharIndex, int lastCharIndex) {
 18
            // Base case: if we have processed all words, return 0
 19
            if (currentIndex >= wordCount) {
 20
                return 0;
 21
 22
            // If this state has already been computed, return the stored value
 23
            if (memoization[currentIndex][firstCharIndex][lastCharIndex] != null) {
 24
                return memoization[currentIndex][firstCharIndex][lastCharIndex];
 25
 26
 27
            28
            int currentWordLength = currentWord.length();
                                                          // length of the current word
            int newLastCharIndex = currentWord.charAt(currentWordLength - 1) - 'a'; // index of the last character
 29
 30
```

// Choose the current word to be at the start of remaining part and compute the remaining minimum

// Choose the current word to be at the end of previously considered words and compute the remaining minimum

(currentWord.charAt(0) - 'a' == lastCharIndex ? 1 : 0);

int choiceAtEnd = dfs(currentIndex + 1, currentWord.charAt(0) - 'a', lastCharIndex) -

(newLastCharIndex == firstCharIndex ? 1 : 0);

// The total minimum length for this state is the length of the current word plus

// Store the computed value in memoization table and return it,

= currentWordLength + Math.min(choiceAtStart, choiceAtEnd);

return memoization[currentIndex][firstCharIndex][lastCharIndex];

if (memo[index][prevLastCharIndex][nextFirstCharIndex] > 0) {

// Get the current word and its length

const currentWordLength = currentWord.length;

const currentWord = words[index];

const option1 =

const option2 =

words[0].length +

return memo[index][prevLastCharIndex][nextFirstCharIndex];

// the adjacent character index from the previous or next word, respectively

dfs(index + 1, currentWord.charCodeAt(0) - 97, nextFirstCharIndex) -

// Store the result (minimum of the two options) in the memo array and return it

dfs(1, words[0].charCodeAt(0) - 97, words[0].charCodeAt(words[0].length - 1) - 97)

(currentWord.charCodeAt(0) - 97 === nextFirstCharIndex ? 1 : 0);

// The two options represent attaching the current word at the beginning or the end

// Calculate the next value recursively while reducing 1 if the first or last character matches

dfs(index + 1, prevLastCharIndex, currentWord.charCodeAt(currentWordLength - 1) - 97) -

return (memo[index][prevLastCharIndex][nextFirstCharIndex] = Math.min(option1, option2) + currentWordLength);

// Call the helper function with the first word and initial indices for previous last character and next first character

(currentWord.charCodeAt(currentWordLength - 1) - 97 === prevLastCharIndex ? 1 : 0);

// the minimum of choosing the word at the start or the end

memoization[currentIndex][firstCharIndex][lastCharIndex]

int choiceAtStart = dfs(currentIndex + 1, firstCharIndex, newLastCharIndex) -

class Solution { public: 11 12 13

C++ Solution

1 #include <vector>

2 #include <string>

#include <cstring>

#include <algorithm>

using namespace std;

#include <functional>

```
// Function to minimize concatenated length of the given words sequence
         int minimizeConcatenatedLength(vector<string>& words) {
             int numWords = words.size(); // Number of words in the vector
             int dp[numWords][26][26]; // Dynamic Programming (DP) table
 14
 15
             memset(dp, 0, sizeof(dp)); // Initialize the DP table with zeros
 16
 17
             // Recursive depth-first search function to find the
 18
             // minimized concatenation length for the given words
             // starting from index i with a and b as the last characters
 19
 20
             function<int(int, int, int)> dfs = [&](int index, int lastCharOfPrev, int firstCharOfNext) {
 21
                 if (index >= numWords) { // Base case: reached the end of the words vector
 22
                     return 0;
 23
 24
 25
                 if (dp[index][lastCharOfPrev][firstCharOfNext]) { // Already calculated this subproblem
 26
                     return dp[index][lastCharOfPrev][firstCharOfNext];
 27
 28
 29
                 string currentWord = words[index]; // Current word to process
 30
                 int wordLength = currentWord.size(); // Length of the current word
                 int option1 = dfs(index + 1, lastCharOfPrev, currentWord[wordLength - 1] - 'a') - (currentWord[0] - 'a' == firstCharOfN
 31
                 int option2 = dfs(index + 1, currentWord[0] - 'a', firstCharOfNext) - (currentWord[wordLength - 1] - 'a' == lastCharOfP
 32
 33
 34
                 // Store the result in the DP table for memoization
 35
                 // Adding the length of the current word and taking the minimum option
                 return dp[index][lastCharOfPrev][firstCharOfNext] = wordLength + min(option1, option2);
 36
             };
 37
 38
             // Start DFS with the first word and the last characters of the first word
 39
 40
             return words[0].size() + dfs(1, words[0].front() - 'a', words[0].back() - 'a');
 41
 42 };
 43
Typescript Solution
  1 // Define the function to minimize the concatenated length of strings in an array
    function minimizeConcatenatedLength(words: string[]): number {
         const numWords = words.length;
        // Create a 3D array to store intermediate results for memoization
        // f[i][a][b] represents the minimum length from words[i], ending
  6
         // with char a and before words[i] starts with char b.
         const memo: number[][][] = Array.from({ length: numWords }, () =>
  8
             Array.from({ length: 26 }, () => Array(26).fill(0))
  9
         );
 10
 11
 12
         // Define a helper method for depth-first search
         const dfs = (index: number, prevLastCharIndex: number, nextFirstCharIndex: number): number => {
 13
 14
             // Base case: when all words have been considered, return 0
 15
             if (index >= numWords) {
 16
                 return 0;
 17
             // If the result is already computed, return it to avoid redundant calculations
 18
```

Time and Space Complexity

complexity as follows:

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

46

45 }

};

);

return (

Time Complexity The function dfs(i: int, a: str, b: str) is recursively called with different parameters, which correspond to the current index (i), the first character of the last added word to string a (a), and the last character of the last added word to string b (b). Since

memoization is used, each state will be computed at most once. There are n possible indices (n being the size of words), and each

word can provide 26 possible characters for a and b (assuming the input is lower-case English letters). Therefore, we have:

The given Python code implements a solution to minimize the concatenated length of a list of words by exploiting memoization

(using the @cache decorator, which caches the results of the dfs function calls). Analyzing the provided code, we can deduce the

For each state, operations are performed in constant time (0(1)) considering there is no loop within dfs, just two recursive calls and a few constant-time conditions and assignments: Operation per state: 0(1)

Number of states: n * 26 * 26

Therefore, the total time complexity is the number of states times the operations per state, which is: Total Time Complexity: 0(n * 26^2)

Space Complexity The space complexity is mainly affected by the call stack during the recursive calls, and the space used for memoization. In the worst case, the recursion depth can go up to n:

 Recursion stack: 0(n) The memoization will store results for every possible state:

 Memoization storage: 0(n * 26^2) Hence, the total space complexity can be seen as the maximum of the above two concerns. Since n * 26^2 is typically greater than

just n: Total Space Complexity: 0(n * 26^2)

Note: The exact constants for the number of characters would depend on the character set allowed in the input.