Medium Leetcode Link

The problem customInterval involves creating a scheduler that executes a function fn repeatedly with intervals that increase linearly

Problem Description

2805. Custom Interval

be used to stop the scheduled executions. customClearInterval is the function used to stop the execution of fn. It takes an id as input, which corresponds to the identifier returned by customInterval, and stops the scheduled execution that was associated with that id.

over time. Each execution interval is determined by the formula delay + period * count, where delay is the initial delay before the

first execution of fn, period is the increment factor which is added to the total delay for each subsequent execution, and count is a

counter that keeps track of how many times fn has been executed. The function customInterval must return an identifier id that can

Intuition

The customInterval function needs to schedule and execute the given function fn at the incrementally increasing intervals. The

approach to this is to set up a recursive timeout system, where after each execution of fn, a new timeout is scheduled with the

updated interval based on the linear pattern. This ensures that fn is executed repeatedly at the correct intervals.

To facilitate starting the timeout, we define a recursiveTimeout function inside customInterval. This helper function uses JavaScript's setTimeout to schedule fn's next execution, increases the count by 1 after each execution, and then calls itself to schedule the next execution.

Date.now(). This ensures each scheduled set of executions has a unique identifier, which is necessary for the customClearInterval function to properly identify and stop the correct execution. The customClearInterval function's intuition is to provide a way to cancel the scheduled execution. It uses the unique identifier id to

An intervalMap is used to keep track of all scheduled timeouts using a unique identifier id which in this case is generated by

look up and clear the scheduled timeout from intervalMap. This prevents future calls of fn and also removes the entry from the map to avoid potential memory leaks from keeping unnecessary timeouts in the map.

Solution Approach The solution to the problem uses a combination of a map for storing timeout references, recursion for scheduling future calls, and the setTimeout function for executing the provided function fn at increasing intervals.

1. Global Map for Timeout References (intervalMap): We initialize intervalMap, a JavaScript Map object, to store and retrieve the

timeout references using a unique number id. This id is used later to clear the timeout if needed. 2. Custom Interval Scheduling (customInterval):

• We first initialize a local count variable to 0 inside customInterval. This variable tracks the number of times fn has been called.

• We declare recursiveTimeout, a recursive function that will handle the scheduling of fn executions. Inside this function, the

setTimeout method is called with a delay calculated using the formula delay + period * count. Each time fn is executed,

• We store the result of setTimeout in the intervalMap. The key is the id, and the value is the timeout reference returned by

• We use Date.now() to generate a unique id for the current scheduling of fn. Date.now() returns the current timestamp in

3. Custom Interval Clearing (customClearInterval):

milliseconds, so it has a high probability of being unique.

setTimeout. This allows us to clear the specific timeout later.

• We immediately call recursiveTimeout to start the interval process.

count is incremented.

Here's how the implementation breaks down step by step:

 This function accepts an id and checks if this id exists in the intervalMap. If it exists, clearTimeout is called with the associated timeout reference, effectively stopping further executions of fn. • The id and its corresponding timeout reference are removed from intervalMap to free up memory and keep the map clean. Recursion is a key pattern used in the solution for scheduling future calls. Each time fn executes, recursiveTimeout schedules the

next execution. Instead of a standard interval where the delay between calls is constant, this pattern allows for the dynamic

calculation of the delay based on the execution count, providing a linearly increasing interval between the calls.

Example Walkthrough Let's illustrate the solution approach with an example: Suppose we want to schedule a function fn that simply logs "Hello, World!" to the console. We want the first execution to happen after an initial delay of 1000ms (1 second), and then each subsequent execution to be delayed by an additional 500ms.

Data structure usage (Map) allows us to efficiently keep track of and manage the different timeouts, providing a clean way to cancel

Now let's use the customInterval with delay of 1000ms and period of 500ms: 1 const id = customInterval(fn, 1000, 500);

4. After 1000ms, fn executes and logs "Hello, World!" to the console for the first time. The count is then incremented to 1.

5. The recursiveTimeout function inside customInterval schedules the next execution of fn using a new timeout. The new delay is

2. The intervalMap will hold this id as a key with the initial timeout reference as its value.

Upon calling this function:

Python Solution

1 from threading import Timer

Dictionary to keep track of custom intervals

def recursive_timeout(count):

from time import time

interval_map = {}

6

12

13

14

15

16

17

18

20

21

22

23

24

25

26

34

35

36

37

38

39

40

48

49

51

52

53

54

8

9

10

12

13

14

15

16

17

18

19

20

21

22

23

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

them when necessary.

We can declare fn as follows:

console.log("Hello, World!");

function fn() {

6. After 1500ms, fn executes for the second time, logging "Hello, World!" again, and count increases to 2.

calculated as 1000 + (500 * 1) = 1500 ms.

Here's a step-by-step explanation of what happens next:

1 customClearInterval(id);

If we want to stop this pattern, we can call customClearInterval and pass our id (1623249048531) as an argument:

1. A unique id for this interval is generated. Let's assume the id returned by Date.now() is 1623249048531.

3. The fn function is scheduled to execute after 1000ms for the first time, as count is 0.

7. This process continues with the delay increasing by 500ms after each execution.

1. The customClearInterval function looks for the id in intervalMap.

increasing intervals and how we can stop the schedule whenever needed.

:param fn: The function to execute after each delay period.

:return: An ID that can be used to clear the interval.

Helper function that recursively sets timers.

recursive_timeout(0) # Start the interval with count 0

current_delay = delay + period * count

Generate a unique ID for this interval

return interval_id # Return the unique ID

interval_id = int(time() * 1000)

def custom_clear_interval(interval_id):

if interval_id in interval_map:

Get the timer and cancel it

del interval_map[interval_id]

interval_map[interval_id].cancel()

Remove the interval ID from the dictionary

2. If it finds the id, it calls clearTimeout, using the timeout reference, which stops future scheduled executions of fn.

This example shows how the customInterval and customClearInterval functions manage the scheduled execution of fn with

def custom_interval(fn, delay, period): 9 Creates a custom interval that mimics setInterval but allows for increasing delay durations. 10 11

:param delay: The initial delay before the function execution in milliseconds.

:param count: The number of times the function has been called.

Schedule the function to be called after the calculated delay

Calculate new delay with added period for each interval

:param period: The additional delay added after each execution in milliseconds.

3. The id is removed from intervalMap, cleaning up the reference and ensuring no memory leaks.

27 timer = Timer(current_delay / 1000, lambda: recursive_timeout(count + 1)) 28 timer.start() # Start the timer 29 30 fn() # Execute the provided function 31 # Store the timer reference using the interval id 33 interval_map[interval_id] = timer

private Map<Long, ScheduledFuture<?>> intervalMap = new HashMap<>(); // Map to keep track of custom intervals

long[] count = new $long[]{0}; // Counter$ to track the number of times the function has been called

ScheduledFuture<?> scheduledFuture = executorService.schedule(task, delay, TimeUnit.MILLISECONDS);

ScheduledFuture<?> scheduledFuture = executorService.schedule(this, delay + period * count[0], TimeUnit.MILLISECONDS)

private ScheduledExecutorService executorService = Executors.newScheduledThreadPool(10);

* Creates a custom interval that mimics setInterval but allows for increasing delay durations.

// Assuming a maximum of 10 concurrent intervals to handle, can be adjusted as needed.

* @param runnable The function (Runnable) to execute after each delay period.

* @param delay The initial delay before the function execution in ms.

* @param period The additional delay added after each execution in ms.

public long customInterval(Runnable runnable, long delay, long period) {

// Helper class that recursively schedules the runnables

// Reschedule this task with increased delay

intervalMap.put(id, scheduledFuture);

// Schedule the task to start after the initial delay

* @return An ID that can be used to clear the interval.

// Execute the provided runnable

class RecursiveTask implements Runnable {

// Increment the count

// Generate a unique ID for this interval

RecursiveTask task = new RecursiveTask();

long id = System.currentTimeMillis();

intervalMap.put(id, scheduledFuture);

return id; // Return the unique ID

public void run() {

count [0]++;

runnable.run();

```
42
43
       Clears a custom interval by ID.
44
45
        :param interval_id: The ID of the interval to clear.
46
47
       # Check if the interval ID exists in the dictionary
```

Java Solution

/**

2 import java.util.Map;

1 import java.util.concurrent.*;

public class CustomInterval {

import java.util.HashMap;

```
43
44
         /**
45
46
47
```

```
* Clears a custom interval by ID.
        * @param id The ID of the interval to clear.
48
49
       public void customClearInterval(long id) {
           ScheduledFuture<?> scheduledFuture = intervalMap.get(id);
50
51
           if (scheduledFuture != null) {
52
               // Cancel the scheduled task
53
               scheduledFuture.cancel(false);
               // Remove the interval ID from the map
54
               intervalMap.remove(id);
55
56
57
58 }
59
C++ Solution
  1 #include <functional>
  2 #include <chrono>
    #include <thread>
  4 #include <map>
    #include <mutex>
  7 // A map to keep track of custom intervals
  8 std::map<long long, std::thread> intervalMap;
  9 std::mutex intervalMapMutex; // Mutex to protect access to the intervalMap
 10
 11 /**
     * Creates a custom interval that mimics setInterval but allows for increasing delay durations.
 13
     * @param fn A function to execute after each delay period.
 14
     * @param delay The initial delay before the function execution in ms.
     * @param period The additional delay added after each execution in ms.
     * @return A unique ID that can be used to clear the interval.
 18
     */
     long long customInterval(const std::function<void()>& fn, int delay, int period) {
         // Counter to track the number of times the function has been called
 20
 21
         int count = 0;
 22
 23
         // Generate a unique ID for this interval
 24
         long long id = std::chrono::system_clock::now().time_since_epoch().count();
 25
 26
         // Helper lambda function that recursively sets timeouts
 27
         std::function<void()> recursiveTimeout = [&fn, delay, period, &count, id]() {
             std::this_thread::sleep_for(std::chrono::milliseconds(delay + period * count));
 28
 29
                 // Ensure exclusive access to the intervalMap before checking
 30
                 std::lock_guard<std::mutex> lock(intervalMapMutex);
 31
 32
                 if (intervalMap.find(id) == intervalMap.end()) {
 33
                     return; // If the interval id is not found, stop the recursion.
 34
 35
 36
             fn(); // Execute the provided function
 37
             count++; // Increment the count
 38
             recursiveTimeout(); // Set up the next interval
 39
         };
 40
 41
         // Start the interval in a new thread
         std::thread intervalThread(recursiveTimeout);
 43
 44
         // Store the thread in the intervalMap
 45
 46
             // Ensure exclusive access to the intervalMap before inserting
             std::lock_guard<std::mutex> lock(intervalMapMutex);
 47
 48
             intervalMap[id] = move(intervalThread);
 49
 50
 51
         // Return the unique ID
 52
         return id;
```

fn(); // Execute the provided function 18 19 count++; // Increment the count recursiveTimeout(); // Set up the next interval 20 21 }, delay + period * count); 22 23 intervalMap.set(id, timeoutId); // Store the timeout reference in the map

const id = Date.now();

* Clears a custom interval by ID.

if (intervalMap.has(id)) {

Typescript Solution

53

54

57

58

59

61

63

64

65

66

67

69

70

71

72

73

/**

*/

10

12

13

14

15

16

17

24

25

26

27

28

29

31

34

36

38

39

40

43

30 }

32 /**

*/

*/

* Clears a custom interval by ID.

* @param id The ID of the interval to clear.

// Check if the interval ID exists in the map

// Remove the interval ID from the map

std::lock_guard<std::mutex> lock(intervalMapMutex);

// If found, it means the thread is running. Join the thread before erasing it.

const intervalMap = new Map<number, NodeJS.Timeout>(); // Map to keep track of custom intervals

* Creates a custom interval that mimics setInterval but allows for increasing delay durations.

let count = 0; // Counter to track the number of times the function has been called

* @param {Function} fn - The function to execute after each delay period.

* @returns {number} An ID that can be used to clear the interval.

// Helper function that recursively sets timeouts

const timeoutId = setTimeout(() => {

// Generate a unique ID for this interval

recursiveTimeout(); // Start the interval

* @param {number} id - The ID of the interval to clear.

// Check if the interval ID exists in the map

clearTimeout(intervalMap.get(id)!);

// Remove the interval ID from the map

return id; // Return the unique ID

function customClearInterval(id: number) {

intervalMap.delete(id);

// Get the timeout and clear it

function recursiveTimeout() {

* @param {number} delay - The initial delay before the function execution in ms.

function customInterval(fn: Function, delay: number, period: number): number {

// Schedule the function to be called after the calculated delay

* @param {number} period - The additional delay added after each execution in ms.

void customClearInterval(long long id) {

auto it = intervalMap.find(id);

if(it->second.joinable()) {

it->second.join();

if (it != intervalMap.end()) {

intervalMap.erase(it);

```
Time and Space Complexity
Time Complexity:
The time complexity of the customInterval function primarily depends on the number of times the callback function fn is executed.
However, since the scheduling of the function execution isn't a part of the actual computation, the time complexity for the JavaScript
runtime to handle the execution of customInterval itself is 0(1). The time complexity of fn will depend on the implementation of the
function that is passed to customInterval.
For customClearInterval, the time complexity is 0(1) since it performs a constant number of operations: checking if the id exists in
the map and potentially clearing the timeout and removing the id from the map.
```

Space Complexity: The space complexity of the customInterval function is O(n), where n is the number of active intervals. This is because it stores

each interval's ID and corresponding timeout in the intervalMap.

Similarly, the space complexity for customClearInterval is 0(1). It does not allocate additional space that grows with the size of the input, as it simply removes an element from intervalMap.