

1408. String Matching in an Array

Easy Array String String Matching

[Leetcode Link](#)

Problem Description

In this problem, we are given an array of string `words`. Our task is to find all the strings in the array that are a substring of another string within the same array. In other words, we are looking for any string `w1` from the `words` array that can be found within another string `w2` in the same array, where `w1` and `w2` are not the same string. A substring, by definition, is a contiguous sequence of characters within a string; it could be as short as one character or as long as the string itself minus one character. Our final output is an array that includes these substrings, and the order of the substrings in the output doesn't matter.

Intuition

The intuition behind the solution is straightforward: we need to find if any word is part of another word in the array. We can achieve this by comparing each word with every other word in the array. This can be done through a nested loop where for every word `w1`, we look through the whole array to check if there's another word `w2` that contains `w1` as a substring. If such a `w2` is found, we can conclude that `w1` is a substring of another word in the array.

We use an inner loop and an outer loop to iterate through the array of words. For each word in the outer loop (`w1`), we iterate through all other words in the array in the inner loop (`w2`). If we find that `w1` is contained within `w2` (`w1` is a substring of `w2`) and `w1` is not the same as `w2` (to avoid comparing a word with itself), we can add `w1` to the answer list. Once `w1` has been found as a substring, we don't need to check the rest of the words for `w1`, so we use a `break` statement to move on to the next word in the outer loop.

This approach ensures that we check all pairs of words to determine which ones are substrings of another. Once all checks are completed, we return the list of substrings we found.

Note that we may have duplicate words in the input array, and our approach avoids adding a word multiple times to the answer list by breaking the inner loop as soon as we find the first match.

Solution Approach

The solution approach takes advantage of a simple brute force method to solve the problem, utilizing two nested `for` loops to compare every pair of words.

Algorithms and Patterns

Brute Force Comparison

- We iterate through the `words` array using an outer loop. Each word encountered in this loop will be referred to as `w1`.
- For each `w1`, we use another inner loop to iterate through all other words in the array, which we refer to as `w2`.
- We compare `w1` to every `w2`, ensuring not to compare a word with itself by checking that the indices `i` and `j` are not equal (`i != j`). If `w1` is the same as `w2`, it doesn't count as a substring, so we only want to find instances where `w1` is contained in a different `w2`.

Substring Check

- The check `w1 in w2` is used to determine if `w1` is a substring of `w2`. This is a built-in operation in Python that checks for the presence of a sequence of characters within another sequence.
- If the condition is met, we append `w1` to our answer list `ans`.
- After appending `w1` to the answer list, we don't need to check it against the remaining `w2` words in the loop, as we have already confirmed it is a substring. This is where we break the inner loop.

Data Structures

- A list `ans` is used to store the words that satisfy the condition of being a substring of another word.

Code Representation

The solution in Python looks like this:

```
1 class Solution:
2     def stringMatching(self, words: List[str]) -> List[str]:
3         ans = []
4         for i, w1 in enumerate(words):
5             for j, w2 in enumerate(words):
6                 if i != j and w1 in w2:
7                     ans.append(w1)
8                     break
9         return ans
```

In this code snippet, `enumerate` is a handy function that provides a counter (`i` and `j`) to the loop which we use to ensure we are not comparing the same word with itself. When we find a match, we immediately break out of the inner loop to avoid unnecessary checks, which is a minor optimization within the brute force approach.

The idea of breaking out of the loop as soon as we find a word is a substring ensures that the algorithm doesn't do excessive work. However, it's worth noting that the algorithm's time complexity is $O(n^2 * m)$, where n is the number of words and m is the average length of a word. This is because, in the worst case, for each outer loop word, we potentially check all other words and each character within those words for being a substring.

By returning the `ans` list after the loops have completed, we have solved the problem by collecting all strings in the input array that are substrings of another word.

Example Walkthrough

Let's consider a small example to illustrate the solution approach. Suppose we have the following array of strings:

```
1 words = ["mass", "as", "hero", "superhero", "cape"]
```

We want to find all strings that are a substring of another string in this list. Using the brute force method, we follow these steps:

- We start with the outer loop, taking `w1 = "mass"`.
- We enter the inner loop and compare `w1` with every `w2`.
 - When `j = 0`, we compare `w1` with `"mass"`; since they are the same, we continue.
 - When `j = 1`, we compare `w1` with `"as"`; the word `"mass"` does not contain `"as"` as a substring, we continue.
 - When `j = 2`, we compare `w1` with `"hero"`, we continue since there's no match.
 - The same goes for `"superhero"` and `"cape"`, no matches are found.
- We move on to `w1 = "as"`.
 - When `j = 0`, comparing `"as"` to `"mass"`, we find that `w1` is a substring of `w2`. We add `"as"` to the answer list and break the loop.
- Next is `w1 = "hero"`.
 - No matches for `"mass"`, `"as"`, but when we reach `"superhero"`, we find that `w1` is a substring of `w2`. We add `"hero"` to the answer list and break the loop.
- For `w1 = "superhero"` and `w1 = "cape"`, we find no substrings, as they are not contained in any other word in the list.

Now that we have gone through each word, our answer list `ans` contains `["as", "hero"]`. These two words were identified as substrings of `"mass"` and `"superhero"` respectively.

By looping through the entire list of words and comparing each pair, we have effectively applied the brute force solution to determine our answer.

Python Solution

```
1 from typing import List
2
3 class Solution:
4     def string_matching(self, words: List[str]) -> List[str]:
5         # Initialize an empty list for the answer
6         matching_substrings = []
7
8         # Iterate over the list of words
9         for index_outer, word1 in enumerate(words):
10             # Compare the current word (word1) with every other word in the list
11             for index_inner, word2 in enumerate(words):
12                 # Make sure not to compare the word with itself
13                 if index_outer != index_inner:
14                     # Check if word1 is a substring of word2
15                     if word1 in word2:
16                         # If it is, add to the answer list and break to avoid duplicates
17                         matching_substrings.append(word1)
18                         break
19
20         # Return the list of matching substrings
21         return matching_substrings
22
```

Java Solution

```
1 import java.util.List;
2 import java.util.ArrayList;
3
4 class Solution {
5     // Method to find all strings in an array that are substrings of another string
6     public List<String> stringMatching(String[] words) {
7         // Initialize an empty list to hold the answer
8         List<String> matchedStrings = new ArrayList<>();
9         // Get the number of words in the array
10        int numberOfWords = words.length;
11
12        // Iterate through each word in the array
13        for (int i = 0; i < numberOfWords; ++i) {
14            // Inner loop to compare the current word with others
15            for (int j = 0; j < numberOfWords; ++j) {
16                // Check if words are different and if the current word is contained within another word
17                if (i != j && words[j].contains(words[i])) {
18                    // If the condition is true, add the current word to the list of matched strings
19                    matchedStrings.add(words[i]);
20                    // Break out of the inner loop, as we already found a matching word
21                    break;
22                }
23            }
24        }
25        // Return the list of matched strings
26        return matchedStrings;
27    }
28 }
29
```

C++ Solution

```
1 class Solution {
2 public:
3     // Function to find all strings in 'words' that are substrings of other strings
4     vector<string> stringMatching(vector<string>& words) {
5         vector<string> result; // To store the substrings
6         int numWords = words.size(); // Number of words in the input vector
7
8         // Loop through each word in the vector
9         for (int i = 0; i < numWords; ++i) {
10            // Nested loop to compare the current word with every other word in the vector
11            for (int j = 0; j < numWords; ++j) {
12                // Check if the current word is a substring of any other word, but not the same word
13                if (i != j && words[j].find(words[i]) != string::npos) {
14                    result.push_back(words[i]); // If it's a substring, add to the result vector
15                    break; // No need to check other words, break out of inner loop
16                }
17            }
18        }
19        return result; // Return the vector containing all substrings
20    }
21 };
22
```

Typescript Solution

```
1 function stringMatching(words: string[]): string[] {
2     const substrings: string[] = []; // Initialize an array to hold our result of substrings
3
4     // Iterate through each word in the provided array
5     for (const targetWord of words) {
6         // Iterate through the words again for comparison
7         for (const word of words) {
8             // Check if the current word is not the targetWord and includes the targetWord as a substring
9             if (word !== targetWord && word.includes(targetWord)) {
10                substrings.push(targetWord); // If conditions met, add the targetWord to our result array
11                break; // Break out of the inner loop as we have found the targetWord as a substring
12            }
13        }
14    }
15    return substrings; // Return the array containing all found substrings
16 }
17
18
```

Time and Space Complexity

Time Complexity

The time complexity of the given code can be analyzed by looking at the two nested loops where it iterates over all possible pairs of strings in the list, except when they are the same string (i.e., where `i != j`). For each pair, the code checks if one string is a substring of another by using `in` operation.

If we assume `n` is the number of words and `m` the maximum length of a word, the check `w1 in w2` has a worst-case complexity of $O(m^2)$ because in the worst case, every character in `w1` might be checked against every character in `w2` before a match is found or the end of `w2` is reached.

Given that we have two nested loops each going through `n` elements, and assuming the worst-case scenario for the substring check, the overall time complexity of this algorithm would be $O(n^2 * m^2)$.

Space Complexity

The space complexity of the code is determined by the additional memory we use, aside from the input. Here, the only extra space that we use is the `ans` list, which in the worst case may contain all the original strings, if all strings are substrings of at least one other string.

Thus the space required for the `ans` list is $O(n * m)$, as it can store at most `n` strings, with each string having a length at most `m`.

The final space complexity for the algorithm is $O(n * m)$ since this is the most significant additional space the algorithm uses.