

2571. Minimum Operations to Reduce an Integer to 0

Medium

Greedy

Bit Manipulation

Dynamic Programming

Leetcode Link

Problem Description

You are given a positive integer `n`. The task is to transform `n` to `0` by repeatedly performing the following operation: add or subtract a power of `2` to/from `n`. The available powers of `2` range from 2^0 up to any higher power (as 2^1 , 2^2 , and so on). The goal is to find the *minimum* number of such operations required to achieve `n = 0`.

In simpler words, you're essentially allowed to repeatedly increase or decrease the integer `n` by any value that is a power of `2` (like `1`, `2`, `4`, `8`, and so on), and you need to find the least number of times you have to do this to get to `0`.

Intuition

The solution involves a strategic approach rather than trying out different powers of `2` at random. We look at the binary representation of the given integer `n`. Since binary representation is based on powers of `2`, incrementing or decrementing by powers of `2` can be visualized as flipping specific bits in the binary form.

So, we scan through the binary digits (bits) of `n` from least significant to most significant (from the right-hand side to the left).

- If we encounter a `1` bit, this represents a power of `2` that we need to cancel out. We keep a running total of consecutive `1` bits because a string of `1`s may be dealt with more efficiently together rather than individually.
- When we encounter a `0` bit, this provides an opportunity to address the consecutive `1` bits encountered before it. If there's only one `1` bit, we can perform a single subtract operation to remove it. If there are multiple `1`s, we can turn all but one of them into `0` by adding a power of `2` that's just higher than the string of `1`s. This adds `1` to the count of subtract operations needed.

In the end, we might be left with a string of `1`s at the most significant end. We'll need two operations if there are multiple `1`s (add and then subtract the next higher power of `2`), or just one if there's a single `1`.

The algorithm hence devised is cautious; it chooses the most effective operation at each step due to its bitwise considerations, ensuring fewer total operations.

Solution Approach

The Python code provided implements the algorithm through a mix of bitwise operations and a greedy approach.

Let's walk through the implementation:

- Initialize `ans` and `cnt`. The variable `ans` keeps track of the total number of operations required, and `cnt` counts the consecutive `1` bits in the binary representation of `n`.
- Process the binary digits of `n` from least significant to most significant. This is done by examining `n` bit by bit in a loop where the iteration involves a right shift operation `n >>= 1`, effectively moving to the next bit towards the left.
- When the current bit is `1` (checked by `if n & 1`), increment the `cnt` by `1`. This is because each `1` represents a power of `2` that must be addressed.
- If the current bit is `0` and `cnt` is not zero, this indicates we have just finished processing a sequence of `1` bits. Now, determine how to handle them:
 - If `cnt` equals `1`, increment `ans` by `1`, as we need one operation to subtract this power of `2`.
 - If `cnt` is more than `1`, increment `ans` by `1` and set `cnt` to `1`. The rationale here is that we've added a power of `2` that turns all but one of the consecutive `1` bits into `0`. We're left with one last subtraction operation to perform later.
- After processing all bits, there may be a leftover `cnt`:
 - If `cnt` is `1`, we only need one more operation, so add `1` to `ans`.
 - If `cnt` is greater than `1`, we need a two-step operation where we first add and then subtract the next power of `2`, hence add `2` to `ans`.
- Finally, return the accumulated result `ans`, which gives us the minimum number of operations needed to transform `n` into `0`.

By leveraging bitwise operations, the solution is both efficient and straightforward. There's no need for iteration or recursion that directly considers powers of `2`; instead, the solution operates implicitly on powers of `2` by manipulating binary digits, which are intrinsically linked to powers of `2`.

Example Walkthrough

Let's illustrate the solution approach using the example of `n = 23`. The binary representation of `23` is `10111`. We will apply the solution approach step by step:

- Initialize `ans = 0` and `cnt = 0`. No operations have been done yet.
- As `n` is `10111`, we process from the rightmost bit to the left:
 - Bit 1 (rightmost): `n & 1` is true so increment `cnt` to `1`.
 - Bit 2: `n & 1` is true so increment `cnt` to `2`.
 - Bit 3: `n & 1` is true so increment `cnt` to `3`.
 - Bit 4: `n & 1` is false, and `cnt` is `3`. Therefore, increment `ans` to `1` and reset `cnt` to `1` (because we perform an add operation to turn the sequence `111` into `1000`, which leaves one operation for later).
 - Last shift will happen, and now `n` becomes `2` (`10` in binary), and we've processed all bits.
- Leftover `cnt` is `1` because our binary representation now starts with `1`. We increment `ans` by `1` because a final subtract operation is needed.
- Finally, `ans` is `2` because we performed `2` operations in total: converting `10111` to `11000` (+1 operation) and then to `0` (-1 operation).

The minimum number of operations required to transform `n = 23` into `0` using the solution approach is `2`.

Python Solution

```
1 class Solution:
2     def minOperations(self, n: int) -> int:
3         # Initialize operations count (ops) and a counter for consecutive ones (consecutive_ones).
4         ops = 0
5         consecutive_ones = 0
6
7         # Process all bits of the integer n from right to left (LSB to MSB).
8         while n:
9             # Check if the least significant bit (LSB) is 1.
10            if n & 1:
11                # If it is, increase the counter for consecutive ones.
12                consecutive_ones += 1
13            # If it is 0 and the counter for consecutive ones is not zero.
14            elif consecutive_ones:
15                # A zero after some ones means a completed set of "10" or "110".
16                # Operation needed to convert this set to "00" or "100".
17                ops += 1
18                # Reset the counter for consecutive ones.
19                # '1' in binary is already minimized, and for '11' we only need one operation
20                # to change it to '10' and then we 'carry the 1' so to speak.
21                consecutive_ones = 0 if consecutive_ones == 1 else 1
22
23            # Right shift n by 1 to check the next bit.
24            n >>= 1
25
26        # If there is a residual 1 then an operation is needed;
27        # this could be a trailing '1' or '10' after the end of the loop.
28        if consecutive_ones == 1:
29            # Increment the operations count by 1.
30            ops += 1
31        # If there are more than 1 ones, an extra operation is needed to handle the carry.
32        elif consecutive_ones > 1:
33            # Increment the operations count by 2. This is the case for '11' in binary,
34            # where one operation is to change '11' to '10' and second operation to change
35            # '10' to '00'.
36            ops += 2
37
38        # Return the number of operations required.
39        return ops
40
```

Java Solution

```
1 class Solution {
2
3     public int minOperations(int num) {
4         // Initialize variables for answer and contiguous ones count
5         int operationsCount = 0;
6         int contiguousOnesCount = 0;
7
8         // Loop while number is greater than zero
9         for (; num > 0; num >>= 1) {
10            // If the least significant bit is 1
11            if ((num & 1) == 1) {
12                // Increment count of contiguous ones
13                contiguousOnesCount++;
14            } else if (contiguousOnesCount > 0) {
15                // If the least significant bit is 0 and we have seen a contiguous sequence of ones
16                operationsCount++; // Increase operations, since this is an operation to flip a zero after a one
17                // Reset/modify contiguous ones count based on the previous count
18                contiguousOnesCount = (contiguousOnesCount == 1) ? 0 : 1;
19            }
20        }
21
22        // After processing all bits, if there is a single one left, it is a valid operation to flip it
23        operationsCount += (contiguousOnesCount == 1) ? 1 : 0;
24
25        // If there are more than one contiguous ones left, we need two operations:
26        // one to flip the first one, and another one for the last one.
27        operationsCount += (contiguousOnesCount > 1) ? 2 : 0;
28
29        // Return the total number of operations required
30        return operationsCount;
31    }
32 }
33
```

C++ Solution

```
1 class Solution {
2 public:
3     int minOperations(int n) {
4         int operations = 0; // This will hold the total number of operations required.
5         int onesCount = 0; // This will count the number of consecutive '1' bits.
6
7         // Process each bit, starting with the least significant bit (LSB).
8         while (n > 0) {
9             if ((n & 1) == 1) {
10                // If the current bit is a '1', increment the count of consecutive ones.
11                ++onesCount;
12            } else if (onesCount > 0) {
13                // If we hit a '0' after counting some ones, we need an operation (either a flip or a move).
14                ++operations;
15
16                // If there was only one '1', we reset the count. Otherwise, we keep the count as '1',
17                // because the bit flip would transform "01" to "10", leaving us with one '1' to move.
18                onesCount = (onesCount == 1) ? 0 : 1;
19            }
20
21            // Right shift the bits in n to process the next bit in the next iteration.
22            n >>= 1;
23        }
24
25        // After processing all bits, if we have one '1' left, we need one more operation to remove it.
26        if (onesCount == 1) {
27            ++operations;
28        }
29
30        // If we have more than one '1', we need an additional two operations: one for flipping and one for moving.
31        if (onesCount > 1) {
32            operations += 2;
33        }
34
35        return operations; // Return the total number of operations calculated.
36    };
37 }
```

Typescript Solution

```
1 function minOperations(n: number): number {
2     let operationsCount = 0; // Will hold the total number of operations required.
3     let consecOnesCount = 0; // Counter for consecutive 1's in binary representation of n.
4
5     // Iterate through the bits of n.
6     while (n !== 0) {
7         // If the least significant bit is a 1.
8         if (n & 1) {
9             consecOnesCount += 1; // We found a consecutive one, increase the counter.
10        }
11        // If it's a 0 and there are consecutive 1's counted before.
12        else if (consecOnesCount > 0) {
13            operationsCount += 1; // We need an operation to separate the consecutive 1's.
14
15            // Reset consecOnesCount or set to 1 based on whether we had a single consecutive one or more.
16            consecOnesCount = (consecOnesCount === 1) ? 0 : 1;
17        }
18
19        // Right shift n to check the next bit.
20        n >>= 1;
21    }
22
23    // If there's a single 1 left.
24    if (consecOnesCount === 1) {
25        operationsCount += 1; // We'll need one more operation.
26    }
27    // If there are more than one consecutive 1's left.
28    else if (consecOnesCount > 1) {
29        operationsCount += 2; // We'll need two more operations to handle them.
30    }
31
32    // Return the total operations count.
33    return operationsCount;
34 }
35
```

Time and Space Complexity

The time complexity of the provided code is $O(\log n)$ because the primary operation within the `while` loop is a bitwise right shift on `n`, which effectively divides `n` by 2. The number of iterations is directly proportional to the number of bits in the binary representation of `n`, which is $\log_2 n$.

The space complexity of the code is $O(1)$ since the extra space used is constant, irrespective of the size of `n`. The variables `ans` and `cnt` use a fixed amount of space during the execution of the algorithm.