

534. Game Play Analysis III

Description

Table: Activity

+-----+-----+

| Column Name | Type |

+-----+-----+

| player_id | int |

| device_id | int |

| event_date | date |

| games_played | int |

+-----+-----+

(player_id, event_date) is the primary key (column with unique values) of this table.
This table shows the activity of players of some games.
Each row is a record of a player who logged in and played a number of games (possibly 0) before logging out on someday using some device.

Write a solution to report for each player and date, how many games played **so far** by the player. That is, the total number of games played by the player until that date. Check the example for clarity.

Return the result table in **any order**.

The result format is in the following example.

Example 1:

Input:
Activity table:

+-----+-----+-----+-----+

| player_id | device_id | event_date | games_played |

+-----+-----+-----+-----+

| 1 | 2 | 2016-03-01 | 5 |

| 1 | 2 | 2016-05-02 | 6 |

| 1 | 3 | 2017-06-25 | 1 |

| 3 | 1 | 2016-03-02 | 0 |

| 3 | 4 | 2018-07-03 | 5 |

+-----+-----+-----+-----+

Output:

+-----+-----+-----+

| player_id | event_date | games_played_so_far |

+-----+-----+-----+

| 1 | 2016-03-01 | 5 |

| 1 | 2016-05-02 | 11 |

| 1 | 2017-06-25 | 12 |

| 3 | 2016-03-02 | 0 |

| 3 | 2018-07-03 | 5 |

+-----+-----+-----+

Explanation:
For the player with id 1, 5 + 6 = 11 games played by 2016-05-02, and 5 + 6 + 1 = 12 games played by 2017-06-25.
For the player with id 3, 0 + 5 = 5 games played by 2018-07-03.
Note that for each player we only care about the days when the player logged in.

