2627. Debounce Medium Leetcode Link

# The core of this problem is to implement a debounced function. When we debounce a function, we're essentially delaying its

Problem Description

execution until a certain amount of time (specified in milliseconds) has passed without it being called again. During this time, if the function is called again, the previous pending execution is cancelled, and the delay timer restarts. This is particularly useful in scenarios where the function is expected to be called frequently, but you only want it to execute after some quiet period, such as when the user stops typing in a search field.

original function once the debounce time has elapsed without new calls. Considering the examples provided, if the debounce time t is set to 50ms:

If the function is called at 30ms, 60ms, and 100ms, the first two calls will be cancelled, and only the third call will actually be

It's important to note that the debounced function should be able to receive and pass on any parameters it is called with to the

executed at 150ms. If the debounce time t is 35ms, the call at 30ms will be cancelled due to the call at 60ms, but the call at 60ms will execute at 95ms.

If there is, we clear this timer using clearTimeout to cancel the previous call.

- The last call at 100ms will then execute at 135ms
- Intuition To implement the debounced function without external libraries like lodash, we start by defining a function that takes in two

## parameters: the function to be debounced fin and the debounce time t. Within our debounce implementation, we maintain a timeout variable that holds a reference to a timer created with setTimeout. This timer is responsible for actually calling our fn function after

the delay t. Each time the debounced function is called, we check if there's an existing timeout timer running (which would mean a previous call is waiting to execute).

fn.apply(this, args) to ensure the function is called with the correct context (this) and arguments.

• We then set a new timeout with the delay t to call our fn function with the current set of arguments args. We use

It is essential that we clear the previous timeout every time our function is called (if it exists) because this enforces the debouncing effect—only allowing the function to execute after t milliseconds have passed since the last call.

Solution Approach The debounce mechanism relies on two main components: closure and timing control via setTimeout and clearTimeout. Here's how

1. Closure: We create an inner function within the debounce function that has access to the outer scope. This inner function uses

variables fn, t, and timeout which are defined in the outer function's scope. The use of closures ensures that the same timeout

our debounced function.

the solution provided makes use of these components:

perform the action once the events have 'settled down.'

could use the debouncing approach described above:

This process repeats for 'p', 'l', and 'e'.

The debounced function usage would look like this:

What happens in this scenario is as follows:

// This simulates the user typing in the search box

6 setTimeout(() => debouncedSearch('ap'), 100); // After 100ms

7 setTimeout(() => debouncedSearch('app'), 160); // After another 60ms

searchDatabase('apple') is executed at 650ms (400ms + 250ms).

optimizing the search function's performance by reducing unnecessary database calls.

# Type alias for a generic function that can take any number of parameters of any type

Creates a debounced version of a function that delays invoking the `target\_function`

:param delay: The number of milliseconds to delay; afterwards the `target\_function` is called.

def debounce(target\_function: GenericFunction, delay: int) -> GenericFunction:

2. Timing Control: The setTimeout function is instrumental in creating the delay mechanism. When it's called, it sets up a timer that, after the specified time t, will execute the provided function—our original function in applied with the call's arguments. If

variable is used across multiple calls to the debounced function, enabling us to keep track of and control the timer.

another call to the debounced function happens before the timer expires, clearTimeout is used to cancel the scheduled execution. The detailed steps in the debounced function are as follows:

We initialize a variable timeout to keep track of the setTimeout timer. It's declared outside the scope of the inner returned

function so that it's not reinitialized with each call—this is critical for the debounced function to have memory of previous calls.

We return an inner function that captures any arguments it's called with using the rest syntax ...args. This function will act as

Within this inner function, we first check if there's an existing timeout (which means a previous call was made within the delay)

Next, we create a new timeout using setTimeout, where we delay the execution of fn for t milliseconds. fn.apply(this, args)

ensures that when the function is eventually called, it has the same this value as if the debounced function hadn't been used,

window). If timeout is not undefined, we clear it using clearTimeout. This cancels the prior scheduled execution.

and it also passes all the captured arguments (args) correctly. • By setting the timeout variable with the result of setTimeout, we maintain a reference to the current timer, which can be cleared if the debounced function is called again within the delay period.

Through this implementation, the debounced function ensures that fn is called only after the debounce time has elapsed since the

last invocation. This setup is particularly effective for event-handling scenarios where the frequency of events is high and we need to

Example Walkthrough Imagine you have developed a search feature in an application that searches for items as the user types in a search box. To improve performance and prevent excessive calls to the search service, you decide to implement a debounced version of the search

Consider your basic search function that performs a database query: function searchDatabase(query) { console.log('Searching for: \${query}'); // This would typically involve a database call

You want to ensure that this search function is called only after the user has stopped typing for at least 250ms. Here's how you

2. Execution: The user types 'apple', and on each keystroke, the debounced function is called. The following occurs:

User types 'p': The previous timeout is cleared, and searchDatabase is scheduled again after 250ms.

User types 'a': searchDatabase is scheduled to be called after 250ms.

### 1. Initialization: You write a debounce function as described, which takes in searchDatabase and 250 (the delay in milliseconds) as parameters and returns a new function that you'll use for performing the search.

'apple'.

5 debouncedSearch('a');

import threading

9

14

15

16

22

24

25

26

33

41

print(message)

import java.util.function.Consumer;

void apply(Object... params);

\* @param targetFunction The function to debounce.

\* @return A new debounced version of the {@code targetFunction}.

Java Solution

@FunctionalInterface

interface GenericFunction {

/\*\*

\*/

9

10

14

18

\*/

function.

If the user stops typing after 'e', then: 3. Completion: Since no new keystrokes occurred for 250ms, the searchDatabase function is finally called with the complete query

- // This creates the debounced search function let debouncedSearch = debounce(searchDatabase, 250);
- 8 setTimeout(() => debouncedSearch('appl'), 220); // After another 60ms 9 setTimeout(() => debouncedSearch('apple'), 400); // After another 180ms, total 400ms since first key stroke
- At 0ms, the user types 'a', and a timer is set to trigger in 250ms. At 100ms, the user types 'p', the previous timer is cleared, and a new timer is set.

This repeats until the user types 'e' at 400ms. Since the user does not type any further, the last timer is not cleared and

In this way, the debounced function ensures that searchDatabase is not called constantly but only after a 250ms pause in typing,

**Python Solution** 1 from typing import Callable

GenericFunction = Callable[..., any]

until after 'delay' milliseconds have elapsed since the last time the debounced 10 function was invoked. 12 13 :param target\_function: The function to debounce.

:return: A new debounced version of the `target\_function`.

timer = threading.Timer(delay / 1000.0, run\_function)

\* Interface for a generic function that can take any number of parameters of any type.

\* Creates a debounced version of a function that delays invoking the {@code targetFunction}

\* Creates a debounced version of a function that delays invoking the `target\_function`

\* @param target\_function The function to debounce.

auto target function copy = target function;

std::future<void> future = task.get\_future();

// Debounced version of the target function

static std::thread task\_thread;

if(task\_thread.joinable()) {

task\_thread.join();

return [=]() mutable {

task();

});

\* @return A new debounced version of the `target\_function`.

// Create a copy of target\_function that is mutable

std::packaged\_task<void()> task(target\_function\_copy);

// If a thread is currently running, join it.

task\_thread = std::thread([=, &task]() {

// Sleep for the delay period

17 GenericFunction debounce(const GenericFunction& target\_function, int delay) {

// Variable to hold a future that is associated with the packaged task

// Create a new thread to run the task after the specified delay.

// Run the task which calls the original target function

// Detach the thread so it can independently complete its execution

std::this\_thread::sleep\_for(std::chrono::milliseconds(delay));

// Static variable to hold the thread that runs the task

// Create a packaged task with the target function inside it

\* until after `delay` milliseconds have elapsed since the last time the debounced function was invoked.

\* @param delay The number of milliseconds to delay; afterwards, the `target\_function` is called.

\* until after {@code delay} milliseconds have elapsed since the last time the debounced function was invoked.

\* @param delay The number of milliseconds to delay; afterwards, the {@code targetFunction} is called.

target\_function(\*args, \*\*kwargs)

- # Variable to hold the timer object timer = None 19 20 def debounced(\*args, \*\*kwargs): 21
  - nonlocal timer # Function that will execute the target function and reset the timer def run\_function(): nonlocal timer timer = None
- 27 # If there is an existing timer, cancel it to reset the debounce timer 28 if timer is not None: 29 timer.cancel() 31 32 # Set a new timer to invoke the target function after the specified delay
- 34 timer.start() 35 36 return debounced 37 # Example usage 39 # def print\_message(message):
- 42 # debounced\_print = debounce(print\_message, 100) # debounced\_print('Hello') # Invocation is cancelled # debounced\_print('Hello') # Invocation is cancelled # debounced\_print('World') # Actually printed to the console after 100ms 46
- public static GenericFunction debounce(GenericFunction targetFunction, int delay) { 20 22 23

```
// A holder for the timer so we can cancel it
       final Consumer<Void>[] timerHolder = new Consumer[1];
       // Return the debounced version of the target function
       return (Object... args) -> {
24
           // Cancel the current timer if one exists
           if (timerHolder[0] != null) {
               timerHolder[0].accept(null);
28
               timerHolder[0] = null;
29
30
           // Create a new timer for the delay period
31
32
           timerHolder[0] = ignored -> new java.util.Timer().schedule(
33
               new java.util.TimerTask() {
                   @Override
34
                   public void run() {
35
                       targetFunction.apply(args); // Invoke the target function after the delay
36
37
38
               },
39
               delay
40
           );
       };
41
42
43
   // Example usage
   public static void main(String[] args) {
       // Create a debounced version of System.out.println
46
       GenericFunction debouncedPrint = debounce(params -> System.out.println(params[0]), 100);
47
48
       // Call the debounced function multiple times
49
       debouncedPrint.apply("Hello"); // Invocation is cancelled
50
       debouncedPrint.apply("Hello"); // Invocation is cancelled
51
       new java.util.Timer().schedule(new java.util.TimerTask() { // Delay to simulate separation of calls
52
53
           @Override
           public void run() {
54
               debouncedPrint.apply("Hello"); // Actually printed to the console after 100ms
56
57
       }, 150);
58 }
59
C++ Solution
  1 #include <iostream>
  2 #include <functional>
    #include <chrono>
  4 #include <thread>
  6 // Type alias for a generic function that can take any number of parameters of any type
    using GenericFunction = std::function<void()>;
```

#### 53 54 55 56 }, 100); 57

9

12

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

16 \*/

/\*\*

```
47
             task_thread.detach();
         };
 48
 49
 50
    // Main function to demonstrate usage
    int main() {
         // Example usage of the debounce function
         auto debounced_log = debounce([]{
             std::cout << "Hello" << std::endl;</pre>
 58
         // Invocation is cancelled
 59
         debounced_log();
 60
 61
         // Invocation is cancelled
 62
         debounced_log();
 63
 64
         // Actually logged to the console after 100ms
 65
         debounced_log();
 66
 67
         // Make sure the main thread is kept alive until the debounced log has a chance to execute
         std::this_thread::sleep_for(std::chrono::milliseconds(200));
 68
 69
 70
         return 0;
 71 }
 72
Typescript Solution
   // Type alias for a generic function that can take any number of parameters of any type
   type GenericFunction = (...params: any[]) => any;
   /**
    * Creates a debounced version of a function that delays invoking the `targetFunction`
    * until after `delay` milliseconds have elapsed since the last time the debounced function was invoked.
    * @param targetFunction The function to debounce.
    * @param delay The number of milliseconds to delay; afterwards, the `targetFunction` is called.
    * @return A new debounced version of the `targetFunction`.
   function debounce(targetFunction: GenericFunction, delay: number): GenericFunction {
       // Variable to hold the timeout identifier
14
       let timeoutId: ReturnType<typeof setTimeout> | undefined;
15
       // Return the debounced version of the target function
16
       return function(...args: any[]): void {
17
           // If there is an existing timeout, clear it to reset the debounce timer
           if (timeoutId !== undefined) {
19
20
               clearTimeout(timeoutId);
21
22
           // Set a new timeout to invoke the target function after the specified delay
           timeoutId = setTimeout(() => {
24
25
               targetFunction.apply(this, args);
26
           }, delay);
       };
27
28 }
29
```

## Time Complexity The time complexity of the debounce function is primarily dependent on the execution of setTimeout and the operations within the

Time and Space Complexity

31 // const debouncedLog = debounce(console.log, 100);

32 // debouncedLog('Hello'); // Invocation is cancelled

// debouncedLog('Hello'); // Invocation is cancelled

// debouncedLog('Hello'); // Actually logged to the console after 100ms

## applied is context-dependent and cannot be determined without specifics about fn. Therefore: Debouncing logic (scheduling and cancelling timeouts): 0(1)

// Example usage

35

 Invoked function fn: O(f(n)), where f(n) represents the time complexity of fn. Space Complexity

The space consumed by arguments (args) depends on the number of arguments and their sizes; however, it is also a constant factor determined by the function's usage, not the debounce function itself. Therefore, space complexity for debounce is:

The space complexity of debounce function includes the space needed for the timeout variable and the arguments passed to fn. The

timeout variable either holds a numeric identifier for the created timeout or is undefined. Hence, it consumes constant space (0(1)).

function passed to debounce. Since setTimeout is a native web API that schedules a script to be run after a specified delay and does

not block the execution flow, its complexity isn't measured in traditional algorithmic terms. However, it schedules a single delayed

function execution, which gives it a constant time operation in this context (0(1)). The time complexity of the actual function fn

 For the closure and timeout identifier: 0(1) • For arguments and context of fn: O(f(n)), where f(n) represents the space complexity of maintaining the arguments and execution context of fn.