2615. Sum of Distances Medium Array Hash Table Prefix Sum Leetcode Link

# **Problem Description**

element arr[i] represents the sum of absolute differences between index i and every index j where the value nums[j] is equal to nums [i], excluding when i and j are the same. If there are no such j values (meaning there are no other identical values to nums [i] in the array), we simply set arr[i] to 0. To illustrate, if nums was [3, 3, 1], then arr would be [1, 1, 0] because:

In this problem, we're presented with an integer array nums which is 0-indexed. We're tasked to find another array arr where each

For i=1, it's the same situation but in reverse, so arr[1] is also 1.

For i=2, nums [2] == 1 and there are no other 1s in the array, so arr [2] is 0.

• For i=0, nums [0] == 3, we find another 3 at index 1, so the sum is |0 - 1| = 1. There are no more 3s, so arr [0] is 1.

We need to perform this calculation efficiently for each index and construct the arr array accordingly.

2. We start from the leftmost index in each group and iterate towards the right.

nums, and the corresponding value is a list of indices where that key appears.

For illustration, let's use nums = [2, 1, 2, 1, 2] to demonstrate the solution approach.

For value 2, the list of indices is [0, 2, 4]. For value 1, the list of indices is [1, 3].

1. We first create the hash map with the list of indices for each value in nums:

Intuition

To find an effective solution, we should try to avoid the naive approach of checking each pair of indices for equality, as that would

## result in an O(n^2) time complexity, which is impractical for large arrays.

the array to the list of indices where that number appears. This will help us compute the sum of distances for each group in aggregate, rather than individually.

Instead, we can optimize by grouping indices with the same values together. We can use a dictionary to map each unique number in

Once we have those index lists, we can iterate over them to calculate the sum of distances for each index in the group. Here's the step-by-step approach: 1. We compute the sum of indices for each group - this gives us a starting sum for the right part of each index.

3. For each index, we maintain two variables: left and right, which represent the sum of distances to indices on the left and right, respectively. 4. As we move from one index to the next within a group, we update left by adding the distance to the next index multiplied by the

- count of indices that are now on the left. 5. We update right by subtracting the same distance multiplied by the count of indices remaining on the right.
- the corresponding position in the arr array. This approach reduces the amount of redundant calculations and brings the complexity down significantly because each distance is

6. We use these left and right accumulators to calculate the total distance for each index, this total distance is what we add to

essentially calculated in linear time relative to the number of occurrences of each unique value. **Solution Approach** 

The solution utilizes a hash map (via Python's defaultdict from the collections module) to group the indices of identical values in nums. Here's how the solution is implemented: 1. Initialize a defaultdict of lists named d. Iterate over nums using enumerate to build the dictionary where each key is a value in

#### 2. Create an array ans filled with zeros of the same length as nums. This array will store our resulting distances for each index. 3. For each list of indices idx in the hash map:

the right.

4. Iterate over each index i in idx:

occurrences of each unique value in nums.

 Initialize left as 0 because there are no indices to the left of our starting point. Calculate the initial value of right by summing up all the indices in idx and adjusting for the lowest index (len(idx) \*

idx[0]). This variable represents the sum of distances of all indices to the right of our current index.

- Set ans[idx[i]] to be the sum of left plus right, which provides the sum of distances for nums[idx[i]].
- Before we move to the next index i+1, we update left and right. Update left by adding the distance to the next index multiplied by i + 1 (because we'll have one more element to the left).

Update right by subtracting the same distance multiplied by (len(idx) - i - 1) to account for having one less element to

5. Loop until all indices in idx are processed. By the end, ans will have the calculated distances for each element in nums. This approach is efficient because it computes the distances for indices of the same value in nums as a whole, minimizing repeated

work. By using left and right accumulators, it avoids iterating over all pairs of indices and scales linearly with the number of

not explicitly stored, they are implied in the use of left and right to keep track of cumulative distances). Example Walkthrough

The algorithmic patterns used here include hashing (to group indices), enumeration (to iterate with indices), and prefix sums (though

Our hash map (d) now looks like this: 1 { 2 2: [0, 2, 4], 3 1: [1, 3]

## 3. We begin processing the list of indices for the value 2:

• First index (i=0):

index.

Second index (i=1):

Third index (i=2):

■ We update right by subtracting 2 \* (3 - 1 - 0) to account for the two spaces we're moving away from the remaining two indices (2 and 4).

2. We then initialize the ans array to [0, 0, 0, 0], corresponding to the five elements in nums.

○ Initial setup for value 2: left = 0, right is calculated by (2 + 4) - (2 \* 0) = 6.

 Update left to be 2 + (2 \* 2) as we're now considering the total distance from the first and second index to the third. ■ Update right to be 2 - (2 \* (2 - 1 - 1)), no change because only one index remains to the right, and we're moving one step away from it.

With value 2 processed, ans becomes [6, 0, 4, 0, 6].

■ ans[1] = left + right  $\rightarrow$  ans[1] = 0 + 2 = 2.

Now, our answer array ans is completely updated to [6, 2, 4, 1, 6].

Update left to be 0 + (1 \* 1),

index in nums, as intended by the solution approach.

def distance(self, nums: List[int]) -> List[int]:

indices\_dict[num].append(index)

# Initialize the answer list with zeros

for indices in indices\_dict.values():

indices\_dict = defaultdict(list)

distances = [0] \* len(nums)

left distance = 0

public long[] distance(int[] nums) {

for index, num in enumerate(nums):

• We set ans [0] = left + right → ans [0] = 0 + 6 = 6.

Now left = 2 and right = 2 (from previous calculations).

• Thus, ans[2] = left + right → ans[2] = 2 + 2 = 4.

Now left = 6 and right = 0 (there are no more indices to the right). ■ So, ans [4] = left + right  $\rightarrow$  ans [4] = 6 + 0 = 6.

After processing both lists of indices, we get arr = [6, 2, 4, 1, 6] corresponding to the sum of absolute differences for each

4. Next, proceed with the indices for value 1:  $\circ$  Initial setup for value 1: left = 0, right is calculated by (3) - (1 \* 1) = 2.

■ We update left to be 0 + (1 \* 2) since we're moving one step to the right, adding two spaces (distance) from the first

left = 1 and right = 0. ■ ans[3] = left + right  $\rightarrow$  ans[3] = 1 + 0 = 1.

class Solution:

10

11

12

13

14

17

18

19

25

26

33

Java Solution

class Solution {

Second index (i=1):

First index (i=0):

Python Solution 1 from collections import defaultdict from typing import List

# Create a dictionary to store indices of each number in nums

# Iterate over the groups of indices for each unique number

if idx\_position + 1 < len(indices):</pre>

int n = nums.length; // Get the length of the input array.

# Initialize the distance from the left and right side

right\_distance = sum(indices) - len(indices) \* indices[0]

• Update right to be 2 - (1 \* (2 - 1 - 0)), which makes right = 1 now.

27 gap = indices[idx\_position + 1] - indices[idx\_position] 28 left\_distance += gap \* (idx\_position + 1) 29 right\_distance -= gap \* (len(indices) - idx\_position - 1) 30 # Return the list of distances 31 32 return distances

# Update the left and right distances for the next index (if not at the end)

long[] answer = new long[n]; // Initialize the answer array to store the final distances.

```
# Iterate through the indices to compute distances
20
               for idx_position in range(len(indices)):
                   # The total distance is the sum of left and right distances
                   distances[indices[idx_position]] = left_distance + right_distance
23
24
```

```
Map<Integer, List<Integer>> indexMap = new HashMap<>(); // Map to store the indices of each number in nums.
           // Loop through nums to fill the indexMap.
           for (int i = 0; i < n; ++i) {
               // If the key doesn't exist, create a new list, then add the index.
9
                indexMap.computeIfAbsent(nums[i], k -> new ArrayList<>()).add(i);
10
11
12
13
           // Iterate over the entry set of the map to calculate distances.
14
           for (List<Integer> indices : indexMap.values()) {
15
                int m = indices.size(); // The frequency of the current number.
                long leftSum = 0; // Sum to store the left side distances.
16
                long rightSum = -1L * m * indices.get(0); // Sum to store the right side distances, initially inverted.
17
               // Initial rightSum calculation by summing all indices.
19
                for (int index : indices) {
20
21
                    rightSum += index;
24
               // Iterate over each index for the current number.
25
               for (int i = 0; i < m; ++i) {
26
                   // Calculate the final distance for the current index.
27
                   int currentIndex = indices.get(i);
28
                   answer[currentIndex] = leftSum + rightSum;
                   // Recalculate leftSum and rightSum for the next index if it exists.
30
                   if (i + 1 < m) {
31
                        int nextIndex = indices.get(i + 1);
32
33
                        long diff = nextIndex - currentIndex; // Difference between the current and the next index.
                        leftSum += diff * (i + 1L);
34
                        rightSum -= diff * (m - i - 1L);
35
36
37
38
39
           return answer; // Return the completed answer array.
40
41
42 }
43
```

#### 28 29 30 31 32

C++ Solution

1 class Solution {

// Function to calculate distances

vector<long long> ans(n);

for (int i = 0; i < n; ++i) {

int n = nums.size();

vector<long long> distance(vector<int>& nums) {

// n holds the length of the input array nums

// Create a vector to store the final answer

unordered\_map<int, vector<int>> indexMap;

// Use a map to store indices of elements in nums

// Populate the map with the indices of each element

2 public:

10

11

12

13

14

```
indexMap[nums[i]].push_back(i);
15
16
17
           // Iterate over each element of the map
           for (auto& [value, indices] : indexMap) {
18
19
               // m holds the number of occurrences of a particular value in nums
               int m = indices.size();
20
21
               // left is used to keep track of the cumulative distance from the left
22
               long long left = 0;
23
               // right is used to keep track of the cumulative distance from the right
               long long right = -1LL * m * indices[0];
24
               // Calculate the initial right value by summing up all indices
25
26
               for (int index : indices) {
27
                   right += index;
               // Iterate over all occurrences of the current value
               for (int i = 0; i < m; ++i) {
                   // Store the total distance at the current index
                   ans[indices[i]] = left + right;
33
34
                   // Update left and right for the next values if not at the end
                   if (i + 1 < m) {
35
36
                       left += (indices[i + 1] - indices[i]) * (i + 1);
37
                       right -= (indices[i + 1] - indices[i]) * (m - i - 1);
38
39
40
           // Return the final vector of distances
41
42
           return ans;
43
44 };
45
Typescript Solution
  1 // Function to calculate distances
    function distance(nums: number[]): number[] {
         // n holds the length of the input array nums
         let n: number = nums.length;
         // Create an array to store the final answer
         let ans: number[] = new Array(n);
  6
         // Use a map to store indices of elements in nums
         let indexMap: Map<number, number[]> = new Map<number, number[]>();
  8
  9
 10
         // Populate the map with the indices of each element
 11
         for (let i = 0; i < n; ++i) {
 12
             if (!indexMap.has(nums[i])) {
 13
                 indexMap.set(nums[i], []);
 14
 15
             indexMap.get(nums[i])!.push(i);
```

#### if (i + 1 < m) { 36 37 left += (indices[i + 1] - indices[i]) \* (i + 1); right -= (indices[i + 1] - indices[i]) \* (m - i - 1); 39 40 1); 41

return ans;

for each unique element.

// Iterate over each element of the map

let m: number = indices.length;

for (let index of indices) {

for (let i = 0; i < m; ++i) {

// Return the final array of distances

Time and Space Complexity

right += index;

let right: number = -1 \* m \* indices[0];

ans[indices[i]] = left + right;

let left: number = 0;

indexMap.forEach((indices: number[], value: number) => {

// Iterate over all occurrences of the current value

// Store the total distance at the current index

// m holds the number of occurrences of a particular value in nums

// Calculate the initial right value by summing up all indices

// left is used to keep track of the cumulative distance from the left

// Update left and right for the next values if not at the end

// right is used to keep track of the cumulative distance from the right

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

42

43

44

45

46

Time Complexity: The first for loop iterates over all n elements of the list nums to create the dictionary d, which takes O(n) time.

## elements. Inside this loop, it performs constant-time operations like addition and subtraction for updating left and right variables.

second loop's time complexity is bounded by O(n).

Therefore, the total time complexity is O(n) + O(n) = O(n). Space Complexity:

• The space taken by the dictionary d depends on the number of unique elements in nums. If there are u unique elements, it could

The above code maintains a dictionary to store indices of each unique element in the list nums and then computes the distance sum

The second loop processes each group of indices stored in the dictionary d. Let k be the maximum size of these index groups.

For each group, it iterates over all elements in the list of indices which, in the worst case, could take 0(k). Since there are as

many groups as there are unique elements in nums, we can say that it takes 0(u \* k) time, where u is the number of unique

Since k times the number of unique elements u cannot exceed n (as each element is part of one group and is visited once), the

take up to 0(u \* k) space, where k is the average size of the index lists for each unique element. However, since there are n total elements,  $\mathbf{u} * \mathbf{k}$  is also bounded by  $\mathbf{n}$ . Therefore, it uses  $\mathbf{0}(\mathbf{n})$  space. We also have the ans array, which is equal in size to nums, adding another O(n) space.

Adding these together, the space complexity of the code is O(n) + O(n) = O(n).