




```
- 🗇 ×
#include<stdio.h>
#include<conio.h>
#include<math.h>
void main()
clrscr(); printf("%f\n",12.5);
printf("%.0f\n",12.5);
printf("%.1f\n",12.5);
printf("%.2f\n",12.5);
printf("%.20f\n",12.5);
printf("%10.2f\n",12.5);
printf("%-10.2f\n",12.5);
printf("%1.2f\n",1.567);
printf("%1.2f\n",1.234);
printf("%1.0f\n",1.9);
printf("%1.0f\n",1.4);
printf("%1.2f\n",floor(1.9));
printf("%1.2f\n",ceil(1.9));
getch();
                                                            ▲ 🔽 😭 🌓 11:37 AM
03-Jun-22
12.500000
12
12.5
12.50
12.500000000000000000000
    12.50
12.50
1.57
1.23
1.00
2.00
                                                            ▲ 😼 😭 🌓 11:37 AM
```


```
- 🗇 ×
#include<stdio.h>
#include<conio.h>
void main()
clrscr(); printf("%s\n","Kishore");
printf("Kishore\n");
printf("%10s\n","Kishore");
printf("%-10s\n","Kishore");
printf("%.3s\n","Kishore");
printf("%10.3s\n","Kishore");
printf("Krish %c Radha\n",3);
printf("%u\n","Bharathi");
printf("Bharathi\n"+1);
printf(1+"Bharathi\n"+1);
printf("Bharathi\n"+8);
printf("%d\n"+1,899);
printf("%d"+1);
getch();
                                                            ▲ 🔁 🗐 🐠 11:55 AM
03-Jun-22
Kishore
Kishore
  Kishore
Kishore
Kis
      Kis
Krish ♥ Radha
504
harathi
arathi
                                                            ▲ 😼 😭 🌓 11:55 AM
```







```
_ 🗇 🗙
  File Edit Run Compile Project Options Debug Break/watch
              Col 20 Insert Indent Tab Fill Unindent * E:NONAME.C
     Line 9
#include<stdio.h>
#include<conio.h>
void main()
clrscr();
printf("%f",12);
getch();
/* runtime error */
▲ 🔽 😭 12:00 PN
  File Edit Run Compile Project Options Debug Break/watch
                     Insert Indent Tab Fill Unindent * E:NONAME.C
     Line 10
              Col 1
#include<stdio.h>
#include<conio.h>
void main()
clrscr();
printf("%f\n",(float)12); /* explicit Type casting */
printf("%d",(int)1.2);
getch();
        ▲ 😼 🖫 🌓 12:01 PM
```







printf("KRISH-%d",printf("\nSaajan-%d\n",printf("Aashique-2")));




p("Khan-%d", p("Dilse-%d\r", p("Dilwale\n")));

Dilwale

Di | se-8\r

Khan-8




```
File
       Edit
            Run
                 Compile
                        Project
                                Options |
                                       Debug
                                             Break/watch
            Col 19 Insert Indent Tab Fill Unindent * E:NONAME.C
    Line 13
#include<stdio.h>
#include<conio.h>
void main()
clrscr();
printf("%d\n",012); /* oct to decimal */
printf("%o\n",012); /* oct to oct */
printf("%o\n",36); /* dec to oct */
printf("%X\n",45); /* dec to hexa */
printf("%o\n",0x20); /* oct to hexa */
getch();
```

