

```
In [1]: import pandas as pd
import seaborn as sns
```

```
In [2]: movies = pd.read_csv(r"C:\Users\ANIL\Downloads\Movie-Rating.csv")
```

```
In [3]: movies
```

```
Out[3]:
```

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009
...	...	...	...	...	...	...
554	Your Highness	Comedy	26	36	50	2011
555	Youth in Revolt	Comedy	68	52	18	2009
556	Zodiac	Thriller	89	73	65	2007
557	Zombieland	Action	90	87	24	2009
558	Zookeeper	Comedy	14	42	80	2011

559 rows × 6 columns

```
In [4]: type(movies)
```

```
Out[4]: pandas.core.frame.DataFrame
```

```
In [5]: movies
```

Out[5]:

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009
...	...	...	...	...	...	...
554	Your Highness	Comedy	26	36	50	2011
555	Youth in Revolt	Comedy	68	52	18	2009
556	Zodiac	Thriller	89	73	65	2007
557	Zombieland	Action	90	87	24	2009
558	Zookeeper	Comedy	14	42	80	2011

559 rows × 6 columns

In [6]: `len(movies)`

Out[6]: 559

In [7]: `movies.head()`

Out[7]:

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

In []:

In [8]: `movies.tail()`

Out[8]:

	Film	Genre	Rotten Tomatoes Ratings %	Audience Ratings %	Budget (million \$)	Year of release
554	Your Highness	Comedy	26	36	50	2011
555	Youth in Revolt	Comedy	68	52	18	2009
556	Zodiac	Thriller	89	73	65	2007
557	Zombieland	Action	90	87	24	2009
558	Zookeeper	Comedy	14	42	80	2011

In [9]: `movies.columns`

Out[9]: Index(['Film', 'Genre', 'Rotten Tomatoes Ratings %', 'Audience Ratings %',
 'Budget (million \$)', 'Year of release'],
 dtype='object')

In [10]: `movies.columns = ['Film', 'Genre', 'CriticRating', 'AudienceRating', 'BudgetMillions',`In [11]: `movies.head()` # Removed Speaces & % Removed noise characters

Out[11]:

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

In [12]: `movies.info()`

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
#   Column          Non-Null Count  Dtype
---  -
0   Film            559 non-null   object
1   Genre           559 non-null   object
2   CriticRating    559 non-null   int64
3   AudienceRating  559 non-null   int64
4   BudgetMillions  559 non-null   int64
5   Year            559 non-null   int64
dtypes: int64(4), object(2)
memory usage: 26.3+ KB
```

In [13]: `movies.describe()` # if you Look at the year the data type is int but when you Look

Out[13]:

	CriticRating	AudienceRating	BudgetMillions	Year
count	559.000000	559.000000	559.000000	559.000000
mean	47.309481	58.744186	50.236136	2009.152057
std	26.413091	16.826887	48.731817	1.362632
min	0.000000	0.000000	0.000000	2007.000000
25%	25.000000	47.000000	20.000000	2008.000000
50%	46.000000	58.000000	35.000000	2009.000000
75%	70.000000	72.000000	65.000000	2010.000000
max	97.000000	96.000000	300.000000	2011.000000

In [14]: `movies['Film']`

```
Out[14]: 0      (500) Days of Summer
          1      10,000 B.C.
          2      12 Rounds
          3      127 Hours
          4      17 Again
          ...
          554     Your Highness
          555     Youth in Revolt
          556     Zodiac
          557     Zombieland
          558     Zookeeper
          Name: Film, Length: 559, dtype: object
```

In [15]: `movies.Film`

```
Out[15]: 0      (500) Days of Summer
          1      10,000 B.C.
          2      12 Rounds
          3      127 Hours
          4      17 Again
          ...
          554     Your Highness
          555     Youth in Revolt
          556     Zodiac
          557     Zombieland
          558     Zookeeper
          Name: Film, Length: 559, dtype: object
```

In [16]: `movies.Film = movies.Film.astype('category')`In [17]: `movies.Film`

```

Out[17]: 0      (500) Days of Summer
         1      10,000 B.C.
         2      12 Rounds
         3      127 Hours
         4      17 Again
         ...
        554      Your Highness
        555      Youth in Revolt
        556      Zodiac
        557      Zombieland
        558      Zookeeper
Name: Film, Length: 559, dtype: category
Categories (559, object): ['(500) Days of Summer ', '10,000 B.C.', '12 Rounds ',
'127 Hours', ..., 'Youth in Revolt', 'Zodiac', 'Zombieland ', 'Zookeeper']

```

```
In [18]: movies.head()
```

```

Out[18]:

```

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009

```
In [19]: movies.info()
```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
#   Column          Non-Null Count  Dtype
---  -
0   Film            559 non-null   category
1   Genre           559 non-null   object
2   CriticRating    559 non-null   int64
3   AudienceRating  559 non-null   int64
4   BudgetMillions  559 non-null   int64
5   Year            559 non-null   int64
dtypes: category(1), int64(4), object(1)
memory usage: 43.6+ KB

```

```

In [20]: movies.Genre = movies.Genre.astype('category')
         movies.Year = movies.Year.astype('category')

```

```
In [21]: movies.Genre
```

```
Out[21]: 0      Comedy
         1      Adventure
         2      Action
         3      Adventure
         4      Comedy
         ...
        554     Comedy
        555     Comedy
        556     Thriller
        557     Action
        558     Comedy
Name: Genre, Length: 559, dtype: category
Categories (7, object): ['Action', 'Adventure', 'Comedy', 'Drama', 'Horror', 'Romance', 'Thriller']
```

```
In [22]: movies.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 559 entries, 0 to 558
Data columns (total 6 columns):
 #   Column          Non-Null Count  Dtype
---  -
 0   Film            559 non-null   category
 1   Genre           559 non-null   category
 2   CriticRating    559 non-null   int64
 3   AudienceRating  559 non-null   int64
 4   BudgetMillions  559 non-null   int64
 5   Year            559 non-null   category
dtypes: category(3), int64(3)
memory usage: 36.5 KB
```

```
In [23]: movies.Genre.cat.categories
```

```
Out[23]: Index(['Action', 'Adventure', 'Comedy', 'Drama', 'Horror', 'Romance',
               'Thriller'],
              dtype='object')
```

```
In [24]: movies.describe()
```

```
Out[24]:
```

	CriticRating	AudienceRating	BudgetMillions
count	559.000000	559.000000	559.000000
mean	47.309481	58.744186	50.236136
std	26.413091	16.826887	48.731817
min	0.000000	0.000000	0.000000
25%	25.000000	47.000000	20.000000
50%	46.000000	58.000000	35.000000
75%	70.000000	72.000000	65.000000
max	97.000000	96.000000	300.000000

In []:

In []:

```
In [25]: from matplotlib import pyplot as plt
import seaborn as sns
%matplotlib inline
import warnings
warnings.filterwarnings('ignore')
```

```
In [26]: j = sns.jointplot( data = movies, x = 'CriticRating', y = 'AudienceRating')
```

```
In [27]: j = sns.jointplot( data = movies, x = 'CriticRating', y = 'AudienceRating', kind='he
```

```
In [28]: m1 = sns.distplot(movies.AudienceRating)
```

```
In [29]: sns.set_style('darkgrid')
```

```
In [30]: m2 = sns.distplot(movies.AudienceRating, bins = 15)
```

```
In [31]: # sns.set_style('darkgrid')
n1 = plt.hist(movies.AudienceRating, bins=15)
```


```
In [32]: sns.set_style('white') # normal
n1 = plt.hist(movies.AudienceRating, bins = 20)
```


```
In [33]: n1 = plt.hist(movies.CriticRating, bins=20) # uniform distribution
```

```
In [34]: # <<< chat - 2
```


```
# Creating stacked histograms & this is bit tough to understand
```

```
In [35]: #h1 = plt.hist(movies.BudgetMillions)
plt.hist(movies.BudgetMillions)
plt.show()
```





```
In [36]: plt.hist(movies[movies.Genre == 'Drama'].BudgetMillions)
plt.show()
```



In [37]: `movies.head()`

Out[37]:

	Film	Genre	CriticRating	AudienceRating	BudgetMillions	Year
0	(500) Days of Summer	Comedy	87	81	8	2009
1	10,000 B.C.	Adventure	9	44	105	2008
2	12 Rounds	Action	30	52	20	2009
3	127 Hours	Adventure	93	84	18	2010
4	17 Again	Comedy	55	70	20	2009


In [38]: `movies.Genre.unique()`

Out[38]: ['Comedy', 'Adventure', 'Action', 'Horror', 'Drama', 'Romance', 'Thriller']
 Categories (7, object): ['Action', 'Adventure', 'Comedy', 'Drama', 'Horror', 'Romance', 'Thriller']


In [39]: *# Below plots are stacked histogram becuae overlaped*

```
plt.hist(movies[movies.Genre == 'Action'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Adventure'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Comedy'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Horror'].BudgetMillions, bins = 20)
plt.hist(movies[movies.Genre == 'Drama'].BudgetMillions, bins = 20)
plt.legend()
plt.show()
```

No handles with labels found to put in legend.



```
In [40]: plt.hist([movies[movies.Genre == 'Action'].BudgetMillions,\n                  movies[movies.Genre == 'Drama'].BudgetMillions,\n                  movies[movies.Genre == 'Thriller'].BudgetMillions,\n                  movies[movies.Genre == 'Comedy'].BudgetMillions],\n              bins = 20, stacked = True)\nplt.show()
```




In [41]: *# if you have 100 categories ypu cant copy paste all the things*


```
for gen in movies.Genre.cat.categories:  
    print(gen)
```

Action
Adventure
Comedy
Drama
Horror
Romance
Thriller


```
In [42]: vis1 = sns.lmplot(data = movies, x = 'CriticRating', y = 'AudienceRating',\  
                           fit_reg=False)  
plt.show()
```




```
In [43]: vis1 = sns.lmplot(data=movies, x='CriticRating', y='AudienceRating',\
                           fit_reg=False, hue = 'Genre')
plt.show()
```




```
In [49]: vis1 = sns.lmplot(data=movies, x='CriticRating', y='AudienceRating',\n                           fit_reg=False, hue = 'Genre', aspect=1)\nplt.show()
```



```
In [70]: k1 = sns.kdeplot([movies.CriticRating,movies.AudienceRating])  
plt.show()
```




```
In [71]: k2 = sns.kdeplot(data=movies, x='CriticRating', y='AudienceRating', shade_lowest=False)
snsplt.show()
```




```
In [78]: sns.set_style('dark')
k1 = sns.kdeplot(data = movies, x="BudgetMillions",y="AudienceRating",shade_lowest=
```


```
plt.show()
```




```
In [81]: sns.set_style('dark')
k1 = sns.kdeplot(data=movies,x="BudgetMillions",y="AudienceRating")
plt.show()
```




```
In [84]: k2 = sns.kdeplot(data=movies,x="BudgetMillions",y="CriticRating")  
plt.show()
```




```
In [64]: sns.set_style('dark')
k1 = sns.kdeplot(data=movies, x='CriticRating', y='AudienceRating', shade = True, sha
plt.show()
```




```
In [87]: # Subplots
f, ax = plt.subplots(1,2, figsize = (12,6))
plt.show()
```






In [102...

```
f, axes = plt.subplots(1,2, figsize = (12,6))
k1 =sns.kdeplot(data=movies,x="BudgetMillions",y="AudienceRating",ax=axes[0])
k2 =sns.kdeplot(data = movies,x="BudgetMillions",y="AudienceRating",ax=axes[1])
plt.show()
```




In [109...


```
# Box Plots -
w = sns.boxplot(data=movies, x ='Genre', y = 'CriticRating')
plt.show()
```




```
In [111... # Violin plot
z = sns.violinplot(data=movies, x='Genre', y = 'CriticRating')
plt.show()
```



```
In [119... w1 = sns.boxplot(data=movies[movies.Genre == 'Drama'], x='Year',y= 'CriticRating')  
plt.show()
```





```
In [120... w1 = sns.violinplot(data=movies[movies.Genre == 'Drama'], x='Year',y= 'CriticRating')  
plt.show()
```



```
In [ ]: # Creating a Facet grid
```


```
In [122... g = sns.FacetGrid(movies, row='Genre', col = 'Year', hue = 'Genre') # kind of subplot.  
plt.show()
```







In [130...

```
# Scatter  
plt.scatter(movies.CriticRating,movies.AudienceRating)  
plt.show()
```



```
In [132... g =sns.FacetGrid(movies, row= 'Genre', col = 'Year', hue = 'Genre')
g = g.map(plt.scatter, 'CriticRating', 'AudienceRating' ) # scatterplots are mapped
plt.show()
```






In [136...

you can populated any type of chat.

```
g = sns.FacetGrid (movies, row = 'Genre', col = 'Year', hue = 'Genre')
```


```
g = g.map(plt.hist, 'BudgetMillions') #scatterplots are mapped in facetgrid
plt.show()
```




In [138...

```
g = sns.FacetGrid(movies, row= 'Genre', col = 'Year', hue= 'Genre')
kws = dict(s=50, linewidth=0.5, edgecolor='black')
```

```
g = g.map(plt.scatter, 'CriticRating', 'AudienceRating', **kws) #scatterplots are map
plt.show()
```





In [148...]

```
# python is not vectorize programming language
# Building dashboards (dashboard - combination of chats)

sns.set_style('darkgrid')
```


```
f, axes = plt.subplots (2,2, figsize = (15,15))

k1 = sns.kdeplot(data= movies,x="BudgetMillions",y="AudienceRating",ax=axes[0,0])
k2 = sns.kdeplot(data=movies,x="BudgetMillions",y="CriticRating",ax = axes[0,1])

k1.set(xlim=(-20,160))
k2.set(xlim=(-20,160))

z = sns.violinplot(data=movies[movies.Genre=='Drama'], x='Year', y = 'CriticRating')

k4 = sns.kdeplot(data=movies,x="CriticRating",y="AudienceRating",shade = True,shade
k4b = sns.kdeplot(data=movies,x="CriticRating",y="AudienceRating",cmap='Reds',ax =
plt.show()
```



In [165... *# How can you style your dashboard using different color map*

```
# python is not vectorize programming language
# Building dashboards (dashboard - combination of chats)
```

```
sns.set_style('dark',{'axes.facecolor':'black'})
f, axes = plt.subplots (2,2, figsize = (15,15))

#plot [0,0]
k1 = sns.kdeplot(data=movies,x="BudgetMillions",y="AudienceRating", \
                 shade = True, shade_lowest=True,cmap = 'inferno', \
                 ax = axes[0,0])

k1b = sns.kdeplot(data=movies,x="BudgetMillions",y="AudienceRating", \
                 cmap='cool', ax=axes[0,0])

#plot [0,1]
k2 = sns.kdeplot(data=movies,x="BudgetMillions",y="CriticRating", \
                 shade=True, shade_lowest=True, cmap='inferno', \
                 ax = axes[0,1])
k2b = sns.kdeplot(data=movies,x="BudgetMillions",y="CriticRating", \
                 cmap = 'cool', ax = axes[0,1])





#plot[1,0]
z = sns.violinplot(data=movies[movies.Genre=='Drama'], \
                  x='Year', y = 'CriticRating', ax=axes[1,0])

#plot[1,1]
k4 = sns.kdeplot(data=movies,x="CriticRating",y="AudienceRating", \
                 shade = True,shade_lowest=False,cmap='Blues_r', \
                 ax=axes[1,1])

k4b = sns.kdeplot(data=movies,x="CriticRating",y="AudienceRating", \
                 cmap='gist_gray_r',ax = axes[1,1])

k1.set(xlim=(-20,160))
k2.set(xlim=(-20,160))

plt.show()
```



In []: