

ANSIBLE INSTALLATIONS

MASTER

```
1, apt-get update
2, apt-get install software-properties-common
3, apt-add-repository ppa:ansible/ansible
4, apt-get update
5, apt-get install ansible
6, ssh-keygen => copy id_rsa.pub
7, goto vi /etc/ansible/hosts (/etc/ansible/roles/inventory here aslo we
can give hosts)
```

```
Ex : [webappraghu]
```

```
IP of slave
```

```
[webservers]
```

```
server1.cyberciti.biz
```

```
104.20.187.5
```

```
104.20.186.5
```

```
[devservers]
```

```
10.98.222.4
```

```
10.98.222.7
```

```
10.98.222.8
```

```
8, ansible -m shell -a 'free -m' webappraghu ( ansible -i hosts -m shell
-a 'uptime' all )
```

```
ansible-doc -l
```

```
ansible-doc apt
```

```
ansible 172.31.42.123 -m apt -a "name=nginx state=installed"
```

```
9, create filename.yml (we can create anywhere and write configurations)
```

```
10, ansible-playbook filename.yml --check (if we remove --check it will
implement push configuration)
```

```
---
```

```
- hosts: droplets
```

```
tasks:
```

```
- name: Installs nginx web server
```

```
apt: pkg=nginx state=installed update_cache=true
```

```
notify:
```

```
- start nginx
```

```
handlers:
```

```
- name: start nginx
```

```
service: name=nginx state=started
```

```
---
```

```
- hosts: droplets
```

```
tasks:
```

```
- name: Installs nginx web server
```

```
apt: pkg=nginx state=present update_cache=true
```

```
- name: Upload default index.html for host
```

```
copy: src=index.html dest=/var/www/html/index.nginx-debian.html
```

```
mode=0644
```

```

    notify:
      - start nginx

handlers:
  - name: start nginx
    service: name=nginx state=started

```

We can then make a directory called `static_files` in our current directory and place an `index.html` file inside.

SLAVE

```

1, apt-get update
2, apt-get install python -y
3, vi /root/.ssh/authorized_keys paste id_rsa.pub
4, ifconfig copy ip and past it in master /etc/ansible/hosts

```

Install ansible on ubuntu 18.04 & 22.04

```

sudo apt-add-repository ppa:ansible/ansible
sudo apt update
sudo apt install ansible -y

```

Re-enable Legacy RSA Keys (Not Recommended) If you cannot upgrade your client and must use older RSA keys, you can temporarily re-enable them by adding the following lines to `/etc/ssh/sshd_config` via the serial console or a User Data script

```

HostKeyAlgorithms | rsa
PubkeyAcceptedAlgorithms | rsa

```

Action: Restart the service after changes: `sudo systemctl restart ssh`

```

sudo vi /etc/ansible/hosts
[webservers]
nodeip-or-private-dns

```

```

[all:vars]
ansible_python_interpreter=/usr/bin/python3

```

make an `ansible.cfg` file inside `/etc` folder and include these below lines.

```

[defaults]
host_key_checking = False

[dashboard:vars]
ansible_ssh_private_key_file=./mykeypair.pem

[dashboard]
1.2.3.4 dashboard_domain=my.domain.info

```

<https://www.digitalocean.com/community/tutorials/how-to-create-ansible-playbooks-to-automate-system-configuration-on-ubuntu>

<https://www.cyberciti.biz/faq/how-to-install-and-configure-latest-version-of-ansible-on-ubuntu-linux/>