

Matrix Chain Multiplication

Matrix Chain Multiplication

compute $m[i, j]$ then $i < j$, we use the value of an element of an optimal solution from step 1. Let us assume that to optimally parenthesize, we split the product $A_i A_{i+1} \cdots A_j$ between A_k and A_{k+1} , where $i \leq k < j$. Then, $m[i, j]$ equals the minimum cost for computing the subproducts $A_{i..k}$ and $A_{k+1..j}$, plus the cost of multiplying these two matrices together. Recalling that each matrix A_i is $p_{i-1} \times p_i$, we see that computing the matrix product $A_{i..k} A_{k+1..j}$ takes $p_{i-1} p_k p_j$ scalar multiplications. Thus, we obtain

$$m[i, j] = m[i, k] + m[k + 1, j] + p_{i-1} p_k p_j.$$

recursive definition for the minimum cost of parenthesizing the product $A_i A_{i+1} \cdots A_j$ becomes

$$m[i, j] = \begin{cases} 0 & \text{if } i = j, \\ \min_{i \leq k < j} \{m[i, k] + m[k + 1, j] + p_{i-1} p_k p_j\} & \text{if } i < j. \end{cases}$$

4/26/2018

3

$m[i, j]$ costs and another auxiliary table

$S[1..n - 2, n]$ that records which index of k achieved the optimal cost in computing $m[i, j]$

MATRIX-CHAIN-ORDER (p)

```


1   $n = p.length - 1$ 
2  let  $m[1..n, 1..n]$  and  $s[1..n - 1, 2..n]$  be new tables
3  for  $i = 1$  to  $n$ 
4       $m[i, i] = 0$ 
5  for  $l = 2$  to  $n$  //  $l$  is the chain length
6      for  $i = 1$  to  $n - l + 1$ 
7           $j = i + l - 1$ 
8           $m[i, j] = \infty$ 
9          for  $k = i$  to  $j - 1$ 
10              $q = m[i, k] + m[k + 1, j] + p_{i-1} p_k p_j$ 
11             if  $q < m[i, j]$ 
12                  $m[i, j] = q$ 
13                  $s[i, j] = k$ 
14  return  $m$  and  $s$ 
```

4

matrix	A_1	A_2	A_3	A_4	A_5	A_6
dimension	30×35	35×15	15×5	5×10	10×20	20×25


4/26/2018

5



4/26/2018

6



$m[1,6]=15125$

$$m[2,5] = \min \begin{cases} m[2,2] + m[3,5] + p_1 p_2 p_5 = 0 + 2500 + 35 \cdot 15 \cdot 20 = 13,000, \\ m[2,3] + m[4,5] + p_1 p_3 p_5 = 2625 + 1000 + 35 \cdot 5 \cdot 20 = 7125, \\ m[2,4] + m[5,5] + p_1 p_4 p_5 = 4375 + 0 + 35 \cdot 10 \cdot 20 = 11,375 \end{cases} = 7125.$$

4/26/2018 8

PRINT-OPTIMAL-PARENS(s; i; j)

```

PRINT-OPTIMAL-PARENS(s, i, j)
1  if i == j
2    print "A"i
3  else print "("
4    PRINT-OPTIMAL-PARENS(s, i, s[i, j])
5    PRINT-OPTIMAL-PARENS(s, s[i, j] + 1, j)
6    print ")"

```

In the example of Figure 15.5, the call PRINT-OPTIMAL-PARENS(s, 1, 6) prints the parenthesization ((A₁(A₂A₃))((A₄A₅)A₆)).

4/26/2018 9