Gesture Glide

Ajay Bhatnagar
Department of CSE'Regional

Noida Institute of Engineering and Technolgy

Greater Noida ,India

ajaybhatnagar1712@gmail.com

Akash Anand
Department of CSE'Regional

Noida Institute of Engineering and Technolgy

Greater Noida ,India

akashhanand5@gmail.com

Ankesh Yadav
Department of CSE'Regional

Noida Institute of Engineering and Technolgy

Greater Noida ,India

roaankesh209@gmail.com

Bedabrata Das
Department of CSE'Regional

Noida Institute of Engineering and Technolgy

Greater Noida ,India

Bedabratadas10@gmail.com

Abstract*— Human-computer interaction (HCI) has been revolutionized by gesture-based technologies, offering intuitive, accessible, and touch-free modes of communication between users and machines. This paper introduces an integrated system for gesture-based control using three primary modules: an eye tracker, a virtual mouse, and a PowerPoint (PPT) controller. The eye tracker interprets gaze and blink patterns for cursor control and click events; the virtual mouse enables comprehensive system control through hand gestures, including cursor navigation, clicking, scrolling, brightness, and volume adjustments; and the PPT controller simplifies slide navigation and annotations using real-time gesture recognition. The entire system is built using Python and open-source libraries such as OpenCV,** *MediaPipe,** *PyAutoGUI***, and** *Aspose.Slides***. Key contributions of this research include the modular integration of these systems, low-cost implementation using only a webcam, and robust performance in real-time scenarios. Experimental evaluations confirm the accuracy and responsiveness of each module, and user feedback highlights the system's practical benefits in education, accessibility, and productivity. This study demonstrates that a unified, camera-based gesture recognition interface can serve as a viable alternative to traditional input systems, especially in environments where hygiene and accessibility are paramount.***

***Keywords*—** *gesture recognition, eye tracking, hand gesture interface, virtual mouse, PowerPoint control, contactless interaction, MediaPipe, PyAutoGUI*

I. Introduction

The demand for touchless and intuitive user interfaces has grown exponentially in recent years due to advances in artificial intelligence, computer vision, and the increasing need for hygienic, contact-free interaction—especially in light of global health concerns. Traditional input mechanisms such as a keyboard, mouse, or touchscreen are often limited by physical reach, hygiene issues, or accessibility constraints. As a result, researchers and developers are turning to gesture-based systems to provide more natural, efficient, and inclusive methods of interacting with digital environments.

Gesture recognition systems have found applications across a wide range of domains, including smart home automation, assistive technologies for individuals with disabilities, public information kiosks, and immersive gaming environments. These systems capture and analyze physical movements—such as hand positions, finger motions, or eye direction—and translate them into digital commands. The motivation for our work stems from the need to develop an integrated, low-cost, and robust solution that supports multiple gesture-based interactions using just a standard webcam.

This paper introduces a comprehensive gesture-controlled interface composed of three independent modules: an eye tracker, a virtual mouse, and a PowerPoint controller. Each module is designed to operate either autonomously or in unison, providing a flexible, multi-modal solution for human-computer interaction. By combining the strengths of facial and hand gesture tracking using open-source libraries like MediaPipe and OpenCV, our system is optimized for real-time use with minimal hardware requirements. Our goal is to contribute a scalable framework that enhances user productivity, accessibility, and convenience in both personal and professional settings.

II. Background

The adoption of **virtual mouse technology** has emerged as a compelling solution for users who lack access to physical mouse devices, offering a convenient and efficient method of computer control. This innovative approach leverages standard **webcams** coupled with advanced **image processing techniques** to transform hand gestures into

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

actionable mouse commands, enabling intuitive navigation and interaction with digital interfaces.

Virtual mice serve as **complementary tools** to traditional input devices like physical mice and keyboards, enriching accessibility and enhancing usability for users across diverse contexts. By eliminating the need for physical hardware, virtual mouse technology promotes **mobility and flexibility**, enabling users to interact with digital content seamlessly.

The underlying principles of virtual mouse technology underscore the convergence of **computer vision, machine learning**, and **human-computer interaction (HCI)**, facilitating a symbiotic relationship between users and digital environments. This technology not only broadens **accessibility** for individuals with disabilities or hardware limitations but also enhances the overall **user experience** by providing alternative input modalities that are intuitive and responsive.

As virtual mouse technology continues to evolve through advancements in **image processing algorithms** and **hardware capabilities**, its potential applications extend beyond traditional computing environments. From **augmented reality interfaces** to **gesture-controlled applications**, the versatility and adaptability of virtual mouse technology hold promise for reshaping the landscape of HCI and ushering in a new era of **interactive computing experiences**.

In summary, the utilization of virtual mouse technology represents a significant milestone in HCI innovation, offering a **flexible and accessible approach** to computer control that transcends physical hardware constraints. Through ongoing development and integration into mainstream computing platforms, virtual mouse technology continues to redefine **user interaction paradigms**, unlocking new possibilities for digital engagement and **user empowerment**.

III. Literature Survey

3.1 Gesture Recognition Based Virtual Mouse and Keyboard

Authors: Sugnik Roy Chowdhury and Sumit Pathak

Computer vision has reached its pinnacle, where a computer can identify its owner using a simple program of image processing. In this stage of development, people are using this vision in many aspects of day-to-day life, like Face Recognition, Color detection, Automatic car, etc. In this project, computer vision is used in creating an Optical mouse and keyboard using hand gestures. The camera of the computer will read the image of different gestures performed by a person's hand and according to the movement of the gestures the Mouse or the cursor of the computer will move, and even perform right and left clicks using different gestures. Similarly, the keyboard functions may be used with some different gestures, like using one finger gesture for alphabet selection and a four-figure gesture to swipe left and right. It will act as a virtual mouse and keyboard with no wire or external devices.

Disadvantages:

- The Convex Hull algorithm can cause problem if another external noise or defect is detected in the working domain of webcam. An attempt to make input mode less constraints dependent for the user's hand gestures has been preferred.

3.2 Design and Development of Hand Gesture Based Virtual Mouse

Authors: Kabid Hassan Shibly and Samrat Kumar Dey

The aim is to control mouse functions using only a simple webcam instead of a traditional or regular hardware device. The Virtual Mouse works as a bridge between the user and the machine and only uses a webcam. It helps the user to interact with the system without any physical devices and control the mouse functions. The concept is implemented using Python programming language and Computer Vision-based library OpenCV. This system has the potential to replace the hardware mouse. The lighting barrier acts as the barrier to this system. That's why the system still can't be enough to replace the traditional mouse as most of the systems are used in poor lighting conditions.

Limitations:

- The Convex Hull algorithm can cause problem if another external noise or defect is detected in the working domain of webcam. An attempt to make input mode less constraints dependent for the user's hand gestures has been preferred.

3.3 Virtual Mouse Control Using Coloured Finger Tips and Hand Gesture Recognition

Authors: Vantukala VishnuTeja Reddy and Thumma Dhyanchand

In human-computer interaction, virtual mouse is implemented with fingertip recognition and hand gesture tracking based on image in a live video is one of the studies. The main objective is to find the solution for the finger tracking in the real world and the cursor control of a computer is still performed physically. The proposed system describes virtual mouse control using fingertip identification and hand gesture recognition. This study consists of two methods for tracking the fingers, one is by using coloured caps and other is by hand gesture detection. This includes three main steps that are finger detection using colour identification, hand gesture tracking and implementation on on-screen cursor. Hand gesture tracking is generated through the detection of contour and formation of a convex hull around it.

Limitations:

- Complex methodology is adopted as there is specific color sequence used for all the mouse control operations which makes the system complex.

3.4 Hand Gesture Based Virtual Mouse

Authors: K Indraneel, P Narendra Reddy, G Srinivas, J Alekh, Vara Prasad, Vijay Ananthoju, and Kumar

1. Hand gesture control for cursor software often requires a data Glove, leading to less effective interaction between the user and the system.
2. Two main types of vision-based hand gesture recognition exist: marker-based and nonmarker-based.
3. Gesture recognition is considered a cutting-edge technology for computer interaction.
4. Existing systems for PC control using hand gestures can be labour-intensive and challenging for users.

5. The proposed framework in the paper utilizes computer vision and hand signals to create a virtual mouse interface, aiming to improve human-computer interaction.

Limitations:

1. The proposed virtual mouse framework relies on computer vision and hand signals, which may have limitations in certain lighting conditions.
2. The use of a camera as the primary input device for controlling the mouse cursor may introduce challenges related to camera quality and positioning.
3. The paper focuses on the development of a virtual mouse interface but does not extensively discuss the potential challenges related to user adaptation and learning curve.
4. The study does not provide a comparative analysis with existing hand gesture recognition systems or traditional mouse devices.

IV. System Overview

The system architecture is designed as a modular, real-time gesture recognition suite comprising three specialized components:

The eye tracker, virtual mouse, and PowerPoint controller. Each of these modules is implemented as an independent subsystem, enabling the user to activate and utilize them based on the task or context. They share a unified vision processing pipeline but perform distinct tasks by interpreting different aspects of the user's body language.

Eye Tracker: This module utilizes facial landmarks to infer the user's gaze direction and translate it into on-screen pointer movement. It also monitors eyelid positions to simulate click events through intentional blinking. The eye tracker is ideal for users with limited mobility or in environments where hands-free interaction is required.

Virtual Mouse: This module replaces the conventional mouse by detecting and analyzing hand gestures using a webcam. Gestures such as fist, pinch, V-sign, and index-only are recognized and mapped to standard mouse actions (e.g., move, click, drag, scroll). Additionally, it extends system control by enabling adjustments to screen brightness and system volume using pinch-based gestures.

PPT Controller: Designed specifically for presentation scenarios, this module interprets high-level hand gestures to control slide transitions and annotate on slides. It enables presenters to move freely without needing a remote or keyboard.

All modules are integrated with a shared interface powered by Python. OpenCV handles video processing, MediaPipe detects body landmarks, and PyAutoGUI executes system-level commands. The architecture is event-driven, ensuring minimal latency and smooth interaction. A layered design further separates detection logic, gesture interpretation, and execution, making the system extensible and maintainable.

V. Module 1: Eye Tracker

This module is responsible for tracking eye movement and simulating cursor movement through non-contact facial tracking. It offers a hands-free alternative for cursor control and click actions by interpreting gaze direction and eyelid movement.

Facial Landmark Detection: MediaPipe FaceMesh is used to extract 468 high-precision facial landmarks in real time. The system focuses on key points around the iris, eyelids, and the surrounding eye socket. Landmarks 474 to 478 provide spatial data used to infer the position of the pupil in relation to the face.

Gaze Estimation and Mapping: The horizontal and vertical position of the eyes within the webcam frame is mapped to the resolution of the screen. This is achieved by translating the position of the iris within the bounds of the face and scaling it to screen width and height. This ensures that even minor eye movements result in corresponding pointer movement.

Blink Detection and Click Simulation: To enable click events, the system monitors the vertical distance between the upper (landmark 145) and lower (landmark 159) eyelids. If the distance falls below a pre-defined threshold, the system interprets it as a blink and triggers a mouse click. To avoid false positives from involuntary blinks, a timing threshold is introduced—only blinks held longer than a brief duration are interpreted as clicks.

Smoothing and Debouncing: Cursor movement derived from gaze is prone to jitter due to micro-movements of the eye and noise in the webcam feed. To mitigate this, cursor updates are smoothed over a few frames using weighted averages. Additionally, a cooldown period is introduced after each blink-based click to prevent unintentional multiple clicks.

Real-World Scenarios: This module proves especially beneficial in environments where hands are either unavailable or need to remain sanitized—such as in hospitals, clean rooms, and accessibility scenarios for users with motor impairments. It can also be used in public kiosks or information terminals where hygiene is critical.

Limitations and Adaptations: While effective in good lighting, performance may degrade in poorly lit environments or when users wear glasses with reflective coatings. Addressing these through adaptive brightness compensation or infrared-based tracking is a proposed enhancement for future work.

The eye tracker serves as a foundational module in our system, proving that minimal hardware setups can still offer reliable, hands-free control in real-time computing environments.

V. Module 2: Virtual Mouse

This module allows the user to control the system using hand gestures and serves as an advanced substitute for the traditional physical mouse. It enables a wide variety of interactions including cursor movement, mouse clicks, system volume adjustment, screen brightness control, and scrolling—all through predefined hand gestures.

Hand Detection and Landmark Tracking: MediaPipe Hands is utilized to track 21 unique points on the user's hand, identifying fingers and their joint positions. These landmark coordinates are used to determine which fingers are raised, bent, or pinched.

Gesture Encoding and Classification: A custom binary gesture encoding scheme translates the state of each finger (open or closed) into a bitmask. For example, a gesture where the index finger is up and all others are down will have a specific gesture ID used to represent cursor

movement. Gestures like V-sign (first two fingers up) and fist (all fingers closed) are recognized and assigned specific actions.

Control Mapping: The following mappings are implemented:

FIST: Enables drag-and-drop functionality by simulating continuous left-click while moving the hand.

INDEX Finger: Triggers right-click functionality.

V_GEST (Index and Middle Finger): Moves the mouse pointer smoothly across the screen.

TWO_FINGER_CLOSED: Recognized for double-click operations.

PINCH_MAJOR: Used to increase or decrease screen brightness.

PINCH_MINOR: Triggers scroll or volume control based on the pinch direction.

Dampening and Smoothening: To eliminate jittery pointer movement caused by small unintentional hand tremors, a dampening algorithm is implemented. It averages the movement over successive frames to produce smoother motion.

Multi-Frame Gesture Stability: Gestures are required to be consistent across a minimum number of frames (typically 4–5) to be validated. This prevents misclassification caused by momentary or ambiguous gestures.

Edge Adaptation: The mouse pointer is constrained within screen boundaries, and frame scaling ensures uniform functionality across screen resolutions.

This module offers an efficient, hygienic, and innovative approach to system control, particularly suitable for users in cleanrooms, laboratories, or users with accessibility requirements.

V. Module 3: PPT Controller

The PowerPoint controller is tailored for use in educational and corporate presentation settings. It allows the presenter to navigate through slides and annotate directly on them using predefined hand gestures, all captured through a standard webcam.

Slide Navigation Based on Gestures: The system detects two primary gestures for controlling slides:

All Fingers Up (Open Palm): Moves the presentation forward to the next slide.

Only Thumb Up: Moves the presentation backward to the previous slide.

Annotation and Drawing Mode: When the annotation mode is activated, finger tip movement is tracked and visualized as on-screen drawing. This functionality is particularly useful for emphasizing specific points during live presentations.

System Integration: The controller communicates with Microsoft PowerPoint via the win32com.client API. This enables direct control over slide transitions, start/stop slideshow, and pointer activation, simulating real remote control behavior.

User Experience Optimization: The gesture detection zone is calibrated to work best when the user's hand is within the top half of the webcam feed. This prevents background interference and allows the system to distinguish between gestures made intentionally versus incidentally.

Delay and Debounce Logic: To prevent rapid, unintended slide transitions from multiple gesture detections in quick succession, the system includes debounce timers and cool-down periods.

Low-Light Optimization: The module has been tested and tuned to perform effectively under standard indoor lighting. Landmark detection thresholds are dynamically adjusted based on ambient light estimation.

With the PPT controller, presenters can walk around freely and interact naturally with their content without touching any device, significantly enhancing engagement and convenience.

VI. Technologies Used

a) The gesture recognition system is built using a collection of open-source libraries and tools, ensuring cost-effective development while maintaining high performance and flexibility. Below is an overview of the key technologies employed:

b) Python: Python serves as the primary programming language due to its readability, vast ecosystem of libraries, and ease of prototyping. Its integration with computer vision and system control libraries makes it ideal for this project.

c) OpenCV (Open Source Computer Vision Library): Used for real-time image capture, preprocessing, frame manipulation, and drawing outputs. It facilitates the detection of motion, object tracking, and conversion of color spaces essential for gesture recognition.

d) MediaPipe: A framework developed by Google for building multimodal applied machine learning pipelines. We utilized its FaceMesh and Hand Tracking modules for highly accurate, real-time facial and hand landmark detection.

e) PyAutoGUI: Allows for programmatic control of the mouse and keyboard. It interprets gesture results into cursor movement, click events, and keystrokes to control system applications.

f) CVZone: A wrapper that simplifies the use of MediaPipe for hand tracking, gesture detection, and finger state evaluation, accelerating development.

g) Aspose.Slides: A Python library used to automate PowerPoint presentations. It provides access to slides, slide transitions, annotations, and other operations required by the PPT controller module.

h) pycaw & screen_brightness_control: Libraries used to control system audio and display brightness. They enable pinch-based gesture interaction with system-level settings.

i) Threading & Timing Libraries: Python's built-in threading and time modules are employed for smooth execution of concurrent tasks, gesture delay management, and input event debouncing.

By combining these technologies, the system achieves a balance between precision, performance, and usability while remaining lightweight and easily deployable across various environments.

VII. Implementation Details

The real-time gesture recognition pipeline is designed to capture, process, classify, and execute gesture-based commands with minimal delay and high reliability. The architecture is event-driven and modular, ensuring scalability and ease of debugging. Here is a breakdown of the pipeline:

Frame Acquisition: The video feed is accessed using OpenCV's VideoCapture class. Frames are captured continuously at a rate optimized to maintain both responsiveness and CPU efficiency. Resolution is standardized to maintain consistency across systems.

Preprocessing: Captured frames are flipped and converted to RGB format. Additional processing such as resizing, grayscale conversion, or histogram equalization can be dynamically applied depending on ambient light conditions.

Landmark Processing: MediaPipe is employed to detect key landmarks on the face or hands. For facial detection, 468 landmarks are analyzed, particularly around the eye region. For hand detection, 21 landmarks per hand are used to determine finger positions and orientations.

Gesture Interpretation: Based on landmark distances, angles, and relative changes, each gesture is converted into a digital signal using heuristic conditions and ratio thresholds. For example, the relative distance between thumb and index finger determines whether a pinch is interpreted as a scroll or brightness control.

Action Execution: The interpreted gesture is passed to PyAutoGUI for mouse and keyboard simulation or to COM interfaces for application-specific tasks such as PowerPoint navigation. To prevent jitter, a dampening factor is used to smooth movements, and delay counters ensure action consistency.

Optimizations:

Threading support to maintain smooth performance

Delay counters and gesture hold-time filtering

Adaptive screen coordinate mapping for different screen sizes

VIII.SYSTEM DESIGN

System design builds upon analysis by defining the system's structure, functionality, and behavior. It involves detailed examination of components, processes, and interactions to identify strengths, weaknesses, and opportunities for improvement. This section provides an overview of the system's key attributes and design process.

VIII.I. System Architecture





FIGURE 8.2.1 SYSTEM ARCHITECTURE

VIII.I.I.I Gesture Based Virtual Mouse

The proposed virtual mouse system uses a laptop or PC webcam to capture video frames. With OpenCV in Python, a video capture object initializes the webcam, continuously streaming frames to the AI virtual system for processing. The system continuously captures frames while running. Each frame is converted from BGR to RGB color space to facilitate hand detection. This detection occurs frame by frame using the following code snippet:

```
python
CopyEdit
def findHands(self, img, draw=True):
    imgRGB = cv2.cvtColor(img, cv2.COLOR_BGR2RGB)
    self.results = self.hands.process(imgRGB)
```

This setup ensures real-time hand detection, enabling responsive and intuitive virtual mouse control, thereby improving user interaction with digital content.



0. WRIST
1. THUMB_CMC
2. THUMB_MCP
3. THUMB_IP
4. THUMB_TIP
5. INDEX_FINGER_MCP
6. INDEX_FINGER_PIP
7. INDEX_FINGER_DIP
8. INDEX_FINGER_TIP
9. MIDDLE_FINGER_MCP
10. MIDDLE_FINGER_PIP
11. MIDDLE_FINGER_DIP
12. MIDDLE_FINGER_TIP
13. RING_FINGER_MCP
14. RING_FINGER_PIP
15. RING_FINGER_DIP
16. RING_FINGER_TIP
17. PINKY_MCP
18. PINKY_PIP
19. PINKY_DIP
20. PINKY_TIP

Hand Landmarks and their Indices

Gesture Based PPT Control System

Once hand gestures are recognized, the system maps specific gestures to commands for navigating presentation slides. For example, raising all fingers signals a "next" slide command, while raising only the index finger triggers a "previous" slide command. This intuitive mapping allows seamless slide control through natural hand gestures.

The system also supports real-time annotation during presentations by tracking hand movements to enable dynamic drawing on slides. This feature enhances audience engagement by allowing presenters to highlight key points, draw diagrams, or underline important information directly on the slides.

Integration with Microsoft PowerPoint is achieved using the win32com.client library, enabling direct slide manipulation via webcam-captured gestures. This eliminates the need for manual controls or additional devices, improving accessibility for users with mobility impairments. Overall, the system streamlines presentation control and offers a more interactive and user-friendly experience.




Figure 8.3.1.3 Eye Tracking Virtual Mouse Flow Chart

IX. *Gesture Algorithm*

Algorithm

Step 1: System Initialization

- Initialize the webcam for real-time image capture.
- Configure the MediaPipe framework for hand tracking and gesture recognition.

Step 2: Real-Time Image Capture

- Continuously capture frames from the webcam for analysis.

Step 3: Hand Detection and Tracking

- Utilize MediaPipe to detect and track hands within captured frames.

Step 4: Gesture Recognition

- Detect predefined finger combinations and gestures.
- Map each recognized gesture to a specific virtual mouse or PowerPoint control command.

Step 5: Command Execution

- Translate gestures into virtual mouse actions such as cursor movement, left-click, right-click, and scrolling.
- For presentations, control slide navigation using hand gestures.

Step 6: Eye Tracking (if applicable)

- Track eye movements to control the cursor position using suitable software/hardware.

Step 7: System Termination

Gracefully shut down and release resources upon user request or after a set duration


X. Methodology

The system employs a transformational mapping technique to convert fingertip coordinates from the camera frame to the full-screen display for precise mouse control. A reference box is established in the camera view, enabling intuitive navigation of the mouse pointer based on detected hand movements. Specific fingers are identified to execute corresponding mouse functions, ensuring accurate interaction.

Incorporating eye tracking provides an alternative, hands-free method for cursor control by monitoring eye movements. This enhances accessibility and delivers a more natural user experience.

Modules Used:

- **OpenCV:** An open-source computer vision library offering real-time image processing and object detection. It supports face and object detection, providing a consistent framework for AI-integrated applications under an Apache 2 license.
- **MediaPipe:** Framework for hand tracking and gesture recognition.
- **PyAutoGUI:** Library for automating mouse and keyboard control.
- **Math:** Used for calculations in gesture recognition and coordinate transformations.



XI. Challenges and Solutions

Developing a reliable and real-time gesture recognition system using only a webcam and open-source tools introduced multiple technical and design challenges:

Gesture Ambiguity and Overlap: Many gestures have similar hand shapes and finger positions, making it hard to distinguish between them, especially in quick succession. This was mitigated by implementing gesture buffers and checking gesture consistency across at least five consecutive frames before executing an action.

Environmental Variability: The system's accuracy decreased significantly under dim lighting or against cluttered backgrounds. To address this, preprocessing steps like histogram normalization were introduced. Detection thresholds were also adjusted dynamically based on ambient light feedback from image histograms.

Click Jitter in Eye Tracking: Gaze-based clicking sometimes caused multiple click triggers due to micro eye movement or detection delay. A cooldown timer and blink hold duration threshold were introduced to improve accuracy.

System Resource Management: On entry-level hardware, real-time detection became laggy. Performance was optimized by reducing frame size, selectively enabling modules, and limiting the number of tracked hands to one unless explicitly configured otherwise.

Hand Orientation and Occlusion: Users often performed gestures from awkward angles or with one finger partially occluded. Additional calibration steps were introduced at system start to align gesture recognition with the user's preferred interaction zone.

The final system integrates all these enhancements to offer stable and practical performance under diverse operating conditions.

XII. Experimental Results

To validate the performance and usability of the system, extensive experiments were conducted with five participants under varying ambient light conditions, backgrounds, and physical setups. The testing covered each module independently and collectively to simulate practical usage.

Setup and Procedure: Participants were provided with a standard laptop setup. Each was instructed to perform 10 distinct tasks using each module, repeated three times for consistency. Scenarios included general computer navigation, volume/brightness adjustments, and PowerPoint slide control.

Environment Testing: Tests were conducted in environments ranging from bright daylight, office lighting, to low-light (below 100 lux) conditions. Variability in clothing, skin tone, and background clutter was also introduced.

Accuracy Evaluation:

Eye tracking cursor deviation was measured using pixel deviation metrics and averaged 3–7 pixels from intended targets.

Hand gesture recognition accuracy across all gestures was found to be 92.5%, with minor confusion observed between fist and pinch gestures.

Click success rate (eye-blink or hand) exceeded 94% when gesture hold thresholds were observed.

Timing Metrics:

The system responded with an average latency of 120 ms from gesture detection to action execution.

Slide transitions using the PPT controller had a delay of 0.7 seconds, inclusive of gesture recognition and COM API interaction.

User Feedback: Participants rated ease of use and intuitiveness highly (average 4.3/5). Common feedback suggested adding visual cues or gesture icons during interaction.

These results affirm the practicality and reliability of the system across real-world use cases and user demographics.

XII. Performance Evaluation

The performance of the system was evaluated across multiple hardware configurations and usage scenarios. All tests were performed on a machine with an Intel i5 processor, 8GB RAM, and a 720p webcam. The evaluation criteria included frame rate, memory usage, CPU load, latency, and multi-gesture recognition efficiency.

Frame Rate: The system consistently achieved an average of 22 FPS across modules. This frame rate ensures smooth visual feedback and real-time responsiveness without noticeable lag.

Memory Footprint: During extended sessions (30+ minutes), the system maintained a memory usage between 250 MB to 400 MB, depending on active modules and gesture complexity.

System Load: The CPU load remained around 45–60%, leaving headroom for background applications and ensuring no system freeze or stutter during operation.


Latency: Gesture-to-action latency was recorded between 100–150 milliseconds, suitable for real-time control scenarios such as presentations and UI navigation.

Multi-Gesture Handling: The system handled transitions between gestures (e.g., switching from V-sign to pinch) with 90% accuracy, thanks to multi-frame gesture confirmation and hand-state persistence.

These results indicate that the system is suitable for deployment on consumer-grade hardware and can operate effectively without the need for external GPU acceleration.

Mouse function performed	Success	Failure	Accuracy (%)
Mouse movement	100	0	100%
Left click Action	96	4	96%
Right click Action	97	3	97%
Scrolling Action	93	7	93%
Brightness level control	85	15	85%
Volume level control	90	4	90%
No action performed	100	0	100%

Table 12.1 Performance Analysis



Performance Graph

XIII. Applications

The versatility of this gesture-based system allows it to be used in a wide range of real-world environments, both for accessibility and convenience:

Healthcare: In hospitals or for users with motor disabilities, the eye tracker and gesture controls allow users to interact with computers or call for assistance without physical contact.

Education: Teachers and lecturers can use the PPT controller to deliver presentations hands-free, annotate directly with gestures, and engage with students in a more interactive way.

Home Automation: The virtual mouse can serve as an intuitive interface to control lighting, music systems, or smart TVs, especially for users who prefer non-verbal interfaces.

Gaming and Entertainment: Basic game controls or media interactions can be achieved through custom hand gestures, creating a more immersive and touchless gaming experience.

Retail and Public Kiosks: In public spaces where hygiene is a concern, touchless kiosks using gesture recognition can offer safe interactions for ticketing, payments, and information access.

Virtual Meetings: During online meetings, users can control slide decks or media without disturbing the flow, keeping hands free for other tasks.

This system's ability to perform using just a webcam makes it an ideal solution for scalable and low-cost deployment.

XIV. Future Work

While the current system offers robust gesture-based control, several areas remain open for improvement and extension:

Voice-Gesture Hybrid Control: Integrating speech recognition modules (e.g., Google Speech API) with gesture detection would allow users to perform multi-modal interactions, such as saying "Next Slide" while gesturing.

AI-Based Gesture Classifier: Although the current system relies on deterministic rules, employing machine learning models like CNNs trained on diverse gesture datasets could improve accuracy and reduce ambiguity, especially in cluttered backgrounds.

Environmental Adaptability: Enhancing performance under low-light or overly bright conditions using infrared-based vision or adaptive brightness correction could expand the range of usability.

Gesture Personalization: Users could be given the option to record and assign their own gestures to specific actions, creating a fully customizable experience.

AR/VR and IoT Integration: Extending gesture control into virtual environments and smart IoT ecosystems would make the system compatible with future smart infrastructure.

Cloud-Based Gesture Analytics: Logging gesture data (with privacy protections) could enable user behavior analysis, gesture optimization, and model improvement through federated learning.

XV. Conclusion

The integration of gesture-based interaction systems into everyday computing environments represents a significant step toward more intuitive and human-centered technologies. In this paper, we introduced a modular system that leverages standard webcam inputs to detect and interpret a variety of natural gestures—eye movements, hand signals, and finger postures—to control essential computer functionalities. Each module—the eye tracker, virtual mouse, and PowerPoint controller—demonstrated unique capabilities while also complementing the broader goal of enabling hands-free, efficient, and hygienic human-computer interaction.

The eye tracking module showed promising results in mapping gaze to cursor positions and implementing blink-based click actions, offering a potential solution for users with physical limitations. The virtual mouse extended system control beyond basic navigation, enabling dynamic adjustment of volume, brightness, and content scrolling through pinch gestures. The PowerPoint controller introduced gesture-driven presentation features that can enhance engagement and ease of instruction in academic and professional settings.

This system not only ensures cost-effective implementation using open-source tools and widely available hardware, but also promotes accessibility, versatility, and real-time performance. With a frame rate of over 20 FPS and high recognition accuracy, our solution provides a robust foundation for gesture-based interfaces.

In essence, the proposed gesture recognition system successfully addresses the limitations of conventional input methods, paving the way for the development of smart, responsive, and touchless computing interfaces. By expanding this work to incorporate additional modalities such as voice and contextual awareness, future iterations can further enrich user experiences and support a broader range of applications in sectors like healthcare, education, automation, and beyond.

XV. References

[1] R. Zhu, Y. Wang, and Y. Wang, "Real-time hand gesture recognition using MediaPipe and CNN-based model," Procedia Computer Science, vol. 210, pp. 57–64, 2024.

[2] A. Patel and M. Shah, "Touchless Interaction Framework Using Hand Gestures for Smart Applications," IEEE Access, vol. 10, pp. 87021–87034, 2022.

[3] S. Kaur and R. Kumar, "A robust eye-tracking system for cursor control using facial landmarks and machine learning," Sensors, vol. 21, no. 18, p. 6249, 2021.

[4] MediaPipe Documentation. Google AI. Available: https://google.github.io/mediapipe/

[5] OpenCV Documentation. OpenCV.org. Available: https://docs.opencv.org/

[6] PyAutoGUI Documentation. Available: https://pyautogui.readthedocs.io/en/latest/

[7] CVZone GitHub Repository. Available: https://github.com/cvzone/cvzone

[8] T. Nguyen, P. Nguyen, and D. Do, "A survey on touchless human-computer interaction technologies using computer vision," Journal of Ambient Intelligence and Humanized Computing, vol. 14, pp. 2111–2132, 2023.

[9] A. Singh and K. P. Singh, "An advanced gesture-controlled interface for smart device interaction," Multimedia Tools and Applications, vol. 82, pp. 22345–22367, 2023.

[10] S. Sana, P. Gaikwad, and S. Patil, "Eye Tracking For Mouse Processing," *Imperial Journal of Interdisciplinary Research*, vol. 3, 2017.

[11] S. Shriram, B. Nagaraj, J. Jaya, S. Shankar, and P. Ajay, "Deep Learning-Based Real-Time AI Virtual Mouse System Using Computer Vision to Avoid COVID-19 Spread," *Journal of Healthcare Engineering*, vol. 2021, Article ID 8133076, 2021, doi: 10.1155/2021/8133076.

[12] J. Katona, "A review of human–computer interaction and virtual reality research fields in cognitive InfoCommunications," *Applied Sciences*, vol. 11, no. 6, p. 2646, 2021.

[13] D. L. Quam, "Gesture recognition with a DataGlove," *IEEE Conference on Aerospace and Electronics*, vol. 2, pp. 755–760, 1990.

[14] F. Raimundo, C. D. Braga, A. M. Albuquerque, and I. C. de Paula, "Static Hand Gesture Recognition Based on Convolutional Neural Networks," *Journal of Electrical and Computer Engineering*, vol. 2019, Article ID 4167890, pp. 1-12, 2019, doi: 10.1155/2019/4167890.