

Activity: Deploy an AKS Cluster Using Azure Portal, Access the Dashboard, and Create Roles for Multiple Users

► Theory

Azure Kubernetes Service (AKS) is Microsoft's managed Kubernetes service that simplifies deploying, managing, and operating Kubernetes clusters in Azure. It abstracts away the complexity of setting up Kubernetes and provides scalability, monitoring, and security capabilities out of the box.

In this activity, we will:

- Deploy an AKS cluster using the Azure portal.
 - Access the Kubernetes Dashboard.
 - Create and assign role-based access control (RBAC) roles to different users.
-

► Steps to Deploy an AKS Cluster using Azure Portal

✓ 1. Login to Azure Portal

Go to: <https://portal.azure.com>

✓ 2. Create a Resource Group

- Search for “Resource Groups”.
- Click **Create** → Enter:
 - Resource Group Name: `aks-rg`
 - Region: `East US` (or your preferred region)
- Click **Review + Create** → **Create**.

✓ 3. Deploy AKS Cluster

- Search for **Kubernetes Services**.
- Click **Create** → **Create Kubernetes Cluster**.
- Fill in the details:
 - **Cluster Name:** `aks-demo`
 - **Region:** Same as Resource Group
 - **Node Size:** `Standard_DS2_v2` (or smaller for testing)
 - **Node Count:** 1 or 2
- Under **Authentication**, enable RBAC.

- Leave other defaults and click **Review + Create**, then **Create**.

✓ It will take ~5–10 minutes for the cluster to be ready.

► Steps to Access the Kubernetes Dashboard

✓ 1. Open Cloud Shell

- Click on the **Cloud Shell** icon in Azure Portal (top navigation bar).
- Choose **Bash** shell.

✓ 2. Connect to AKS Cluster

Run this command to configure kubectl:

```
bash
CopyEdit
az aks get-credentials --resource-group aks-rg --name aks-demo
```

✓ 3. Enable Kubernetes Dashboard Add-on (optional in new AKS versions):

```
bash
CopyEdit
az aks enable-addons --addons kube-dashboard --resource-group aks-rg --name
aks-demo
```

✓ 4. Access the Dashboard

Run:

```
bash
CopyEdit
kubectl proxy
```

Open this URL in your browser:

```
bash
CopyEdit
http://localhost:8001/api/v1/namespaces/kubernetes-
dashboard/services/https:kubernetes-dashboard:/proxy/
```

► Steps to Create Roles for Multiple Users

✓ 1. Create Role YAML File (role.yaml)

Example Role to allow listing pods:

```
yaml
CopyEdit
apiVersion: rbac.authorization.k8s.io/v1
kind: Role
metadata:
  namespace: default
  name: pod-reader
rules:
- apiGroups: [""]
  resources: ["pods"]
  verbs: ["get", "watch", "list"]
```

Apply the role:

```
bash
CopyEdit
kubectl apply -f role.yaml
```

✅ 2. Create RoleBinding for a User (rolebinding.yaml)

Example RoleBinding for a user:

```
yaml
CopyEdit
apiVersion: rbac.authorization.k8s.io/v1
kind: RoleBinding
metadata:
  name: read-pods-binding
  namespace: default
subjects:
- kind: User
  name: "john@example.com" # Replace with the Azure AD user email
  apiGroup: rbac.authorization.k8s.io
roleRef:
  kind: Role
  name: pod-reader
  apiGroup: rbac.authorization.k8s.io
```

Apply the RoleBinding:

```
bash
CopyEdit
kubectl apply -f rolebinding.yaml
```

✅ 3. Repeat for Multiple Users

You can create separate RoleBindings for other users like:

- raj@example.com
- emma@example.com

► Conclusion

- ✓ Successfully deployed an AKS cluster using Azure Portal.
- ✓ Accessed the Kubernetes dashboard using `kubectl proxy`.
- ✓ Created RBAC roles and role bindings to control user access.

► Additional Useful Commands

```
bash
CopyEdit
kubectl get pods --all-namespaces
kubectl get roles --namespace default
kubectl get rolebindings --namespace default
```
