

NAME: Ajay Srinivas R

REG NO: 230701017

Ex no:13

WORKING WITH TRIGGER

Initial:

```
CREATE TABLE orders ( order_id  
NUMBER PRIMARY KEY, item_id  
NUMBER, quantity NUMBER,  
order_date DATE, running_total  
NUMBER, user_id NUMBER,  
FOREIGN KEY (item_id) REFERENCES items(item_id)  
);
```

```
INSERT INTO orders (order_id, item_id, quantity, order_date, running_total, user_id)  
VALUES (1, 1, 20, SYSDATE, 20, 101);  
INSERT INTO orders (order_id, item_id, quantity, order_date, running_total, user_id)  
VALUES (2, 2, 30, SYSDATE, 50, 102);
```

```
CREATE TABLE items ( item_id  
NUMBER PRIMARY KEY, item_name VARCHAR2(50),  
stock_level  
NUMBER, pending_orders NUMBER  
DEFAULT 0  
);
```

```
INSERT INTO items (item_id, item_name, stock_level, pending_orders)  
VALUES (1, 'Item A', 100, 0);  
INSERT INTO items (item_id, item_name, stock_level, pending_orders)  
VALUES (2, 'Item B', 50, 0);
```

```
INSERT INTO items (item_id, item_name, stock_level, pending_orders) VALUES  
(3, 'Item C', 150, 0);
```

```
CREATE TABLE audit_log ( log_id  
NUMBER PRIMARY KEY,  
table_name VARCHAR2(50),  
operation VARCHAR2(10),  
change_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
user_id NUMBER, details VARCHAR2(200)  
);
```

```
CREATE SEQUENCE audit_log_seq  
START WITH 1  
INCREMENT BY 1;
```

- Program 1

Write a code in PL/SQL to develop a trigger that enforces referential integrity by preventing the deletion of a parent record if child records exist.

```
CREATE OR REPLACE TRIGGER prevent_parent_delete  
BEFORE DELETE ON items  
FOR EACH ROW DECLARE  
    child_count NUMBER;  
  
BEGIN  
  
    SELECT COUNT(*) INTO child_count FROM orders  
    WHERE item_id = :OLD.item_id;  
  
    IF child_count > 0 THEN  
        RAISE_APPLICATION_ERROR(-20001, 'Cannot delete item; dependent  
orders exist.');
```

```
    END IF;
```

```
END; /
```

- Write a code in PL/SQL to create a trigger that checks for duplicate values in a specific column and raises an exception if found.

```
CREATE OR REPLACE TRIGGER check_for_duplicates
```

```
BEFORE INSERT OR UPDATE ON orders
```

```
FOR EACH ROW DECLARE
```

```
    duplicate_count NUMBER;
```

```
BEGIN
```

```
SELECT COUNT(*) INTO duplicate_count FROM orders
```

```
WHERE item_id = :NEW.item_id AND order_id != :NEW.order_id;
```

```
IF duplicate_count > 0 THEN
```

```
    RAISE_APPLICATION_ERROR(-20002, 'Duplicate item entry found in orders.');
```

```
END IF;
```

```
END; /
```

- Write a code in PL/SQL to create a trigger that restricts the insertion of new rows if the total of a column's values exceeds a certain threshold.

```
CREATE OR REPLACE TRIGGER restrict_insertion
```

```
BEFORE INSERT ON orders
```

```
FOR EACH ROW DECLARE
```

```
    total_quantity NUMBER;
```

```
BEGIN
```

```
SELECT SUM(quantity) INTO total_quantity FROM orders;
```

```
IF (total_quantity + :NEW.quantity) > 500 THEN
```

```
    RAISE_APPLICATION_ERROR(-20003, 'Cannot insert order; total  
    quantity exceeds threshold.');
```

```
END IF;
```

```
END; /
```

- Write a code in PL/SQL to design a trigger that captures changes made to specific columns and logs them in an audit table.

```
CREATE OR REPLACE TRIGGER log_changes
```

```
AFTER UPDATE ON orders
```

```
FOR EACH ROW
```

```
BEGIN
```

```
/
```

```
INSERT INTO audit_log (log_id, table_name, operation, user_id, details) VALUES  
(audit_log_seq.NEXTVAL, 'orders', 'UPDATE', :NEW.user_id, 'Order ' ||  
:NEW.order_id || ' changed from ' || :OLD.quantity || ' to ' || :NEW.quantity ); END;
```

- Write a code in PL/SQL to implement a trigger that records user activity (inserts, updates, deletes) in an audit log for a given set of tables.

```
CREATE OR REPLACE TRIGGER log_user_activity
```

```
AFTER INSERT OR DELETE OR UPDATE ON orders
```

```
FOR EACH ROW
```

```
BEGIN
```

```
INSERT INTO audit_log (log_id, table_name, operation, user_id, details) VALUES  
(audit_log_seq.NEXTVAL, 'orders',
```

```
CASE
```

```
WHEN INSERTING THEN 'INSERT' WHEN UPDATING THEN 'UPDATE' WHEN DELETING THEN  
'DELETE'
```

```
END,
```

```
NVL(:NEW.user_id, :OLD.user_id), 'User action recorded on order ' ||  
NVL(:NEW.order_id, :OLD.order_id));
```

```
END; /
```

- Write a code in PL/SQL to implement a trigger that automatically calculates and updates a running total column for a table whenever new rows are inserted.

```
CREATE OR REPLACE TRIGGER update_running_total
AFTER INSERT ON orders
FOR EACH ROW
BEGIN
    UPDATE orders SET running_total = (SELECT SUM(quantity) FROM orders)
    WHERE order_id = :NEW.order_id;
END; /
```

- Write a code in PL/SQL to create a trigger that validates the availability of items before allowing an order to be placed, considering stock levels and pending orders

```
CREATE OR REPLACE TRIGGER validate_item_availability
BEFORE INSERT ON orders

FOR EACH ROW DECLARE
    available_stock NUMBER;

BEGIN

    SELECT stock_level - pending_orders INTO available_stock FROM items
    WHERE item_id = :NEW.item_id;

    IF :NEW.quantity > available_stock THEN
        RAISE_APPLICATION_ERROR(-20004, 'Insufficient stock available for the
        order.');
```

```
    END IF;

    UPDATE items SET pending_orders = pending_orders + :NEW.quantity
    WHERE item_id = :NEW.item_id;

END; /
```

Result:

The given programs are performed successfully.