Name : Ajay T Naik

SRN : PES1UG24CS552

Section : 5J

Screenshot 1:

```
C:\Users\Admin\L6_L7_03_coffee_shop_order>python processor.py
[1, 2, 3]
7.5
True
```

Screenshot 2:

```
C:\Users\Admin\L6_L7_03_coffee_shop_order>python -m pytest test_processor.py
============================= test session starts =============================
platform win32 -- Python 3.13.0, pytest-9.2.0, pluggy-1.7.0
rootdir: C:\Users\Admin\L6_L7_03_coffee_shop_order
plugins: anyio-4.11.0, hypothesis-6.170.15
collected 3 items

test_processor.py FFF                                                    [100%

================================== FAILURES ===================================
_____________________ test_process_order_no_crash _____________________
  + Exception Group Traceback (most recent call last):
  |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py", line 5, in test_process_order_no_crash
  |     def test_process_order_no_crash(item, quantity):
  |                   ^^^
  | ExceptionGroup: Hypothesis found 2 distinct failures. (2 sub-exceptions)
  +-+---------------- 1 ----------------
    | Traceback (most recent call last):
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py", line 7, in test_process_order_no_crash
    |     process_order(item, quantity)
    |     ~~~~~~~~~~~~~^^^^^^^^^^^^^^^^
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\processor.py", line 2, in process_order
    |     return [int(x) for x in item.split(',')]
    |                ~~~^^^
    | ValueError: invalid literal for int() with base 10: ''
    |
    | During handling of the above exception, another exception occurred:
    |
    | Traceback (most recent call last):
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py", line 9, in test_process_order_no_crash
    |     assert False, f"process_order crashed with inputs ({item}, {quantity}) due to: {e}"
    | AssertionError: process_order crashed with inputs (, None) due to: invalid literal for int() with base 10: ''
    | assert False
    | Failing test case: test_process_order_no_crash(
    |     item='',
    |     quantity=None,  # or any other generated value
    | )
    | Explanation:
    |     These lines were always and only run by failing test cases:
    |         C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py:8
    +---------------- 2 ----------------
```

```
    +--------------- 2 ---------------
    | Traceback (most recent call last):
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py", line 7, in test_process_order_no_crash
    |     process_order(item, quantity)
    |     ~~~~~~~~~~~~~^^^^^^^^^^^^^^^^
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\processor.py", line 2, in process_order
    |     return [int(x) for x in item.split(',')]
    |                             ^^^^^^^^^
    | AttributeError: 'NoneType' object has no attribute 'split'
    |
    | During handling of the above exception, another exception occurred:
    |
    | Traceback (most recent call last):
    |   File "C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py", line 9, in test_process_order_no_crash
    |     assert False, f"process_order crashed with inputs ({item}, {quantity}) due to: {e}"
    | AssertionError: process_order crashed with inputs (None, None) due to: 'NoneType' object has no attribute 'split'
    | assert False
    | Failing test case: test_process_order_no_crash(
    |     # The test always failed when commented parts were varied together.
    |     item=None,  # or any other generated value
    |     quantity=None,  # or any other generated value
    | )
    | Explanation:
    |     These lines were always and only run by failing test cases:
    |         C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py:8
    +-----------------------------------
_____ test_calculate_total_no_crash _____

prices = None

    @given(st.lists(st.floats(allow_nan=False)) | st.none())
    def test_calculate_total_no_crash(prices):
        try:
>           calculate_total(prices)

test_processor.py:14:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

prices = None

    def calculate_total(prices):
>       return sum(prices)
               ^^^^^^^^^^
E       TypeError: 'NoneType' object is not iterable

processor.py:5: TypeError

During handling of the above exception, another exception occurred:

    @given(st.lists(st.floats(allow_nan=False)) | st.none())
>   def test_calculate_total_no_crash(prices):
                  ^^^

test_processor.py:12:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

prices = None

    @given(st.lists(st.floats(allow_nan=False)) | st.none())
    def test_calculate_total_no_crash(prices):
        try:
            calculate_total(prices)
        except Exception as e:
>           assert Error, f"calculate_total crashed with input {prices} due to: {e}"
                  ^^^^^
E           NameError: name 'Error' is not defined
E           Failing test case: test_calculate_total_no_crash(
E               prices=None,
E           )
E           Explanation:
E               These lines were always and only run by failing test cases:
E                   C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py:15

test_processor.py:16: NameError
_____ test_validate_coupon_no_crash _____

coupon = None

    @given(st.text() | st.none())
    def test_validate_coupon_no_crash(coupon):
```

```
    def test_validate_coupon_no_crash(coupon):
        try:
>           validate_coupon(coupon)

test_processor.py:21:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

coupon = None

    def validate_coupon(coupon):
>       return coupon.strip() == "COFFEE10"
               ^^^^^^^^^^^^
E       AttributeError: 'NoneType' object has no attribute 'strip'

processor.py:8: AttributeError

During handling of the above exception, another exception occurred:

    @given(st.text() | st.none())
>   def test_validate_coupon_no_crash(coupon):
                ^^^

test_processor.py:19:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

coupon = None

    @given(st.text() | st.none())
    def test_validate_coupon_no_crash(coupon):
        try:
            validate_coupon(coupon)
        except Exception as e:
>           assert False, f"validate_coupon crashed with input {coupon} due to: {e}"
E           AssertionError: validate_coupon crashed with input None due to: 'NoneType' object has no attribute 'strip'
E           assert False
E           Failing test case: test_validate_coupon_no_crash(
E               coupon=None,
E           )
E           Explanation:
E               These lines were always and only run by failing test cases:
E                   C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py:22
```

```
test_processor.py:19:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

coupon = None

    @given(st.text() | st.none())
    def test_validate_coupon_no_crash(coupon):
        try:
            validate_coupon(coupon)
        except Exception as e:
>           assert False, f"validate_coupon crashed with input {coupon} due to: {e}"
E           AssertionError: validate_coupon crashed with input None due to: 'NoneType' object has no attribute 'strip'
E           assert False
E           Failing test case: test_validate_coupon_no_crash(
E               coupon=None,
E           )
E           Explanation:
E               These lines were always and only run by failing test cases:
E                   C:\Users\Admin\L6_L7_03_coffee_shop_order\test_processor.py:22

test_processor.py:23: AssertionError
=========================================================================== short test summary info ============================================================================
FAILED test_processor.py::test_process_order_no_crash - ExceptionGroup: Hypothesis found 2 distinct failures. (2 sub-exceptions)
FAILED test_processor.py::test_calculate_total_no_crash - NameError: name 'Error' is not defined
FAILED test_processor.py::test_validate_coupon_no_crash - AssertionError: validate_coupon crashed with input None due to: 'NoneType' object has no attribute 'strip'
============================================================================ 3 failed in 6.90s =============================================================================

C:\Users\Admin\L6_L7_03_coffee_shop_order>A
```

Screenshot 3:

```
C:\Users\Admin\L6_L7_03_coffee_shop_order>python processor.py
Successfully ordered 2 Latte(s).
10.25
True
```

Screenshot 4:

```
C:\Users\Admin\L6_L7_03_coffee_shop_order>python -m pytest test_processor.py
============================================================================ test session starts ============================================================================
platform win32 -- Python 3.13.0, pytest-9.2.0, pluggy-1.7.0
rootdir: C:\Users\Admin\L6_L7_03_coffee_shop_order
plugins: anyio-4.11.0, hypothesis-6.170.15
collected 3 items

test_processor.py ...                                                                                                                                          [100%]

============================================================================ 3 passed in 4.69s =============================================================================
```