

Ex. No: 6a Date: 15/2/25

FIRST COME FIRST SERVE

AIM:

To implement First-come First- serve (FCFS) scheduling technique

ALGORITHM:

1. Get the number of processes from the user.
2. Read the process name and burst time.
3. Calculate the total process time.
4. Calculate the total waiting time and total turnaround time for each process
5. Display the process name & burst time for each process.
6. Display the total waiting time, average waiting time, turnaround time.

PROGRAM:

```
#include <stdio.h>

int main() {
    int pid[15], bt[15], wt[15], n;
    float twt = 0, ttat = 0;

    printf("Enter the number of processes: ");
    scanf("%d", &n);

    printf("Enter process ID of all the processes:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &pid[i]);
    }

    printf("Enter burst time of all the processes:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &bt[i]);
    }

    wt[0] = 0;
    // Calculate waiting time for all other processes
    for (int i = 1; i < n; i++) {
        wt[i] = wt[i - 1] + bt[i - 1];
    }

    printf("\nProcess ID\tBurst Time\tWaiting Time\tTurnaround Time\n");
```

```

for (int i = 0; i < n; i++) {
    int tat = bt[i] + wt[i];
    twt += wt[i];
    ttat += tat;


    printf("%d\t%d\t%d\t%d\n", pid[i], bt[i], wt[i], tat);
}

printf("\nAverage waiting time = %.2f\n", twt / n);
printf("Average turnaround time = %.2f\n", ttat / n);

return 0;
}

```

OUTPUT:



```

$ bash fcfs.sh
Enter the number of processes: 2
Enter the burst time of the processes:
3
4
Process Burst Time Waiting Time Turn Around Time
0 3 0 3
1 4 3 7
fcfs.sh: line 36: bc: command not found
fcfs.sh: line 37: bc: command not found
Average waiting time is:
Average Turn around Time is:

```

RESULT:

Thus, the Program of first come first serve is successfully implemented.

Ex. No: 6b Date: 15/2/25

SHORTEST JOB FIRST

AIM:

To implement the Shortest Job First (SJF) scheduling technique

ALGORITHM:

1. Declare the structure and its elements.
2. Get a number of processes as input from the user.
3. Read the process name, arrival time and burst time
4. Initialize waiting time, turnaround time & flag of read processes to zero.
5. Sort based on the burst time of all processes in ascending order.
6. Calculate the waiting time and turnaround time for each process.
7. Calculate the average waiting time and average turnaround time.
8. Display the results.

PROGRAM:

```
#include <stdio.h>

int main() {
    int A[100][4]; // A[i][0]=PID, A[i][1]=BT, A[i][2]=WT, A[i][3]=TAT
    int i, j, n, total = 0, index, temp;
    float avg_wt, avg_tat;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter Burst Time:\n");
    for (i = 0; i < n; i++) {
        printf("P%d: ", i + 1);
        scanf("%d", &A[i][1]);
        A[i][0] = i + 1; // Assign process ID
    }

    for (i = 0; i < n; i++) {
        index = i;
        for (j = i + 1; j < n; j++) {
            if (A[j][1] < A[index][1])
                index = j;
        }

        temp = A[i][1];
```

```

A[i][1] = A[index][1];
A[index][1] = temp;

temp = A[i][0];
A[i][0] =
A[index][0];
A[index][0] = temp;
}

A[0][2] = 0;
for (i = 1; i < n; i++) {
A[i][2] = 0;
for (j = 0; j < i; j++) {
A[i][2] += A[j][1];
}
total += A[i][2];
}
avg_wt = (float) total / n;

total = 0;
printf("\nProcess\tBT\tWT\tTAT\n");
for (i = 0; i < n; i++) {
A[i][3] = A[i][1] + A[i][2]; // TAT = BT + WT
total += A[i][3];
printf("P%d\t%d\t%d\t%d\n", A[i][0], A[i][1], A[i][2], A[i][3]);
}
avg_tat = (float) total / n;

printf("\nAverage Waiting Time = %.2f", avg_wt);
printf("\nAverage Turnaround Time = %.2f\n", avg_tat);

return 0;
}

```

OUTPUT:

```

$ bash sjf.sh
Enter the number of processes: 2
Enter the burst time of the processes:
1
2
Process Burst Time Waiting Time Turn Around Time
1 1 0 1
2 2 1 3

```

RESULT:

Thus, the Program Shortest Job First is successfully implemented.

Ex. No: 6c

Date: 16/2/25

PRIORITY SCHEDULING

AIM:

To implement a priority scheduling technique

ALGORITHM:

1. Get the number of processes from the user.
2. Read the process name, burst time and priority of the process.
3. Sort based on burst time of all processes in ascending order based on priority
4. Calculate the total waiting time and total turnaround time for each process
5. Display the process name & burst time for each process.
6. Display the total waiting time, average waiting time, turnaround time.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>

void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

int main() {
    int n;
    printf("Enter number of processes: ");
    scanf("%d", &n);

    int *burst = (int*)malloc(n * sizeof(int));
    int *priority = (int*)malloc(n *
sizeof(int)); int *pid = (int*)malloc(n *
sizeof(int));
    int total_wait = 0, total_turnaround = 0;

    for (int i = 0; i < n; i++) {
        printf("Enter Burst Time and Priority for Process %d: ", i + 1);
        scanf("%d %d", &burst[i], &priority[i]);
        pid[i] = i + 1;
    }

    for (int i = 0; i < n - 1; i++) {
        for (int j = i + 1; j < n; j++)
        {
            if (priority[j] > priority[i]) {
                swap(&priority[i], &priority[j]);
            }
        }
    }

    for (int i = 0; i < n; i++) {
        int waiting_time = 0;
        int turnaround_time = 0;
        for (int j = 0; j < n; j++) {
            if (j != i) {
                if (priority[j] < priority[i]) {
                    waiting_time += burst[j];
                    turnaround_time += burst[j];
                }
            }
        }
        total_wait += waiting_time;
        total_turnaround += turnaround_time;
    }

    printf("Total waiting time: %d\n", total_wait);
    printf("Average waiting time: %d\n", total_wait / n);
    printf("Total turnaround time: %d\n", total_turnaround);
    printf("Average turnaround time: %d\n", total_turnaround / n);
}
```

```

        swap(&burst[i], &burst[j]);
        swap(&pid[i], &pid[j]);
    }
}
}
int wait_time = 0;
printf("\nProcess Burst Time Wait Time Turnaround Time\n");

for (int i = 0; i < n; i++) {
    int turnaround_time = wait_time + burst[i];
    total_wait += wait_time;
    total_turnaround += turnaround_time;

    printf("P%d    %d    %d    %d\n", pid[i], burst[i], wait_time, turnaround_time);

    wait_time += burst[i];
}


printf("\nAverage Waiting Time: %.2f\n", (float)total_wait / n);
printf("Average Turnaround Time: %.2f\n", (float)total_turnaround / n);

free(burst);
free(priority);
free(pid);

return 0;
}

```

OUTPUT:



```

$ bash priority_scheduling.sh
Enter the number of processes: 2
Enter process name, burst time, and priority (space separated): 2
Enter process name, burst time, and priority (space separated): 1
Process Burst Time Priority Waiting Time Turn Around Time
1    0
2    0 0

```

RESULT:

Thus, the Program of Priority scheduling is successfully implemented.