```
import numpy as np
import pandas as pd
```

df=pd.read\_csv("/content/Mall\_Customers.csv")

df

	CustomerID	Genre	Age	Annual Income (k\$)	Spending Score (1-100)
0	1	Male	19	15	39
1	2	Male	21	15	81
2	3	Female	20	16	6
3	4	Female	23	16	77
4	5	Female	31	17	40
195	196	Female	35	120	79
196	197	Female	45	126	28
197	198	Male	32	126	74
198	199	Male	32	137	18
199	200	Male	30	137	83

200 rows × 5 columns

x=df.iloc[:,3:]#all rows and 3 onwards columns print("The X value is:",x)

The X value is:	Annual Income (k\$)	Spending Score (1-100)
0	15	39
1	15	81
2	16	6
3	16	77
4	17	40
	• • •	•••
195	120	79
196	126	28
197	126	74
198	137	18
199	137	83

[200 rows x 2 columns]

from sklearn.cluster import KMeans,AgglomerativeClustering

```
km=KMeans(n_clusters=3)
km.fit_predict(x)
```

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/\_kmeans.py:870: FutureWarning: The default value of `n\_init` will change frow warnings.warn(

SSE=[]

4

```
for i in range(1,16):
```

km=KMeans(n\_clusters=i)

 $\quad \text{km.fit\_predict(x)} \quad$ 

SSE.append(km.inertia\_)

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/\_kmeans.py:870: FutureWarning: The default value of `n\_init` will change frow warnings.warn(

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/\_kmeans.py:870: FutureWarning: The default value of `n\_init` will change frow warnings.warn(

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/\_kmeans.py:870: FutureWarning: The default value of `n\_init` will change frow warnings.warn(

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/\_kmeans.py:870: FutureWarning: The default value of `n\_init` will change from the control of the con

```
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from
                         warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
/usr/local/lib/python 3.10/dist-packages/sklearn/cluster/\_kmeans.py: 870: Future Warning: The default value of `n\_init` will change from the control of th
                         warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                         warnings.warn(
```

SSE

```
[269981.28,

181363.59595959593,

106348.37386211122,

73679.78903948836,

44448.4554479337,

37233.814510710006,

30273.394312070042,

25018.781613414067,

21818.114588452176,

19681.25582847105,

17508.97057740007,

15993.9422660915,

14367.900783072084,


13204.839599686027,

11630.993181818183]
```

 ${\tt import\ matplotlib.pyplot\ as\ plt}$ 

```
plt.title("Elbow Method")
plt.xlabel("Value of K")
plt.ylabel("SSE")
plt.grid()
plt.xticks(range(1,16))
plt.plot(range(1,16),SSE,marker=".",color="blue")
```

[<matplotlib.lines.Line2D at 0x7d95d502d0f0>]



from sklearn.metrics import silhouette\_score

```
SILOUT=[]
for i in range(2,16):#for finding nearest value we need to start from 2
```


```
km=KMeans(n_clusters=i)
labels=km.fit_predict(x)
score=silhouette_score(x,labels)
SILOUT.append(score)
```

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the following of the foll
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/ kmeans.py:870: FutureWarning: The default value of `n init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
                       warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/ kmeans.py:870: FutureWarning: The default value of `n init` will change from
                       warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/ kmeans.py:870: FutureWarning: The default value of `n init` will change from the control of the con
                       warnings.warn(
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from the control of the con
  /usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from
                       warnings.warn(
```

```
plt.title("silhouette Method")
plt.xlabel("Value of K")
plt.ylabel("silhouette score")
plt.grid()
plt.xticks(range(2,16))
plt.plot(range(2,16),SILOUT,color="blue")
```

4

[<matplotlib.lines.Line2D at 0x7d95d50ce5c0>]



km=KMeans(n\_clusters=5,random\_state=0)
km.fit\_predict(x)

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change frow warnings.warn(
array([4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3, 4, 3,
```

```
plt.figure(figsize=(16,9))
plt.subplot(1,2,1)
plt.title("Unclustered Data")
plt.xlabel("Annual Income")
plt.ylabel("Spending Score")
plt.scatter(x['Annual Income (k$)'],x['Spending Score (1-100)'])

plt.subplot(1,2,2)
plt.title("clustered Data")
plt.xlabel("Annual Income")
plt.ylabel("Spending Score")
plt.scatter(x['Annual Income (k$)'],x['Spending Score (1-100)'],c=labels)
```

## <matplotlib.collections.PathCollection at 0x7d95d4e2c580>

