English V Q Q Logir



3D printers

Materials

Parts & Accessories

Software

3D Models



[Solved] Setting the printer to ready via an input pin on the GPIO



QMcMurray

(@qmcmurray)

Active Member

*

Setting the printer to ready via an input pin on the GPIO

I've modified my MK4S with an auto eject scrapper so I can queue up multiple prints with having to unload the printer manually.

It sends a finish signal Via the GPIO to a micro controller to start the sequence.

If you are curious this is the set up for the auto eject. Not my design, but works great: https://github.com/d-weber/prusa-chain-production/

Hats off the the designer d-weber.

However, the thorn in the lions paw is the set ready on the printer.

On the store page for the GPIO it claims it can be used to set the printer to ready.

This is what I have tried:

I've made Pin 6 on the GIPO to an input so I can have it execute a macro from a gcode file on the USB.

The macro is 2 lines of code:

- 1. M72 S1; Set printer to ready State
- 2. M300; Buzz to confirm macro was executed

I'm trying to use the M72 command to set the printer to the ready state. It seems like it should work.

https://help.prusa3d.com/article/prusa-firmware-specific-g-

1 of 5 21-04-2025, 05:42 pm

English v Q @ Logi

ו know tne macro is executed pecause וז puzzes. שנו tne printer doesn t change.

- Does anyone understand the M72 command?
- Is there an alterative to way to do set the printer to ready through gcode?

I'm not much of a programmer so I'm out of my element.

Any help would be appreciated!

This topic was modified 3 months ago 2 times by **QMcMurray**

• Log in to be able to post





Posted: 01/02/2025 3:41 am

LarGriff liked



Topic starter answered:

RE: Setting the printer to ready via an input pin on the GPIO

M1200 can be used to set the printer to ready from gcode.

QMcMurray
(@qmcmurray)



Active Member







Posted: 02/02/2025 3:51 pm

Valjuvic_2, Stumml and LarGriff liked

≔ All forum topics

≺ Previous Topic

Log in to be able to post

Next Topic >

Related Topics

ls my GPIO set-up correct?

1 month ago

GPIO Projects

3 months ago

How do I make a fan turn on at the end of a print?

4 months ago


Topic Tags: GPIO (15), Set Ready (3), Auto Eject (1), gcode (166)

Share:



2 of 5 21-04-2025, 05:42 pm

English V Q Q Login



3 of 5 21-04-2025, 05:42 pm

English V Q Q Login





Blog



Flash Conte sts Them e: Fridge Repair s

Practi cal Sara Studio Gillis



Previe W

Prusa

Slicer 2.9.1: Smart er Seque ntial Printin g & Stron ger Multi-Materi

al

Newsletter

Signup and get our monthly squeeze on updates, blog, printables and much more.

E-mail


I would like to receive the e-book "Basics of 3D Printing" as a gift

By clicking, you agree to receive our newsletter.

Subscribe

This site is protected by reCAPTCHA Enterprise and the Google <u>Privacy Policy</u> and <u>Terms of Service</u> apply.







21-04-2025, 05:42 pm 4 of 5

English \vee Q Q Login

.

E-shop	Printables	Communit	Help	Software	Company
3D Printers Printer Upgrades Accessories Prusa Merchandise	3D Models 3D Design Contests Weekly 3D Prints	World Map Forum User Groups Events	Prusa Help Prusa Academy 3D Printing Calculator s	PrusaSlice r Prusa.app Prusa Connect Drivers and Software	About Us Blog Press Timeline Contact Us

General Terms and Conditions

General Terms and Conditions of Use of the PRUSA Websites

Privacy Policy

Information about cookies

Status Page

General Terms and Conditions
| General Terms and Conditions of Use of the PRUSA Websites
| Privacy Policy | Information about cookies
| Status Page | Cookie settings
| Supplemental Statements

© Prusa Research a.s.

5 of 5 21-04-2025, 05:42 pm