

Assignment Questions

Q1. SELECT clause with WHERE, AND, DISTINCT, Wild Card (LIKE)

- a. Fetch the employee number, first name and last name of those employees who are working as Sales Rep reporting to employee with employee number 1102 (**Refer employee table**)

Expected output:

	employeeNumber	firstname	lastname
▶	1337	Loui	Bondur
	1370	Gerard	Hernandez
	1401	Pamela	Castillo
	1501	Larry	Bott
	1504	Barry	Jones
	1702	Martin	Gerard

- b. Show the unique productline values containing the word cars at the end from the **products table**.

Expected output:

productLine
Classic Cars
Vintage Cars

Q2. CASE STATEMENTS for Segmentation

- a. Using a CASE statement, segment customers into three categories based on their country: (**Refer Customers table**)

"North America" for customers from USA or Canada

"Europe" for customers from UK, France, or Germany

"Other" for all remaining countries

Select the customerNumber, customerName, and the assigned region as "CustomerSegment".

Expected output:

	customerNumber	customerName	CustomerSegment
►	103	Atelier graphique	Europe
	112	Signal Gift Stores	North America
	114	Australian Collectors, Co.	Other
	119	La Rochelle Gifts	Europe
	121	Baane Mini Imports	Other
	124	Mini Gifts Distributors Ltd.	North America
	125	Havel & Zbyszek Co	Other
	128	Blauer See Auto, Co.	Europe
	129	Mini Wheels Co.	North America
	131	Land of Toys Inc.	North America
	141	Euro+ Shopping Channel	Other
	144	Volvo Model Replicas, Co	Other
	145	Danish Wholesale Imports	Other
	146	Saveley & Henriot, Co.	Europe

Q3. Group By with Aggregation functions and Having clause, Date and Time functions

- a. Using the **OrderDetails** table, identify the top 10 products (by productCode) with the highest total order quantity across all orders.

Expected output:

	productCode	total_ordered
►	S18_3232	1808
	S18_1342	1111
	S700_4002	1085
	S18_3856	1076
	S50_1341	1074
	S18_4600	1061
	S10_1678	1057
	S12_4473	1056
	S18_2319	1053
	S24_3856	1052

- b. Company wants to analyse payment frequency by month. Extract the month name from the payment date to count the total number of payments for each month and include only those months with a payment count exceeding 20. Sort the results by total number of payments in descending order. (**Refer Payments table**).

Expected output:

payment_month	num_payments
December	43
November	42
March	24
May	23
April	22

Q4. CONSTRAINTS: Primary, key, foreign key, Unique, check, not null, default

Create a new database named **Customers_Orders** and add the following tables as per the description

- a. Create a table named **Customers** to store customer information. Include the following columns:

customer_id: This should be an integer set as the PRIMARY KEY and AUTO_INCREMENT.

first_name: This should be a VARCHAR(50) to store the customer's first name.

last_name: This should be a VARCHAR(50) to store the customer's last name.

email: This should be a VARCHAR(255) set as UNIQUE to ensure no duplicate email addresses exist.

phone_number: This can be a VARCHAR(20) to allow for different phone number formats.

Add a NOT NULL constraint to the first_name and last_name columns to ensure they always have a value.

- b. Create a table named **Orders** to store information about customer orders. Include the following columns:

order_id: This should be an integer set as the PRIMARY KEY and AUTO_INCREMENT.

customer_id: This should be an integer referencing the customer_id in the Customers table (FOREIGN KEY).

order_date: This should be a DATE data type to store the order date.

total_amount: This should be a DECIMAL(10,2) to store the total order amount.

Constraints:

- Set a FOREIGN KEY constraint on customer_id to reference the Customers table.
- Add a CHECK constraint to ensure the total_amount is always a positive value.

Q5. JOINS

- a. List the top 5 countries (by order count) that Classic Models ships to. (Use the Customers and Orders tables)

Expected output:

	country	order_count
▶	USA	112
	France	37
	Spain	36
	Australia	19
	New Zealand	15

Q6. SELF JOIN

- a. Create a table **project** with below fields.

- EmployeeID : integer set as the PRIMARY KEY and AUTO_INCREMENT.
- FullName: varchar(50) with no null values
- Gender : Values should be only 'Male' or 'Female'
- ManagerID: integer

Add below data into it.

	EmployeeID	FullName	Gender	ManagerID
▶	1	Pranaya	Male	3
	2	Priyanka	Female	1
	3	Preety	Female	NULL
	4	Anurag	Male	1
	5	Sambit	Male	1
	6	Rajesh	Male	3
	7	Hina	Female	3

Find out the names of employees and their related managers.

Expected output:

Manager Name	Emp Name
Pranaya	Priyanka
Pranaya	Anurag
Pranaya	Sambit
Preety	Pranaya
Preety	Rajesh
Preety	Hina

Q7. DDL Commands: Create, Alter, Rename

a. Create table facility. Add the below fields into it.

- Facility_ID
- Name
- State
- Country

i) Alter the table by adding the primary key and auto increment to Facility_ID column.

ii) Add a new column city after name with data type as varchar which should not accept any null values.

Field	Type	Null	Key	Default	Extra
Facility ID	int	NO	PRI	NULL	auto increment
Name	varchar(100)	YES		NULL	
City	varchar(100)	NO		NULL	
State	varchar(100)	YES		NULL	
Country	varchar(100)	YES		NULL	

Q8. Views in SQL

a. Create a view named `product_category_sales` that provides insights into sales performance by product category. This view should include the following information:

productLine: The category name of the product (from the ProductLines table).

total_sales: The total revenue generated by products within that category (calculated by summing the `orderDetails.quantity * orderDetails.priceEach` for each product in the category).

number_of_orders: The total number of orders containing products from that category.

(Hint: Tables to be used: Products, orders, orderdetails and productlines)

The view when read should show the output as:

	productLine	total_sales	number_of_orders
▶	Classic Cars	3853922.49	209
	Motorcycles	1121426.12	79
	Planes	954637.54	66
	Ships	663998.34	68
	Trains	188532.92	47
	Trucks and Buses	1024113.57	75
	Vintage Cars	1797559.63	187

Q9. Stored Procedures in SQL with parameters

a. Create a stored procedure `Get_country_payments` which takes in year and country as inputs and gives year wise, country wise total amount as an output. Format the total amount to nearest thousand unit (K)

Tables: Customers, Payments

Expected output:

Year	country	Total Amount
2003	France	283K

Q10. Window functions - Rank, dense_rank, lead and lag

a) Using customers and orders tables, rank the customers based on their order frequency

	customerName	Order_count	order_frequency_rnk
►	Euro + Shopping Channel	26	1
	Mini Gifts Distributors Ltd.	17	2
	Australian Collectors, Co.	5	3
	Reims Collectables	5	3
	Danish Wholesale Imports	5	3
	Dragon Souvenirs, Ltd.	5	3
	Down Under Souvenirs, Inc	5	3
	Royale Belge	4	4
	Anna's Decorations, Ltd	4	4

b) Calculate year wise, month name wise count of orders and year over year (YoY) percentage change. Format the YoY values in no decimals and show in % sign.

Table: Orders

Expected output:

Year	Month	Total Orders	% YoY Change
2003	January	5	NULL
2003	February	3	-40%
2003	March	6	100%
2003	April	7	17%
2003	May	6	-14%
2003	June	7	17%
2003	July	7	0%
2003	August	5	-29%
2003	September	8	60%
2003	October	18	125%
2003	November	30	67%
2003	December	9	-70%
2004	January	8	-11%
2004	February	11	38%

Q11.Subqueries and their applications

a. Find out how many product lines are there for which the buy price value is greater than the average of buy price value. Show the output as product line and its count.

Expected output:

productLine	Total
Classic Cars	24
Vintage Cars	10
Trucks and Buses	7
Motorcycles	6
Planes	5
Ships	1
Trains	1

Q12. ERROR HANDLING in SQL

Create the table Emp_EH. Below are its fields.

- EmpID (Primary Key)
- EmpName
- EmailAddress

Create a procedure to accept the values for the columns in Emp_EH. Handle the error using exception handling concept. Show the message as “Error occurred” in case of anything wrong.

Q13. TRIGGERS

Create the table Emp_BIT. Add below fields in it.

- Name
- Occupation
- Working_date
- Working_hours

Insert the data as shown in below query.

```
INSERT INTO Emp_BIT VALUES
('Robin', 'Scientist', '2020-10-04', 12),
('Warner', 'Engineer', '2020-10-04', 10),
('Peter', 'Actor', '2020-10-04', 13),
('Marco', 'Doctor', '2020-10-04', 14),
('Brayden', 'Teacher', '2020-10-04', 12),
('Antonio', 'Business', '2020-10-04', 11);
```

Create before insert trigger to make sure any new value of Working_hours, if it is negative, then it should be inserted as positive.

