

DMS-DR-1079
APRIL, 1971

REVISION A
JULY 1971

— SPACE SHUTTLE —



**STATIC AERODYNAMIC CHARACTERISTICS
OF THE BOEING SPACE SHUTTLE
BOOSTER CONFIGURATION AT MACH
0.10 TO 0.29**

By

Jacque Houser



UNIVERSITY OF WASHINGTON

LOW SPEED WIND TUNNEL

SADSAC SPACE SHUTTLE
AEROTHERMODYNAMIC
DATA MANAGEMENT SYSTEM

CONTRACT NAS8-4016
MARSHALL SPACE FLIGHT CENTER

SPACE DIVISION  CHRYSLER
CORPORATION

FACILITY FORM 602

Reproduced by
**NATIONAL TECHNICAL
INFORMATION SERVICE**
U S Department of Commerce
Springfield VA 22151

N71-37498
(ACCESSION NUMBER)
193
(PAGES)
Col-119964
(NASA CR OR TMX OR AD NUMBER)

63
(THRU)
31
(CODE)
31
(CATEGORY)

DMS-DR-1079
REVISION A
JULY, 1971

SADSAC/SPACE SHUTTLE

WIND TUNNEL TEST DATA REPORT

CONFIGURATION: BOEING 0.02992 SCALE BOOSTER

TEST PURPOSE: TO OBTAIN LOW SPEED PERFORMANCE, STABILITY AND
CONTROL DATA

TEST FACILITY: UNIVERSITY OF WASHINGTON LOW SPEED TUNNEL

TESTING AGENCY: BOEING CO.

TEST NO. & DATE: UWAL 1021, JANUARY, 1971

TEST CONDUCTOR(S): JACQUE HOUSER - 206-773-2072

DATA MANAGEMENT SERVICES

LIAISON: John C. Vangrove DATA OPERATIONS: James R. Zeller
RELEASE APPROVAL: N. D. Kemp
N. D. Kemp, Supervisor
Aero Thermo Data Group

This report has been prepared by Chrysler Corporation Space Division under a Data Management Contract to the NASA. Chrysler assumes no responsibility for the data presented herein other than its display characteristics.

TABLE OF CONTENTS

	<u>PAGE NUMBER</u>
ABSTRACT	2
LIST OF FIGURES	3
LIST OF TABLES	4
SUMMARY	5
AXIS SYSTEMS	6
SUMMARY OF SADSAC NOMENCLATURE	7
CONFIGURATIONS INVESTIGATED	8
DATA SET COLLATIONS	9
TEST FACILITY DESCRIPTION	12
TEST CONDITIONS	13
DATA REDUCTION	15
SUMMARY PLOT INDEX	16
MODEL SKETCHES AND PHOTOGRAPHS	20
MODEL COMPONENT DESCRIPTIONS	36
STANDARD NOMENCLATURE	46
TABULAR DATA AVAILABILITY DATA PLOTS	55
DATA	56

ABSTRACT

Experimental aerodynamic investigations have been conducted in the University of Washington Aeronautical Laboratory Low Speed Wind Tunnel on a Boeing Space Shuttle Booster Configuration. Test were conducted on a 0.02992 scale model vehicle during late January, 1971, over an angle of attack range from -8° to $+32^\circ$ and from -10° to 10° sideslip at Mach numbers below 0.29. Tests variables included configuration build-up, elevator deflections of $\pm 30^\circ$, flap 15° and 40° , and stabilizer deflections of $+10^\circ$ and -20° .

LIST OF FIGURES

<u>FIGURE NUMBER</u>	<u>TITLE</u>	<u>PAGE NUMBER</u>
1	Axis Systems	6
2	Three View Assembly Drawing AX 1193E-2	21
3	Assembly Plan View, Configuration $B_1W_1V_1H_1N_1S_1 + F_1$	22
4	Assembly Side View, Configuration $B_1W_1V_1H_1N_1$	23
5	Body - B_1	24
6	Wings - W_1, W_2	25
7	Horizontal Tail - H_1	26
8	Horizontal Tail - H_2	27
9	Vertical Tail - V_1	28
10	Engine Pod - N_1	29
11	Flow-through Engine Pod - N_2	30
12	Simulated Fowler Flap - F_1	31
13	Model Installed on UWAL Single Strut	32
14	Rear View of Model - Configuration $B_1W_1H_1V_1N_1$	33
15	3/4 - Rear View of Model Showing Flap Deflection- Configuration $B_1W_1H_1V_1N_1 + F_1^{D0}$	34
16	Rear View of Model Showing Flow-through Nacelles and Enlarged Horizontal Tail - Configuration $B_1W_2H_2V_1N_2$	35

LIST OF TABLES

<u>TABLE NUMBER</u>	<u>TITLE</u>	<u>PAGE NUMBER</u>
I	Test Conditions	14

SUMMARY

An investigation was conducted in the University of Washington Aeronautical Laboratory Low Speed Wind Tunnel to determine the static longitudinal and lateral aerodynamic characteristics of a Boeing Space Shuttle Booster Configuration. Tests were conducted on a 0.02992 scale model of the vehicle configuration during January, 1971, over an angle of attack range from -8° to 32° and from -10° to $+10^{\circ}$ sideslip at Mach numbers below 0.29. Test variables included configuration buildup, elevator deflections of $\pm 30^{\circ}$, stabilizer deflections of $+10^{\circ}$ to -20° , and flap of 15° and 40° . Also tested were combinations of varying wing, horizontal stabilizer, and engine nacelle configurations.

Notes:

1. Positive directions of force coefficients moment coefficients, and angles are indicated by arrows.
2. For clarity, origins of wind and stability axes have been displaced from the center of gravity.




Figure 1. Axis systems, showing direction and sense of force and moment coefficients, angle of attack, and sideslip angle

COEFFICIENT	COEFFICIENT NAME	SADSAC NOMENCLATURE		
		BODY AXIS	STABILITY AXIS	WIND AXIS
C _A	Total Axial Force	CA	-	-
C _{AB}	Base Axial Force	CAB	--	-
C _{AF}	Forebody Axial Force	CAF	-	-
C _D	Total Drag Force	-	CD	CDTTL
C _{DB}	Base Drag Force	-	CDB	CDBASE
C _{DF}	Forebody Drag Force	-	CDF	CDFORE
C _L	Lift Force	-	CL	CL
C _N	Normal Force	CN	-	-
C _Y	Side Force	CY	CY	CC
C _l	Rolling Moment	CBL	CSL	CWL
C _m	Pitching Moment	CLM	CLM	CPM
C _n	Yawing Moment	CYN	CLN	CLN
L/D	Lift-To-Drag Force Ratio	-	L/D	CL/CD
L/D	Lift-To-Forebody Drag Force Ratio	-	L/DF	CL/CDF
N/A	Normal-To-Axial Force Ratio	N/A	-	-
N/A	Normal-To-Forebody Axial Force Ratio	CN/CAF	-	-

SUMMARY OF SADSAC NOMENCLATURE - AERODYNAMIC FORCE AND MOMENT COEFFICIENTS

CONFIGURATIONS INVESTIGATED.

Configuration Nomenclature

B₁ - Body
W₁, W₂ - Wing with ailerons
H₁, H₂ - Horizontal stabilizer with elevator
V₁ - Vertical tail with rudder
N₁ - Engine pack/N₂ - Engine pack with flow-through engines
F₁ - Simulated Fowler flap
S₁ - Spoiler

Dimensional data for these components are given on the configuration descriptor forms which follow.

Configuration Combinations Tested

B ₁	B ₁ W ₁ H ₁ N ₁	B ₁ W ₂ H ₁ V ₁
B ₁ N ₁	B ₁ W ₁ H ₁ V ₁	B ₁ W ₂ H ₁ V ₁ N ₂
B ₁ W ₁ N ₁	B ₁ W ₁ H ₁ V ₁ N ₁	B ₁ W ₂ H ₁ V ₁ N ₁
B ₁ H ₁ N ₁	B ₁ W ₁ H ₁ V ₁ N ₁ F ₁	B ₁ W ₂ N ₁
B ₁ V ₁ N ₁	B ₁ W ₂ H ₂ V ₁	B ₁ W ₂
B ₁ W ₁ V ₁ N ₁	B ₁ W ₂ H ₂ V ₁ N ₂	

The above configurations were tested with the following surface deflection angles where appropriate:

Aileron	0°
Stabilizer	-20°, 0°, 10°
Elevator	-30°, 0°, 30°
Rudder	0°
Flap	15°, 40°

TEST UWAL-1021 DATA SET COLLATION SHEET

SHEET 1 of 3

PRETEST

POST TEST

DATA SET IDENTIFIER	CONFIGURATION	SCHD.	PARAMETERS/VALUES				NO. OF RUNS	MACH NUMBERS (OR ALTERNATE INDEPENDENT VARIABLE)					
			α	β	S_d	S_s	S_e	S_r	0.10	0.15	0.26	0.29	
RU1011	B1	A	0°	-	-	-	-	-	005				
016	B1	0°	C	-	-	-	-	-	4				
026	B,N,	0°	C	-	-	-	-	-	7				
021	B,N,	A	0°	-	-	-	-	-	6				
031	B,W,N,	A	0°	0°	-	-	-	-	12				
041	B,H,N,	A	0°	-	0°	0°	-	-	8				
051	B,V,N,	A	0°	-	-	-	0°	-	9				
056	B,V,N,	0°	C	-	-	-	0°	-	10				
061	B,W,V,N,	A	0°	0°	-	-	0°	-	13				
076	B,W,H,N,	0°	C	0°	0°	0°	0°	-	15				
071	B,W,H,N,	A	0°	0°	0°	0°	0°	-	14				
081	B,W,H,V,	A	0°	0°	0°	0°	0°	0°	17				
086	B,W,H,V,	0°	C	-	-	-	-	-	16				
091	B,W,H,V,N,	A	0°	-	-	-	-	-	18				
A91		A	0°	-	-	-	-	-	20				
095		B	0°	-	-	-	-	-	22				
A95		B	0°	-	-	-	-	-	21				
093		A	-1°	-	-	-	-	-	23				
09A		0°	D	-	-	-	-	-	24				
V 097	V	10°	C	V	V	V	V	V	25				

1 7 13 19 25 31 37 43 49 55 61 67 7576

CL CD CLM CLN CY CSL CDB

COEFFICIENTS:

a or β A) $-8^\circ \rightarrow 32^\circ, \Delta\alpha = 2^\circ$

SCHEDULES B) $-8^\circ \rightarrow 14^\circ, \Delta\alpha = 2^\circ$

C) $-4^\circ \rightarrow 10^\circ, \Delta\beta = 2^\circ$

D) $-10^\circ \rightarrow 10^\circ, \Delta\beta = 2^\circ$

IDPVAR(1) IDPVAR(2) NDV

NASA-MSFC-MAF

TEST UWAL-1021 DATA SET COLLATION SHEET

SHEET 2 of 3

PRETEST
 POSTTEST

DATA SET IDENTIFIER	CONFIGURATION	SCHD.	PARAMETERS/VALUES					NO. of RUNS	MACH NUMBERS (OR ALTERNATE INDEPENDENT VARIABLE)				
			α	β	S_B	S_S	S_C	S_R	0.10	0.15	0.26	0.29	
RU1098	<u>B,W,H,V,N,</u>	20	C	0°	0°	0°	0°	0°		26			
099	<u>B,W,H,V,N,</u>	32	C	0°	0°	0°	0°	0°		27			
101	<u>B,W,H,V,N,F¹⁵</u>	A	0°							42			
104	<u>B,W,H,V,N,F¹⁵</u>	A	-10°							41			
141	<u>B,W,H,V,N,F⁴⁰</u>	A	0°							38			
142			-4°							39			
144			-10°							40			
151			0°		-20°					29			
171					10°					37			
181	<u>B,W,H,V,N,</u>				-20°					28			
201					10°					36			
211					0°	-30°				44			
241					0°	30°				43			
291	<u>B,W,H,V,N,F⁴⁰</u>				-20°	-30°				30			
321					-20°	30°				31			
331	<u>B,W,H,V,N,</u>				-20°	30°				32			
341					10°	30°				35			
351					10°	-30°				34			
361					V	V				33			

1	7	13	19	25	31	37	43	49	55	61	67	75 76
CL	CD	CLM	CLN	CY	CSL	COB						

COEFFICIENTS:

 α or β : A) $-8^\circ \rightarrow 32^\circ, \Delta\alpha = 2^\circ$ B) $-8^\circ \rightarrow 10^\circ, \Delta\alpha = 2^\circ$ C) $-4^\circ \rightarrow 10^\circ, \Delta\beta = 2^\circ$ D) $-10^\circ \rightarrow 10^\circ, \Delta\beta = 2^\circ$

IDPVAR(1) IDPVAR(2) NDV

NASA-MSFC-MAF

TEST UWAL-1021 DATA SET COLLATION SHEET

SHEET 3 / 3

PRETEST

POSTTEST

DATA SET IDENTIFIER	CONFIGURATION	SCHD.	PARAMETERS / VALUES					NO. OF RUNS	MACH NUMBERS (OR ALTERNATE INDEPENDENT VARIABLE)			
			α	B	S_d	S_s	S_e		0.10	0.15	0.26	0.29
RUI451	B, W_2, H_2, V_1	A	0°	0°	0°	0°	0°		45	-	-	-
461	B, W_2, H_2, V, N_2								46	-	-	-
471	B, W_2, H, V, N_2								48	-	-	-
481	B, W_2, H, V_1								47	-	-	-
491	B, W_2, H, V_1, N_1					↓	↓	↓	49	-	-	-
501	B, W_2, N_1					—	—	—	50	-	-	-
511	B, W_2		↓	↑	↓	—	—	—	51	-	-	-

1 7 13 19 25 31' 37 43 49 55 61 67 75 76
CL CD CLM CLN CY CSL CDB

COEFFICIENTS:

α or β

SCHEDULES

$$A) -8^\circ \rightarrow 32^\circ \quad A\alpha = 2^\circ$$

$$\text{c)} -8^\circ \rightarrow 14^\circ \quad \Delta x = 2^\circ$$

$$\text{c) } -4^\circ \rightarrow 10^\circ, \Delta\beta = 2^\circ$$

$$D) = 10^\circ \rightarrow (10^\circ, 4\beta^3 \approx 2^\circ)$$

→ IDPVAR(1) IDPVAR(2) NDV

FACILITY DESCRIPTION

The F. K. Kirsten 8' x 12' wind tunnel of the University of Washington Aeronautical Laboratory (UWAL) is a double return closed circuit wind tunnel. The test section is 8 feet high and 12 feet wide with corner fillets 1 1/2 feet on the side. The test section is vented to the atmosphere at the test section - diffuser junction. A maximum velocity of 250 mph is attained through two 500 H.P. D.C. drive motors; one located in each return leg of the circuit.

The normal mode of mounting force models is on a single strut up through the test section floor from an external, six-component virtual-center balance. Balance output is normally digitized and punched in cards in a format compatible with the University of Washington IBM 709 computer. The total range of angles in the pitch mode is approximately 40°. The range of angles in the yaw mode is ±30°.

TEST CONDITIONS

Data were recorded under conditions as described in Table I, which also gives an estimate of the data accuracy.

The model was single strut mounted on the UWAL external balance using the UWAL single strut and pitch arm #2 and the UWAL #3 wind shield. In order to assure a turbulent boundary layer, on all runs #80 grit was applied at a density of 80-100 grains/inch at the following locations.

Body	- Fus. Sta. 8 1/10 inch wide strip
Wing	- both surfaces at 10% chord, 1/10 inch wide strip
Vertical and Horizontal Tails	- both surfaces @ 10% chord, 1/10 inch strip

TABLE I
TEST CONDITIONS

BALANCE UTILIZED: UWAL External 6-Component

CAPACITY:

ACCURACY:

**COEFFICIENT
TOLERANCE:**

L	<input checked="" type="checkbox"/>	2500	lb.
SF	<input type="checkbox"/>	250	lb.
D	<input checked="" type="checkbox"/>	250	lb
PM	<input type="checkbox"/>	5000	in-lb
YM	<input type="checkbox"/>	5000	in-lb
RM	<input type="checkbox"/>	5000	in-lb

1.0 lb.
0.1 lb.
0.1 lb.
1.0 in-lb
1.0 in-lb
1.0 in-lb

• 0,25 %	of $C_{L\max}$
• 1 %	of $C_{r\max}$
• 0,05 %	of $C_{D\max}$
• 0,05 %	of $C_{m\max}$
• 0,025 %	of $C_{n\max}$
• 0,01 %	of $C_{e\max}$

COMMENTS: * Minimum Readable Value

DATA REDUCTION

The six component force and moment data were recorded using an external six-component virtual-center balance. The force and moments have been reduced to coefficient form in stability axis system utilizing the following reference values.

$$S_{REF} = \text{wing planform area} = 4.42 \text{ ft}^2$$

$$b = \text{wing span} = 66.60 \text{ inches}$$

$$l_{REF} = \bar{c} = \text{wing mean aerodynamic chord} = 10.1 \text{ inches}$$

Moments are referenced about a center of gravity location which is at fuselage station 55.636 buttock line 0.0, and water line 5.86 inches (see Figure 4).

Additionally, static pressures were recorded at (9) positions on the body base and were averaged to obtain a base drag coefficient.

$$C_{D_b} = \left\{ \frac{p_\infty - \frac{(p_1 + p_2 + \dots + p_9)}{9}}{q} \right\} \left\{ A_b / S_{REF} \right\} \cos \alpha$$

$$\text{where } A_b = 117.5 \text{ in}^2$$

The data have been corrected for low speed wall effects by the methods given in UWAL Report WC 111-A, and for solid and wake blockage effects by methods according to Boeing memo G-8354-14.

SUMMARY PLOT INDEX

PLOT TITLE	PLOTTED COEFFICIENTS SCHEDULE	CONDITIONS VARYING	MACH NUMBER	α SCHEDULE	β SCHEDULE	PAGES
Configuration Buildup	A	Configuration	.153	-8°- 32°	0°	1-10
Configuration Buildup	B	Configuration	.153	-8°- 32°	0°	11-12
Configuration Buildup	C	Configuration	.153	-8°- 32°	0°	13-14
Effect of Reynolds Number	A	Reynolds Number	.101-.285	-8°- 32°	0°	15-19
Effect of Reynolds Number	B	Reynolds Number	.101-.285	-8°- 32°	0°	20
Effect of Reynolds Number	C	Reynolds Number	.101-.285	-8°- 32°	0°	21
Effect of Sideslip	D	Sideslip Angle	.154	-8°- 32°	0°/-10°	22-29
Effect of Sideslip	B	Sideslip Angle	.154	-8°- 32°	0°/-10°	30
Effect of Sideslip	C	Sideslip Angle	.154	-8°- 32°	0°/-10°	31
Flap Effectiveness Beta = 0°	A	Flap Angle	.154	-8°- 32°	0°	32-36
Flap Effectiveness Beta = 0°	B	Flap Angle	.154	-8°- 32°	0°	37
Flap Effectiveness Beta = 0°	C	Flap Angle	.154	-8°- 32°	0°	38
Flap Effectiveness Beta = -4°	D	Flap Angle	.154	-8°- 32°	-4°	39-46
Flap Effectiveness Beta = -4°	B	Flap Angle	.154	-8°- 32°	-4°	47
Flap Effectiveness Beta = -4°	C	Flap Angle	.154	-8°- 32°	-4°	48
Flap Effectiveness Beta = -10°	D	Flap Angle	.154	-8°- 32°	-10°	49-56
Flap Effectiveness Beta = -10°	B	Flap Angle	.154	-8°- 32°	-10°	57
Flap Effectiveness Beta = -10°	C	Flap Angle	.154	-8°- 32°	-10°	58

SUMMARY PLOT INDEX
(Continued)

PLOT TITLE	PLOTTED COEFFICIENTS SCHEDULE	CONDITIONS VARYING	MACH NUMBER	SCHEDULE	SCHEDULE	PAGES
Stabilizer Effectiveness, Flaps Up	A	Horizontal Stabili- zer	.154	-8°- 32°	0°	59-63
Stabilizer Effectiveness Flaps Up	B	Horizontal Stabili- zer	.154	-8°- 32°	0°	64
Stabilizer Effectiveness Flaps Up	C	Horizontal Stabili- zer	.154	-8°- 32°	0°	65
Stabilizer Effectiveness Flap = 40	A	Horizontal Stabili- zer	.154	-8°- 32°	0°	66-70
Stabilizer Effectiveness Flap = 40	B	Horizontal Stabili- zer	.154	-8°- 32°	0°	71
Stabilizer Effectiveness Flap = 40	C	Horizontal Stabili- zer	.154	-8°- 32°	0°	72
Elevator Effectiveness, Flaps Up, Horizontal Tail = 0	A	Elevator Deflection Angle	.154	-8°- 32°	0°	73-77
Elevator Effectiveness, Flaps Up, Horizontal Tail = 0	B	Elevator Deflection Angle	.154	-8°- 32°	0°	78
Elevator Effectiveness, Flaps Up, Horizontal Tail = 0	C	Elevator Deflection Angle	.154	-8°- 32°	0°	79
Elevator Effectiveness, Flaps Up, Horizontal Tail = -20	A	Elevator Deflection Angle	.154	-8°- 32°	0°	80-84
Elevator Effectiveness, Flaps Up, Horizontal Tail = -20	B	Elevator Deflection Angle	.154	-8°- 32°	0°	85
Elevator Effectiveness, Flaps Up, Horizontal Tail = -20	C	Elevator Deflection Angle	.154	-8°- 32°	0°	86

SUMMARY PLOT INDEX
(Continued)

PLOT TITLE	PLOTTED COEFFICIENTS		CONDITIONS VARYING	NUMBER	α SCHEDULE	β SCHEDULE	PAGES
	SCHEDULE						
Elevator Effectiveness, Flaps Up, Horizontal Tail = 10	A		Elevator Deflection	.154	-8° - 32°	0°	87-91
Elevator Effectiveness, Flaps Up, Horizontal Tail = 10	B		Elevator Deflection Angle	.154	-8° - 32°	0°	92
Elevator Effectiveness, Flaps Up, Horizontal Tail = 10	C		Elevator Deflection Angle	.154	-8° - 32°	0°	93
Elevator Effectiveness, Flap = 40, Horizontal Tail = -20	A		Elevator Deflection Angle	.154	-8° - 32°	0°	94-98
Elevator Effectiveness, Flap = 40, Horizontal Tail = -20	B		Elevator Deflection Angle	.154	-8° - 32°	0°	99
Elevator Effectiveness, Flap = 40, Horizontal Tail = -20	C		Elevator Deflection Angle	.154	-8° - 32°	0°	100
Effect of Aft Wing and Large Stabilizer	A		Configuration	.153-	-8° - 32°	0°	101-105
Effect of Aft Wing and Large Stabilizer	B		Configuration	.153	-8° - 32°	0°	106
Effect of Aft Wing and Large Stabilizer	C		Configuration	.153	-8° - 32°	0°	107
Effect of Nacelles and Aft Wing	A		Configuration	.154	-8° - 32°	0°	108-112
Effect of Nacelles and Aft Wing	B		Configuration	.154	-8° - 32°	0°	113

SUMMARY PLOT INDEX
(Continued)


PLOT TITLE	PLOTTED COEFFICIENTS SCHEDULE	CONDITIONS VARYING	MACH NUMBER	α SCHEDULE	β SCHEDULE	PAGES
Effect of Nacelles and Aft Wing	C	Configuration	.154	-8° - 32°	0°	114
Effect of Nacelles and Aft Wing - Tail Off	A	Configuration	.154	-8° - 32°	0°	115-119
Effect of Nacelles and Aft Wing - Tail Off	B	Configuration	.154	-8° - 32°	0°	120
Effect of Nacelles and Aft Wing - Tail Off	C	Configuration	.154	-8° - 32°	0°	121
Configuration Buildup In Yaw	E	Configuration	.153	0°	-10° - 10°	122-128
Configuration Buildup In Yaw	F	Configuration	.153	0°	-10° - 10°	129
Combined Pitch and Yaw	E	Angle of Attack	.154	0° - 32°	-10° - 10°	130-136
Combined Pitch and Yaw	F	Angle of Attack	.154	0° - 32°	-10° - 10°	137

COEFFICIENT SCHEDULE


A CL vs. α	B CL vs. CD	C CL vs. CLM	D CL vs. α	E CY vs. β	F CY vs. CLN
CD vs. α			CD vs. α	CIN vs. β	
CIM vs. α			CIM vs. α	CSL vs. β	
L/D vs. α			CY vs. α	CL vs. β	
CDB vs. α			CIN vs. α	CIM vs. β	
			L/D vs. α	CDB vs. β	
			CDB vs. α		

MODEL SKETCHES AND PHOTOGRAPHS

AX 1193 E-Z
ASSEMBLY



PLAN VIEW



SIDE VIEW

AX 1193E-Z
(ASSEMBLY PLAN VIEW)




FIGURE 3. PLAN VIEW .B,₁W,V,H,N,S,₁+F₁

AX 1193 E-Z
ASSEMBLY







FIGURE 4. SIDE VIEW B,W,V;H,N_i

AX 1193E-2 BODY, B₁



SECTION
@ STA 24 283



REAR VIEW

FIGURE 5. Body B₁

A X 1193 E-Z , C₆ WING, W₂
 REF · Z9-4610Z




FIGURE 6. WING- W₁, W₂

AX 1193E-Z, HORIZ.TAIL H₁

REF: Z9-46103





FIGURE 7. HORIZONTAL TAIL, H₁

AX 1193E-2, HORIZ. TAIL H₂

REF DWG. Z9-46148



AX 1193E-Z VERTICAL TAIL, V₁
 REF: 1193-30






FIGURE 9. VERTICAL TAIL, V₁



N₁
FIGURE 10. ENGINE POD
REF DWG 1193-46



N₂
FIGURE 11. ENGINE POD
REF: DWG 1193-50

AX 1193E-2 FLAP PROFILE AND POSITIONS

REF: 1193-31




FIGURE 12. SIMULATED FOWLER FLAP, F_1





Figure 13 Model Installed on UWAL Single Strut



NOT REPRODUCIBLE

33

Figure 14 Rear View of Model - Configuration B₁W₁H₁V₁N₁




Figure 15 3/4- Rear View of Model Showing Flap Deflection
Configuration $B_1 W_1 H_1 V_1 N_1 + F_1^{40}$




Figure 16 Rear View of Model Showing Flow-through Nacelles and
Enlarged Horizontal Tail- Configuration $B_1 W_2 H_2 V_1 N_2$

MODEL COMPONENT DESCRIPTIONS

MODEL COMPONENT: BODY - B₁

GENERAL DESCRIPTION: A 0.02992 scale booster body
derived from the Model 979-107 Booster

DRAWING NUMBER:

29-44294 orig.
1193-43 modif.

DIMENSIONS:

	FULL-SCALE	MODEL SCALE
Length	2751 in	82.31 in
Max. Width	420 in	13.60 in
Max. Depth	400 in	13.43 in
Fineness Ratio	6.55	6.0
Area		
Max. Cross-Sectional		150.6 in ²
Planform		
Wetted		
Base	895.8 ft ²	117.5 in ²

MODEL COMPONENT: Wing-W₁ (W₂ is wing W₁, moved 2.06" aft (M.S.))

GENERAL DESCRIPTION: A 0.02992 scale Model 1979-107 wing

DRAWING NUMBER: Model: 29-46102
Full Scale: 164-10038

DIMENSIONS:

FULL-SCALE

MODEL SCALE

TOTAL DATA

Area		
Planform	<u>4938 ft²</u>	<u>4.42 ft²</u>
Wetted		
Span (equivalent)	<u>185.9 ft</u>	<u>66.6 -</u>
Aspect Ratio	<u>7.0</u>	<u>6.98</u>
Rate of Taper	<u>0.121</u>	<u>0.122</u>
Taper Ratio	<u>0.4</u>	<u>0.404</u>
Dihedral Angle, degrees	<u>5.0°</u>	<u>5.0°</u>
Incidence Angle, degrees	<u>4.0°</u>	<u>4.0°</u>
Aerodynamic Twist, degrees	<u>0°</u>	<u>0°</u>
Toe-In Angle	—	—
Cant Angle	—	—
Sweep Back Angles, degrees		
Leading Edge	<u>6°-54'</u>	<u>6°-57'</u>
Trailing Edge	<u>-6°-54'</u>	<u>-6°-57'</u>
0.25 Element Line	<u>30-271</u>	<u>30-271</u>
Chords:		
Root (Wing Sta. 0.0)	<u>455 in</u>	<u>13.613</u>
Tip, (equivalent)	<u>184 in</u>	<u>5.505</u>
MAC	<u>338 in</u>	<u>10.111</u>
Fus. Sta. of .25 MAC	<u>285.9 in</u>	<u>53.636</u>
W.P. of .25 MAC	<u>255</u>	<u>5.86</u>
B.L. of .25 MAC	<u>478</u>	<u>14.3</u>
Airfoil Section		
Root	<u>NACA 0015-64</u>	<u>NACA 0015-64</u>
Tip	<u>Same</u>	<u>Same</u>

EXPOSED DATA

Area		
Span, (equivalent)		
Aspect Ratio		
Taper Ratio		
Chords		
Root		
Tip		
MAC		
Fus. Sta. of .25 MAC		
W.P. of .25 MAC		
B.L. of .25 MAC		

* 57.70 for W₂

MODEL COMPONENT:

Horizontal Tail - H1

GENERAL DESCRIPTION: A 0.02992 scale Model 979-107
horizontal tail with movable elevator

DRAWING NUMBER:

Full scale BAC 164-10038

Model scale 29-46103

DIMENSIONS:

Area (exposed)

FULL-SCALE

MODEL SCALE

2164 ft²

139.38 in² ea. side

Span (equivalent)

128 ft

45.96 in

Inb'd equivalent chord

372 in.

11.130 QBL 6.283

Outb'd equivalent chord

186 in.

5.565 in

Ratio movable surface chord/
total surface chord

At Inb'd equiv. chord

0.234

0.232

At Outb'd equiv. chord

0.215

0.216

Sweep Back Angles, degrees

Leading Edge

27°-36'

28°1'

Tailing Edge

12°

11°-18'

Hingeline

15°-30'

15°-46'

Area Moment (Normal to hinge line)

elevator one side

615 ft³

28.4 in³

Angular travel

horiz tail

-20° to +10°

-20°-10°, 0°+10°

elevator

-30° to +30°

-30°,-15°, 0°, 15°, 30°

MODEL COMPONENT: Horizontal Tail - H₂

GENERAL DESCRIPTION: A 0.02992 scale horizontal tail
with fixed elevator

DRAWING NUMBER: Model Scale 29-46148

DIMENSIONS:

	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area (exposed)		<u>167.7 in² ea side</u>
Span (equivalent)		<u>48.66 in</u>
Inb'd equivalent chord		<u>12.04 @ BL 6.283</u>
Outb'd equivalent chord		<u>6.05</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord		<u>0.302</u>
At Outb'd equiv. chord		<u>0.278</u>
Sweep Back Angles, degrees		
Leading Edge		<u>28°-1'</u>
Tailing Edge		<u>9°-49'</u>
Hingeline		<u>15°-46'</u>
Area Moment (Normal to hinge line)		<u>64.3 in³</u>

MODEL COMPONENT: Vertical Tail - V₁

GENERAL DESCRIPTION: A 0.02992 scale Model 979-107 vertical tail with movable rudder

DRAWING NUMBER: BAC S.O. 1193-30 Model
BAK 164-1001Z Fullscale

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area	<u>1000 ft²</u>	<u>128.33 in²</u>
Span (equivalent)	<u>464 in</u>	<u>13.883 in.</u>
Aspect Ratio	<u>1.5</u>	<u>1.5</u>
Inb'd equivalent chord	<u>412 in</u>	<u>12.327 in</u>
Outb'd equivalent chord	<u>206 in</u>	<u>6.164 in.</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.324</u>	<u>0.324</u>
At Outb'd equiv. chord	<u>0.347</u>	<u>0.347</u>
Sweep Back Angles, degrees		
Leading Edge	<u>39° 40'</u>	<u>39° 41'</u>
Tailing Edge	<u>20° 27'</u>	<u>20° 27'</u>
Hingeline	<u>26° 50'</u>	<u>26° 51'</u>
Area Moment (Normal to hinge line) rudder	<u>1231.5 ft²</u>	<u>59.57 in²</u>
Airfoil Section		NACA 0015-64

MODEL COMPONENT: Fly-home Engine Pack - N

GENERAL DESCRIPTION: Right- and left-hand engine packs approximating configuration proposed for Model 979-107 booster.

DRAWING NUMBER: 1193-46

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Length	_____	<u>7.87 in.</u>
Max. Width	_____	<u>3.33 in.</u>
Max. Depth	_____	<u>5.38 in.</u>
Fineness Ratio	_____	<u>2.36</u>
Area		
Max. Cross-Sectional	_____	<u>16.6 in².</u>
Planform	_____	_____
Wetted	_____	_____
Base	_____	_____

MODEL COMPONENT: Fly-home Engine Pack - N2

GENERAL DESCRIPTION: Right- and left-hand engine packs
with six flow-through simulated engines each.

DRAWING NUMBER: 1193-50

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Length	<u>5.80 in</u>
Max. Width	<u>3.33 in</u>
Max. Depth	<u>5.38 in</u>
Fineness Ratio	<u>1.74</u>
Area		
Max. Cross-Sectional	<u>16.6 in²</u>
Planform
Wetted
Base	<u>5.2 in²</u>
Engine Diameter		
Inboard (3)	<u>1.0 in</u>
Outboard (3)	<u>1.25 in</u>

MODEL COMPONENT: Wing Flaps - F.

GENERAL DESCRIPTION: 0.02992 scale flaps simulating constant chord Fowler flaps on the Model 979-107 booster.

Model BAC S.O. 1193-31
Full scale BAC 164-10038

DIMENSIONS:

	FULL-SCALE	MODEL SCALE
Area	<u>256.25 ft²</u>	<u>33.25 in²</u>
Span (equivalent)	<u>51.25 ft</u>	<u>18.47 in.</u>
Inb'd equivalent chord	<u>60 in</u>	<u>1.8 in</u>
Outb'd equivalent chord	<u>60 in</u>	<u>1.8 in.</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.15</u>	<u>0.15</u>
At Outb'd equiv. chord	<u>0.22</u>	<u>0.22</u>
Sweep Back Angles, degrees		
Leading Edge	<u>6° 51'</u>	<u>6° 57'</u>
Tailing Edge	<u>6° 51'</u>	<u>6° 57'</u>
Hingeline	<u>6° 57'</u>	<u>6° 57'</u>
Area Moment (Normal to hinge line) about leading edge	<u>610.63 ft³</u>	<u>29.92 in³</u>

MODEL COMPONENT:

Spoilers - 5.

GENERAL DESCRIPTION:

0.02992 scale two-position spoilers
simulating the Model 979-107 booster spoilers.
Positions of 45° and 80° available

DRAWING NUMBER:

BAC SD 1193-28 model

DIMENSIONS:

	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area (each side)	<u>123.26 ft²</u>	<u>15.9 in.²</u>
Span (equivalent) each side	<u>41.67 ft</u>	<u>14.93 in.</u>
Inb'd equivalent chord	<u>44 in.</u>	<u>1.32 in.</u>
Outb'd equivalent chord	<u>27 in.</u>	<u>0.81 in.</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.13</u>	<u>0.13</u>
At Outb'd equiv. chord	<u>0.127</u>	<u>0.127</u>
Sweep Back Angles, degrees		
Leading Edge	<u>5.5°</u>	<u>5.5°</u>
Tailing Edge	<u>3.33°</u>	<u>3.33°</u>
Hingeline	<u>6.5°</u>	<u>5.5°</u>
Area Moment (Normal to hinge line) about L.E.	<u>195.16 ft³</u>	<u>8.93 in.³</u>

STANDARD NOMENCLATURE

NOMENCLATURE

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
A_b		base area; m^2 , ft^2 , in^2
a		speed of sound; m/sec , ft/sec
AR	ASPECT	aspect ratio, b^2/S
b	REFB	wing span or reference span; m , ft , in
c		wing chord; m , ft , in
\bar{c}		wing mean aerodynamic chord or reference chord; m , ft , in (see ℓ_{ref} or refl)
c.g.		center of gravity
C. P.		center of pressure
C_A	CA	axial force coefficient, F_A/qS_{ref}
C_{A_b}	CAB	base axial force coefficient, $[(p_\infty - p_b)/q] (A_b/S_{\text{ref}})$
C_{A_f}	CAF	forebody axial force coefficient, $C_A - C_{A_b}$
C_D	CDTTL	drag force coefficient in the wind axis system, $F_D/q S_{\text{ref}}$

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
C_D	CD	drag force coefficient in the stability axis system, $F_D/q S_{ref}$
C_L	CL	lift force coefficient (stability or wind axis) $F_L/q S_{ref}$
C_l	CBL	rolling moment coefficient in body axis system, $M_x/q S_{ref} b$
$C_{l,s}$	CSL	rolling moment coefficient in the stability axis system, $M_{x,s}/q S_{ref} b$
$C_{l,w}$	CWL	rolling moment coefficient in the wind axis system, $M_{x,w}/q S_{ref} b$
C_m	CLM	pitching moment coefficient in the body axis system, $M_y/q S_{ref} \ell_{ref}$
$C_{m,s}$	CLM	pitching moment coefficient in the stability axis system, $C_{m,s} = C_m$
$C_{m,w}$	CPM	pitching moment coefficient in the wind axis system, $M_{y,w}/q S_{ref} \ell_{ref}$
C_N	CN	normal force coefficient in the body axis system, $F_N/q S_{ref}$

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
C_n	CYN	yawing moment coefficient in the body axis system, $M_z/q S_{ref} b$
$C_{n,s}$	CLN	yawing moment coefficient in the stability axis system, $C_{n,s} = C_{n,w}$
$C_{n,w}$	CLN	yawing moment coefficient in the wind axis system, $M_{z,w}/q S_{ref} b$
C_p	CP	pressure coefficient, $(p-p_\infty)/q$
C_y	CY	side force coefficient (body or stability axis system), $F_y/q S_{ref}$
C_c	CC	side force coefficient (wind axis system), $F_y/q S_{ref}$
F_A		axial force; N, lb
F_D		drag force in wind axis system; N, lb
F'_D		drag force in the stability axis system; N, lb
F_L		lift force (stability or wind axis system); N, lb
F_N		normal force; N, lb

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
F_Y		side force; N, lb
	N/A	normal to axial force ratio
l_{ref}	REFL	reference length; m, ft, in (see \bar{c})
L/D	L/D	lift-to-drag ratio, C_L/C_D (stability axis system)
L/D	CL/CD	lift-to-drag ratio, C_L/C_D (wind axis system)
M	MACH	Mach number
MRP	MRP	abbreviation for moment reference point
	XMRP	abbreviation for moment reference point on x-axis
	YMRP	abbreviation for moment reference point on y-axis
	ZMRP	abbreviation for moment reference point on z-axis
M_x		rolling moment in the body axis system; N-m, ft-lb
$M_{x,s}$		rolling moment in the stability axis system; N-m, ft-lb

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
$M_{x,w}$		rolling moment in the wind axis system; N-m, ft-lb
M_y		pitching moment in the body (or stability) axis system; N-m, ft-lb
$M_{y,w}$		pitching moment in the wind axis system; N-m, ft-lb
M_z		yawing moment in the body axis system; N-m, ft-lb
$M_{z,w}$		yawing moment in the wind axis system; N-m, ft-lb
p		static pressure; N/m ² ; psi
P		total pressure; N/m ² ; psi
q	Q(PSI) Q(PSF)	dynamic pressure; N/m ² , psi, psf
RN/L	RN/L	Reynold's number per unit length; million/ft.
s		wing area; m ² , ft ²
S_{ref}	REFS	reference area; m ² , ft ²
T		temperature; °K, °C, °R, °F
v		speed of vehicle relative to surrounding atmosphere; m/sec, ft/sec

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
i_T		tail incidence positive when trailing edge down, deg
\bar{V}		velocity of vehicle relative to surrounding atmosphere; m/sec, ft/sec
α	ALPHA	angle of attack, angle between the projection of the wind X_w -axis on the body X, Z-plane and the body X-axis; deg
β	BETA	sideslip angle, angle between the wind X_w -axis and the projection of this axis on the body X-Z-plane; deg
γ		ratio of specific heats
Γ	DIHDRL	wing dihedral angle; deg
δ		control surface deflection angle; deg positive deflections are: AILRON - left aileron trailing edge down ELEVTR - trailing edge down RUDDER - trailing edge to the left FLAP - trailing edge down TAB - trailing edge down with respect to control surface
AIRRON		air density; K_g/m^3 , slugs/ft ³
ELEVTR		
RUDDER		
FLAP		
TAB		

NOMENCLATURE (continued)

<u>SYMBOL</u>	<u>SADSAC SYMBOL</u>	<u>DEFINITION</u>
θ		pitch angle, angle of rotation about the body Y-axis, positive when the positive Z-axis is rotated toward the positive X-axis; deg
ϕ	PHI	roll angle, angle of rotation about the body X-axis, positive when the positive Y-axis is rotated toward the positive Z-axis; deg
ψ	PSI	yaw angle, angle of rotation about the body Z-axis, positive when the positive X-axis is rotated toward the positive Y-axis; deg

NOMENCLATURE (continued)

<u>SUBSCRIPTS</u>	<u>DEFINITION</u>
a	aileron
b	base
c	canard
e	elevator or elevon
f	flap
r	rudder or ruddervator
s	stability axis system
t	tail, or total conditions
w	wind axis system
ref	reference conditions
∞	freestream condition

TABULATED DATA LISTING

A tabulated data listing, consisting of all aero data sets, both original and those created in arriving at the plotted material to be presented subsequently, is available as an addendum to this report. The tabular listing is made up in two sections:

- (a) a brief summary list of all data sets containing the identifier, the descriptor, and the resident dependent variables.
- (b) a full list of all data sets containing all resident or selected aerodynamic coefficients of the data sets as well as the above mentioned information.

The listing is currently sent on limited distribution to the following organizations:

NASA AMES	Mr. V. Stevens
NASA MSC	Mr. Ray Nelson


If copies of this listing are desired, please contact the above or the cognizant SADSAC personnel who, for this data, is:

J. R. Ziler
Department 2780
Chrysler Corporation Space Division
New Orleans, La. 70129

(504) 255-2304

DATA


CONFIGURATION BUILDUP


DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1D11)		UWAL-1021 BAC C-6 BOOSTER	B1	BETA	REFERENCE INFORMATION
(AU1D21)		UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000	REFS 4.4200 SQ.FT.
(AU1D31)		UWAL-1021 BAC C-6 BOOSTER	B1W1N1	0.000	REFL 10.1000 INCHES
(AU1D41)		UWAL-1021 BAC C-6 BOOSTER	B1H1N1	0.000	REFB 66.6000 INCHES
(AU1D71)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1N1	0.000	XHRP 55.6360 INCHES
(AU1D91)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1	0.000	YMRP 0.0000 INCHES
					ZHRP 5.8600 INCHES
MACH		0.153			SCALE 2.9920 PERCNT

LIFT COEFFICIENT, CL

CONFIGURATION BUILDUP



ANGLE OF ATTACK, ALPHA, DEGREES


DATA SET SYMBOL	CONFIGURATION DESCRIPTION	BETA
(AU1021)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1031)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1051)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1061)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1081)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1091)	UWAL-1021 RAC C-6 BOOSTER	0.000

MACH 0.153

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	BETA
(AU1021)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1031)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1051)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1061)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1081)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1091)	UWAL-1021 RAC C-6 BOOSTER	0.000

REFERENCE INFORMATION	
REFS 4.42C0	SQ.FT.
REFL 18.1000	INCHES
REFB 66.5000	INCHES
XHRF 55.6360	INCHES
YHRF 0.0000	INCHES
ZHRF 5.8600	INCHES
SCALE 2.9920	PERCNT

CONFIGURATION BUILDUP


DATA SET SYMBOL CONFIGURATION DESCRIPTION


(AU1011)	UWAL-1021 BAC C-6 BOOSTER	B1	0.000
(AU1021)	UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000
(AU1031)	UWAL-1021 BAC C-6 BOOSTER	B1W1N1	0.000
(AU1041)	UWAL-1021 BAC C-6 BOOSTER	B1H1N1	0.000
(AU1071)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1N1	0.000
(AU1091)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1	0.000
HACH			0.153


BETA

0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.4200	SQ.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XHRF	59.6360	INCHES
YHRP	0.0000	INCHES
ZNRP	5.8600	INCHES
SCALE	2.9920	PERCNT





DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1D11)	UWAL-1021 BAC C-6 BOOSTER
(AU1D21)	UWAL-1021 BAC C-6 BOOSTER
(AU1D31)	UWAL-1021 BAC C-6 BOOSTER
(AU1D41)	UWAL-1021 BAC C-6 BOOSTER
(AU1D71)	UWAL-1021 BAC C-6 BOOSTER
(AU1D91)	UWAL-1021 BAC C-6 BOOSTER


MACH 0.153

BETA
0.000
0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION
REFS 4.4205 SQ FT.
REFL 15.10L0 INCHES
REFB 66.6900 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCNT

PITCHING MOMENT COEFFICIENT, CLM

CONFIGURATION BUILDUP



ANGLE OF ATTACK, ALPHA, DEGREES


DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1021)	UWAL-1021 BAC C-6 BOOSTER
(AU1031)	UWAL-1021 BAC C-6 BOOSTER
(AU1051)	UWAL-1021 BAC C-6 BOOSTER
(AU1061)	UWAL-1021 BAC C-6 BOOSTER
(AU1081)	UWAL-1021 BAC C-6 BOOSTER
(AU1091)	UWAL-1021 BAC C-6 BOOSTER

BETA	
B1N1	0.000
B1WIN1	0.000
B1VIN1	0.000
B1WIVIN1	0.000
B1WIHV1	0.000
B1WIHV1N1	0.000

MACH 0.153

REFERENCE INFORMATION
REFS 4.4201 SQ.FT.
REFL 16 10LJ INCHES
REFB 66.6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2 9920 PERCNT

CONFIGURATION BUILDUP



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1D1)	□	UWAL-1021 BAC C-6 BOOSTER	B1	BETA
(AU1D2)	△	UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000
(AU1D3)	◇	UWAL-1021 BAC C-6 BOOSTER	B1WIN1	0.000
(AU1D4)	◆	UWAL-1021 BAC C-6 BOOSTER	B1H1N1	0.000
(AU1D5)	◆	UWAL-1021 BAC C-6 BOOSTER	B1WIH1N1	0.000
(AU1D6)	□	UWAL-1021 BAC C-6 BOOSTER	B1WIH1V1N1	0.000


MACH 0.153

BETA

0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.4201	SC.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1021)		UWAL-1021 BAC C-6 BOOSTER	B1N1
(AU1031)		UWAL-1021 BAC C-6 BOOSTER	B1W1N1
(AU1051)		UWAL-1021 BAC C-6 BOOSTER	B1V1N1
(AU1061)		UWAL-1021 BAC C-6 BOOSTER	B1W1V1N1
(AU1081)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1
(AU1091)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1

MACH 0.153


BETA

0.000
0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4,4200	SQ.FT.
REFL	16,1000	INCHES
REFB	66,3000	INCHES
XMRP	55,6360	INCHES
YMRP	0,0000	INCHES
ZMRP	5,8600	INCHES
SCALE	2,9920	PERCNT

CONFIGURATION BUILDUP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1025) UWAL-1021 BAC C-6 BOOSTER
 (AU1031) UWAL-1021 BAC C-6 BOOSTER
 (AU1041) UWAL-1021 BAC C-6 BOOSTER
 (AU1072) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER

ANGLE OF ATTACK, ALPHA, DEGREES


BETA
 0.000
 0.000
 0.000
 0.000
 0.000

REFERENCE INFORMATION
 REFS 4.420L SQ.FT.
 REFL 10.1100 INCHES
 REFb 66.6300 INCHES
 XHrp 55.6360 INCHES
 YMfp 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.153

BASE DRAG COEFFICIENT, CDB

CONFIGURATION BUILDUP




ANGLE OF ATTACK, ALPHA, DEGREES

DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1021)	UWAL-1021 BAC C-6 BOOSTER
(AU1031)	UWAL-1021 BAC C-6 BOOSTER
(AU1051)	UWAL-1021 BAC C-6 BOOSTER
(AU1061)	UWAL-1021 BAC C-6 BOOSTER
(AU1091)	UWAL-1021 BAC C-6 BOOSTER

BETA	
B1N1	0.000
B1WN1	0.000
B1VN1	0.000
B1W1V1N1	0.000
B1W1H1V1N1	0.000

REFERENCE INFORMATION		
REFS	4.4200	SQ.FT.
REFL	14.1000	INCHES
REFB	66.3000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.153



DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1B21)	UWAL-1021 BAC C-6 BOOSTER
(AU1B22)	UWAL-1021 BAC C-6 BOOSTER
(AU1B31)	UWAL-1021 BAC C-6 BOOSTER
(AU1B32)	UWAL-1021 BAC C-6 BOOSTER
(AU1D03)	UWAL-1022 BAC C-6 BOOSTER
(AU1D02)	UWAL-1022 BAC C-6 BOOSTER

MACH 0.153


BETA

0.000
0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION
REFS 4.4210 SQ.FT.
REFL 10.1500 INCHES
REFB 66.6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZHRP 5.8600 INCHES
SCALE 2.9920 PERCNT

LIFT COEFFICIENT, CL

CONFIGURATION BUILDUP




DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1021)	UWAL-1021 BAC C-S BOOSTER
(AU1031)	UWAL-1021 BAC C-6 BOOSTER
(AU1051)	UWAL-1021 BAC C-6 BOOSTER
(AU1061)	UWAL-1021 BAC C-6 BOOSTER
(AU1081)	UWAL-1021 BAC C-6 BOOSTER
(AU1091)	UWAL-1021 BAC C-6 BOOSTER

	BETA
B1N1	0.000
B1W1N1	0.000
B1V1N1	0.000
B1W1V1N1	0.000
B1W1H1V1	0.000
B1W1H1V1N1	0.000

MACH 0.153

REFERENCE INFORMATION	
REFS 4.421G	SQ.FT.
REFL 11.1000	INCHES
REFB 66.0000	INCHES
XMRP 55.6360	INCHES
YMRP 0.0000	INCHES
ZMRP 5.8600	INCHES
SCALE 2.9920	FRCNT




DATA SET SYMBOL	CONFIGURATION DESCRIPTION	BETA	
(AU1D11)	UWAL-1021 BAC C-6 BOOSTER	B1	0.000
(AU1D21)	UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000
(AU1D31)	UWAL-1021 BAC C-6 BOOSTER	B1WIN1	0.000
(AU1D41)	UWAL-1021 BAC C-6 BOOSTER	B1H1N1	0.000
(AU1D73)	UWAL-1021 BAC C-6 BOOSTER	B1WINH1N1	0.000
(AU1D91)	UWAL-1021 BAC C-6 BOOSTER	B1WINH1V1N1	0.000


-TACH D.153

BETA
0.000

REFERENCE INFORMATION
REFS 4.4203 SQ.FT.
REFL 10.1030 INCHES
REFB 66.6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCNT



EFFECT OF REYNOLDS NUMBER




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1A91) □ UWAL-1D21 SAC C-6 BOOSTER
 (AU1B91) ▲ UWAL-1D21 SAC C-6 BOOSTER
 (AU1C95) ○ UWAL-1D21 SAC C-6 BOOSTER
 (AU1A95) △ UWAL-1D21 SAC C-6 BOOSTER

RN/L BETA
 0.700 0.000
 1.100 0.000
 1.800 0.000
 2.100 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6600 INCHES
 XMPP 55.6360 INCHES
 YMPP 0.0000 INCHES
 ZMPP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.101

EFFECT OF REYNOLDS NUMBER



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1A91) UWAL-1021 BAC C-6 BOOSTER
 (AU1B91) UWAL-1021 BAC C-6 BOOSTER
 (AU1C95) UWAL-1021 BAC C-6 BOOSTER
 (AU1A95) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1 B1W1H1V1N1 B1W1H1V1N1 B1W1H1V1N1

RN/L BETA
 0.700 0.000
 1.100 0.000
 1.600 0.000
 2.000 0.000

REFERENCE INFORMATION
 REFS 4 4206 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCLE 2.9920 PERCNT

NACH 0.101

EFFECT OF REYNOLDS NUMBER




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AUIAS1) \circlearrowleft UVAL-1021 BAC C-6 BOOSTER
 (AUID91) \diamond UVAL-1021 BAC C-6 BOOSTER
 (AUID95) $\diamond\triangle$ UVAL-1021 BAC C-6 BOOSTER
 (AUIASS) \square UVAL-1021 BAC C-6 BOOSTER

RN/L BETA
 B1W1H1V1N1 0.700 0.000
 B1W1H1V1N1 1.100 0.000
 B1W1H1V1N1 1.800 0.000
 B1W1H1V1N1 2.000 0.000

REFERENCE INFORMATION
 PEFS 4 4230 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACN 0.101

EFFECT OF REYNOLDS NUMBER



DATA SET SYMBOL CONFIGURATION DESCRIPTION


(AU1A91) \square UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1B91) \diamond UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1D95) \triangle UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1A95) \square UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

RN/L BETA
 0.700 0.000
 1.100 0.000
 1.800 0.000
 2.000 0.000

REFERENCE INFORMATION
 REFS 4.420C SQ.FT.
 REFL 1G.10C9 INCHES
 REF8 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACH D.101

EFFECT OF REYNOLDS NUMBER



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1A91) UWAL-1021 BAC C-6 BOOSTER
 (AU1D91) UWAL-1021 BAC C-6 BOOSTER
 (AU1B95) UWAL-1021 BAC C-6 BOOSTER
 (AU1E95) UWAL-1021 BAC C-6 BOOSTER


RN/L BETA
 0.700 0.000
 1.100 0.000
 1.800 0.000
 2.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 RCFL 10 10PJ INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YNRP 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.101

PAGE 19

LIFT COEFFICIENT, CL



DRAG COEFFICIENT, CD

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1A91) UWAL-1D21 BAC C-6 BOOSTER
 (AU1G91) UWAL-1D21 BAC C-6 BOOSTER
 (AU1G95) UWAL-1D21 BAC C-6 BOOSTER
 (AU1A95) UWAL-1D21 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

RN/L BETA
 0.700 0.000
 1.100 0.000
 1.800 0.000
 2.000 0.000


REFERENCE INFORMATION
 REFS 4.42GJ SQ.FT
 REFL 10,1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.181

EFFECT OF REYNOLDS NUMBER



MACH 0.101



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) Q UWAL-1D21 BAC C-6 BOOSTER
 (AU1093) A UWAL-1D21 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1

BETA
 0.000
 -10.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.0000 INCHES
 XMRF 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER

ANGLE OF ATTACK, ALPHA, DEGREES


BETA
9.000
-10.000

REFERENCE INFORMATION
 REFS 4.42DC SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6300 INCHES
 XMRP 55.6360 INCHES
 YMNP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

RACH 0.153

EFFECT OF SIDESLIP

PITCHING MOMENT COEFFICIENT, CLM



ANGLE OF ATTACK, ALPHA, DEGREES

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER


BETA
 B1W1H1V1N1 0.000
 B1W1H1V1N1 -10.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 16.10E3 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE ~ 24

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER

B1WIH1V1N1
 B1WIH1V1N1

BETA
 0.000
 -10.000


REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6600 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCENT

HACH 0.154

PAGE 25

YAWING MOMENT COEFFICIENT, CLN (STABILITY AXIS)

EFFECT OF SIDESLIP




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) Q UWAL-1021 BAC C-6 BOOSTER
 (AU1093) R UWAL-1021 BAC C-6 BOOSTER

B1WIHIV1N1 B1WIHIV1N1
 BETA
 0.000
 -10.000

REFERENCE INFORMATION
 REFS 4 4204 SQ.FT.
 RCFL 16.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
B1W1H1V1N1

BETA
0.000
-10.000

REFERENCE INFORMATION
 REFS 4.4201 SQ.FT.
 RCFL 10.1010 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1D91) UWAL-1021 BAC C-6 BOOSTER
 (AU1D93) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1

BETA
 0.000
 -10.000

REFERENCE INFORMATION
 REFS 4.42RD SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2 992D PERCNT

MACH 0.154

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1093) UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1
B1W1H1V1N1


BETA
0.000
-10.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 20

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1D21 BAC C-6 BOOSTER
 (AU1093) UWAL-1D21 BAC C-6 BOOSTER

B1W1H1V1N1
 B1W1H1V1N1


BETA
 0.000
 -10.000

REFERENCE INFORMATION
 REFS 4.42E0 SQ.FT.
 REFL 10.1E0 INCHES
 REFB 66.5000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 38

EFFECT OF SIDESLIP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AUI092) UWAL-1B21 BAC C-6 BOOSTER
 (AUI093) UWAL-1B21 BAC C-6 BOOSTER

B1W1H1V1N1
B1W1H1V1N1

BETA
0.000
-10.000


REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.5000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 31

FLAP EFFECTIVENESS BETA = 0

LIFT COEFFICIENT, CL



ANGLE OF ATTACK, ALPHA, DEGREES

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1101) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER


FLAP BETA
 B1WIH1V1N1 0.000 0.000
 B1WIH1V1N1F115 15.000 0.000
 B1WIH1V1N1F140 40.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6300 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000- INCHES
 ZMRP 5.8600- INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE -32

FLAP EFFECTIVENESS BETA = 0



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1D91) UWAL-1021 BAC C-6 BOOSTER
 (AU1D01) UWAL-1021 BAC C-6 BOOSTER
 (AU1I41) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1F115
 B1W1H1V1N1F140


FLAP BETA
 0.000 0.000
 15.000 0.000
 40.000 0.000

REFERENCE INFORMATION
 REFS 4.420C SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6300 INCHES
 XMRP 55.6360 INCHES
 YMRO 0.0000 INCHES
 ZMRP 5.6600 INCHES
 SCALE 2.9920 PERCNT

KACH 0.154

PAGE 33






MACH 0.154

PAGE 35

BASE DRAG COEFFICIENT, CDB

FLAP EFFECTIVENESS BETA = 0



ANGLE OF ATTACK, ALPHA, DEGREES

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER,
 (AU1101) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER


	FLAP	BETA
BIWIH1VIN1	0.000	0.000
BIWIH1VIN1F115	15.000	0.000
BIWIH1VIN1F140	40.000	0.000

REFERENCE	INFORMATION
REFS	4.4200 SQ.FT.
REFL	10.1000 INCHES
REFB	66.6360 INCHES
XMRP	55.6360 INCHES
YMRP	0.0000 INCHES
ZMRP	5.8600 INCHES
SC/LE	2.9920 PERCNT

MACH 0.154

PAGE 36

FLAP EFFECTIVENESS BETA = 0




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1101) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1143) \diamond UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1
 B1W1H1V1N1F115
 B1W1H1V1N1F140

FLAP BETA
 0.000 0.000
 15.000 0.000
 40.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 19.1020 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1101) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER

FLAP BETA
 B1WIHIV1N1 0.000 0.000
 B1WIHIV1N1F115 15.000 0.000
 B1WIHIV1N1F140 40.000 0.000

MACH 0.154

REFERENCE INFORMATION
 REFS 4.4201 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.0000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRP 5.8600 INCHES
 SCALE 2.9920 PERCNT



PARAMETRIC VALUES

BETA	- 4.000	AIRLON	0.000
HTAIL	0.000	ELEVTR	0.000
RUDDER	0.000	FLAP	40.000

DATA HIST. CODE V

REFERENCE INFORMATION

REFS	4.4200	SQ.FT.
REFL	10.10L9	INCHES
REFB	65.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT


UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1F140

(AU1142) 28 MAY 71

PAGE

39



SYMBOL	MACH	PARAMETRIC VALUES			
○	0.154	BETA	- 4.000	AIRLON	0.000
		HTAIL	0.000	ELEVTR	0.000
		PUPPER	0.000	FLAT	4.100

REFERENCE INFORMATION		
REFS	4.4200	SQ.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT


- DATA HIST. CODE -

UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1F140

(AU1142) 28 MAY 71

PAGE 40



SYMBOL	MACH	PARAMETRIC VALUES			
		BETA	- 4.000	AILRDN	0.000
	0.154	HTAIL	0.000	ELEVTR	0.000
		RUDDER	0.000	FLAP	40.000

REFERENCE INFORMATION		
REFS	4,4200	SQ.FT
REFL	10,1000	INCHES
REFB	66,6000	INCHES
XHRF	55,6360	INCHES
YHRF	0,0000	INCHES
ZHRF	5,8600	INCHES
SCALE	2,9920	PERCNT

DATA HIST. CODE V

UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1F140

(AU1142) 28 MAY 71

PAGE

41

LATERAL FORCE COEFFICIENT, CY



SYMBOL MACH PARAMETRIC VALUES
○ 0.154 BETA - 4.000 AILRDN 0.000
 HTAIL 0.000 ELEVTR 0.000
 RUDDER 0.090 FLAP 40.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1600 INCHES
 REFb 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT


DATA HIST. CODE V

UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1F140

CAU1142 28 MAY 71


PAGE 42



SYMBOL MACH PARAMETRIC VALUES
○ 0.154 BETA - 4.000 AILRDN 0.000
 HTAIL 0.000 ELEVTR 0.000
 RUDDER 0.000 FLAP 40.000

DATA MIST. CODE V

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REF_L 10.1000 INCHES
 REF_B 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

ROLLING MOMENT COEFFICIENT, C_{SR} (STABILITY AXIS)


ANGLE OF ATTACK, ALPHA, DEGREES

SYMBOL MACH PARAMETRIC VALUES
○ 0.154 BETA - 4.000 AILRDN 0.000
 HTAIL 0.000 ELEVTR 0.000
 RUDDER 0.000 FLAP 40.000

DATA HIST. CODE V

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

FLAP EFFECTIVENESS BETA = -4



SYMBOL	PARAMETRIC VALUES			REFERENCE INFORMATION	
	MACH	BETA	AILRDN	REFS	SQ.FT.
○	0.154	-4.000	0.000	REFL	10 1000
		HTAIL	0.000	REFB	66.6000
		RUDER	0.000	XMRP	55.6360
			FLAP	YMRP	0.0000
			45.000	ZMRP	5.8600
				SCALE	2.9920 PERCNT


DATA HIST. CODE V

UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1F140

(AU1142) 28 MAY 71


PAGE -45



SYMBOL MACH PARAMETRIC VALUES REFERENCE INFORMATION
 Q 0.154 BETA - 4.000 AILRDN 0.000 REFS 4.4200 SQ.FT.
 HTAIL 0.000 ELEVTR 0.000 REFL 10.1000 INCHES
 RUDDER 0.000 FLAP 40.000 REF0 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

DATA HIST. CODE V

FLAP EFFECTIVENESS BETA = -4



SYMBOL MACH PARAMETRIC VALUES
○ 0.154 BETA - 4.000 AILRDN 0.000
 HTAIL 0.000 ELEVTR 0.000
 RUDDER 0.000 FLAP 40.000

REFERENCE INFORMATION
REFS 4.4200 SQ.FT.
REFL 10.1000 INCHES
REFB 66.6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCENT

DATA HIST. CODE


UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1F140

(AU1142) 28 MAY 71

PAGE 47

FLAP EFFECTIVENESS BETA = -4




SYMBOL MACH PARAMETRIC VALUES
□ 0.154 BETA - 4.000 AILRDN 0.000
 HTAIL 0.000 ELEVTR 0.000
 RUDDER 0.000 FLAP 40.000

DATA HIST. CODE V

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.106C INCHES
 REFB 66.6000 INCHES
 XHRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

FLAP EFFECTIVENESS BETA = -10




DATA SET SYMBOL : CONFIGURATION DESCRIPTION
 (AU1D93) UWAL-1021 BAC C-6 BOOSTER
 (AU1104) UWAL-1021 BAC C-6 BOOSTER
 (AU1144) UWAL-1U21 BAC C-6 BOOSTER

FLAP BETA
 B1W1HIVIN1 0.000 -10.000
 B1W1HIVIN1F115 15.000 -10.000
 B1W1HIVIN1F140 40.000 -10.000

REFERENCE INFORMATION
 REFS 4.420J SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154


DRAG COEFFICIENT, CD




HACH C 0.154

FLAP BETA
0.000 -10.000
15.000 -10.000
40.000 -10.000

REFERENCE INFORMATION
REFS 4 4200 SQ.FT
REFL 10.1000 INCHES
REFB 66.6300 INCHES
XHRF 55.6360 INCHES
YMRP 0 0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCNT



LATERAL FORCE COEFFICIENT, CY




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1093) Q UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1104) A UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1F115
 (AU1144) D UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1F140

FLAP BETA
 0.000 -10.000
 15.000 -10.000
 40.000 -10.000

REFERENCE INFORMATION
 REFS 4.4205 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH C 0.154




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1093) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1104) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1144) \diamond UWAL-1021 BAC C-6 BOOSTER

BIWIH1VIN1
 BIWIH1VIN1F115
 BIWIH1VIN1F140

FLAP BETA
 0.000 -10.000
 15.000 -10.000
 40.000 -10.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 RCFL 1G 1000 INCHES
 REF8 66.6000 INCHES
 XMRP 55 6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2 9920 FERCNT

MACH 0.154



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1093)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1
(AU1104)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1F115
(AU1144)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1F140


FLAP BETA

0.000	-10.000
15.000	-10.000
40.000	-10.000

REFERENCE INFORMATION


REFS	4.420C	SQ.FT.
REFL	10.10LJ	INCHES
REFB	66.6900	INCHES
XHRS	55.6360	INCHES
YHRS	0.0000	INCHES
ZHRS	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154



MACH 0.154

BASE DRAG COEFFICIENT, CDB



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1093)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1	FLAP 0.000	BETA -10.000
(AU1104)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1F115	15.000	-10.000
(AU1144)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1F140	40.000	-10.000

MACH 0.154


FLAP BETA

0.000	-10.000
15.000	-10.000
40.000	-10.000

REFERENCE INFORMATION

REFS	4.4200	SQ.FT.
REFL	16.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0009	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

FLAP EFFECTIVENESS BETA = -10



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1093) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1104) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1144) \diamond UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1F15
 B1W1H1V1N1F140

FLAP BETA
 0.000 -10.000
 15.000 -10.000
 40.000 -10.000

REFERENCE INFORMATION
 REFS 4.420ⁿ Sq.FT.
 REFL 10.1000 INCHES
 REF8 66.6000 INCHES
 XMRF 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZHRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

LIFT COEFFICIENT, CL




MACH 0.154

FLAP BETA

REFERENCE INFORMATION

REFS	4.42D0	SQ.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

STABILIZER EFFECTIVENESS, FLAPS UP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1191) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER


HTAIL BETA
 -20.000 0.000
 0.000 0.000
 10.000 0.000

REFERENCE INFORMATION
 REFS 4.42DQ SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMPP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.992G PERCNT

MACH 0.154

PAGE 59

STABILIZER EFFECTIVENESS, FLAPS UP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1181) ○ UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1091) △ UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N2
 (AU1201) ◇ UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

HTAIL BETA


-20.000 0.000
 0.000 0.000
 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT
 REFL 10 1050 INCHES
 REFB 66.6000 INCHES
 XHRP 55.6360 INCHES
 YMNP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 1.154

PAGE 60

STABILIZER EFFECTIVENESS, FLAPS UP




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER

HTAIL BETA
 BIWIHIVINI -20,000 0.000
 BIWIHIVINI 0,000 0.000
 BIWIHIVINI 10,000 0.000

REFERENCE INFORMATION
 REFS 4.42E0 SQ.FT.
 REFL 10,10J0 INCHES
 REFB 66.9000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0090 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.992D PERCNT

MACH 0.154

STABILIZER EFFECTIVENESS, FLAPS UP



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER

HTAIL BETA

B1WIH1V1N1 -20.000 0.000
 B1WIH1V1N1 0.000 0.000
 B1WIH1V1N1 10.000 0.000


REFERENCE INFORMATION

REFS 4 420ⁿ SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 62

STABILIZER EFFECTIVENESS, FLAPS UP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER

HTAIL BETA


-20,000 0.000
 0,000 0.000
 10,000 0.000

REFERENCE INFORMATION
 REFS 4.4206 SQ.FT.
 RCFL 16.1063 INCHES
 REFB 66.6900 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 63

STABILIZER EFFECTIVENESS, FLAPS UP



DRAG COEFFICIENT, CD

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1181)	○	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1
(AU1091)	△	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1
(AU1201)	◊	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1

HTAIL BETA


-20,000	0.000
0,000	0.000
10,000	0.000

REFERENCE INFORMATION

REFS	4.4200	SQ.FT.
REFL	10 100J	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH = 0.154

STABILIZER EFFECTIVENESS, FLAPS UP



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU101) ○ UWAL-1021 BAC C-6 BOOSTER
 (AU1091) △ UWAL-1021 BAC C-6 BOOSTER
 (AU1201) ◊ UWAL-1021 BAC C-6 BOOSTER


HTAIL BETA
 B1W1H1V1N1 -20,000 0.000
 B1W1H1V1N1 0,000 0.000
 B1W1H1V1N1 10,000 0.000

REFERENCE INFORMATION
 REFS 4,4200 SQ.FT.
 REFL 10,1000 INCHES
 REFB 66,6600 INCHES
 XHRC 55,6360 INCHES
 YMRF 0,0000 INCHES
 ZHRC 5,8600 INCHES
 SCALE 2,9920 PERCNT


MACH 0.164

PAGE 65

STABILIZER EFFECTIVENESS, FLAP = 40



STABILIZER EFFECTIVENESS, FLAP = 40



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER
 (AU1171) UWAL-1021 BAC C-6 BOOSTER


HTAIL BETA

-20.000 0.000
 0.000 0.000
 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 <REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XNRP 55.6360 INCHES
 YNRP 0.0000 INCHES
 ZNRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PITCHING MOMENT COEFFICIENT, CLM



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER
 (AU1171) UWAL-1021 BAC C-6 BOOSTER


HTAIL BETA
 B1WIH1V1N1F140 -20,000 0.000
 B1WIH1V1N1F140 0,000 0.000
 B1WIH1V1N1F140 10,000 0.000

REFERENCE INFORMATION
 REFS 4.420L SQ.FT.
 REFL 10.100U INCHES
 REFB 66.650D INCHES
 XHRP 55.636D INCHES
 YHRP 0.000D INCHES
 ZHRF 5.860D INCHES
 SCALE 2.992D PERCNT

MACH 0.154

PAGE 68

STABILIZER EFFECTIVENESS, FLAP = 40




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1151) UHAW-1021 BAC C-6 BOOSTER
 (AU1241) UHAW-1021 BAC C-6 BOOSTER
 (AU1171) UHAW-1021 BAC C-6 BOOSTER

HTAIL BETA
 B1W1H1V1N1F140 -20.000 0.000
 B1W1H1V1N1F140 0.000 0.000
 B1W1H1V1N1F140 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4209 SQ.FT.
 REFL 10 1620 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

STABILIZER EFFECTIVENESS, FLAP = 40



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER
 (AU1171) UWAL-1021 BAC C-6 BOOSTER


ANGLE OF ATTACK, ALPHA, DEGREES

	HTAIL	BETA
B1WIH1V1N1F14D	-20,000	0.000
B1WIH1V1N1F14D	0,000	0.000
B1WIH1V1N1F14D	10,000	0.000

REFERENCE INFORMATION		
REFS	4,420	SQ.FT.
REFL	10,100	INCHES
REFB	66,600	INCHES
XHRP	55.6369	INCHES
YNRP	0.0000	INCHES
ZHRP	5.8600	INCHES
SCALE	2.9920	PERCNT


MACH , 0.154

STABILIZER EFFECTIVENESS, FLAP = 40



PAGE

STABILIZER EFFECTIVENESS, FLAP = 40




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (AU1141) UWAL-1021 BAC C-6 BOOSTER
 (AU1171) UWAL-1021 BAC C-6 BOOSTER

HTAIL BETA
 B1W1H1V1N1F140 -20.000 0.000
 B1W1H1V1N1F140 0.000 0.000
 B1W1H1V1N1F140 10.000 0.000

REFERENCE INFORMATION
 REFS 4.420J SQ.FT.
 REFL 15.10' 0 INCHES
 REFB 66 6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZMRP 5 8600 INCHES
 SCALE 2.992G PERCNT

HACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1211) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1091) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1241) \diamond UWAL-1021 BAC C-6 BOOSTER


BIW1H1V1N1
 BIW1H1V1N1
 BIW1H1V1N1

ELEVTR -30,000 0.000 0.000
 HTAIL 0,000 0.000 0.000
 BETA 30,000 0.000 0.000

REFERENCE INFORMATION
 REFS 4.4203 SQ FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 FRCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1211)	○	UWAL-1D21 BAC C-6 BOOSTER	B1W1H1V1N1
(AU1091)	△	UWAL-1D21 BAC C-6 BOOSTER	B1W1H1V1N1
(AU1241)	◇	UWAL-1D21 BAC C-6 BOOSTER	B1W1H1V1N1

ELEVTR HTAIL BETA


-30.000	0.000	0.000
0.000	0.000	0.000
30.000	0.000	0.000

REFERENCE INFORMATION

REFS	4.42CD	SQ.FT
REFL	10.1000	INCHES
REFB	66.9000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1211) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1691) Δ UWAL-1021 BAC C-6 BOOSTER
 (AU1241) \diamond UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA

-30.000 0.000 0.000
 0.000 0.000 0.000
 30.000 0.000 0.000

REFERENCE INFORMATION
 REFS 4.4201 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.0000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1211) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1091) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1241) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

ELEVTR HTAIL BETA


-30.000 0.000 0.000
 0.000 0.000 0.000
 30.000 0.000 0.000

REFERENCE INFORMATION

REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFL 66.6900 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1211) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER
 (AU1241) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

ELEVTR HTAIL BETA
 -30.000 0.000 0.000
 0.000 0.000 0.000
 30.000 0.000 0.000

REFERENCE INFORMATION
 REFS 4 42CD SQ.FT
 REFL 15.1130 INCHES
 REFB 66.5000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0



DRAG COEFFICIENT, CD


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1211) ○ UWAL-1021 BAC C-6 BOOSTER
 (AU1091) □ UWAL-1021 BAC C-6 BOOSTER
 (AU1241) ◇ UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 B1W1H1V1N1 -30.000 0.000 0.000
 B1W1H1V1N1 0.000 0.000 0.000
 B1W1H1V1N1 30.000 0.000 0.000

REFERENCE INFORMATION		
REFS	4.4260	SQ.FT.
REFL	10.1000	INCHES
REFB	66.0000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1211) UWAL-1021 BAC C-6 BOOSTER
 (AU1D91) UWAL-1021 BAC C-6 BOOSTER
 (AU1241) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

ELEVTR HTAIL BETA
 -30.000 0.000 0.000
 0.000 0.000 0.000
 30.000 0.000 0.000

REFERENCE INFORMATION
 REFS 4 420ⁿ SQ FT
 REFL 10 1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 FERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1361) UWAL-1021 BAC C-6 BOOSTER
 (AU1161) UWAL-1021 BAC C-6 BOOSTER
 (AU1331) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 BIWIHIVIN1 -30.000 -20.000 0.000
 BIWIHIVIN1 0.000 -20.000 0.000
 BIWIHIVIN1 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.420" SQ.FT.
 RCFL 10.1060 INCHES
 REFB 66.6200 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 1 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AUI1361) UWAL-1021 BAC C-6 BOOSTER
 (AUI1181) UWAL-1021 BAC C-6 BOOSTER
 (AUI1331) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

ELEVTR -30,000 -20,000 0,000
 HTAIL 0,000 -20,000 0,000
 BETA 30,000 -20,000 0,000

REFERENCE INFORMATION
 REFS 4 4200 SQ.FT.
 REFL 10 1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1361) UWAL-1021 BAC C-6 BOOSTER
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1331) UWAL-1021 BAC C-6 BOOSTER


ELEVTR HTAIL BETA
 B1W1H1V1N1 -30,000 -20,000 0.000
 B1W1H1V1N1 0,000 -20,000 0.000
 B1W1H1V1N1 30,000 -20,000 0.000

REFERENCE INFORMATION
 REFS 4.42C0 SQ FT.
 REFL 10.1000 INCHES
 REFB 66.3000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCENT

MACH 0.154

PAGE 82

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1361) UWAL-1021 BAC C-6 BOOSTER
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1331) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 -50.000 -20.000 0.000
 0.000 -20.000 0.000
 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.42" D SQ.FT.
 REFL 1L 1000 INCHES
 REFB 66.5000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1181) Q UHAL-1021 BAC C-6 BOOSTER
 (AU1331) A UHAL-1021 BAC C-6 BOOSTER


ANGLE OF ATTACK, ALPHA, DEGREES

ELEVTR HTAIL BETA
 0.000 -20.000 0.000
 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.4201 SQ.FT
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 0-20



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1361) UWAL-1021 BAC C-6 BOOSTER
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1531) UWAL-1021 BAC C-6 BOOSTER


BIWIH1V1N1
 BIWIH1V1N1
 BIWIH1V1N1

ELEVTR HTAIL BETA

-30.000 -20.000 0.000
 0.000 -20.000 0.000
 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.4210 SG.FT.
 REFL 10.1600 INCHES
 REFB 66.5000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1361) UWAL-1021 BAC C-6 BOOSTER
 (AU1181) UWAL-1021 BAC C-6 BOOSTER
 (AU1331) UWAL-1021 BAC C-6 BOOSTER


ELEVTR HTAIL BETA
 B1WH1V1N1 -30.000 -20.000 0.000
 B1WH1V1N1 0.000 -20.000 0.000
 B1WH1V1N1 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 RETL 10.1000 INCHES
 REFb 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 86

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) \square UWAL-1021 BAC C-6 BOOSTER
 (AU1201) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1341) \diamond UWAL-1021 BAC C-6 BOOSTER

B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

ELEVTR -30.000 HTAIL 10.000 BETA 0.000
 0.000 10.000 0.000
 30.000 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4203 SQ.FT.
 REFL 10.100J INCHES
 REFB 66.8C00 INCHES
 XHRP 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZMRP 5.8680 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1201) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1341) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1


ELEVTR HTAIL BETA

-30.000 10.000 0.000
 0.000 10.000 0.000
 30.000 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCENT

MACH 0.354

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER
 (AU1341) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 B1WIH1V1N1 -30.000 10.000 0.000
 B1WIH1V1N1 0.000 10.000 0.000
 B1WIH1V1N1 30.000 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 16.1000 INCHES
 REFb 66.5000 INCHES
 XHRP 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZHRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) UWAL-1021 BAC C-6 BOOSTER
 (AU1201) UWAL-1021 BAC C-6 BOOSTER
 (AU1341) UWAL-1021 BAC C-6 BOOSTER

ANGLE OF ATTACK, ALPHA, DEGREES


ELEVTR HTAIL BETA
 -30,000 10,000 0.000
 0,000 10,000 0.000
 30,000 10,000 0.000

REFERENCE INFORMATION
 REFS 4.4240 SQ.FT.
 REFL 10.1000 INCHES
 REFb 66.6400 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 90

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) UWAL-1021 BAC C-6 BOOSTER
 (AU1291) UWAL-1021 BAC C-6 BOOSTER
 (AU1341) UWAL-1021 BAC C-6 BOOSTER


ELEVTR HTAIL BETA
 -30.000 10.000 0.000
 0.000 10.000 0.000
 30.000 10.000 0.000

REFERENCE INFORMATION
 REFS 4.42DJ SQ.FT.
 REFL 10.1000 INCHES
 REF8 66 6000 INCHES
 XMRP 55.6360 INCHES
 YART 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACH D.154

PAGE 91

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10



DRAG COEFFICIENT, CD


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) UWAL-1021 BAC C-6 BOOSTER B1WIH1V1N1
 (AU1201) UWAL-1021 BAC C-6 BOOSTER B1WIH1V1N1
 (AU1341) UWAL-1021 BAC C-6 BOOSTER B1WIH1V1N1

MACH 0.154

ELEVTR HTAIL BETA
 -30.000 10.000 0.000
 0.000 10.000 0.000
 30.000 10.000 0.000

REFERENCE	INFORMATION
REFS	4.42GJ SQ.FT.
REFL	10.1000 INCHES
REFB	66.0000 INCHES
XMRP	55.5360 INCHES
YMRP	0.0000 INCHES
ZMRP	5.8800 INCHES
SCALE	2.9920 PERCNT

ELEVATOR EFFECTIVENESS, FLAPS UP, HORIZONTAL TAIL = 10




PITCHING MOMENT COEFFICIENT, CLM

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1351) O UWAL-1021 BAC C-6 BOOSTER
 (AU1201) A UWAL-1021 BAC C-6 BOOSTER
 (AU1341) D UWAL-1021 BAC C-6 BOOSTER


ELEVTR HTAIL BETA
 B1W1H1V1N1 -30.000 10.000 0.000
 B1W1H1V1N1 0.000 10.000 0.000
 B1W1H1V1N1 30.000 10.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 56.6000 INCHES
 XHRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154



ELEVATOR EFFECTIVENESS, FLAP = 40, HORIZONTAL TAIL = -20




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1291) UWAL-1021 BAC C-6 BOOSTER
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (4U1321) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 B1W1H1V1N1F140 -30.000 -20.000 0.000
 B1W1H1V1N1F140 0.000 +20.000 0.000
 B1W1H1V1N1F140 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.420^f SQ FT.
 REFL 10.100^d INCHES
 REFB 66.6300 INCHES
 XMRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.155

ELEVATOR EFFECTIVENESS, FLAP =40, HORIZONTAL TAIL = -20



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1291) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1F140
 (AU151) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1F140
 (AU1521) UWAL-1921 BAC C-6 BOOSTER B1W1H1V1N1F140

ELEVTR HTAIL BETA


-30.000 -20.000 0.000
 5.000 -20.000 0.000
 30.000 -20.000 0.000

REFERENCE INFORMATION

REFS 4.4200 SQ.FT.
 REFL 19.1600 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.155

ELEVATOR EFFECTIVENESS, FLAP = 40, HORIZONTAL TAIL = -20




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1291) O UWAL-1021 BAC C-6 BOOSTER
 (AU1151) △ UWAL-1021 BAC C-6 BOOSTER
 (AU1321) ◇ UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA
 B1W1H1V1N1F14D -30.000 -20.000 0.000
 B1W1H1V1N1F14D 0.000 -20.000 0.000
 B1W1H1V1N1F14D 30.000 -20.000 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 16.1000 INCHES
 REF8 66.0000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACH 0.155

ELEVATOR EFFECTIVENESS, FLAP = 40, HORIZONTAL TAIL = -20



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1291) UWAL-1021 BAC C-6 BOOSTER
 (AU1151) UWAL-1021 BAC C-6 BOOSTER
 (AU1321) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA


B1W1H1V1N1F140 -30.000 -20.000 0.000
 B1W1H1V1N1F140 0.000 -20.000 0.000
 B1W1H1V1N1F140 30.000 -20.000 0.000

REFERENCE INFORMATION

REFS 4 4204 SQ.FT.
 RCFL 16 1863 INCHES
 REFB 66.0000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.155

ELEVATOR EFFECTIVENESS, FLAP = 40, HORIZONTAL TAIL = -20



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1291) UWAL-1D21 BAC C-6 BOOSTER
 (AU1151) UWAL-1D21 BAC C-6 BOOSTER
 (AU1321) UWAL-1D21 BAC C-6 BOOSTER

B1W1H1V1N1F140
 B1W1H1V1N1F140
 B1W1H1V1N1F140

ELEVTR HTAIL BETA
 -30.000 -20.000 0.000


REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XNRP 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZNRP 5.8800 INCHES
 SCALE 2.9920 PERCNT

MACH 0.155

PAGE 99

ELEVATOR EFFECTIVENESS, FLAP = 40, HORIZONTAL TAIL = -20

LIFT COEFFICIENT, CL



PITCHING MOMENT COEFFICIENT, CLM

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1291) UWAL-1021 BAC C-6 BOOSTER
(AU1151) UWAL-1021 BAC C-6 BOOSTER
(AU1321) UWAL-1021 BAC C-6 BOOSTER

ELEVTR HTAIL BETA

B1W1H1V1N1F140 -30.000 -20.000 0.000
B1W1H1V1N1F140 0.000 -20.000 0.000
B1W1H1V1N1F140 30.000 -20.000 0.000


REFERENCE INFORMATION

REFS 4.420C SQ.FT.
RFFL 10.1029 INCHES
REFB 66.6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCENT

HACH .0.155

PAGE 100

EFFECT OF AFT WING AND LARGE STABILIZER




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) UWAL-1021 BAC C-6 BOOSTER
 (AU1481) UWAL-1021 BAC C-6 BOOSTER
 (AU1451) UWAL-1021 BAC C-6 BOOSTER
 (AU1461) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W1H1V1 0.000
 B1W2H1V1 0.000
 B1W2H2V1 0.000
 B1W2H2V1N2 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT
 REFL 10.1000 INCHES
 REFB 66.0000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACH 0.153

PAGE 101




HACH 0.153

BETA

REFERENCE INFORMATION

EFFECT OF AFT WING AND LARGE STABILIZER




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1681) UWAL-1021 BAC C-6 BOOSTER
 (AU1481) UWAL-1021 BAC C-6 BOOSTER
 (AU1451) UWAL-1021 BAC C-6 BOOSTER
 (AU1461) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W1H1V1 0.000
 B1W2H1V1 0.000
 B1W2H2V1 0.000
 B1W2H2V1N2 0.000

REFERENCE INFORMATION
 REFS 4.4260 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRP 55.6360 INCHES
 YMRP 0.0000 INCHES
 ZHRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.153

EFFECT OF AFT WING AND LARGE STABILIZER




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1081) UWAL-1D21 BAC C-6 BOOSTER
 (AU1481) UWAL-1D21 BAC C-6 BOOSTER
 (AU1451) UWAL-1D21 BAC C-6 BOOSTER
 (AU1461) UWAL-1D21 BAC C-6 BOOSTER

BETA
 B1W1H1V1 0.000
 B1W2H1V1 0.000
 B1W2H2V1 0.000
 B1W2H2V1N2 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.5000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.153

EFFECT OF AFT WING AND LARGE STABILIZER



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) \circ UWAL-1021 BAC C-6 BOOSTER
 (AU1451) \triangle UWAL-1021 BAC C-6 BOOSTER
 (AU1461) \diamond UWAL-1021 BAC C-6 BOOSTER


BETA
 B1W2H1V1 0.000
 B1W2H2V1 0.000
 B1W2H2V1N2 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT
 RSFL 10 10³ INCHES
 REFB 66.8000 INCHES
 XHRP 55.6360 INCHES
 YHRP 0.0000 INCHES
 ZNRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 105

EFFECT OF AFT WING AND LARGE STABILIZER



DATA SET SYMBOL CONFIGURATION DESCRIPTION


DATA SET SYMBOL	CONFIGURATION DESCRIPTION	BETA
(AU1481)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1481)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1481)	UWAL-1021 BAC C-6 BOOSTER	0.000

REFERENCE INFORMATION

REFS	4.42 RD	SQ.FT.
REFL	10.1L00	INCHES
REFB	66 S200	INCHES
XHRF	55.6360	INCHES
YHRF	0.0000	INCHES
ZHRF	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.153

EFFECT OF AFT WING AND LARGE STABILIZER



DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1081)	UWAL-1021 BAC C-6 BOOSTER
(AU1481)	UWAL-1021 BAC C-6 BOOSTER
(AU1451)	UWAL-1021 BAC C-6 BOOSTER
(AU1461)	UWAL-1021 BAC C-6 BOOSTER


BETA	
B1W1H1V1	0.000
B1W2H1V1	0.000
B1W2H2V1	0.000
B1W2Y2V1N2	0.000

BETA
0.000
0.000
0.000
0.000

REFERENCE INFORMATION
REFS 4.420C SQ FT.
REFL 15 1809 INCHES
REFB 66.6000 INCHES
XHRF 55.6360 INCHES
YHRF 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCNT

HACH 6.153

EFFECT OF NACELLES AND AFT WING




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) UWAL-1021 BAC C-6 BOOSTER
 (AU1471) UWAL-1021 BAC C-6 BOOSTER
 (AU1491) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W2H1V1 0.000
 B1W2H1V1N2 0.000
 B1W2H1V1N1 0.000
 B1W1H1V1N1 0.000

REFERENCE INFORMATION
 REFS 4.4210 58.FT.
 kEFL 1L.1500 INCHES
 REFB 66.5000 INCHES
 XHRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) UWAL-1021 BAC C-6 BOOSTER B1W2H1V1
 (AU1471) UWAL-1021 BAC C-6 BOOSTER B1W2H1V1N2
 (AU1491) UWAL-1021 BAC C-6 BOOSTER B1W2H1V1N1
 (AU1091) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

BETA
 0.000
 0.000
 0.000
 0.000

REFERENCE INFORMATION
 REFS 4 4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6300 INCHES
 XHRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRP 5.8800 INCHES
 SCALE 2.9920 PERCNT

NACH 0.154

EFFECT OF NACELLES AND AFT WING




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) Q UWAL-1021 BAC C-6 BOOSTER B1W2H1V1
 (AU1471) A UWAL-1021 BAC C-6 BOOSTER B1W2H1V1N2
 (AU1491) D UWAL-1021 BAC C-6 BOOSTER B1W2H1V1N1
 (AU1091) S UWAL-1021 BAC C-6 BOOSTER B1W2H1V1N1

BETA
 0.000
 0.000
 0.000
 0.000

REFERENCE INFORMATION
 REFS 4.4210 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMNP 55.6360 INCHES
 YMNP 0.0000 INCHES
 ZMNP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1481)		UWAL-1021 BAC C-6 BOOSTER	B1W2H1V1
(AU1471)		UWAL-1021 BAC C-5 BOOSTER	B1W2H1V1N2
(AU1491)		UWAL-1021 BAC C-6 BOOSTER	B1W2H1V1N1
(AU1091)		UWAL-1021 BAC C-5 BOOSTER	B1W14V1N1

BETA


0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.4290	SQ.FT.
REFL	16.10C9	INCHES
REFB	66.6000	INCHES
XMRF	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRF	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154

BASE DRAG COEFFICIENT, CDB



DATA SET SYMBOL CONFIGURATION DESCRIPTION


(AU1481)	○	UWAL-1021 BAC C-6 BOOSTER	B1W2H1V1	BETA
(AU1491)	△	UWAL-1021 BAC C-6 BOOSTER	B1W2H1V1N1	0.000
(AU1591)	◇	UWAL-1021 BAC C-6 BOOSTER	B1'141/IN1	0.000

BETA

REFS	4.4200	SQ.FT.
REFL	10 1000	INCHES
REFB	66.6600	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9926	PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1481) UWAL-1021 BAC C-6 BOOSTER
 (AU1471) UWAL-1021 BAC C-6 BOOSTER
 (AU1491) UWAL-1021 BAC C-6 BOOSTER
 (AU1091) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W2H1V1 0.000
 B1W2H1V1N2 0.000
 B1W2H1V1N1 0.000
 B1W1H1V1N1 0.000

REFERENCE INFORMATION
 REFS 4.42^{1D} SQ.FT.
 REFL 11.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING




DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AU1481)	UWAL-1021 BAC C-6 BOOSTER
(AU1471)	UWAL-1021 BAC C-6 BOOSTER
(AU1491)	UWAL-1021 BAC C-6 BOOSTER
(AU1091)	UWAL-1021 BAC C-6 BOOSTER

BETA
0.000
0.000
0.000
0.000

REFERENCE INFORMATION
REFS 4.42D3 SQ FT.
REFL 10 1000 INCHES
REFB 66.0000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1021 BAC C-6 BOOSTER
 (AU1501) UWAL-1021 BAC C-6 BOOSTER
 (AU1031) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W2 0.000
 B1W2N1 0.000
 B1W1N1 0.000

REFERENCE INFORMATION
 REFS 4.420L SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6900 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1D21 BAC C-6 BOOSTER
 (AU1501) UWAL-1D21 BAC C-6 BOOSTER
 (AU1631) UWAL-1G21 BAC C-6 BOOSTER

BETA
 B1W2 0.000
 B1WN1 0.000
 B1WIN1 0.000

REFERENCE INFORMATION
 REFS 4.420^E SQ.FT.
 REFL 15.10L3 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1D21 BAC C-6 BOOSTER
 (AU1501) UWAL-1D21 BAC C-6 BOOSTER
 (AU1031) UWAL-1D21 BAC C-6 BOOSTER

BETA
 0.000
 0.000
 0.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 19.1050 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

HACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1021 BAC C-6 BOOSTER
 (AU1501) UWAL-1021 BAC C-6 BOOSTER
 (AU1031) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W2 0.000
 B1W2N1 0.000
 B1WIN1 0.000

REFERENCE INFORMATION
 REFS 4.420C SQ FT.
 REFL 1G 10CJ INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING-TAIL OFF




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1021 BAC C-6 BOOSTER
 (AU1501) UWAL-1021 BAC C-6 BOOSTER
 (AU1031) UWAL-1021 BAC C-6 BOOSTER

BETA
 B1W2 0.000
 B1W2N1 0.000
 B1WIN1 0.000

REFERENCE INFORMATION
 REFS 4.4201 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8660 INCHES
 SCALE 2.9920 PERCENT

MACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1511) UWAL-1021 BAC C-6 BOOSTER B1W2
 (AU1501) UWAL-1021 BAC C-6 BOOSTER B1W2N1
 (AU1031) UWAL-1021 BAC C-6 BOOSTER B1W1N1

BETA


0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.420C	SQ.FT
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XHRF	55.6360	INCHES
YHRF	0.0000	INCHES
ZHRF	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154

EFFECT OF NACELLES AND AFT WING--TAIL OFF



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1511) UWAL-1021 BAC C-6 BOOSTER
 (AU1501) UWAL-1021 BAC C-6 BOOSTER
 (AU1031) UWAL-1021 BAC C-6 BOOSTER


BETA
 B1W2 0.000
 B1W2N1 0.000
 B1WIN1 0.000

REFERENCE INFORMATION
 REFS 4 42D SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMNP 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCENT


MACH 0.154

LATERAL FORCE COEFFICIENT, CY

CONFIGURATION BUILDUP IN YAW



CONFIGURATION BUILDUP IN YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1D16)		UWAL-1021 BAC C-6 BOOSTER	B1
(AU1D28)		UWAL-1021 BAC C-6 BOOSTER	B1N1
(AU1D56)		UWAL-1021 BAC C-6 BOOSTER	B1V1N1
(AU1D75)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1N1
(AU1D85)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V3
(AU1D9A)		UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1

HACH 0.153

ALPHA


0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.4200	SQ.FT.
REFL	10.1000	INCHES
REFB	65.6600	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCENT

CONFIGURATION BUILDUP IN YAW

ROLLING MOMENT COEFFICIENT, CSL (STABILITY AXIS)



SIDE SLIP ANGLE, BETA, DEGREES


DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1016) UWAL-1021 BAC C-6 BOOSTER B1
 (AU1026) UWAL-1021 BAC C-6 BOOSTER B1N1
 (AU1056) UWAL-1021 BAC C-6 BOOSTER B1VIN1
 (AU1076) UWAL-1021 BAC C-6 BOOSTER B1W1H1N1
 (AU1086) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1
 (AU109A) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

MACH 0.153

ALPHA
0.000
0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION
 REFS 4.420R SQ.FT.
 REFL 10.100J INCHES
 REFB 66.600D INCHES
 XHRF 55.636D INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

CONFIGURATION BUILDUP IN YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1D16) UWAL-1021 BAC C-6 BOOSTER B1
 (AU1D26) UWAL-1021 BAC C-6 BOOSTER B1N1
 (AU1D56) UWAL-1021 BAC C-6 BOOSTER B1V1N1
 (AU1D76) UWAL-1021 BAC C-6 BOOSTER B1W1H1N1
 (AU1D86) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1
 (AU1D9A) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1


HACH 0.153

ALPHA

0.000
0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION

REFS	4.4262	SQ FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8606	INCHES
SCALE	2.9920	PERCNT




DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ALPHA	
(AU1016)	UWAL-1021 BAC C-6 BOOSTER	B1	0.000
(AU1026)	UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000
(AU1056)	UWAL-1021 BAC C-6 BOOSTER	B1V1N1	0.000
(AU1076)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1N1	0.000
(AU1086)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1	0.000
(AU109A)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1	0.000

MACH 0.153

REFERENCE INFORMATION
REFS 4 4209 SQ.FT.
REFL 10.1000 INCHES
REFB 66 6000 INCHES
XMRP 55.6360 INCHES
YMRP 0.0000 INCHES
ZMRP 5.8600 INCHES
SCALE 2.9920 PERCENT

PITCHING MOMENT COEFFICIENT, CLM

CONFIGURATION BUILDUP IN YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU1016) UWAL-1021 BAC C-6 BOOSTER
 (AU1026) UWAL-1021 BAC C-6 BOOSTER
 (AU1056) UWAL-1021 BAC C-6 BOOSTER
 (AU1076) UWAL-1021 BAC C-6 BOOSTER
 (AU1086) UWAL-1021 BAC C-6 BOOSTER
 (AU109A) UWAL-1021 BAC C-6 BOOSTER

MACH 0.153


ALPHA

B1 0.000
 D1N1 0.000
 B1VIN1 0.000
 B1W1I1N1 0.000
 B1W1H1V1 0.000
 B1W1H1V1N1 0.000

REFERENCE INFORMATION

REFS	4.4200	SQ.FT
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XNRP	55.6360	INCHES
YNRP	0.0000	INCHES
ZNRP	5.8600	INCHES
SCALE	2.9920	PERCNT

CONFIGURATION BUILDUP IN YAW




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU1026) UWAL-1021 BAC C-6 BOOSTER
 (AU1056) UWAL-1021 BAC C-6 BOOSTER
 (AU1076) UWAL-1021 BAC C-6 BOOSTER
 (AU1086) UWAL-1021 BAC C-6 BOOSTER
 (AU109A) UWAL-1021 BAC C-6 BOOSTER

B1N1 ALPHA
 B1V1N1 0.000
 B1W1H1N1 0.000
 B1W1H1V1 0.000
 B1W1H1V1N1 0.000

REFERENCE INFORMATION
 REFS 4.42G3 SQ.FT.
 REFL 10 1950 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.153

CONFIGURATION BUILDUP IN YAW


DATA SET SYMBOL CONFIGURATION DESCRIPTION

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	B1	B1N1
(AU1D16)	UWAL-1021 BAC C-6 BOOSTER	B1	0.000
(AU1D26)	UWAL-1021 BAC C-6 BOOSTER	B1N1	0.000
(AU1D56)	UWAL-1021 BAC C-6 BOOSTER	B1V1N1	0.000
(AU1D76)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1N1	0.000
(AU1D86)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1	0.000
(AU1D9A)	UWAL-1021 BAC C-6 BOOSTER	B1W1H1V1N1	0.000


MACH 0.153

ALPHA

0.000
0.000
0.000
0.000
0.000

REFERENCE INFORMATION		
REFS	4.42'D	SQ.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.992G	PERCNT

COMBINED PITCH AND YAW




DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU109A) UWAL-1021 BAC C-6 BOOSTER
 (AU1097) UWAL-1021 BAC C-6 BOOSTER
 (AU1098) UWAL-1021 BAC C-6 BOOSTER
 (AU1099) UWAL-1021 BAC C-6 BOOSTER

ALPHA
 B1W1H1VIN1 0.000
 B1W1H1VIN1 10.000
 B1W1H1VIN1 20.000
 B1W1H1VIN1 32.000

REFERENCE INFORMATION
 REFS 4.4230 SQ.FT
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

COMBINED PITCH AND YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AU109A) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1D97) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1D98) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1D99) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1

ALPHA

0.000
10.000
20.000
32.000


REFERENCE INFORMATION

PEFS	4.4230	SQ FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PER CENT

MACH 0.154

ROLLING MOMENT COEFFICIENT, CSL (STABILITY AXIS)

COMBINED PITCH AND YAW



SIDE SLIP ANGLE, BETA, DEGREES

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU109A) UWAL-1021 BAC C-6 BOOSTER
 (AU1097) UWAL-1021 BAC C-6 BOOSTER
 (AU1098) UWAL-1021 BAC C-6 BOOSTER
 (AU1099) UWAL-1021 BAC C-6 BOOSTER


ALPHA
 BIW1H1V1N1 0.000
 BIW1H1V1N1 10.000
 BIW1H1V1N1 20.000
 BIW1H1V1N1 32.000

REFERENCE INFORMATION
 REFS 4 42L0 SQ.FT
 REFL 10.1000 INCHES
 RCFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8860 INCHES
 SCALE 2.9920 PERCN

MACH 0.154

PAGE 132

COMBINED PITCH AND YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AUI097) UWAL-1021 BAC C-6 BOOSTER
 (AUI097) UWAL-1021 BAC C-6 BOOSTER
 (AUI098) UWAL-1021 BAC C-6 BOOSTER
 (AUI099) UWAL-1021 BAC C-6 BOOSTER


B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1
 B1W1H1V1N1

ALPHA
 0.000
 10.000
 20.000
 32.000

REFERENCE INFORMATION
 REFS - 4230 SQ.FT
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCENT

MACH 0.154

COMBINED PITCH AND YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU109A) UWAL-1021 BAC C-6 BOOSTER BIWIHIVIN1
 (AU1097) UWAL-1021 BAC C-6 BOOSTER BIWIHIVIN1
 (AU1098) UWAL-1021 BAC C-6 BOOSTER BIWIHIVIN1
 (AU1099) UWAL-1021 BAC C-6 BOOSTER BIWIHIVIN1


SIDE SLIP ANGLE, BETA, DEGREES

ALPHA
0.000
10.000
20.000
32.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 RFFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRF 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRF 5.8600 INCHES
 SCALE 2.9920 FERNT

MACH 0.154

COMBINED PITCH AND YAW



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU109A) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1097) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1098) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1
 (AU1099) UWAL-1021 BAC C-6 BOOSTER B1W1H1V1N1


ALPHA
0.000
10.000
20.000
32.000

REFERENCE INFORMATION
 REFS 4.4200 SQ.FT.
 REFL 10.1000 INCHES
 REFB 66.6000 INCHES
 XMRP 55.6360 INCHES
 YMRF 0.0000 INCHES
 ZMRP 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

BASE DRAG COEFFICIENT, CDB

COMBINED PITCH AND YAW



SIDE SLIP ANGLE, BETA, DEGREES

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AU109A) UWAL-1021 BAC C-6 BOOSTER
 (AU1097) UWAL-1021 BAC C-6 BOOSTER
 (AU1098) UWAL-1021 BAC C-6 BOOSTER
 (AU1099) UWAL-1021 BAC C-6 BOOSTER

ALPHA
 B1W1H1V1N1
 0.000
 B1W1H1V1N1
 10.000
 B1W1H1V1N1
 20.000
 B1W1H1V1N1
 32.000


REFERENCE INFORMATION
 REFS 4.4203 SQ.FT.
 REFL 10 1G:00 INCHES
 REFB 66.6000 INCHES
 XHRF 55.6360 INCHES
 YHRF 0.0000 INCHES
 ZHRF 5.8600 INCHES
 SCALE 2.9920 PERCNT

MACH 0.154

PAGE 136

LATERAL FORCE COEFFICIENT. CY

COMBINED PITCH AND YAW



YAWING MOMENT COEFFICIENT. CLN (STABILITY AXIS)

DATA SET SYMBOL CONFIGURATION DESCRIPTION

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ALPHA
(AU109A)	UWAL-1021 BAC C-6 BOOSTER	0.000
(AU1097)	UWAL-1021 BAC C-6 BOOSTER	10.000
(AU1098)	UWAL-1021 BAC C-6 BOOSTER	20.000
(AU1099)	UWAL-1021 BAC C-6 BOOSTER	32.000

REFERENCE INFORMATION		
REFS	4.4200	SQ.FT.
REFL	10.1000	INCHES
REFB	66.6000	INCHES
XMRP	55.6360	INCHES
YMRP	0.0000	INCHES
ZMRP	5.8600	INCHES
SCALE	2.9920	PERCNT

MACH 0.154