BundleFuse: From Prior Work to the Research Question

5 November 2026

This document develops the motivation and positioning before the experimental case. Its purpose is to explain what is inherited, what question is being asked, and how the implemented construction addresses that question. It is a focused positioning argument, not an exhaustive literature review or a claim of established priority. The accompanying technical note defines the exact scores and their assumptions.

1 Begin with the kind of relationship the task requires

A partial bundle specifies a context for choosing another item. A camera bag can complete a camera kit even though its appearance and function differ from the camera. A second camera may be more similar but less useful as a completion. Thus a useful ranking must represent the relationship required by the context, rather than assume that resemblance always implies suitability.

This distinction has an established basis. McAuley, Pandey and Leskovec model substitutable and complementary product links using product-associated information, including review text and category structure [1]. Their work motivates relation-sensitive recommendation. It does not establish that every pair from different categories is complementary, or that a category rule solves compatibility.

For bundle completion, the relationship can also vary by domain. Repetition of a product role can be undesirable in an outfit, while a shared artist can be useful in a playlist. This motivates retaining several precisely defined relationship scores. It does not justify assuming that all of them are useful everywhere.

2 What explicit recommendation models already establish

Item-relation methods provide a natural starting point: score a candidate by its relationships to the observed items. Let $\mathcal{I}$ be a catalogue, S its observed subset, $c \notin S$ a candidate, and M_{cs} an estimated relation between c and s. The additive score is

$$r(c \mid S) = \sum_{s \in S} M_{cs}.$$

This notation describes a class of estimators; it is not presented as a new formula.

EASE demonstrates that a shallow linear recommendation model with a closed-form solution can achieve strong ranking performance [2]. Side-information extensions of SLIM already combine purchase histories and item attributes in a regularized linear model [3]. More recently, the FEASE preprint extends EASE with user and item side features for cold-start handling [4].

These works constrain our claim. Explicit scoring, side-information fusion and the absence of a deep downstream encoder are established possibilities. Furthermore, a model originally formulated

for user histories can often be applied to an observed item set. Merely renaming a history as a partial bundle does not create a new method.

The remaining design issue for this work is more specific: *which relations should an explicit estimator preserve when completing bundles, and how should their scores be combined?* Historical overlap, category relations and descriptive resemblance are related measurements, but they are not interchangeable definitions of compatibility.

3 What modern bundle construction already addresses

CLHE directly addresses sparse bundle histories by combining multimodal features, item-level user feedback and bundle composition. It uses hierarchical self-attention and item- and bundle-level contrastive objectives [5]. Its motivation already includes the observation that features can be available for items with little bundle history. BundleFuse must acknowledge that motivation as prior work.

RaMen develops characteristic and collaborative strategies together with hypergraph structure to learn bundle representations [6]. It explicitly models multiple kinds of relationships. A claim that earlier bundle models consider only similarity, ignore direct item associations, or neglect multi-item structure would misrepresent this comparator.

These papers motivate a question about the *construction of the predictor*. They do not imply that another learned encoder is the only way to use the available information, nor that their representation learning is unnecessary. That issue is comparative and must be investigated.

4 State the question without inventing an unaddressed problem

The research question is:

> Given historical bundles and available item attributes, how far can explicit, relation-specific compatibility estimates support bundle completion without training a new neural bundle encoder?

This asks about the usefulness and limits of a particular alternative construction. It does not assert that no earlier model combines these inputs. Its value depends on defining a nontrivial construction, explaining its choices, and eventually showing what those choices achieve relative to appropriate alternatives.

The distinction from neural bundle encoders is that the relevant relationships enter as directly computed candidate scores. The distinction from a generic linear recommender must be established through the specific relation constructions and combination rule, not merely through the claim that the method is simple.

5 Develop the construction from that question

5.1 Preserve directly observed relations

Let B be the binary training-bundle by item matrix and let x_S be the indicator vector of S. Then $(B^\top B x_S)_c$ counts recorded co-memberships with the query items. BundleFuse uses weighted overlap and alternative summaries of history to reduce particular effects of frequency, bundle size and sparse direct observations. This step inherits the explicit item-relation perspective. Its

particular weights and summary operators are modeling choices, not consequences of the cited papers.

5.2 Share evidence while retaining the type of relationship

Exact co-occurrence has no direct evidence for an unobserved pair. BundleFuse also constructs category relations and scores from descriptive features. Category relations aggregate observations across items, while feature relationships extend coverage beyond recorded pairs. The category component can distinguish support between categories from penalties for repeating a rarely repeated category.

These choices connect the relation-sensitive view to an explicit score construction. They do not identify economic substitutes or complements from category labels alone. The distinction is operational: each formula specifies which observed relationship it measures and what response it assigns to the candidate.

Category or cluster centering of descriptors and graph-adjusted features provide further candidate estimators. Their purpose is to separate a group's mean descriptor from within-group variation and to combine descriptions with historical relationships. These operations are not proofs of disentanglement. Their individual utility remains an empirical question. The complete method should disclose each operation, even when several share one conceptual role.

5.3 Combine scores with different scales and coverage

Let $r_h(c \mid S)$ denote raw channel h, let $z_h(c \mid S)$ be its catalogue-standardized value for the query, and let $w_h \geq 0$ be its validation-selected weight. The additive core is

$$Y_0(c \mid S) = \sum_h w_h z_h(c \mid S).$$

This exposes the construction to inspection: the meaning of a channel, its scale transformation and its contribution to a candidate score are explicit. It does not make channels independent or their weights causally interpretable. The use of validation to choose weights is fitting, even without neural gradient training.

The signal menu therefore belongs inside the explanation of these relation estimates. It is not a list of independent novelty claims. A convincing presentation must explain why each family is considered, state its overlap with other families, and identify which components survive selection in the reported model.

5.4 Introduce optional corrections after the core

Let Y be the combined score including any selected multi-item corrections, and μ_0 a scaled fallback assembled from a restricted set of channels. Let f_c be the number of candidate appearances in training and $\kappa > 0$ the fallback strength. The backoff score is

$$\theta(c \mid S) = \frac{f_c}{f_c + \kappa} Y(c \mid S) + \frac{\kappa}{f_c + \kappa} \mu_0(c \mid S).$$

It provides an explicit rule for changing the balance with candidate history. Frequency is a proxy for available historical evidence, not a calibrated uncertainty. The two estimates overlap; the fallback is not a history-independent expert.

Related empirical-Bayes product-search work already combines behavioral information with non-behavioral priors [7]. Consequently, neither interpolation nor shrinkage toward descriptive evidence

is new by itself. BundleFuse's specific fallback, its overlap with the combined score, and the candidate-frequency rule must be defined and defended in the bundle setting. The technical note gives a pointwise regularization interpretation without assuming a validated noise model.

The incidence surplus and Rao-based term address an additional question: can support involving several observed items change the assessment beyond separate matches? They are explicit optional corrections. Their presence does not establish that higher-order interactions are the principal explanation of the method's accuracy.

6 State the contribution at the level the construction supports

The proposed methodological contribution is the *particular explicit scoring construction for bundle completion*: historical relation estimates, category and descriptive estimates, query-wise scale alignment, and specified optional corrections. The paper must distinguish those design choices from the established ingredients. A coherent combination can be useful, but naming its ingredients differently does not establish novelty.

The central hypothesis is that carefully constructed relation scores provide a competitive and inspectable alternative for this task. This is an affirmative, testable hypothesis. It does not require asserting that neural models are excessive, that all low-rank representations lose necessary information, or that the scorer has a universal computational advantage.

A reviewer may reasonably ask whether BundleFuse is a feature-engineered ensemble. The descriptive answer is that it combines engineered scores. The scientific answer must specify the relationships those scores encode, why those relationships matter for completion, and the distinctive behavior of the resulting estimator. A new technical principle cannot be inferred solely from benchmark wins. The contribution may ultimately be a well-supported construction and analysis rather than a general new theory of recommendation.

7 An introduction built from this path

Completing a bundle requires selecting items that are appropriate companions to those already present. Prior work on product relationships distinguishes substitutability from complementarity, establishing that relevance to an item need not mean resemblance [1]. For completion, historical co-membership supplies direct relational evidence, while item attributes allow that evidence to extend beyond exact observed pairs.

Both explicit and neural models have established ways to exploit such information. Shallow and side-information recommendation models demonstrate the viability of explicit scoring [2, 3, 4]; modern bundle models learn representations from several sources and relationships [5, 6]. These developments motivate examining the extent to which bundle compatibility can be estimated directly from specified relations, with the contributions of those relations remaining visible.

We investigate this question through BundleFuse. The method constructs historical, category and descriptive compatibility scores, places them on comparable scales, and selects their combination using validation examples. It also provides explicit candidate-frequency and multi-item corrections. This formulation makes the design question concrete: which relational estimates are useful for completing a bundle, and when do the corrections add information beyond their combination?

How this relates to the existing documents. This is the motivation and positioning that should precede `publication_argument_technical.tex`. The historical manuscript's introduction and related-work text contain stronger claims about cost, zero parameters, prior methods and

broad superiority that require reconciliation. They should not be used as the current statement of the contribution. Experimental evidence belongs after this argument and must remain within its verified scope.

References

[1] J. McAuley, R. Pandey, J. Leskovec. Inferring Networks of Substitutable and Complementary Products. KDD, 2015. https://cseweb.ucsd.edu/~jmcauley/pdfs/kdd15.pdf.

[2] H. Steck. Embarrassingly Shallow Autoencoders for Sparse Data. WWW, 2019. https://arxiv.org/abs/1905.03375.

[3] X. Ning, G. Karypis. Sparse Linear Methods with Side Information for Top-N Recommendations. WWW 2012 companion/poster version. https://archives.iw3c2.org/www2012/proceedings/companion/p581.pdf.

[4] E. D. Cui, L. Zhang, W. P. Lee. Shallow AutoEncoding Recommender with Cold Start Handling via Side Features. Preprint, 2025. https://arxiv.org/abs/2504.02288v4.

[5] Y. Ma et al. Leveraging Multimodal Features and Item-level User Feedback for Bundle Construction. WSDM, 2024. https://arxiv.org/abs/2310.18770.

[6] H.-S. Nguyen et al. RaMen: Multi-Strategy Multi-Modal Learning for Bundle Construction. Preprint, 2025. https://arxiv.org/abs/2507.14361.

[7] C. Han et al. Addressing Cold Start in Product Search via Empirical Bayes. CIKM, 2022. https://doi.org/10.1145/3511808.3557066.