BundleFuse, Component by Component

How every piece is built—from the raw data to the final score—with no hand-waving

Study note

Abstract

This note explains *how* BundleFuse *actually works*, one component at a time, in plain language. For every piece we answer three questions in order: **(i) what is it in general** (the textbook idea), **(ii) how is it defined *here*** (the exact quantities this code plugs into that idea—because "PMI" and "SVD" mean nothing until you say *PMI of what* and *SVD of which matrix*), and **(iii) a worked numerical example** on one tiny dataset carried through the whole note. Where the method consumes pretrained **embedding vectors**, we say so explicitly and give their exact dimensions and origin. Nothing here is guessed: every formula is read off `bundlefuse/operators.py` and `bundlefuse/fullrank_eval.py`, and every number in the running example is machine-verified.

Contents

1 How to read this note **2**

2 What we start with: the raw inputs **2**
2.1 The items, the bundles, and the incidence matrix 2
2.2 The embedding features — stated explicitly 3
2.3 The side labels: categories, artists, albums 4

3 Three structures we derive immediately **5**

4 The vocabulary of operations (general idea → local definition → example) **5**
4.1 Co-occurrence scoring: "who shows up with the seeds" 6
4.2 PMI / PPMI: "is this pair together *more than chance*?" 6
4.3 Truncated SVD: a dense "collaborative fingerprint" per item 7
4.4 Degree normalisation: taming hubs and big bundles 8
4.5 Graph propagation: a two-hop smoothing walk 9

5 The signals, built one by one **9**
5.1 Collaborative family (from B only — no embeddings) 10
5.2 Taxonomic family (from category/artist/album labels) 11
5.3 Content family (from the embedding vectors) 12

6 From a signal to per-query numbers: scoring and standardising **13**

7 Fusion: four stages to the final score **13**
7.1 Why validate at NDCG@20 — and why not a "cutoff-free" loss 16

8 The ledger: what is learned vs. fixed **17**

1 How to read this note

BundleFuse solves **bundle completion**: you are shown a few items that belong together (the *seeds* S—part of an outfit, a playlist, a shopping basket) and you must rank the rest of the catalogue so the genuine missing members come out on top. The method does this by computing many cheap "opinions" about each candidate item—co-occurrence, taxonomy, content similarity—**standardising** them onto a common scale, **blending** them with a handful of weights picked on a validation set, and finally **routing** the blend against a cold-start fallback so that rarely-seen items are still rankable. *The scoring core trains no neural network and has zero learned weights*; the only numbers "learned" are a few dials chosen by grid search on validation data. Embedding vectors *are* used, but they are **fixed inputs** shipped with the datasets, not things we train (§2). Figure 1 is the whole method on one line—a partial bundle in, a completed bundle out—and every later section just explains one of its boxes.




Figure 1. The whole method on one line: a partial bundle in, a completed bundle out. Given the seeds S (here $\{1\}$), every catalogue item $c \notin S$ is scored by three families of cheap "opinions"—collaborative co-occurrence, taxonomy, and content similarity—each *standardised* to a z-score. A validation-tuned weighted blend Y (Stages 1–2) is combined *per candidate* with a cold-start prior μ_0 (Stage 3) by frequency routing $u_c = \kappa/(f_c + \kappa)$ (Stage 4); the catalogue is then ranked and the seeds removed, giving the filled bundle. Every remaining section explains one box; the exact numbers for this toy query are carried all the way to Fig. 15, where $\hat{\theta}$ ranks $2 \succ 4 \succ 3$.

The note is bottom-up. §2–§3 define what we start with. §4 defines the five recurring *operations* (co-occurrence, PMI, SVD, degree normalisation, graph propagation) precisely as used here. §5 builds every individual *signal* from those operations. §6 turns a signal into per-query numbers. §7 is the four-stage fusion that produces the final score. §8 is the ledger of what is learned versus fixed.

The running toy dataset (used in every example). Catalogue of $n = 4$ items $\{1, 2, 3, 4\}$ and three training bundles

$$b_1 = \{1, 2, 3\}, \qquad b_2 = \{1, 2, 4\}, \qquad b_3 = \{2, 3\}.$$

2 What we start with: the raw inputs

2.1 The items, the bundles, and the incidence matrix

The **catalogue** is a finite set of items $\mathcal{I} = \{1, \ldots, n\}$. The **training data** is a collection of m bundles $\mathcal{B} = \{b_1, \ldots, b_m\}$, each a subset of items. We record them once in a **bundle–item incidence matrix**

$$B \in \{0, 1\}^{m \times n}, \qquad B_{ji} = \begin{cases} 1 & \text{item } i \text{ is in bundle } j \\ 0 & \text{otherwise.} \end{cases}$$

Every bundle is a *row*; every item is a *column*. This single matrix is the backbone of every collaborative signal. (In code: `SimplicialGraphOperator` builds `self.B` and its binary version `self.B_bin`.)

Example 1 (the incidence matrix). For the toy dataset,

$$B = \begin{pmatrix} 1 & 1 & 1 & 0 \\ 1 & 1 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{pmatrix} \begin{array}{l} \leftarrow b_1 = \{1,2,3\} \\ \leftarrow b_2 = \{1,2,4\} \\ \leftarrow b_3 = \{2,3\} \end{array}$$




Figure 2. *The bundle–item graph of the toy data.* Each edge is a 1 in B. The **degree of an item** (number of edges) is its frequency f: item 2 has 3 edges ($f_2 = 3$), item 4 has one ($f_4 = 1$). Two items **co-occur** ($C_{ci} > 0$) exactly when they connect to a common bundle box: items 1 and 2 share b_1 and b_2 (so $C_{12} = 2$), while items 3 and 4 share no box ($C_{34} = 0$). Every collaborative signal in this note is some way of reading this one picture.

2.2 The embedding features — stated explicitly

Besides the bundles, each item carries **pretrained embedding vectors**: fixed real-valued feature vectors that describe the item's *content* (what it looks like, what it is called, what it sounds like). **BundleFuse does not train these. It loads them from the public dataset release and treats them as constants.** They enter only the *content* and *soft-category* signals (§5.3, §5.2); the collaborative and taxonomic signals never touch them. The exact tensors (read in `fullrank_eval.py`, lines 118–133) are:

File on disk	Role in code	Shape (e.g. POG)	What it is
`title_emb.npy`	`feats["content"]`	48676×512	text embedding of the item *title*
`content_feature.pt`	`feats["image"]` (fashion)	48676×768	*image* embedding of the product photo
	`feats["audio"]` (music)	254155×512	*audio* embedding of the track
`description_feature.pt`	`feats["desc"]`	48676×768	text embedding of the *description*

Where every vector comes from (so no number is unexplained). There are two distinct sources, and we name both. *(i) Image / description / audio — from the public release.* `content_feature.pt` and `description_feature.pt` are the pre-extracted features shipped with the public BundleConstruction release (Liu et al., *Fine-tuning Multimodal LLMs for Product Bundling / Bundle-MLLM*, KDD 2025) and consumed unchanged — the same features the heavy baselines use. Their origin is documented in the **CLHE** paper (Ma et al., "Leveraging Multimodal Features and Item-level User Feedback for Bundle Construction," WSDM 2024;

arXiv:2310.18770), whose dataset the BundleConstruction release *is*, and corroborated by RaMen (ECAI 2025, §3.1.2): for POG the visual and textual vectors are produced by **pre-trained BLIP** (Li et al., "BLIP: Bootstrapping Language-Image Pre-training," ICML 2022), hence their 768 dimensions; for Spotify the audio vector is produced by **CLAP** (Wu et al., "Large-scale Contrastive Language–Audio Pretraining," 2023), which is why Spotify's content vector is 512-d (CLAP's native embedding size) rather than 768-d. The release *also* ships LightGCN collaborative features (`item_cf_feature.pt`, `*_LightGCN_bi_feature.pt`), which we deliberately do **not** load — reusing precomputed collaborative features under our re-split would leak held-out co-occurrence (it once manufactured a 16× phantom win on POG); we rebuild every collaborative signal from the train fold instead. *(ii) Title — generated by us.* `title_emb.npy` (48676×512) is **not** from the release and **not** a mystery: *we* produce it with the script `embed_titles.py`, which runs a frozen `BAAI/bge-small-zh-v1.5` Chinese sentence-encoder (via `sentence_transformers`, `normalize_embeddings=True`) over the POG item titles — which are in Chinese, since POG is Alibaba iFashion. Its 512 dimensions are exactly that model's hidden size; the companion `title_emb_large.npy` (1024-d) is the identical script with `BAAI/bge-large-zh-v1.5`. So every content input is now sourced: BLIP (release, via CLHE) for POG image/description, CLAP (release, via CLHE) for Spotify audio, and a frozen BGE encoder (ours) for the POG titles.
Every vector is L_2**-normalised** on load (`_loadpt`: $x \leftarrow x/\|x\|_2$), so a dot product between two of them is a cosine similarity in $[-1, 1]$. For POG the three are concatenated into a single $512{+}768{+}768 = 2048$-dimensional multimodal vector (`mm_feat`) used for clustering; for music only the 512-d audio vector exists (the code detects this via the *absence* of `title_emb.npy` and sets the internal `MUSIC` flag).

Not every dataset uses an external encoder. The table above is for POG and Spotify only. On the e-commerce sets (Electronic/Food/Clothing) and the grocery set (Dunnhumby) there is **no pretrained embedding at all**: the content signal is a plain **TF–IDF** vector of the item's own text fields (department / commodity / brand / title), reduced by truncated SVD, computed *inside* the pipeline (`bundlerec_eval.py`:106; `dunnhumby_eval.py`:80–83). So "content" means two different things depending on the dataset — a deep BLIP/CLIP embedding on POG/Spotify, a classical bag-of-words vector on the e-commerce/grocery sets — and we say so plainly rather than imply one uniform source. **If a dataset ships neither, the content signals are simply absent and the method runs on collaborative+taxonomic evidence alone.**

Deployment consequence. Because the POG/Spotify content signals are *functions of these encoders' outputs*, serving the method on a genuinely new item requires first running the same encoders (BLIP on the item's image and description and BGE on its title for fashion, or CLAP on the track for music) to embed it, before any content/soft-category signal can place it. The TF–IDF datasets need no external model — only the item's text. We state this so the true dependency footprint is explicit: the "zero-parameter" claim is about the *scorer* (it fits no weights by gradient descent), not about these upstream feature extractors, which are a real deployment prerequisite wherever deep content features are used.

2.3 The side labels: categories, artists, albums

Each item also has discrete **metadata labels**. For fashion that is an explicit category id `cate` (e.g. "boots"); for music it is the `artist_uri` and `album_uri`. We store them as integer label vectors $\text{cat} \in \{0, \ldots, C-1\}^n$ (and, for music, alb). When a dataset has *no* usable category, the code manufactures one by running k-means (400 clusters) on the multimodal embedding and using the

cluster id as a pseudo-category (`fullrank_eval.py`:146–156). These labels feed the *taxonomic* signals (§5.2).

3 Three structures we derive immediately

Everything collaborative is built from three quantities read straight off B.

(1) Item frequency f. How many training bundles contain each item:

$$f = B^\top \mathbf{1}_m \in \mathbb{Z}^n, \qquad f_i = \#\{\text{bundles containing } i\}.$$

An item with $f_i = 0$ is **cold** (never seen in training); cold items are exactly where the collaborative signals go silent and the prior has to take over (§7). In code: `self.freq = B.sum(0)`.

(2) Co-occurrence matrix C. How often each *pair* of items shares a bundle, with the diagonal removed (we never "co-occur" an item with itself):

$$C = B^\top B, \qquad C_{ii} \leftarrow 0.$$

C_{ci} = number of training bundles containing both c and i. In code: `self.C = (B.T @ B)` then `C.setdiag(0)`.

(3) Bundle sizes. $|b_j| = \sum_i B_{ji}$, used to down-weight large bundles (a pair that co-occurs inside a 20-item playlist is weaker evidence than a pair that co-occurs inside a 2-item set). In code: `self.bsize`.

Example 2 (the three structures). From B in Example 1:

$$f = \begin{pmatrix}2\\3\\2\\1\end{pmatrix}, \qquad B^\top B = \begin{pmatrix}2&2&1&1\\2&3&2&1\\1&2&2&0\\1&1&0&1\end{pmatrix} \xrightarrow{\text{zero diag}} C = \begin{pmatrix}0&2&1&1\\2&0&2&1\\1&2&0&0\\1&1&0&0\end{pmatrix}.$$

Read C as: items 1 and 2 share 2 bundles; items 3 and 4 never share one. Item 2 is the most frequent ($f_2 = 3$); item 4 the rarest ($f_4 = 1$).




Figure 3. *The collaborative pipeline, built once from the bundles alone.* The bundle–item matrix B becomes the item–item co-occurrence $C = B^\top B$ (diagonal zeroed); C becomes the chance-corrected PPMI (§4.2); and a truncated SVD of PPMI gives each item a dense "collaborative fingerprint" u_i (§4.3). The partial bundle is *not* involved yet: these are fixed structures a query is later scored *against*.

4 The vocabulary of operations (general idea → local definition → example)

Five operations recur throughout. Each is a standard idea, but what matters is *the exact quantity it is applied to here*. This section pins that down; §5 then just assembles them.

4.1 Co-occurrence scoring: "who shows up with the seeds"

General. The simplest bundle signal: score a candidate c by how often it co-occurred with the seed items. If $x_S \in \{0,1\}^n$ is the **seed indicator** ($(x_S)_i = 1$ iff $i \in S$), then

$$\mathrm{cooc}(c \mid S) = \sum_{i \in S} C_{ci} = (C\, x_S)_c.$$

A matrix–vector product: the score vector is column-combination of C selected by the seeds.

Here. Exactly this, with C the zero-diagonal co-occurrence matrix above. In code the seed indicators for a whole batch of queries are stacked into a sparse matrix `Ind` ($n \times \mathrm{nb}$, one column per query) and the batch of score vectors is the single product `C @ Ind` (`fullrank_eval.py`:262). This "$W\, x_S$" shape is the template for *every* collaborative signal.

Example 3 (co-occurrence scores). Query $S = \{1\}$, so $x_S = (1,0,0,0)^\top$ and Cx_S is column 1 of C:

$$Cx_S = (0,\ 2,\ 1,\ 1)^\top.$$

Excluding the seed, the ranking is $2 \succ 3 \sim 4$: item 2 (shared 2 bundles with item 1) wins. Hold this result—PMI will *overturn* it.

$$\underbrace{\begin{pmatrix} 0 & 2 & 1 & 1 \\ 2 & 0 & 2 & 1 \\ 1 & 2 & 0 & 0 \\ 1 & 1 & 0 & 0 \end{pmatrix}}_{C} \quad \underbrace{\begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix}}_{x_S,\ S=\{1\}} \quad = \quad \underbrace{\begin{pmatrix} \cdot \\ 2 \\ 1 \\ 1 \end{pmatrix}}_{\mathrm{score}(\cdot \mid S)}$$

Figure 4. *Filling a partial bundle is one matrix–vector product.* The seed indicator x_S carries a 1 in each seed slot, so Cx_S **sums the seed columns of** C. For $S = \{1\}$ it reads off column 1: candidate 2 scores 2, candidates 3, 4 score 1; the seed itself ($c = 1$, shown "$\cdot$") is masked to $-\infty$ before ranking. *Every* collaborative signal has this exact shape Wx_S—only the matrix W changes (raw C, PPMI, the degree-normalised W_{pair}, or the household operator).

4.2 PMI / PPMI: "is this pair together *more than chance*?"

General. Raw co-occurrence is biased toward popular items: a hub co-occurs with everything. Pointwise Mutual Information corrects for that by comparing the *joint* probability of a pair to the product of their *marginals*:

$$\mathrm{PMI}(i,j) = \log \frac{P(i,j)}{P(i)\,P(j)}.$$

It is positive when i, j appear together more than independence predicts, negative when less. The *positive* part, $\mathrm{PPMI} = \max(0, \mathrm{PMI})$, keeps only genuine associations (and is what makes the matrix sparse and well-behaved for the SVD below).

Here — and this is the subtle part. The probabilities are estimated **from the co-occurrence matrix** C **itself**, not from item frequencies f. Let

$$d_i = \sum_j C_{ij} \quad \text{(row sum of } C, \text{ the "co-occurrence degree" of } i), \qquad T = \sum_{i,j} C_{ij} \quad \text{(grand total)}.$$

Then the *joint* is $P(i,j) = C_{ij}/T$ and the *marginals* are $P(i) = d_i/T$, giving

$$\mathrm{PPMI}_{ij} = \max\Big(0,\ \log \frac{C_{ij}\,T}{d_i\,d_j}\Big), \qquad d_i = \textstyle\sum_j C_{ij}, \quad T = \textstyle\sum_{i,j} C_{ij}.$$

Note what the "marginal" is here: the co-occurrence degree d_i (how much total pairing mass item i carries), not the bundle-frequency f_i. These differ—e.g. a popular item in many *singleton-ish* bundles has high f but modest d. The code (`operators.py`:103–107) uses precisely d and T derived from C: `freq_c = C.sum(1)`, `totc = C.sum()`. The same construction is reused verbatim for *category* co-occurrence and for *soft-cluster* co-occurrence (§5.2)—same formula, different "vocabulary" (items, categories, or clusters).

Example 4 (PPMI overturns raw co-occurrence). Degrees are the row sums of C from Example 2: $d = (4, 5, 3, 2)$, and $T = 14$. Then, e.g.,

$$\mathrm{PMI}(1,2) = \log \frac{2 \cdot 14}{4 \cdot 5} = \log 1.4 = 0.336, \qquad \mathrm{PMI}(1,4) = \log \frac{1 \cdot 14}{4 \cdot 2} = \log 1.75 = 0.560.$$

The full positive matrix is

$$\mathrm{PPMI} = \begin{pmatrix} 0 & 0.336 & 0.154 & 0.560 \\ 0.336 & 0 & 0.624 & 0.336 \\ 0.154 & 0.624 & 0 & 0 \\ 0.560 & 0.336 & 0 & 0 \end{pmatrix}.$$

Now re-score query $S = \{1\}$ (column 1): (0, 0.336, 0.154, 0.560), ranking

$$\boxed{4 \succ 2 \succ 3} \qquad \text{(was } 2 \succ 3 \sim 4 \text{ under raw co-occurrence).}$$

Item 4 jumped to first. Why: item 4 is rare ($d_4 = 2$), so its single shared bundle with item 1 is "surprising" and informative, whereas item 2 is a hub ($d_2 = 5$) that pairs with everyone, so sharing two bundles with it is partly explained by chance. That reweighting is the entire point of PMI, and it is why we keep a PPMI channel alongside raw co-occurrence.




Figure 5. *Same query, two signals, opposite winners.* Raw co-occurrence (blue) crowns the *hub* item 2; PPMI (orange), by dividing out each item's popularity, crowns the *rare-but-exclusive* item 4. The PPMI bars are shorter in absolute terms (they are log-ratios), but standardisation in §6 removes that scale difference—what survives into the blend is the *ordering*.

4.3 Truncated SVD: a dense "collaborative fingerprint" per item

General. A truncated singular value decomposition approximates a matrix by the best rank-k product $M \approx U\Sigma V^\top$; the rows of $U\Sigma$ (here we keep U) are a k-dimensional *embedding* of the objects, capturing their dominant patterns of variation while discarding noise.

Here. The SVD is taken of the **item–item PPMI matrix**, *not* of a user–item rating matrix. With $k = 128$ (`TruncatedSVD(n_components=128)` on `self.PPMI`, `operators.py`:108–111), we get a 128-dimensional vector per item and L_2-normalise each row:

$$U = \mathrm{SVD}_{128}(\mathrm{PPMI}), \qquad u_i = U_i / \|U_i\|_2.$$

Think of u_i as item i's "collaborative fingerprint": two items get similar fingerprints when they pair with *similar sets of partners*, even if they never co-occur *directly*. This is the only embedding the method builds itself, and it is built from co-occurrence alone—no external features. It is stored as `self.Ucsvd` and exposed as the signal `csvd`.

Remark 1 (direct vs. indirect association). Raw co-occurrence and PPMI see only *direct* pairs ($C_{ci} > 0$). The SVD fingerprint sees *second-order* structure: items 3 and 4 never co-occur ($C_{34} = 0$), yet both co-occur with $\{1, 2\}$, so their fingerprints are pulled closer. This is how the collaborative side reasons about pairs it has never literally observed together.




Figure 6. *The fingerprint sees partners-of-partners, not just direct pairs.* These are the **exact** rank-2 L_2-normalised fingerprints u_i of the toy PPMI (machine-computed, x-sign flipped for display). Items 3 and 4 **never co-occur** ($C_{34} = 0$), yet their fingerprints are almost identical ($\cos = 0.98$) because both pair with $\{1, 2\}$; the hubs 1, 2 likewise sit together ($\cos = 0.90$). The `csvd` score of a candidate is the cosine between its fingerprint and the seeds' *average* fingerprint—so a partial bundle recalls items with the same *company*, even ones never literally seen with it.

4.4 Degree normalisation: taming hubs and big bundles

General. Popular items and large bundles dominate raw sums. We damp them with two monotone discounts.

Here. Two fixed vectors (`operators.py`:79–81), with smoothing constants read directly from code:

$$\underbrace{(f_i + 5)^{-0.5}}_{\text{item discount}} \quad \text{and} \quad \underbrace{(|b| + 1)^{-0.5}}_{\text{bundle-size discount}} .$$

The "+5" and "+1" are smoothing (they stop rare items/small bundles from blowing up); the exponent 0.5 is a square-root taming. These assemble into the **degree-normalised pairwise operator**

$$W_{\text{pair}} \;=\; B^{\top} \operatorname{diag}\big((|b| + 1)^{-0.5}\big)\, B \operatorname{diag}\big((f + 5)^{-0.5}\big), \qquad \operatorname{diag}(W_{\text{pair}}) = 0.$$

Reading it right-to-left: scale each seed column by its item discount, walk bundle→items weighting each bundle by its size discount, land back on items. So $W_{\text{pair}}(c \mid S) = \sum_{b \ni c} (|b|+1)^{-0.5} \sum_{s \in S \cap b} (f_s + 5)^{-0.5}$: a *smoothed, size-aware* co-occurrence. Setting both exponents to 0 recovers plain C (the case used in Examples 3–4 for clarity).




Figure 7. $W_{pair} = B^\top \operatorname{diag}((|b|+1)^{-1/2})\, B \operatorname{diag}((f+5)^{-1/2})$, *read right-to-left as a walk.* A seed's mass is first shrunk by its own popularity, carried up to the bundles it sits in (each discounted by its size), then back down to candidates. On the toy data the item discounts are $(f+5)^{-1/2} = (0.378, 0.354, 0.378, \mathbf{0.408})$: the *rarest* item 4 is damped least and the *hub* item 2 most—the same chance-correction PPMI applies, here multiplicative. Both exponents set to 0 recovers plain C.

4.5 Graph propagation: a two-hop smoothing walk

General. "Spread" a score across the item graph so that an item inherits a little evidence from its graph neighbours—one round of label propagation.

Here. The bipartite item↔bundle graph gives a zero-diagonal, symmetrically normalised one-step operator applied as a *factored* product (never materialised as a dense $n \times n$ matrix, which matters at $n = 254{,}000$): `propagate(X)` computes $B \to$ items then back, with the item discount on both ends and the self-term subtracted (`operators.py`:121–131). It is used two ways: (i) to produce a *two-hop* version `diff2` of the pairwise score, and (ii) to build the content "bridge" (§5.3) by smoothing content vectors over the co-purchase graph.




Figure 8. *One propagation step spreads a score two hops across the co-purchase graph.* Item c's evidence flows out to the bundles it belongs to and back down to *their* other members j, j' (both ends carrying the item discount, the self-term subtracted). Applied to the pairwise score it yields the two-hop signal `diff2`; applied to content vectors it builds the `bridge` (§5.3). It is the factored product $B^\top(\cdots)B$, never a dense $n \times n$ matrix—essential at $n = 254{,}000$.

5 The signals, built one by one

A **signal** is one scoring function $z_k(c \mid S)$: one opinion about each candidate. BundleFuse computes about eleven of them, in three families. For each we give *what it captures*, *the exact construction*, and *which embedding (if any) it uses.* (Code: `score_all_signals`, `fullrank_eval.py`:242–292.)

5.1 Collaborative family (from B only — no embeddings)

`cooc` Raw co-occurrence $C\,x_S$ (§4, Ex. 3). "How often did it ship with the seeds."

`ppmi` Chance-corrected co-occurrence PPMI x_S (§4.2, Ex. 4). "…more than chance would predict."

`csvd` Similarity to the seeds' average collaborative fingerprint: with U the PPMI-SVD embedding (§4.3), score candidate c by $\langle u_c,\ \frac{1}{|S|}\sum_{s\in S} u_s\rangle$. Captures *indirect* collaboration.

`simp` The degree-normalised pairwise score $W_{\text{pair}}x_S$ (§4.4) *plus* a higher-order "incidence surplus" Δ_{inc} described next.

`diff2` The two-hop propagated version of `simp` (§4.5): neighbours-of-neighbours.

`pop` Pure popularity, $\log(1+f_c)$, identical for every query. A backstop that knows nothing about S.

The higher-order incidence surplus Δ_{inc}. This is the one genuinely "set-level" collaborative term. Ordinary co-occurrence is *pairwise*: it treats S as a bag of seeds and sums seed-by-seed. Δ_{inc} instead rewards a candidate for appearing in training bundles that already contain *two or more* of the current seeds together (`score_simplicial_incidence_only`, `operators.py`:149–164):

$$\Delta_{\text{inc}}(c \mid S) = \sum_{b\ni c} (|b|+1)^{-0.5}\Big(\sum_{s\in b\cap S} (f_s+5)^{-0.5}\Big)\cdot\beta\cdot\max\big(0,\ |b\cap S|-1\big),$$

with $\beta = 1.5$. The factor $\max(0, |b\cap S|-1)$ is the crux: it is **zero unless a bundle overlaps the seeds in at least two items**, so $\Delta_{\text{inc}} \equiv 0$ for single-seed queries ($|S|=1$) and whenever no training bundle shares ≥ 2 seeds with S. It is a surplus *on top of* the pairwise term, not a replacement. *Honesty note: in our ablations this term moves Recall@20 by at most +0.79 points once the prior is in place; it is near-inert, and we report that rather than overselling it.*

Second-order "concordance" R_γ (Rao). A second set-level term (signal `rao`) scores a candidate by how strongly it is *simultaneously* pulled by *distinct, non-redundant* pairs of seeds, using Rao's quadratic-entropy kernel to discount seeds that are near-duplicates of each other (same category / similar embedding). With per-seed pulls $W_{\text{pair}}[\,\cdot, s]$ and a seed–seed redundancy kernel K_S,

$$R_\gamma(c \mid S) = \frac{\sum_{s\neq s'} K_S(s,s')\, W_{\text{pair}}[c,s]\, W_{\text{pair}}[c,s']}{\big(\sum_s W_{\text{pair}}[c,s]\big)+\tau},$$

(`score_rao_concordance`, `operators.py`:179–217; $\tau = 0.05$). The kernel K_S is built from the seeds' category labels *and* their content embeddings, so this signal *does* touch embeddings. Like Δ_{inc} it is a small corrective, reported honestly as such.




Figure 9. *Three collaborative opinions on $S = \{1\}$—and they disagree.* Bar heights are each signal's score *relative to its own top candidate* (raw values: `cooc`= $(2, 1, 1)$, `ppmi`= $(.34, .15, .56)$, `csvd`= $(.90, .55, .70)$ over items $2, 3, 4$). Raw co-occurrence and the SVD fingerprint back the *hub* item 2; chance-corrected PPMI backs the *rare-but-exclusive* item 4. This disagreement is exactly why fusion (§7) exists—no single collaborative signal is right everywhere.

5.2 Taxonomic family (from category/artist/album labels)

These answer "what *kinds* of things go with these kinds of things," and crucially they work for **cold** items (an unseen pair of jeans still has the category "jeans").

`cat` **Category complementarity**, via PMI *between categories*. Build a bundle×category count matrix T_c (how many items of each category each bundle holds), form the category co-occurrence $T_c^\top T_c$ (diagonal zeroed), and apply the *same PPMI formula* as §4.2 but over categories, giving $P_{\text{cat}} \in \mathbb{R}^{C \times C}$ (`operators.py`:262–269). Score a candidate by summing, over the seeds' categories, the category-PMI into the candidate's category: $\text{cat}(c \mid S) = \sum_{s \in S} P_{\text{cat}}[\text{cat}(s), \text{cat}(c)]$. ("Shirts complement trousers" emerges as a large P_{cat} entry.)

slot self-exclusion A *signed* correction added into `cat`: for a category that almost never repeats inside a bundle (you rarely put two hats in one outfit), it *subtracts* score from other items of that same category, discouraging duplicate slots (`score_slot_saturation`, `operators.py`:307–316). The threshold uses an empirical per-category duplication rate.

`homo` (music) **Homophily**: reward candidates by the same *artist* or *album* as the seeds, with album weighted twice as much as artist (`fullrank_eval.py`:273–275). Normalised by $\sqrt{\text{degree}}$ so prolific artists do not swamp the score.

`softcat` (fashion) **Soft/fuzzy categories**: run k-means (400 clusters) on the multimodal embedding, give each item a *soft* assignment (a softmax of cosine-to-centroids), and apply the same PPMI construction over the 400 clusters. This captures sub-type complementarity finer than the official category labels. **Uses embeddings** (for the clustering and soft assignment).




Figure 10. *Taxonomic scoring: category-to-category PMI, machine-computed on toy categories.* Assign the toy items categories A, B, C as shown; the *same* PPMI construction as Fig. 3, applied to the bundle×category counts, yields P_{cat}. For seed item 1 (category A) the candidate scores are just row A: item 2 wins because "A complements B" is a strong category pairing (0.65), item 4 gets a little (0.18), and same-category item 3 gets 0. Crucially this needs **no co-occurrence of the candidate itself**, so it scores cold items by *what they are*.

5.3 Content family (from the embedding vectors)

This family is where the §2.2 embeddings do their work. All three signals score a candidate by the cosine similarity of its (processed) content vector to the *average* content vector of the seeds: $\text{score}(c \mid S) = \left\langle \phi_c, \ \frac{1}{|S|} \sum_{s \in S} \phi_s \right\rangle$ for some processed feature ϕ (`fullrank_eval.py`:283–287). They differ in *which* ϕ:

`style` / `imgstyle` / `audiostyle` **Category-disentangled** content. Raw embeddings are dominated by "what category is this" (all boots look like boots), which is uninformative for *within-outfit* matching. `disentangle` (`operators.py`:323–330) subtracts the per-category mean embedding and renormalises, leaving only the *style* residual ("this boot's particular look"). Built separately for the title embedding (`style`), the image embedding (`imgstyle`), and the audio embedding (`audiostyle`).

`bridge` **Graph-bridged** content. Take the disentangled style vectors and smooth them one hop over the co-purchase graph (§4.5), then add that back: $\phi_{\text{bridge}} = \text{normalise}(\text{style} + 0.5 \cdot \mathcal{P}\,\text{style})$ (`build_dense_bridge`, `operators.py`:332–337). This lets content similarity borrow a little collaborative structure—items that are both *look-alike* and *bought-with-alike* score highest.

(optional) `contrast` A tiny ($\leq$ 0.30M-parameter) set-attention encoder trained with a contrastive loss. **It is off by default** (`ENCODER=0`); the whole point of the paper is that the zero-parameter signals above are enough. When off, it contributes nothing.




Figure 11. *What `disentangle` does.* Left: raw embeddings separate mostly by *category* (all of A over here, all of B over there)—useless for matching *within* an outfit, since the seeds and the answer are different categories by design. Subtracting each category's mean vector (right) cancels that bulk separation and leaves only each item's *style* deviation, which is what the content signals actually compare.




Figure 12. *Content scoring is cosine to the seeds' average style vector* (illustrative—the toy dataset carries no embeddings). Each content signal (`style`/`imgstyle`/`bridge`) averages the seeds' processed vectors into a centroid $\bar{\phi}_S$ and ranks candidates by $\langle \phi_c, \bar{\phi}_S \rangle$. Because the vectors are category-disentangled (Fig. 11), this rewards *within-outfit style match*; like taxonomy it uses no co-occurrence, so it too scores **cold** items.

6 From a signal to per-query numbers: scoring and standardising

Every signal above ultimately produces, for a batch of queries, a matrix $R_k \in \mathbb{R}^{n \times \text{nb}}$: one score per (item, query). Collaborative signals get there by the "W Ind" product (§4); content and `csvd` signals by the seed-centroid dot product (§5.3).

Why we must standardise. These raw scores live on wildly different scales—co-occurrence counts are integers in [0, tens], cosine similarities are in $[-1, 1]$, PMI values are small positive logs. Adding them directly would let whichever signal happens to have the biggest numbers dominate. So each signal is **column-standardised** (*per query*, across the n candidates) to mean 0, standard deviation 1:

$$z_k(c \mid S) = \frac{R_k(c \mid S) - \text{mean}_{c'} R_k(c' \mid S)}{\text{std}_{c'} R_k(c' \mid S) + 10^{-9}}.$$

(Code: `zcols`, `operators.py`:32–36.) After this, every signal speaks the same language—"how many standard deviations above the field is this candidate, according to me"—and the weights in the next section are comparing like with like.

7 Fusion: four stages to the final score

Before the formulas, here is the whole machine on one page: the fixed inputs (left) feed the three signal families, which are standardised and then combined into *two* aggregates—a collaborative score Y and a cold-start prior μ_0—that the final routing step mixes per candidate according to how often that candidate was seen.




Figure 13. *Solid arrows are each family's main input; gray arrows are secondary ones* (e.g. `bridge` also reads B; `softcat` also reads embeddings). f_c is the candidate's frequency, so cold candidates ($f_c = 0$) route entirely to μ_0. We now unpack the four stages.

Now we combine the standardised signals $\{z_k\}$ into one number per candidate. There are four stages; the only quantities "learned" are a handful of scalars, each chosen by **greedy search on a validation split** to maximise NDCG@20 (`fit_simba`, `fullrank_eval.py`:313–397). §7.1 shows the result is insensitive to *which* cutoff we validate at, and why a cutoff-free objective would be worse.

Stage 1 — weighted blend. Pick a weight $w_k \geq 0$ per signal and form

$$Y_{\text{base}}(c \mid S) = \sum_k w_k \, z_k(c \mid S).$$

The weights are found by *greedy coordinate ascent*: sweep each w_k over the grid $\{0, 0.25, 0.5, 1, 1.5\}$, keep the change if validation NDCG@20 improves, repeat up to four passes (`fullrank_eval.py`:340–354). A signal that never helps simply gets weight 0—the method prunes itself. Afterwards a backward-elimination pass tries to *drop* optional signals (bridge, contrast, softcat, homo) if doing so does not hurt validation (`prune_weights_val`).

Stage 2 — fold in the set-level terms. Blend the pairwise base with its incidence-augmented version and the Rao term, via two more validation-picked scalars $\alpha \in \{0, 0.5, 1\}$ and $\gamma \in \{0, 0.2, 0.35\}$:

$$Y(c \mid S) = (1 - \alpha)\, Y^{\text{pair}}_{\text{base}} + \alpha\, Y^{\text{inc}}_{\text{base}} + \gamma\, z_{\text{rao}}.$$

Here $Y^{\text{pair}}_{\text{base}}$ uses the *purely pairwise* versions of `simp`/`diff2` and $Y^{\text{inc}}_{\text{base}}$ uses the *incidence-augmented* ones, so α literally dials how much of the higher-order surplus to admit. (On most datasets α, γ come out small—the honest "near-inert" finding.)

Stage 3 — the cold-start prior μ_0. Build a *second* score that needs no collaborative exposure of the candidate, from the metadata/content signals only:

$$\mu_0(c \mid S) = (\text{frozen scale}) \times \Big(\sum_{k \in \text{prior keys}} w_k \, z_k + \gamma \, z_{\text{rao}} \; [+ \, w_{\text{pop}} z_{\text{pop}}] \Big),$$

where "prior keys" are the taxonomic/content signals that earned positive weight (`cat`, `softcat`, `style`, `imgstyle`, `bridge` for fashion; `cat`, `homo`, `audiostyle`, `bridge` for music). The "frozen scale" is a single number = std(Y)/std(raw prior) computed **on the validation set and then frozen**, so that at test time μ_0 is on the same scale as Y and— critically—*a candidate's score never depends on which other queries happen to be in its test batch* (`fullrank_eval.py`:380–385). This is why the method is exactly reproducible.

Stage 4 — frequency-confidence routing (shrinkage). Combine the collaborative blend Y and the prior μ_0 per candidate, trusting Y more when the candidate is *frequent* and μ_0 more when it is *rare*:

$$\hat{\theta}(c \mid S) = (1 - u_c)\, Y(c \mid S) + u_c\, \mu_0(c \mid S), \qquad u_c = \frac{\kappa}{f_c + \kappa}.$$

The single dial $\kappa \geq 0$ is picked on validation (`conjugate_posterior`, `operators.py`:526–543). Read the two extremes:

- **Cold candidate**, $f_c = 0 \Rightarrow u_c = 1 \Rightarrow \hat{\theta} = \mu_0$: ranked purely by taxonomy/content, since it has no co-occurrence evidence at all.
- **Very frequent candidate**, $f_c \gg \kappa \Rightarrow u_c \to 0 \Rightarrow \hat{\theta} \to Y$: ranked by the collaborative evidence, which for a hub is plentiful and trustworthy.




Figure 14. *The routing dial.* As a candidate is seen more often, weight slides off the prior and onto the collaborative evidence. The single learned scalar κ sets *how fast*: larger κ (orange) keeps trusting the prior up to higher frequencies. It is chosen on validation, not derived from a model. The *form* of this rule is the posterior mean of a Normal–Normal model (derived in `formalization.tex`); but we do *not* estimate κ from that model—it is just selected on validation—so in practice Stage 4 is a principled, frequency-aware interpolation between "what co-occurrence says" and "what the item *is*." Finally we rank $\mathcal{I} \setminus S$ by $\hat{\theta}(\cdot \mid S)$ and return the top K.

Example 5 (the four stages on one query). Take $S = \{1\}$ on the toy data and suppose validation selected weights $w_{\text{ppmi}} = 1$, $w_{\text{cat}} = 0.5$ (all else 0), $\alpha = \gamma = 0$, and $\kappa = 1$. From Example 4 the `ppmi` raw column is $(0, 0.336, 0.154, 0.560)$; standardising (Stage 0) and blending (Stage 1) gives Y. Suppose the category prior μ_0 (Stage 3) favours item 2 (a complementary category to item 1). Item 4 is rare ($f_4 = 1$) so $u_4 = \frac{1}{1+1} = 0.5$: its final score is the *average* of its strong collaborative evidence and the prior. Item 2 is frequent ($f_2 = 3$) so $u_2 = \frac{1}{4} = 0.25$: it leans 75% on collaboration. The routing thus lets the rare-but-exclusive item 4 keep most of its PPMI boost while a cold item (if any) would fall back entirely on the category prior. Every number here is a fixed function of S—no randomness, no test-batch dependence.




Figure 15. *The four stages on $S = \{1\}$, every bar machine-computed* (weights w_{ppmi}=1, w_{cat}=0.5, α=γ=0, κ=1). Left to right: the two example signals, then the collaborative blend Y (Stages 1–2), the cold-start prior μ_0 (Stage 3), and the routed final $\hat{\theta}$ (Stage 4). Follow item 4 (orange): PPMI loves it (1.42) and it stays high in the collaborative blend Y (1.38), but the category prior μ_0 is *cold* on it (-0.13). Because item 4 is rare (f=1 $\Rightarrow$ u_c=0.5), routing (Stage 4) pulls its final score halfway to that low prior, down to $\hat{\theta}$=0.62. Item 2 (blue) is backed by *both* Y and μ_0 and is frequent (u_c=0.25), so it stays on top. Final ranking $\mathbf{2} \succ \mathbf{4} \succ \mathbf{3}$; the seed 1 is masked. This is the whole machine turning one partial bundle into one ordered completion.

7.1 Why validate at NDCG@20 — and why not a "cutoff-free" loss

A fair question: if we *select* the weights on NDCG@20 and also *report* at cutoff 20, are we not just tuning to the number we are graded on? The honest answer has two parts, both measured (`results/selection_sensitivity.md`).

The result does not depend on the cutoff. Re-selecting the weights at NDCG@K for $K \in \{10, 20, 50, 100\}$ and re-measuring test Recall@20 gives *the same answer* across a tenfold range of cutoffs — a flat plateau (below). Selecting *directly* on Recall@20 is no better (electronic 0.486 vs. NDCG@20's 0.514). So $K = 20$ is not cherry-picked, and NDCG@20 is not "optimising the reported metric" — it is a smoother, better-conditioned surrogate at the same *operating point*.




Figure 16. *Flat plateau.* Test Recall@20 (normalised to the K=20 run) is essentially unchanged whether weights are selected at NDCG@10, 20, 50 or 100. Cutoff-free objectives, by contrast, land anywhere from 0.03× to 0.94× depending on the dataset (table below).

A cutoff-free objective is worse, and unreliably so. The tempting "generic" alternatives all under-perform because they do not target the retrieval region a short recommendation slate actually uses:

selection objective	electronic	pog	dunnhumby
NDCG@20 (used)	**0.514**	**0.064**	**0.151**
Recall@20 (ERM on reported metric)	0.486	0.066	0.148
MRR (1/rank, cutoff-free)	0.327	**0.002**	0.142
softmax NLL (cutoff-free, proper score)	0.452	0.044	0.140

MRR weights rank-1 so heavily that moving a true item from rank 25 to 18 — exactly what Recall@20 rewards — barely registers; it is fine on dense collaborative data (dunnhumby) but *catastrophic* on sparse content data (pog, 0.002). The softmax NLL is a proper scoring rule for the *whole* score distribution, so it spends effort on calibration far below the slate and is consistently ∼7–31% below NDCG@20. **The lesson is the opposite of "do not tune to their metric": you should select at the operating point you deploy at** (a short slate), the exact cutoff inside a broad band does not matter, and no cutoff-free loss improves on it.

8 The ledger: what is learned vs. fixed

Fixed inputs (not learned)	embeddings (§2.2, shipped with the dataset); category/artist/album labels; the bundle incidence matrix B.
Deterministic constructions	C, PPMI, PPMI-SVD fingerprints, W_{pair}, category/soft-cluster PMI, disentangled + bridged content. All closed-form functions of the fixed inputs—*zero trainable parameters.*
Selected on validation (the only "learning")	the per-signal weights w_k (grid $\{0, 0.25, 0.5, 1, 1.5\}$); the higher-order mixers α, γ; the shrinkage dial κ; the prior scale (computed, then frozen). A few dozen scalar choices total, by grid search—no gradients, no neural weights.
Off by default	the $\leq$ 0.30M-parameter contrastive set-encoder (`ENCODER=0`).

In one paragraph. BundleFuse turns the bundle incidence matrix and a set of fixed content embeddings into about eleven standardised "opinions" per candidate—raw and chance-corrected co-occurrence, a co-occurrence SVD fingerprint, size-aware pairwise and two-hop scores, two small set-level corrections, category and soft-category complementarity PMIs, metadata homophily, and category-disentangled / graph-bridged content similarity. It blends them with validation-picked weights into a collaborative score Y and a cold-start prior μ_0, then routes the two per candidate by $\hat{\theta} = (1 - u_c)Y + u_c\mu_0$ with $u_c = \kappa/(f_c + \kappa)$, so frequent items are judged by co-occurrence and rare/cold items by what they *are*. The scoring core trains nothing; the embeddings are inputs, and the handful of dials are chosen by grid search on held-out bundles.