

UNIX COMMANDS			
S.No	Command Name	Variation	Description
1	ls	a. `ls`	List files in the current directory
		b. `ls -a`	List all files (including hidden files) in the current directory
		c. `ls -l`	List files in long format
2	pwd	a. `pwd`	Display the current working directory
3	cd	a. `cd directory_name`	Change the current directory
		b. `cd ~`	Change to the home directory
4	mkdir	a. `mkdir new_directory`	Create a new directory
5	mv	a. `mv file1 file2`	Move or rename files or directories
6	cp	a. `cp file1 file2`	Copy files or directories
7	rm	a. `rm file`	Remove files
		b. `rm -r directory`	Remove directories recursively
8	touch	a. `touch new_file`	Create an empty file or update the modification time
9	ln	a. `ln -s source_file link_name`	Create a symbolic link to a file
10	rmdir	a. `rmdir directory_name`	Remove an empty directory
11	tree	a. `tree`	Display the directory structure in a tree-like format
12	cat	a. `cat file1 file2`	Concatenate files and display their contents
		b. `cat > file`	Create a new file or overwrite an existing file
		c. `cat >> file`	Append to an existing file
13	echo	a. `echo "Hello, World!"`	Display the specified text
		b. `echo \$VARIABLE`	Display the value of a variable
14	less	a. `less file`	View the contents of a file page by page
15	head	a. `head file`	Display the first 10 lines of a file
		b. `head -n 5 file`	Display the first 5 lines of a file
16	tail	a. `tail file`	Display the last 10 lines of a file
		b. `tail -n 5 file`	Display the last 5 lines of a file
		c. `tail -f file`	Follow the changes made to a file in real-time
17	diff	a. `diff file1 file2`	Compare two files and display the differences
18	cmp	a. `cmp file1 file2`	Compare two files byte by byte
19	comm	a. `comm file1 file2`	Compare two sorted files and display lines that are unique to each file or common to both
20	sort	a. `sort file`	Sort the lines of a file in alphabetical order
		b. `sort -r file`	Sort the lines of a file in reverse alphabetical order
		c. `sort -n file`	Sort the lines of a file numerically
21	sed	a. `sed 's/old/new/g' file`	Replace all occurrences of "old" with "new" in a file
		b. `sed '1d' file`	Delete the first line of a file
22	awk	a. `awk '{print \$1}' file`	Print the first field of each line in a file
		b. `awk '/pattern/ {action}' file`	Perform actions on lines matching a specific pattern
23	cut	a. `cut -d ':' -f 1,3 file`	Extract the first and third fields from a file using ":" as the delimiter
24	paste	a. `paste file1 file2`	Merge corresponding lines from two files
25	join	a. `join file1 file2`	Join lines from two files based on a common field
26	wc	a. `wc file`	Display the number of lines, words, and bytes in a file
		b. `wc -l file`	Display the number of lines in a file
		c. `wc -w file`	Display the number of words in a file
		d. `wc -c file`	Display the number of bytes in a file
27	grep	a. `grep "pattern" file`	Search for a pattern in a file and display matching lines
		b. `grep -i "pattern" file`	Search for a pattern case-insensitively
		c. `grep -r "pattern" directory`	Search for a pattern recursively in a directory
28	tr	a. `tr "a-z" "A-Z" < file`	Convert lowercase letters to uppercase in a file
		b. `tr -d "pattern" < file`	Delete characters matching a pattern from a file
29	uniq	a. `uniq file`	Remove consecutive duplicate lines from a file
		b. `uniq -c file`	Count the number of occurrences of each unique line in a file
30	strings	a. `strings file`	Extract printable strings from binary files

31	gzip	a. `gzip file`	Compress a file using gzip compression
		b. `gzip -d file.gz`	Decompress a gzipped file
32	gunzip	a. `gunzip file.gz`	Decompress a gzipped file
33	bzip2	a. `bzip2 file`	Compress a file using bzip2 compression
		b. `bzip2 -d file.bz2`	Decompress a bzipipped file
34	bunzip2	a. `bunzip2 file.bz2`	Decompress a bzipipped file
35	xz	a. `xz file`	Compress a file using xz compression
		b. `xz -d file.xz`	Decompress an xzipped file
36	unxz	a. `unxz file.xz`	Decompress an xzipped file
37	lzip	a. `lzip file`	Compress a file using lzip compression
		b. `lzip -d file.lz`	Decompress an lzipped file
38	lzop	a. `lzop file`	Compress a file using lzop compression
		b. `lzop -d file.lzo`	Decompress an lzoped file
39	rzip	a. `rzip file`	Compress a file using rzip compression
		b. `rzip -d file.rz`	Decompress an rzipped file
40	lrzip	a. `lrzip file`	Compress a file using lrzip compression
		b. `lrzip -d file.lrz`	Decompress an lrzipped file
41	plzip	a. `plzip file`	Compress a file using plzip compression
		b. `plzip -d file.plz`	Decompress a plzipped file
42	zip	a. `zip archive.zip file1 file2`	Create a zip archive
		b. `zip -r archive.zip directory`	Create a zip archive recursively
43	unzip	a. `unzip archive.zip`	Extract files from a zip archive
44	tar	a. `tar -cf archive.tar file1 file2`	Create a tar archive
		b. `tar -xf archive.tar`	Extract files from a tar archive
		c. `tar -tf archive.tar`	List the contents of a tar archive
		d. `tar -czf archive.tar.gz directory`	Create a gzipped tar archive
		e. `tar -xzf archive.tar.gz`	Extract files from a gzipped tar archive
		f. `tar -cjf archive.tar.bz2 directory`	Create a bzipipped tar archive
		g. `tar -xjf archive.tar.bz2`	Extract files from a bzipipped tar archive
45	ifconfig	a. `ifconfig`	Display network interface information
		b. `ifconfig eth0`	Display information for the eth0 interface
		c. `ifconfig eth0 up`	Bring up the eth0 interface
		d. `ifconfig eth0 down`	Bring down the eth0 interface
46	traceroute	a. `traceroute host`	Trace the route to a specified host
47	wget	a. `wget url`	Download a file from a specified URL
		b. `wget -c url`	Resume a partially downloaded file
		c. `wget -r url`	Download a website recursively
48	ufw	a. `ufw enable`	Enable the uncomplicated firewall
		b. `ufw disable`	Disable the uncomplicated firewall
		c. `ufw status`	Check the status of the firewall
		d. `ufw allow 22`	Allow incoming connections on port 22
49	iptables	a. `iptables -L`	List the firewall rules
		b. `iptables -A INPUT -p tcp --dport 80 -j ACCEPT`	Allow incoming connections on port 80
		c. `iptables -D INPUT -p tcp --dport 80 -j ACCEPT`	Delete the rule allowing incoming connections on port 80
50	ssh	a. `ssh user@host`	Connect to a remote host via SSH
		b. `ssh -i key_file user@host`	Connect to a remote host using a specific SSH key
		c. `ssh-keygen`	Generate SSH keys
51	service	a. `service nginx start`	Start the nginx service
		b. `service nginx stop`	Stop the nginx service
		c. `service nginx restart`	Restart the nginx service
52	ps	a. `ps`	Display information about running processes
		b. `ps aux`	Display information about all running processes
		c. `ps -ef`	Display information about all running processes in full-format
53	netstat	a. `netstat -antp`	Display network connections, listening ports, and process IDs
		b. `netstat -r`	Display the routing table

54	ping	a. `ping host`	Send ICMP echo requests to a specified host
55	scp	a. `scp file user@host:/path/to/destination`	Copy a file to a remote host using SCP
		b. `scp user@host:/path/to/file /local/path`	Copy a file from a remote host using SCP
56	rsync	a. `rsync -avz /source/directory user@host:/destination/directory`	Synchronize directories using rsync
		b. `rsync -avz user@host:/source/directory /destination/directory`	Synchronize directories from a remote host using rsync
57	crontab	a. `crontab -e`	Edit the crontab file
		b. `crontab -l`	List the current crontab
		c. `crontab -r`	Remove the current crontab
58	telnet	a. `telnet host port`	Connect to a remote host and port using telnet
59	nc (netcat)	a. `nc -l 8000`	Listen on port 8000 using netcat
		b. `nc host 8000`	Connect to a host on port 8000 using netcat
60	curl	a. `curl url`	Retrieve the contents of a URL using curl
		b. `curl -o file url`	Save the output of a URL to a file using curl
		c. `curl -X POST -d "data=value" url`	Send a POST request with data using curl
61	whois	a. `whois domain`	Retrieve WHOIS information for a domain
62	dig	a. `dig domain`	Perform a DNS lookup for a domain
		b. `dig -x ip_address`	Perform a reverse DNS lookup for an IP address
63	nslookup	a. `nslookup domain`	Perform a DNS lookup for a domain using nslookup
64	host	a. `host domain`	Perform a DNS lookup for a domain using host
65	route	a. `route`	Display the routing table
		b. `route add default gw gateway`	Add a default gateway to the routing table
		c. `route del default gw gateway`	Remove a default gateway from the routing table
66	ss	a. `ss -antp`	Display socket statistics
		b. `ss -s`	Display socket summary statistics
67	systemctl	a. `systemctl start service`	Start a systemd service
		b. `systemctl stop service`	Stop a systemd service
		c. `systemctl restart service`	Restart a systemd service
		d. `systemctl status service`	Check the status of a systemd service
68	journalctl	a. `journalctl`	Display the systemd journal logs
		b. `journalctl -u service`	Display logs for a specific systemd service
		c. `journalctl -f`	Follow the systemd journal logs in real-time
69	nmap	a. `nmap host`	Scan a host for open ports and running services
		b. `nmap -sV host`	Scan a host and determine the version of running services
		c. `nmap -sS -p- host`	Perform a SYN stealth scan on all ports of a host
70	uname	a. `uname`	Display information about the operating system
		b. `uname -a`	Display detailed information about the operating system
71	whoami	a. `whoami`	Display the current user's username
72	tar	a. `tar -cf archive.tar file1 file2`	Create a tar archive
		b. `tar -xf archive.tar`	Extract files from a
73	mount	a. `mount`	Mount a file system
		b. `mount /dev/sdb1 /mnt`	Mount a specific file system to a mount point
74	chmod	a. `chmod permissions file`	Change the permissions of a file or directory
		b. `chmod +x script.sh`	Make a script executable
75	chown	a. `chown user:group file`	Change the owner and group of a file
76	passwd	a. `passwd`	Change the user's password
77	du	a. `du`	Display disk usage by directory
		b. `du -h`	Display disk usage in a human-readable format
78	free	a. `free`	Display memory usage information
79	shutdown	a. `shutdown now`	Shutdown the system immediately
		b. `shutdown -r now`	Restart the system immediately
80	reboot	a. `reboot`	Reboot the system
81	poweroff	a. `poweroff`	Power off the system

82	halt	a. `halt`	Halt the system
83	pkill	a. `pkill process_name`	Send a signal to a process by name
84	sleep	a. `sleep 5`	Pause the execution for a specified time
85	exit	a. `exit`	Exit the current shell session
86	logout	a. `logout`	Logout from the current shell session
87	umount	a. `umount /mnt`	Unmount a mounted file system
88	fdisk	a. `fdisk /dev/sda`	Partition table manipulator for Linux
89	fsck	a. `fsck /dev/sda1`	Check and repair a Linux file system
90	mkfs	a. `mkfs.ext4 /dev/sdb1`	Create a new ext4 file system
91	file	a. `file filename`	Determine file type
92	stat	a. `stat filename`	Display file or file system status
93	lsof	a. `lsof -i :80`	List open files and processes
94	uptime	a. `uptime`	Display system uptime and load
95	users	a. `users`	Display currently logged-in users
96	useradd	a. `useradd username`	Add a new user
97	userdel	a. `userdel username`	Delete a user
98	usermod	a. `usermod -aG group username`	Modify user attributes
99	groupadd	a. `groupadd groupname`	Add a new group
100	groupdel	a. `groupdel groupname`	Delete a group
101	groupmod	a. `groupmod -n newgroup oldgroup`	Modify group attributes
102	chgrp	a. `chgrp groupname filename`	Change group ownership of a file
103	umask	a. `umask 022`	Set default file permissions
104	su	a. `su username`	Switch user
105	sudo	a. `sudo command`	Execute a command as a superuser
106	printenv	a. `printenv`	Print environment variables
107	set	a. `set`	Display shell variables
108	unalias	a. `unalias aliasname`	Remove an alias
109	jobs	a. `jobs`	Display background jobs
110	bg	a. `bg %1`	Move a job to the background
111	fg	a. `fg %1`	Bring a job to the foreground
112	halt	a. `halt`	Halt the system
113	shutdown	a. `shutdown now`	Shutdown the system immediately
114	reboot	a. `reboot`	Reboot the system
115	poweroff	a. `poweroff`	Power off the system
116	init	a. `init 0`	Change system runlevel
117	dmesg	a. `dmesg`	Display kernel messages
118	runlevel	a. `runlevel`	Display previous and current system runlevel
119	apt	a. `apt install package`	Package management for Debian-based systems
120	pacman	a. `pacman -Syu`	Package management for Arch Linux
121	yum	a. `yum install package`	Package management for Red Hat-based systems
122	rpm	a. `rpm -qa`	RPM package manager
123	dpkg	a. `dpkg -l`	Debian package manager
124	kill	a. `kill PID`	Terminate a process by PID
125	killall	a. `killall process_name`	Terminate all processes by name
126	top	a. `top`	Display real-time system processes
127	htop	a. `htop`	Display real-time system processes with detailed information
128	ps	a. `ps`	Display information about running processes
129	jobs	a. `jobs`	Display background jobs
130	bg	a. `bg %1`	Move a job to the background
131	fg	a. `fg %1`	Bring a job to the foreground
132	pkill	a. `pkill process_name`	Send a signal to a process by name
133	time	a. `time command`	Measure the execution time of a command
134	timeout	a. `timeout 5 command`	Execute a command with a time limit
135	watch	a. `watch command`	Execute a command repeatedly at a specified interval
136	nice	a. `nice command`	Execute a command with a modified priority
137	renice	a. `renice priority PID`	Modify the priority of a running process
138	alias	a. `alias aliasname=command`	Create an alias for a command
139	history	a. `history`	Display command history

140	whereis	a. `whereis command`	Locate the binary, source, and manual page files for a command
141	find	a. `find path -name filename`	Search for files based on various criteria
142	which	a. `which command`	Locate the executable of a command
143	apropos	a. `apropos keyword`	Search for manual pages based on a keyword
144	sudo	a. `sudo command`	Execute a command as a superuser
145	su	a. `su username`	Switch user
146	printenv	a. `printenv`	Print environment variables
147	set	a. `set`	Display shell variables
148	unalias	a. `unalias aliasname`	Remove an alias
149	export	a. `export VARIABLE=value`	Set an environment variable
150	source	a. `source script.sh`	Execute a script in the current shell
151	man	a. `man command`	Display the manual page for a command
152	info	a. `info command`	Display detailed information about a command
153	bc	a. `bc`	Perform arithmetic operations with arbitrary precision
154	expr	a. `expr expression`	Evaluate an expression and display the result
155	factor	a. `factor number`	Factor a number into prime factors
156	seq	a. `seq 1 10`	Generate a sequence of numbers
157	yes	a. `yes`	Output a string repeatedly until stopped
158	test	a. `test condition`	Evaluate a conditional expression
159	let	a. `let "expression"`	Evaluate an arithmetic expression
160	printf	a. `printf "format" arguments`	Format and print output
161	screen	a. `screen`	Start a new screen session
162	tmux	a. `tmux`	Start a new tmux session
163	at	a. `at time`	Schedule a command to run at a specified time
164	batch	a. `batch`	Schedule a command to run when system load permits
165	atq	a. `atq`	List scheduled jobs
166	atrm	a. `atrm job_id`	Remove a scheduled job
167	cron	a. `cron`	Schedule recurring jobs
168	anacron	a. `anacron`	Schedule recurring jobs with anacron



```
manoj@manoj-virtual-machine: ~$ history
999 alias ll='ls -lrt'
1000 ll
1001 info
1002 emacs one.txt
1003 gzip one.sh
1004 gzip six.txt
1005 ls -lrt
1006 gunzip six.txt.gz
1007 ls -lrt
1008 tar six.txt
1009 tar -cvf six.tar six.txt
1010 tar -xvf six.tar six.txt
1011 ls -lrt
1012 rm six.txt
1013 ls -lrt
1014 tar -xvf six.tar
1015 ls -lrt
1016 bzip six.txt
1017 bzip one.txt
1018 bzip2 one.txt
1019 ls -lrt
1020 bunzip one.txt.bz2
1021 bunzip2 one.txt.bz2
1022 ls -lrt
1023 ps
1024 pkill 2931
1025 ps
1026 pgrep
1027 apropos search
1028 apropos display
1029 apropos EDITOR
1030 apropos host
1031 cat one.sh
1032 chmod 777 one.txt
1033 cat one.sh
1034 ls -lrt
1035 cat one.txt
1036 sudo cat one.txt
1037 su manu
1038 groupadd ex one.txt
1039 sudo groupadd ex one.txt
1040 sudo groupadd ex
1041 ls -lrt
1042 chgrp ex two.txt
1043 sudo chgrp ex two.txt
1044 ls -lrt
1045 sudo groupdel ex
1046 ls -lrt
1047 sudo chgrp manoj two.txt
1048 ls -lrt
1049 ip
1050 ping
1051 ping manoj
1052 ping root
1053 sudo nmap
```

```
manoj@manoj-virtual-machine: ~$ history
1058 ping -c manoj
1059 ping -c one.txt
1060 ping google.com
1061 traceroute
1062 traceroute manoj
1063 traceroute google.com
1064 netstat
1065 sudo apt install net-tools
1066 netstat
1067 file
1068 file one.txt
1069 diff one.txt two.txt
1070 sudo diff one.txt two.txt
1071 ddate
1072 sudo apt install ddate
1073 ddate
1074 rename one.txt 1.txt
1075 sudo apt install rename
1076 sudo apt install rename
1077 rename one.txt 1.txt
1078 cmp one.txt two.txt
1079 sudo cmp one.txt two.txt
1080 cp one.txt 1.txt
1081 sudo cp one.txt 1.txt
1082 cat 1.txt
1083 chmod 777 1.txt
1084 sudo chmod 777 1.txt
1085 cat 1.txt
1086 timeout
1087 timeout one.txt
1088 timeout 1s cat one.txt
1089 sudo timeout 5s cat one.txt
1090 sudo timeout 10s cat one.txt
1091 ls -lrt one.txt
1092 chmod 777 one.txt
1093 sudo chmod 777 one.txt
1094 ls -lrt one.txt
1095 timeout 5s cat one.txt
1096 timeout 1m cat one.txt
1097 timeout 0.1s cat one.txt
1098 vim one.txt
1099 timeout 5s cat one.txt
1100 vim one.txt
1101 timeout 5s cat one.txt
1102 mv one.txt one.sh
1103 timeout 5s cat one.sh
1104 mv one.txt ./one.sh
1105 timeout 5s cat ./one.sh
1106 vim one.txt
1107 vim one.sh
1108 timeout 5s ./one.sh
1109 timeout 5s one.sh
1110 timeout 10s one.sh
1111 timeout 11s one.sh
1112 tree unix
1113 sudo apt install tree
```

```
manoj@manoj-virtual-machine: ~$ history
1114 last
1115 tree unix
1116 tree demo
1117 cd -
1118 cd -
1119 tree quiz
1120 cd quiz
1121 usermod
1122 ls -al
1123 ls -al
1124 ls -al
1125 expr
1126 dirname
1127 dirname
1128 expr 5+4
1129 expr 5 + 4
1130 expr 5 * 4
1131 expr 5 / 4
1132 expr 5 % 4
1133 pwd
1134 dirname /home/manoj/unix/quiz
1135 tr "abc" [:upper:]
1136 tr "abc" [:upper:] [:lower:]
1137 echo "hello" | tr -d 'l'
1138 echo "hello" | tr -d 'aeiou'
1139 id
1140 whois domain
1141 sudo apt install whois
1142 whois domain
1143 wget one.txt
1144 wget two.txt
1145 file
1146 file two.txt
1147 w
1148 man w
1149 write manu
1150 hello manu how are you?
1151 write manu
1152 du
1153 du
1154 du -h
1155 du -h quiz
1156 du -h one.txt
1157 du -h one.sh
1158 pkill manu
1159 userdel manu
1160 userdel manu
1161 sudo userdel manu
1162 pkill 5635
1163 sudo userdel manu
1164 user manu
1165 su manu
1166 userdel manu
1167 sudo userdel manu
```

## DIFFERENCE BETWEEN “systemctl” AND “service”:

In simple terms, `systemctl` and `service` are commands used in Unix-like operating systems to manage services, which are programs that run in the background and provide specific functionality.

Here's the main difference:

### 1. `systemctl`:

- `systemctl` is a more modern and powerful command used for controlling systemd, which is a system and service manager for Linux.
- It can start, stop, restart, enable, disable, reload, or check the status of a service.
- It offers more detailed control and management options compared to the `service` command.

Example: `systemctl start apache2`

### 2. `service`:

- `service` is a simpler and older command used for managing services in Unix-like systems that use System V init system or other older init systems.
- It can start, stop, restart, or check the status of a service.
- It's more straightforward and may be more familiar to users accustomed to older Unix systems.

Example: `service apache2 restart`

In summary, `systemctl` is more powerful and is commonly used in modern Linux distributions, while `service` is simpler and may still be used in systems that haven't adopted systemd.

: INTERVIEW QUESTIONS :

-----

1)What command would you use to display the current directory you're in?

Answer: The command to display the current directory is pwd, which stands for "print working directory."

2)Explain the difference between ls and ls -l commands.

Answer: ls lists the files and directories in the current directory, while ls -l provides a detailed listing of files and directories, including permissions, owner, group, size, and modification date.

3)How would you search for a specific string within a file in Unix?

Answer: You can use the grep command followed by the string you want to search for and the file name. For example, grep "search\_string" file\_name.

4)Can you explain the purpose of the grep command in Unix? Provide an example.

Answer: The grep command is used to search for patterns within files. For example, grep "pattern" file.txt searches for the pattern "pattern" within the file "file.txt".

5)How would you create a new directory in Unix?

Answer: You can create a new directory using the mkdir command followed by the directory name. For example, mkdir new\_directory.

6)Explain the difference between cp and mv commands in Unix.

Answer: The cp command is used to copy files or directories from one location to another, while the mv command is used to move files or directories from one location to another.

7)How do you check the amount of free disk space available on a Unix system?

Answer: You can use the df command to display information about disk space usage, including the amount of free disk space available.

8)What command would you use to view the contents of a file in Unix without opening it?

Answer: You can use the cat command to display the contents of a file without opening it. For example, cat file.txt.

9)Can you explain what the chmod command does in Unix? Provide an example.

Answer: The chmod command is used to change the permissions of a file or directory. For example, chmod 755 file.txt sets the permissions of "file.txt" to read, write, and execute for the owner, and read and execute for others.

10)How would you terminate a running process in Unix?

Answer: You can use the kill command followed by the process ID (PID) of the process you want to terminate. For example, kill PID. If the process is unresponsive, you can use kill -9 PID to forcefully terminate it.