Requêttes Algébrique

1.

R1= jointure (Editeur E, Journal J, E.code-e=J.code-e)
R2= jointure (R1, distribution D, R1.code-j = D.code-j)
R3= jointure(R2, PonitdeVente PV, R2.code-pv = PV.code-PV)
R4= séléction (R3, adressecomplète="Grand Tunis")
R5= projection (R4, code-e, raison-sociale)

2.

R6= Projection (Journal, code-j)
R7=Projection (Livraison, code-j)
R8= différence (R6,R7)
R9= jointure (R8, Journal J, R8.code-j=J.code-j)
R10= jointure (R9, Editeur E, R9.code-e = E.code-e)
R11= projection (R10, titre, raison-sociale)

3.

Y= projection (Depot, no-depot)
R12=Jointure (R1, Livraison L, R1.code-j=L.code-j)
X= Projection (R12, no-depot, code-e, raison-sociale)
R13= division (X,Y)

4.

R14= jointure (Journal J, Livraison L, J.code-j=L.code-j)
R15= jointure (R14, Depot D, R14.no-depot=D.no-depot)
R16= selection (R15, adresse="Tunis" and adresse="SFAX")
R17= projection (R16, code-j)

Requetes SQL

1.

```
Select code-d from Achat
where qtée-achetée = ( select MAX(qtée-achetée) from Achat);
```

2.

```
select select SUM(qte-demandée)
 from achat
 group by code-j;
```

3.

```
select code-d from distribution D, Journal J
where D.code-j=j.code-j
and (qte-dist * prix) = (select Max(qte-dist * prix) from distribution D,
Journal J where D.code-j=J.code-j);
```

4.

```
Select code-d, adresse
from distribution DD, Distributeur D
where D.code-d = DD.code-d
and qtee-dist= (select SUM(qtee-dist) AS qte
from Distribution where qte >=30);
```

5.

```
select * from journal
where (prix >=20) and (périodicité=7);
```