

Update on Ara

08/03/2023

Matteo Perotti
Matheus Cavalcante

Professor Luca Benini Integrated Systems Laboratory ETH Zürich

Energy Efficiency

Scaling

- #Lanes
- Data width
- Data type

fmatmul, 128x128x128

Lanes	Efficiency (GOPS/W)
2	30.09
4	34.33
8	32.47

Energy Efficiency

Scaling

- #Lanes
- Data width
- Data type

fmatmul, 128x128x128


Lanes	Efficiency (GOPS/W)
2	30.09
4	34.33
8	32.47


CVA6 Power is ~constant


∑(Lane Power) ~doubles

Ara non-lane power?

SLDU, MASKU, VLSU







ETH Zürich


8L

3



How do Ara's units scale in AREA?


Relative area increase when scaling up






How do Ara's units scale in AREA?

Relative area increase when scaling up




SLDU is also the largest unit 8L: SLDU area == 1.7x VLSU area


SLDU - Connections



SLDU - Connections




64*L² connections




SLDU - A New Hope





SLDU - A New Hope





SLDU - A New Datapath


Support slides by power-of-two strides only

Either we slide or we re-encode

Some difficulties to support undisturbed policy


Non-power-of-two Strides?

- uOps injection from the frontend?
- Slide by 5?
 - ➤ Slide by 4 + Slide by 1




Non-power-of-two Strides?

- uOps injection from the frontend?
- Slide by 5?
 - Slide by 4 + Slide by 1
- After the Slide by 4, store the intermediate result in the VRF





Undisturbed policy? Masked elements?
















Solution - Vertical uOps

- uOps in the Slide Unit
- Slide by 5?
 - Slide by 4 + Slide by 1
- Buffer each chunk of vector in the SLDU

Slide by 4 + Slide by 1 each chunk





Results

- 4-lane design
 - 26'000 μ m² \rightarrow 9'800 μ m² (**-63%**)
- 8-lane design
 - 122'000 μ m² \rightarrow 17'000 μ m² (-86%)

SLDU is the smallest all-to-all unit now!

Efficiency

New results soon:

Optimized SLDU

- Clock-gate the macros (D\$, I\$, VRF banks)
 - -8% power!
- Different data types