

cableglands

EWG2250 SEALS & PROTECTS

- EWG2250 Weatherproof Compound is soft enough to be readily moulded around terminals or intricate contours or pressed into cavities.
- Non sticky formulation - with good adhesion to moulded plastic and other surfaces.
- Resists the dislodging effects of vibration
- Prevents moisture creeping along the interface.
- Does not harden on exposure to air or sunlight
- Does not shrink, crack or peel.
- Readily removed & replaced safely by hand.

INSTRUCTIONS:

- Press compound tightly around required area
- Ensure surface is clean & dry
 - Press compound tightly around required area.

FOR PROFESSIONAL USE ONLY

For Health & Safety Information an SDS is available on request

Cable Glands UK, Unit 17, Premier park, Acheson way, Trafford Park Road,
Trafford Park, Manchester M17 1GA
tel: 0161 874 1480 fax: 0161 877 2013
info@cableglandsuk.com · www.cableglandsuk.com

Flash Point	+210°C
Operating temperature	-20°C to +80°C
Volume Resistivity at 20°C (ASTM D257:1975)	8 x 10 ¹⁰ Ohm.m
Colour	Reddish Brown
Electrical Breakdown at 20°C	18 kV / mm

SEALS & PROTECTS

EWG2250

2x250g pack – EWG2250


**Electrical Weatherproof
COMPOUND**

Electrical Weatherproof

cableglands

SEALS & PROTECTS

EWG2250



2x250g pack – EWG2250

**Electrical Weatherproof
COMPOUND**

Electrical Weatherproof

cableglands

SEALS & PROTECTS

EWG2250

2x250g pack – EWG2250

**Electrical Weatherproof
COMPOUND**

Electrical Weatherproof

cableglands

cableglands

**Electrical Weatherproof
COMPOUND**

2x250g pack – EWG2250

cableglands

**Electrical Weatherproof
COMPOUND**

2x250g pack – EWG2250