

## Experiment 06

**Aim: To study the usage of For loop in shell.**

- Using a for loop in shell scripting can be handy for iterating through lists of items or performing operations on files.
- In shell scripting, for loops typically follow this syntax:

```
for item in list
do
    # commands to be executed for each item
done
```

### Program Case 1: Echo Basic Manage

```
vi forloop1.sh
#!/bin/bash
SERVERS="s1 s2 s3"
for S in $SERVERS; do
    echo "updating pkg on: $S"
done
~
~
chmod u+rxw forloop1.sh
./forloop1.sh
```

```
localhost:~# vi forloop1.sh
#!/bin/bash
SERVERS="s1 s2 s3"
for S in $SERVERS; do
    echo "updating pkg on: $S"
done
~
~
~
localhost:~# chmod u+rxw forloop1.sh
localhost:~# ./forloop1.sh
updating pkg on: s1
updating pkg on: s2
updating pkg on: s3
```

### Program Case 2: Iterating through range of Numbers

```
vi for2.sh
#!/bin/bash
for value in {1..5}
do
    echo "number: $value"
done
~
~
chmod u+rxw for2.sh
./for2.sh
```

```
localhost:~# vi for2.sh
#!/bin/bash
for value in {1..5}
do
    echo "number: $value"
done
~
~
localhost:~# chmod u+rx for2.sh
localhost:~# ./for2.sh
number: 1
number: 2
number: 3
number: 4
number: 5
```

### Program Case 3: Iterating through multiple files

```
vi forloop3.sh
#!/bin/bash
for file in /root/*
do
    chmod 755 "$file"
    echo "update permission for: $file"
done
~
chmod u+rx forloop3.sh
./forloop3.sh
```

```
localhost:~# vi forloop3.sh
#!/bin/bash
for file in /root/*
do
    chmod 755 "$file"
    echo "update permission for: $file"
done
~
~
localhost:~# chmod u+rx forloop3.sh
localhost:~# ./forloop3.sh
update permission for: /root/bench.py
update permission for: /root/forloop3.sh
update permission for: /root/hello.c
update permission for: /root/hello.js
update permission for: /root/readme.txt
```

### Program Case 4: Creating an Infinite Loop

```
vi forloop4.sh
#!/bin/bash
for (( ; ; ))
do
    echo "This is infinite loop"
    echo "Use Ctrl+C to stop it"
done
~
~
chmod u+rx forloop4.sh
./forloop4.sh
```

```
localhost:~# vi forloop4.sh
#!/bin/bash
for (( ; ; ))
do
    echo "This is infinite loop"
    echo "Use Ctrl+C to stop it"
done
~
~
localhost:~# chmod u+rx forloop4.sh
localhost:~# ./forloop4.sh
This is infinite loop
Use Ctrl+C to stop it
This is infinite loop
Use Ctrl+C to stop it
This is infinite loop
Use Ctrl+C to stop it
This is infinite loop
^C
localhost:~#
```

### Program Case 5: Implementing a Nested for loop

```
vi forloop5.sh
#!/bin/bash
for serverd in A B C; do
    for app in apache dp; do
        echo "$serverd can run $app LAMP package"
    done
done
~
~
Chmod 711 forloop5.sh
./forloop5.sh
```

```
localhost:~# vi forloop5.sh
#!/bin/bash
for serverd in A B C; do
    for app in apache dp; do
        echo "$serverd can run $app LAMP package"
    done
done
~
~
localhost:~# chmod 711 forloop5.sh
localhost:~# ./forloop5.sh
A can run apache LAMP package
A can run dp LAMP package
B can run apache LAMP package
B can run dp LAMP package
C can run apache LAMP package
C can run dp LAMP package
```

**Program Case 6: Array utilization in for loop**

```

vi forloop6.sh
#!/bin/bash
apps=("apache" "mysql" "php")
for app in "${apps[@]}"
do
    echo "The application name is $app"
done
~
~
chmod 711 forloop6.sh
./forloop6.sh

```

```

localhost:~# vi forloop6.sh
#!/bin/bash
apps=("apache" "mysql" "php")
for app in "${apps[@]}"
do
    echo "The application name is $app"
done
~
~
localhost:~# chmod 711 forloop6.sh
localhost:~# ./forloop6.sh
The application name is apache
The application name is mysql
The application name is php

```

**Program Case 7: Using break statement in for loop**

```

vi forloop7.sh
#!/bin/bash
for file in ~/.* ; do
    if [[ "$file" == "./data.txt" ]]
    then
        echo "$file is available"
        break
    fi
done
~
chmod 711 forloop7.sh
./forloop7.sh

```

```

localhost:~# vi forloop7.sh
#!/bin/bash
for file in ~/.* ; do
    if [[ "$file" == "./data.txt" ]]
    then
        echo "$file is available"
        break
    fi
done
~
~
localhost:~# chmod 711 forloop7.sh
localhost:~# ./forloop7.sh

```

**Program Case 8: Use of command substitution**

```
vi forloop8.sh
#!/bin/bash
for log in $(cat ~/testfile)
do
    echo "Log entry: $log"
done
~
~
chmod 711 forloop8.sh
./forloop8.sh
```

```
localhost:~# vi forloop8.sh
#!/bin/bash

for log in $(cat ~/testfile)
do
    echo "Log entry:..$log"
done
~
~
~
localhost:~# chmod 711 forloop8.sh
localhost:~# ./forloop8.sh
cat: can't open '/root/testfile': No such file or directory
```