

# Communication Technologies 1 (CT1)

## Machine Learning

# Viterbi Algorithm

Akancha Choudhary, Philipp Copei, Robert Koczula, Tobias Schellien

Lecture in SS 2019

19.09.2019




# Agenda



- Introduction
- Viterbi Algorithm
- Experiment
- Summary
- Questions

# Introduction


- Algorithm to recreate state sequences
- Example student travels between rooms



$a_{ij}$  : transition probability from one state to the next

# Introduction – Hidden Markov Model (HMM)

- State space  $S=\{A, B, C\}$
- Initial probability of states
- Transition matrix  $A$  that store the transition probability between true states
- Observation space  $O=\{1, 2, 3\}$
- Emission matrix  $B$  that stores the transition probability from true states to observing states
- Sequence of observations  $y_1, y_2, \dots, y_T$



$b_{ij}$  : probability of an observation for a hidden state

# Introduction - Observations

## Problem:

We don't know the true states of a HMM

## Given:


HMM with observed states and transition probabilities

## Target:

Estimate the true state (hidden state)

## How:

Use the observations of the system  
-> emission is visible and gives a stochastically hint



# Viterbi Algorithm

- Invented by Andrew J. Viterbi in 1967
- Input via HMM and state sequence
- Calculates path with highest probability
- Used for decodation of convolutial codes
- Extended by G. D. Forney for reduction of communication errors

# Viterbi Algorithm - Pseudo Code 1/3

- Given: a sentence of length  $n$
- Matrix  $\vartheta$  storing highest reachability probabilities
- Matrix  $\psi$  storing contributing states for reachability
- Initialization:

for all states  $i$  do

$$\vartheta_1(i) = \pi_i * B_{i1}$$

$$\psi_1(i) = 0$$

end

## Viterbi Algorithm - Pseudo Code 2/3

- Induction:

for t := 2 to n step 1 do

  for all states i do

$$\vartheta_t(i) = B_{it} * \max_{1 \leq j \leq |S|} (A_{ji} * \vartheta_{t-1}(i))$$

$$\psi_t(i) = \arg \max_{1 \leq j \leq |S|} (A_{ji} * \vartheta_{t-1}(i))$$

  end

end



## Viterbi Algorithm - Pseudo Code 3/3

- Termination and path-readout:

$$y_T = \arg \max_{1 \leq j \leq |S|} (\vartheta_T(j))$$


for  $j := n$  to 1 step -1 do

$$y_t = \psi_{t+1}(y_{t+1})$$

end

$$P(y_1, \dots, y_T) = \max_{1 \leq j \leq |S|} (\vartheta_n(j))$$


# Experiment



N=55

AAAAAABBBBCBBBBBCBCAAAAAABBBBBBAAABBBBAAAAAACAAAAAAA  
111111122322222232311111232223111222212111113122121111

# Experiment - Used Sequence



	1	2	3
A	0.9	0.1	0.0
B	0.1	0.8	0.1
C	0.0	0.1	0.9

AAAAAABBBBCBBBBBCBCAAAAABBBBBBAAABBBBBAAAAAACAAAAAAA  
 1111111223222222323111112322231112222121111131221211111

# Experiment - Recreated Sequence

AAAAAABBBBCBBBBBBCBCAAAAAABBBBBBAAABBBBAAAAAACAAAAA  
 1111111223222222323111112322231112222121111131221211111  
 AAAAAAABBBB BBBB BCBAAAAA BBBB CAAABBBBAAAAAACAAAAA

# Summary

- Applying viterbi algorithm in real time case.
- We observe the relation between true state and hidden state.
- We also observe the downside of the algorithm.
- Student travelling between rooms.
- Use result for analyzing and reducing error.

# Summary

- Applying viterbi algorithm in real time case.
- We observe the relation between true state and hidden state.
- We also observe the downside of the algorithm.
- Student travelling between rooms.
- Use result for analyzing and reducing error.

```

AAAAAABBBBCBBBBBBCBAAAAAABBBBBBAAABBBBAAAAAACAAAAA
11111111223222222323111112322231112222121111131221211111
AAAAAABBBB BBBB BB CAAAAA BBBB C AAABBBBAAAAAACAAAAA

```

Questions?

- Pseudo Code: [kontext.fraunhofer.de/haenelt/kurs/folien/Haenelt\\_Viterbi-Algorithmus.pdf](http://kontext.fraunhofer.de/haenelt/kurs/folien/Haenelt_Viterbi-Algorithmus.pdf)
- Used Images: <https://forschung.bissantz.de/hidden-markov-modelle-so-bekommt-man-zustaende>
- [1] <https://de.wikipedia.org/wiki/Viterbi-Algorithmus>, 2018.
- [2] S. Alhaidari and M. Zohdy. Network anomaly detection using two-dimensional hidden markov model based viterbi algorithm. April 2019.
- [3] A. R. Arsadjaja and A. I. Kistijantoro. Online speech decoding optimization strategy with viterbi algorithm on gpu. 2018.
- [4] J. Bobbin. An incremental viterbi algorithm. 2017.
- [5] M. S. I. Chen Yuan and A. S. Khalsa. Modified viterbi algorithm based distribution system restoration strategy for grid resiliency. 2017.



- [6] G. C. D. Hernando, V. Crespi. Efficient computation of the hidden markov model entropy for a given observation sequence. June 2005.
- [7] G. Forney. The viterbi algorithm. 1973.
- [8] B. . C. GmbH. Hidden-markov-modelle: So bekommt man Zustände! December 2014.
- [9] K. M. Kilavo Hassan and S. I. Mrutu. Performance of soft viterbi decoder enhanced with non-transmittable codewords for storage media. ELECTRICAL and ELECTRONIC ENGINEERING, 2018.
- [10] E. G. S.-T. lecture WS 2012/13 University in Jena. Chapter 5 Slide 39 ff. [www.minet.uni-jena.de/fakultaet/schukat/MAS/Scriptum/lect05-HMM.pdf](http://www.minet.uni-jena.de/fakultaet/schukat/MAS/Scriptum/lect05-HMM.pdf), 2019.
- [11] J. H. Ritendra Datta and B. Ray. On efficient Viterbi decoding for hidden semi-markov models. December 2008.
- [12] S. Singhal and M. Gilani. [https://www.eetimes.com/document.asp?doc\\_id=1277544#](https://www.eetimes.com/document.asp?doc_id=1277544#), 2002.

- [13] R. Yazdani, A. Segura, J.-M. Arnau, and A. Gonz´alez. Low-power automatic speech recognition through a mobile gpu and a viterbi accelerator. 2017.
- [14] G. Yin and D. Bruckner. Data analyzing and daily activity learning with hidden markov model. November 2010.
- [15] <https://www.youtube.com/watch?v=6JVqutwtzmo>.