196. Delete Duplicate Emails

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Person`

```
+-------------+---------+
| Column Name | Type    |
+-------------+---------+
| id          | int     |
| email       | varchar |
+-------------+---------+
id is the primary key (column with unique values) for this table.
Each row of this table contains an email. The emails will not contain uppercase letters.
```

Write a solution to **delete** all duplicate emails, keeping only one unique email with the smallest `id`.

For SQL users, please note that you are supposed to write a `DELETE` statement and not a `SELECT` one.

For Pandas users, please note that you are supposed to modify `Person` in place.

After running your script, the answer shown is the `Person` table. The driver will first compile and run your piece of code and then show the `Person` table. The final order of the `Person` table **does not matter.**

The result format is in the following example.

Example 1:

> **Input:**
> Person table:
> +----+------------------+
> | id | email |
> +----+------------------+
> | 1 | john@example.com |
> | 2 | bob@example.com |
> | 3 | john@example.com |
> +----+------------------+
> **Output:**
> +----+------------------+
> | id | email |
> +----+------------------+
> | 1 | john@example.com |
> | 2 | bob@example.com |
> +----+------------------+
> **Explanation:** john@example.com is repeated two times. We keep the row with the smallest Id = 1.

Accepted 22 / 22 testcases passed

Akankshyaa submitted at Nov 02, 2026 14:28

Solution

Save 41%

Big Diwali Dhamaka

Unlock the Full Experience with Premium for ₹583.25/mo — Ends Nov 8!

Runtime

1047 ms | Beats **22.01%**



Code | MySQL

```mysql
# Write your MySQL query statement below
DELETE p1
FROM person p1
JOIN person p2
ON p1.email=p2.email
AND p1.id>p2.id;
```

More challenges

- 1107. New Users Daily Count
- 1934. Confirmation Rate

```mysql
# Write your MySQL query statement below
DELETE p1
FROM person p1
JOIN person p2
ON p1.email=p2.email
AND p1.id>p2.id;
```

Saved

Testcase | Test Result

Accepted Runtime: 93 ms

Case 1

Input

Person =

id	email
1	john@example.com
2	bob@example.com
3	john@example.com

Output

id	email
1	john@example.com
2	bob@example.com

Expected

id	email
1	john@example.com
2	bob@example.com

AS / db lc, day - 5 / 2 / 11 / 26

leetcode - 196 - Delete Duplicate emails.

We are given a table called Person.
It contains two colums :-

id	email
1	john@example.com
2	bob@example.com
3	john@example.com

We have to delete duplicate email addresses.
but the imp. cond^n is, if the same email appears multiple times, we must keep the row having the smallest ID. for ex, in above, john@example.com occures twice. we keep row 103 since it is smaller than 103. we delete 103.

since table:-

id	email
1	john@example.com
2	bob@example.com.

__/__/____

SQL concepts (A) DELETE, it is used to remove existing rows from a table.

syntax, DELETE FROM table_name
WHERE condition;

* DELETE removes rows permanently from the table.

(B) SELF JOIN ⇒ JOIN combines two tables. But if we want to compare a table with itself, that's called a SELF JOIN.

(C) Primary key ⇒ here, id is the primary key. that means every row has a unique ID.

for example,

id	email
1	john@example.com
2	bob@example.com
3	john@example.com.

even though the email is repeated, the IDs are different.