

ICPC TEAM REFERENCE DOCUMENT

Kaaju Kishmish

Akansh Khandelwal • Shreyans Garg • Tanmay Mittal

1 HeavyDS

1.1 Iterative

```
struct Data{
};

Data op(const Data &a, const Data &b){
}

struct segtree{
    vector<Data> d;
    int _n, log, size;
    unsigned int bit_ceil(unsigned int n) {
        unsigned int x = 1;
        while (x < (unsigned int)(n)) x <= 1;
        return x;
    }
    segtree(int n): _n(n) {
        size = (int)bit_ceil((unsigned int)(n));
        log = __builtin_ctz((unsigned int)size);
        d.resize(2*size, Data());
    }
    void update(int k) { d[k] = op(d[2*k], d[2*k+1]); }
    void set(int p, Data x) {
        p += size;
        d[p] = x;
        for (int i = 1; i <= log; i++) update(p >> i);
    }
    Data prod(int l, int r) { // !!! q(l,r) return l to r-1
        if (l == r) return Data();
        l += size;
        r += size;
        Data sml = Data(), smr = Data();
        while (l < r) {
            if (l&1) sml = op(sml, d[l++]);
            if (r&1) smr = op(d[--r], smr);
            l >>= 1;
            r >>= 1;
        }
        return op(sml, smr);
    }
};
```

1.2 Lazy

```
struct Min{
    int x;
    Min(int x = inf) : x(x) {}
};

Min operator+(const Min& a, const Min& b){
    return std::min(a.x, b.x);
}

void apply(int &a, int b){
    a += b;
}

void apply(Min& a, int b){
```

```
    a.x += b;
}

// Always make a class for them and define basic overloads
template<class Node, class Lazy, class Merge = std::plus<Node>>
struct LazySegTree {
    const int _n;
    const Merge _merge;
    std::vector<Node> _segT;
    std::vector<Lazy> _lazy;
    LazySegTree(int n) : _n(n), _merge(Merge()), _segT(4 <<
    ↪ std::__lg(n)), _lazy(4 << std::__lg(n)) {}
    LazySegTree(std::vector<Node> init) :
    ↪ LazySegTree(init.size()) {
        std::function<void(int, int, int)> build = [&](int
    ↪ node, int st, int en){
            if(en - st == 1){
                _segT[node] = init[st];
                return;
            }
            int md = (st + en) >> 1;
            build(node << 1, st, md);
            build(node << 1 | 1, md, en);
            pull(node);
        };
        build(1, 0, _n);
    }
    void pull(int node){
        _segT[node] = _merge(_segT[node << 1], _segT[node << 1
    ↪ | 1]);
    }
    void apply(int node, const Lazy& lazy){
        ::apply(_segT[node], lazy);
        ::apply(_lazy[node], lazy);
    }
    void push(int node){
        apply(node << 1, _lazy[node]);
        apply(node << 1 | 1, _lazy[node]);
        _lazy[node] = Lazy();
    }
    void update(int node, int st, int en, int idx, const Node&
    ↪ nodeVal){
        if(en - st == 1){
            _segT[node] = nodeVal;
            return;
        }
        push(node);
        int md = (st + en) >> 1;
        if(idx < md){
            update(node << 1, st, md, idx, nodeVal);
        }
        else{
            update(node << 1 | 1, md, en, idx, nodeVal);
        }
        pull(node);
    }
    void update(int idx, const Node& nodeVal){
        update(1, 0, _n, idx, nodeVal);
    }
    Node rangeQuery(int node, int st, int en, int ql, int qr){
        if(st >= qr || en <= ql){
            return Node();
        }
    }
```

```

    }
    if(st >= ql && en <= qr){
        return _segT[node];
    }
    push(node);
    int md = (st + en) >> 1;
    return _merge(rangeQuery(node << 1, st, md, ql, qr),
        ↪ rangeQuery(node << 1 | 1, md, en, ql, qr));
}
Node rangeQuery(int ql, int qr){
    return rangeQuery(1, 0, _n, ql, qr);
}
void rangeApply(int node, int st, int en, int ql, int qr,
    ↪ const Lazy& lazy){
    if(st >= qr || en <= ql){
        return;
    }
    if(st >= ql && en <= qr){
        apply(node, lazy);
        return;
    }
    push(node);
    int md = (st + en) >> 1;
    rangeApply(node << 1, st, md, ql, qr, lazy);
    rangeApply(node << 1 | 1, md, en, ql, qr, lazy);
    pull(node);
}
void rangeApply(int ql, int qr, const Lazy& lazy){
    rangeApply(1, 0, _n, ql, qr, lazy);
}
};

// LazySegTree<Min, int> seg(a);
// For range [i, j] use i, j + 1

```

1.3 PersistentSegmentTree

```

struct PST{
    struct Node{
        int sum = 0;
        int l = 0, r = 0;
    };
    const int n;
    vector<Node> tree;
    int timer = 1;
    PST(int n, int mx_nodes) : n(n), tree(mx_nodes) {}
    Node merge(int l, int r){
        return Node({tree[l].sum + tree[r].sum, l, r});
    }
    int build(int st, int en, const vector<int> &init){
        if(st == en){
            tree[timer] = Node({init[st], 0, 0});
            return timer++;
        }
        int md = (st + en) >> 1;
        tree[timer] = merge(build(st, md, init), build(md + 1,
            ↪ en, init));
        return timer++;
    }
    int update(int root, int idx, int val, int st, int en){
        if(st == en){
            tree[timer] = Node({val, 0, 0});
            return timer++;
        }
        int md = (st + en) >> 1;
        if(idx <= md){
            tree[timer] = merge(update(tree[root].l, idx, val,
                ↪ st, md), tree[root].r);
        }
        else{
            tree[timer] = merge(tree[root].l,
                ↪ update(tree[root].r, idx, val, md + 1, en));
        }
        return timer++;
    }
    int query(int root, int l, int r, int st, int en){
        if(r < st || en < l) return 0;
    }
}

```

```

    if(l <= st && en <= r) return tree[root].sum;
    int md = (st + en) >> 1;
    return query(tree[root].l, l, r, st, md) +
        ↪ query(tree[root].r, l, r, md + 1, en);
}
int build(const vector<int> &init){
    return build(0, n - 1, init);
}
int update(int root, int idx, int val){
    return update(root, idx, val, 0, n - 1);
}
int query(int root, int l, int r){
    return query(root, l, r, 0, n - 1);
}
};

```

1.4 Fenwick_sum

```

struct FenwickTree {
    vector<int> bit; // binary indexed tree
    int n;
    FenwickTree(int n) {
        this->n = n;
        bit.assign(n, 0);
    }
    FenwickTree(vector<int> const &a) : FenwickTree(a.size()) {
        for (size_t i = 0; i < a.size(); i++)
            add(i, a[i]);
    }
    int sum(int r) {
        int ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
        return ret;
    }
    int sum(int l, int r) {
        return sum(r) - sum(l - 1);
    }
    void add(int idx, int delta) {
        for (; idx < n; idx = idx | (idx + 1))
            bit[idx] += delta;
    }
};

```

1.5 SparseTable

```

int log_floor(int x){
    return x ? __builtin_clzll(1) - __builtin_clzll(x) : -1;
}
template<typename T, class F = function<T(const T&,const T&>>>
struct SPARSE_TABLE{
    int n;
    vector<vector<T>> st;
    F fun;
    SPARSE_TABLE(const vector<T> &v, const F &f) : fun(f){
        n = static_cast<int>(v.size());
        int maxN = log_floor(n) + 1;

        st.resize(maxN);
        st[0] = v;

        for(int i = 1; i < maxN; i++){
            st[i].resize(n - (1 << i) + 1);

            for(int j = 0; j + (1 << i) <= n; j++){
                st[i][j] = fun(st[i - 1][j], st[i - 1][j + (1
                    ↪ << i - 1)]);
            }
        }
    }
    T get(int l, int r){
        int h = log_floor(r - l + 1);
        // works for idempotent functions only ykw
        return fun(st[h][l], st[h][r - (1 << h) + 1]);
    }
}

```

```

    }
};

```

1.6 MergeSortTree

```

template <typename T>
struct MergeSortTree {
    int n;
    vector<vector<T>> tree;

    // Constructor: builds the tree from input vector a
    MergeSortTree(const vector<T>& a) {
        n = a.size();
        tree.resize(4 * n);
        build(1, 0, n - 1, a);
    }

    void build(int node, int start, int end, const vector<T>&
    ↪ a) {
        if (start == end) {
            tree[node] = {a[start]};
            return;
        }
        int mid = (start + end) / 2;
        build(2 * node, start, mid, a);
        build(2 * node + 1, mid + 1, end, a);

        // Merge two sorted vectors
        merge(tree[2 * node].begin(), tree[2 * node].end(),
            tree[2 * node + 1].begin(), tree[2 * node + 1].end(),
            ↪ 1].end(),
            back_inserter(tree[node]));
    }

    // Internal query function for Lower Bound (smallest value
    ↪ >= x)
    T query_lb(int node, int start, int end, int l, int r, T x)
    ↪ {
        if (start > end || start > r || end < l)
            return numeric_limits<T>::max(); // Return INF

        if (start >= l && end <= r) {
            auto it = lower_bound(tree[node].begin(),
            ↪ tree[node].end(), x);
            if (it != tree[node].end())
                return *it;
            return numeric_limits<T>::max();
        }

        int mid = (start + end) / 2;
        return min(query_lb(2 * node, start, mid, l, r, x),
            query_lb(2 * node + 1, mid + 1, end, l, r,
            ↪ x));
    }

    // Internal query function for Count (number of elements <=
    ↪ x)
    int query_count(int node, int start, int end, int l, int r,
    ↪ T x) {
        if (start > end || start > r || end < l)
            return 0;

        if (start >= l && end <= r) {
            // upper_bound gives first element > x, so index
            ↪ gives count of elements <= x
            return upper_bound(tree[node].begin(),
            ↪ tree[node].end(), x) - tree[node].begin();
        }

        int mid = (start + end) / 2;
        return query_count(2 * node, start, mid, l, r, x) +
            query_count(2 * node + 1, mid + 1, end, l, r,
            ↪ x);
    }

    // Public Interface: Find smallest number >= x in range [l,
    ↪ r]

```

```

T lower_bound_val(int l, int r, T x) {
    return query_lb(1, 0, n - 1, l, r, x);
}

// Public Interface: Count numbers <= x in range [l, r]
int count_less_equal(int l, int r, T x) {
    return query_count(1, 0, n - 1, l, r, x);
}
};

```

2 Graphs

2.1 Dinic

```

template<class T>
struct Flow {
    const int n;
    struct Edge {
        int to;
        T cap;
        Edge(int to, T cap) : to(to), cap(cap) {}
    };
    std::vector<Edge> e;
    std::vector<std::vector<int>> g;
    std::vector<int> cur, h;
    Flow(int n) : n(n), g(n) {}

    bool bfs(int s, int t) {
        h.assign(n, -1);
        std::queue<int> que;
        h[s] = 0;
        que.push(s);
        while (!que.empty()) {
            const int u = que.front();
            que.pop();
            for (int i : g[u]) {
                auto [v, c] = e[i];
                if (c > 0 && h[v] == -1) {
                    h[v] = h[u] + 1;
                    if (v == t) {
                        return true;
                    }
                    que.push(v);
                }
            }
        }
        return false;
    }

    T dfs(int u, int t, T f) {
        if (u == t) {
            return f;
        }
        auto r = f;
        for (int &i = cur[u]; i < (int)g[u].size(); ++i) {
            const int j = g[u][i];
            auto [v, c] = e[j];
            if (c > 0 && h[v] == h[u] + 1) {
                auto a = dfs(v, t, std::min(r, c));
                e[j].cap -= a;
                e[j ^ 1].cap += a;
                r -= a;
                if (r == 0) {
                    return f;
                }
            }
        }
        return f - r;
    }

    void addEdge(int u, int v, T c) {
        g[u].push_back(e.size());
        e.emplace_back(v, c);
        g[v].push_back(e.size());
        e.emplace_back(u, 0);
    }
}

```

```

T maxFlow(int s, int t) {
    T ans = 0;
    while (bfs(s, t)) {
        cur.assign(n, 0);
        ans += dfs(s, t, std::numeric_limits<T>::max());
    }
    return ans;
}

void get(int end){
    vector<int> path;
    cur.assign(n, 0);
    int u = 1;
    while(u != end){
        path.push_back(u);
        dbg(path)
        for (int &i = cur[u]; i < (int)(g[u].size()); ++i)
            ↪ {
                const int j = g[u][i];
                auto [v, c] = e[j];
                dbg(u, v, c, j)
                if (j % 2 == 0 && c == 0) {
                    e[j].cap = 1;
                    u = v;
                    break;
                }
            }
        path.push_back(end);
        cout<<path.size()<<endl;
        for(int i : path) cout<<i<<" ";
        cout<<endl;
    }
};

queue<int> q;
vector<bool> vis(n + 1, false);
q.push(1);
vis[1] = true;
while(!q.empty()){
    int u = q.front(); q.pop();
    for(auto i : mf.g[u]){
        auto [v, c] = mf.e[i];
        if(c > 0 && !vis[v]){
            vis[v] = true;
            q.push(v);
        }
    }
}

for(int i = 1; i <= n; i++){
    for(auto id : mf.g[i]){
        auto [v, c] = mf.e[id];
        if(v != s and c == 0){
            cout<<i<<" "<<v - n<<endl;
        }
    }
}
}

```

2.2 LCA

```

// LCA and Binary Lifting
void dfs(int v, int p){
    up[0][v] = p;
    for(int i = 1; i < 20; i++){
        up[i][v] = up[i - 1][up[i - 1][v]];
    }
    for(auto x : g[v]){
        if(x == p) continue;
        dst[x] = dst[v] + 1;
        dfs(x, v);
    }
}

auto lca = [&](int x, int y){
    if(dst[x] < dst[y]) swap(x, y);
    for(int i = 19; i >= 0; i--){
        if(dst[up[i][x]] >= dst[y]){
            x = up[i][x];
        }
    }
}

```

```

if(x == y) return x;
for(int i = 19; i >= 0; i--){
    if(up[i][x] != up[i][y]){
        x = up[i][x];
        y = up[i][y];
    }
}
return up[0][x];
};

```

2.3 CutPoint

```

vll g[NUM];
bool vis[NUM];
ll in[NUM];
ll low[NUM];
int timer = 0;

void CutPoints(ll src, ll parent = -1)
{
    vis[src] = true;
    in[src] = low[src] = timer;
    timer++;
    int children = 0;
    for (auto child : g[src])
    {
        if (child == parent)
            continue;
        if (vis[child])
        {
            low[src] = min(low[src], in[child]);
        }
        else
        {
            CutPoints(child, src);
            low[src] = min(low[src], low[child]);
            if (low[child] >= in[src] && parent != -1)
            {
                // Src is a cut point!
                // CAUTION: Might get called multiple times due
                ↪ to satisfiability of multiple children
            }
            children++;
        }
    }
    if (parent == -1 && children > 1){
        // Root is a cut point!
        // used children instead of size of adj bcoz we dont
        ↪ use back edges
    }
}

```

2.4 TreeIsomorphism

```

class Tree {
public:
    vector<vector<int>> adj;
    vector<int> centroid;
    vector<int> sub;
    vector<int> id;
    vector<int64_t> powr;

    void dfs(int curNode, int prevNode) {
        sub[curNode] = 1;
        bool is_centroid = true;
        vector<pair<int, int>> nodes;
        for (int v : adj[curNode]) {
            if (v != prevNode) {
                dfs(v, curNode);
                sub[curNode] += sub[v];
                if (sub[v] > (int)adj.size() / 2) {
                    is_centroid = false;
                }
            }
        }
    }
}

```

```

        nodes.emplace_back(id[v], v);
    }
}
// Canonical ordering: sort children by their hash
sort(nodes.begin(), nodes.end());

id[curNode] = 1;
for (auto& p : nodes) {
    // Polynomial hash combination
    id[curNode] = ((powr[sub[p.second] + 1] *
        ↪ id[curNode]) % MOD + id[p.second]) % MOD;
}
id[curNode] *= 2;
id[curNode] %= MOD;

// Check "parent" component size for centroid
↪ definition
if ((int)adj.size() - sub[curNode] > (int)adj.size() /
    ↪ 2) {
    is_centroid = false;
}
if (is_centroid) {
    centroid.push_back(curNode);
}
}

vector<int> getCentroids() {
    // Clear previous runs if any
    centroid.clear();
    dfs(0, -1);
    return centroid;
}

// Computes hash for a specific rooting
int getHash(int root) {
    dfs(root, -1);
    return id[root];
}

void add_edge(int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}

Tree(int n) {
    adj.resize(n);
    sub.resize(n);
    id.resize(n);
    powr.resize(n + 1);
    powr[0] = 1;
    for (int i = 1; i <= n; i++) {
        powr[i] = (2 * powr[i - 1]) % MOD;
    }
}

};

int main() {
    // Example: Two trees that look different but are
    ↪ structurally the same
    // Tree 1: 0-1, 1-2
    Tree t1(3);
    t1.add_edge(0, 1);
    t1.add_edge(1, 2);

    // Tree 2: 1-0, 0-2 (Same line graph, just labeled
    ↪ differently)
    Tree t2(3);
    t2.add_edge(1, 0);
    t2.add_edge(0, 2);

    // Step 1: Find centroids for both trees
    // This allows us to find a "Canonical Root"
    vector<int> c1 = t1.getCentroids();
    vector<int> c2 = t2.getCentroids();

    bool isomorphic = false;

    // Step 2: Compare hashes rooted at centroids
    // A tree can have up to 2 centroids. We must check all
    ↪ combinations.

```

```

    for (int root1 : c1) {
        for (int root2 : c2) {
            if (t1.getHash(root1) == t2.getHash(root2)) {
                isomorphic = true;
            }
        }
    }

    if (isomorphic)
        cout << "The trees are Isomorphic!" << endl;
    else
        cout << "The trees are Different." << endl;

    return 0;
}

```

2.5 Centroid

```

int nn;
void dfs1(int u, int p)
{
    sub[u] = 1;
    nn++;
    for (auto it = g[u].begin(); it != g[u].end(); it++)
        if (*it != p)
        {
            dfs1(*it, u);
            sub[u] += sub[*it];
        }
}

int dfs2(int u, int p)
{
    for (auto it = g[u].begin(); it != g[u].end(); it++)
        if (*it != p && sub[*it] > nn / 2)
            return dfs2(*it, u);
    return u;
}

void decompose(int root, int p)
{
    nn = 0;
    dfs1(root, root);
    int centroid = dfs2(root, root);
    if (p == -1)
        p = centroid;
    par[centroid] = p;
    for (auto it = g[centroid].begin(); it !=
        ↪ g[centroid].end(); it++)
    {
        g[*it].erase(centroid);
        decompose(*it, centroid);
    }
    g[centroid].clear();
}

```

2.6 Mcmf

```

using i64 = long long;
template<class T>
struct MinCostFlow {
    struct _Edge {
        int to;
        T cap;
        T cost;
        _Edge(int to_, T cap_, T cost_) : to(to_), cap(cap_),
            ↪ cost(cost_) {}
    };
    int n;
    std::vector<_Edge> e;
    std::vector<std::vector<int>>> g;
    std::vector<T> h, dis;
    std::vector<int> pre;
    bool dijkstra(int s, int t) {
        dis.assign(n, std::numeric_limits<T>::max());
        pre.assign(n, -1);
    }
}

```

```

std::priority_queue<std::pair<T, int>,
↳ std::vector<std::pair<T, int>>,
↳ std::greater<std::pair<T, int>>> que;
dis[s] = 0;
que.emplace(0, s);
while (!que.empty()) {
    T d = que.top().first;
    int u = que.top().second;
    que.pop();
    if (dis[u] != d) {
        continue;
    }
    for (int i : g[u]) {
        int v = e[i].to;
        T cap = e[i].cap;
        T cost = e[i].cost;
        if (cap > 0 && dis[v] > d + h[u] - h[v] +
↳ cost) {
            dis[v] = d + h[u] - h[v] + cost;
            pre[v] = i;
            que.emplace(dis[v], v);
        }
    }
}
return dis[t] != std::numeric_limits<T>::max();
}
MinCostFlow() {}
MinCostFlow(int n_) {
    init(n_);
}
void init(int n_) {
    n = n_;
    e.clear();
    g.assign(n, {});
}
void addEdge(int u, int v, T cap, T cost) {
    g[u].push_back(e.size());
    e.emplace_back(v, cap, cost);
    g[v].push_back(e.size());
    e.emplace_back(u, 0, -cost);
}
std::pair<T, T> flow(int s, int t) {
    T flow = 0;
    T cost = 0;
    h.assign(n, 0);
    while (dijkstra(s, t)) {
        for (int i = 0; i < n; ++i) {
            h[i] += dis[i];
        }
        T aug = std::numeric_limits<int>::max();
        for (int i = t; i != s; i = e[pre[i] ^ 1].to) {
            aug = std::min(aug, e[pre[i]].cap);
        }
        for (int i = t; i != s; i = e[pre[i] ^ 1].to) {
            e[pre[i]].cap -= aug;
            e[pre[i] ^ 1].cap += aug;
        }
        flow += aug;
        cost += aug * h[t];
    }
    return std::make_pair(flow, cost);
}
struct Edge {
    int from;
    int to;
    T cap;
    T cost;
    T flow;
};
std::vector<Edge> edges() {
    std::vector<Edge> a;
    for (int i = 0; i < e.size(); i += 2) {
        Edge x;
        x.from = e[i + 1].to;
        x.to = e[i].to;
        x.cap = e[i].cap + e[i + 1].cap;
        x.cost = e[i].cost;
        x.flow = e[i + 1].cap;
        a.push_back(x);
    }
}

```

```

    }
    return a;
}
};

```

2.7 Hld

```

struct hld {
    vector<vector<int>> g;
    vector<int> par, dpth, heavy, root, pos, subt, inv;
    vector<vector<int>> up;
    segtree seg;
    int cur_pos = 0;
    hld(int n){
        g.resize(n + 1), par.resize(n + 1), dpth.resize(n +
↳ 1);
        heavy.resize(n + 1, -1), root.resize(n + 1),
↳ pos.resize(n + 1), inv.resize(n + 1);
        subt.resize(n + 1, 1);
        up.resize(n + 1);
        for(int i = 0; i <= n; i++){
            up[i].resize(20, 0);
        }
        seg = segtree(n + 1);
        cur_pos = 0;
    }
    void add_edge(int u, int v){
        g[u].push_back(v);
        g[v].push_back(u);
    }
    void run(int rt){
        dfs_sz(rt, 0);
        dfs_hld(rt, rt);
    }
    int dfs_sz(int v, int p){
        int sz = 1, mx_sz = 0;
        par[v] = p;
        up[v][0] = p;
        for(int i = 1; i < 20; i++){
            up[v][i] = up[up[v][i - 1]][i - 1];
        }
        for(auto x : g[v]){
            if(x == p) continue;
            dpth[x] = dpth[v] + 1;
            int c_sz = dfs_sz(x, v);
            sz += c_sz;
            if(c_sz > mx_sz){
                mx_sz = c_sz;
                heavy[v] = x;
            }
        }
        return subt[v] = sz;
    }
    void dfs_hld(int v, int h){
        root[v] = h;
        pos[v] = cur_pos, inv[cur_pos] = v;
        cur_pos++;
        if(heavy[v] != -1) dfs_hld(heavy[v], h);
        for(auto x : g[v]){
            if(x == par[v] || x == heavy[v]) continue;
            dfs_hld(x, x);
        }
    }
    bool is_anc(int a, int b) {
        return pos[a] <= pos[b] && pos[b] < pos[a] + subt[a];
    }
    int kth(int v, int k) {
        for (int i = 0; i < 20; i++) {
            if (k & (1 << i)) {
                v = up[v][i];
            }
        }
        return v;
    }
    int hehe(int v, int u) {
        // u is ancestor of v
        int dif = dpth[v] - dpth[u] - 1;
    }
}

```

```

    return kth(v, dif);
}
mint qry(int a, int b) {
    mint res = 0;
    for (; root[a] != root[b]; b = par[root[b]]) {
        if (dpth[root[a]] > dpth[root[b]])
            swap(a, b);
        mint cur_heavy_path_max = seg.prod(pos[root[b]],
            ↪ pos[b] + 1).x;
        res += cur_heavy_path_max;
    }
    if (dpth[a] > dpth[b])
        swap(a, b);
    mint last_heavy_path_max = seg.prod(pos[a], pos[b] +
    ↪ 1).x;
    res += last_heavy_path_max;
    return res;
}
};

```

2.8 Euler

```

// Hierholzer's Algorithm undirected
// check remove the seen for directed
void dfs(int node) {
    while (!g[node].empty()) {
        auto [son, idx] = g[node].back();
        g[node].pop_back();
        if (seen[idx]) { continue; }
        seen[idx] = true;
        dfs(son);
    }
    path.push_back(node);
}
for (int node = 0; node < n; node++) {
    if (degree[node] % 2) {
        cout << "IMPOSSIBLE" << endl;
        return 0;
    }
}
dfs(0);
if (path.size() != m + 1) {
    cout << "IMPOSSIBLE";
}
}

```

2.9 Kosaraju

```

vector<int> g[n + 1], rg[n + 1];
for(auto [x, y, w] : eds){
    g[x].push_back(y);
    rg[y].push_back(x);
}
vector<int> order;
vector<int> vis(n + 1, -1);
function<void(int)> dfs = [&](int v){
    vis[v] = 1;
    for(auto x : g[v]){
        if(vis[x] == -1) dfs(x);
    }
    order.push_back(v);
};
for(int i = 1; i <= n; i++) if(vis[i] == -1) dfs(i);
reverse(al(order));
int idx = 1;
for(int i = 1; i <= n; i++) vis[i] = -1;
function<void(int, vector<int>&)> dfs2 = [&](int v,
    ↪ vector<int>& cmp){
    vis[v] = 1;
    for(auto x : rg[v]){
        if(vis[x] == -1) dfs2(x, cmp);
    }
    cmp.push_back(v);
};
vector<int> dag(n + 1, -1);
for(auto x : order){

```

```

    if(vis[x] == -1){
        vector<int> cmp;
        dfs2(x, cmp);
        for(auto y : cmp) dag[y] = idx;
        idx++;
    }
}
set<int> ng[idx], idg(idx, 0);
for(int i = 1; i <= n; i++){
    for(auto x : g[i]){
        if(dag[x] != dag[i]){
            ng[dag[i]].insert(dag[x]);
        }
    }
}
for(int i = 1; i < idx; i++){
    for(auto x : ng[i]) idg[x]++;
}
queue<int> q;
vector<int> dp(idx, 0);
for(int i = 1; i < idx; i++){
    if(idg[i] == 0){
        q.push(i);
        dp[i] = 1;
    }
}
while(!q.empty()){
    auto v = q.front(); q.pop();
    for(auto x : ng[v]){
        idg[x]--;
        dp[x] = max(dp[x], dp[v] + 1);
        if(!idg[x]) q.push(x);
    }
}
}

```

2.10 Tarjan

```

class TarjanSolver {
private:
    vector<vector<int>> rev_adj;
    vector<int> post;
    vector<int> comp;

    vector<bool> visited;
    int timer = 0;
    int id = 0;
    void fill_post(int at) {
        visited[at] = true;
        for (int n : rev_adj[at]) {
            if (!visited[n]) { fill_post(n); }
        }
        post[at] = timer++;
    }
    void find_comp(int at) {
        visited[at] = true;
        comp[at] = id;
        for (int n : adj[at]) {
            if (!visited[n]) { find_comp(n); }
        }
    }
public:
    const vector<vector<int>> &adj;
    TarjanSolver(const vector<vector<int>> &adj)
        : adj(adj), rev_adj(adj.size()), post(adj.size()),
        ↪ comp(adj.size()),
        visited(adj.size()) {
        vector<int> nodes(adj.size());
        for (int n = 0; n < adj.size(); n++) {
            nodes[n] = n;
            for (int next : adj[n]) { rev_adj[next].push_back(n); }
        }
        for (int n = 0; n < adj.size(); n++) {
            if (!visited[n]) { fill_post(n); }
        }
        std::sort(nodes.begin(), nodes.end(),

```



```

        [&](int n1, int n2) { return post[n1] > post[n2];
        ↪ });
visited.assign(adj.size(), false);
for (int n : nodes) {
    if (!visited[n]) {
        find_comp(n);
        id++;
    }
}
}
int comp_num() const { return id; }
int get_comp(int n) const { return comp[n]; }
};

void tarjan(int u) {
    dfn[u] = low[u] = ++ clk;
    s[++ p] = u;
    ins[u] = 1;
    for (int i = head[u] ; i ; i = rest[i]) {
        int v = to[i];
        if (wid[i] > mid) continue;
        if (!dfn[v]) {
            tarjan(v);
            low[u] = min(low[u], low[v]);
        } else if (ins[v]) {
            low[u] = min(low[u], dfn[v]);
        }
    }
    if (dfn[u] == low[u]) {
        ++ cnt;
        int v;
        do {
            ins[v = s[p --]] = 0;
            id[v] = cnt;
        } while (u != v);
    }
}
}

```

2.11 Bridges

```

// Bridges
vector<int> tin(n + 1, -1), low(n + 1, -1), vis(n + 1, 0);
int clk = 0;
vector<pair<int, int>> ans;
function<void(int, int)> dfs = [&](int v, int p){
    vis[v] = 1;
    tin[v] = low[v] = clk ++;
    for (auto x : g[v]){
        if (x == p) continue;
        if (!vis[x])
            dfs(x, v);
        low[v] = min(low[v], low[x]);
        if (low[x] > tin[v]){
            ans.push_back({v, x});
        }
    }
};

for (int i = 1; i <= n; i++){
    if (!vis[i]){
        dfs(i, -1);
    }
}

// Articulation Points
function<void(int, int)> dfs = [&](int v, int p){
    vis[v] = 1;
    tin[v] = low[v] = clk ++;
    int c = 0;
    for (auto x : g[v]){
        if (x == p) continue;
        if (vis[x]){
            low[v] = min(low[v], tin[x]);
        }
        else{
            dfs(x, v);
            low[v] = min(low[v], low[x]);
        }
    }
}

```

```

        if (low[x] >= tin[v] && p != -1){
            ans.insert(v);
        }
        c ++;
    }
}
if (c > 1 && p == -1){
    ans.insert(v);
}
};

for (int i = 1; i <= n; i++){
    if (!vis[i]){
        dfs(i, -1);
    }
}
}

```

2.12 Toposort

```

vector<int> topoSort(const vector<vector<int>>& gr) {
    vector<int> indeg(n), q;
    for (auto& li : gr) for (int x : li) indeg[x]++;
    rep(i, 0, n) if (indeg[i] == 0) q.push_back(i);
    rep(j, 0, sz(q)) for (int x : gr[q[j]])
        if (--indeg[x] == 0) q.push_back(x);
    return q;
}

```

2.13 Distances

```

// Bellman Ford
vector<int> d(n, INF);
d[v] = 0;
for (int i = 0; i < n - 1; ++i)
    for (Edge e : edges)
        if (d[e.a] < INF)
            d[e.b] = min(d[e.b], d[e.a] + e.cost);

// Dijkstra Algorithm
void dijkstra(int s, vector<int> & d, vector<int> & p) {
    int n = adj.size();
    d.assign(n, INF);
    p.assign(n, -1);

    d[s] = 0;
    using pii = pair<int, int>;
    priority_queue<pii, vector<pii>, greater<pii>> q;
    q.push({0, s});
    while (!q.empty()) {
        int v = q.top().second;
        int d_v = q.top().first;
        q.pop();
        if (d_v != d[v])
            continue;

        for (auto edge : adj[v]) {
            int to = edge.first;
            int len = edge.second;

            if (d[v] + len < d[to]) {
                d[to] = d[v] + len;
                p[to] = v;
                q.push({d[to], to});
            }
        }
    }
}

// Floyd Warshall
for (int k = 0; k < n; ++k) {
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j) {
            if (d[i][k] < INF && d[k][j] < INF)
                d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
        }
    }
}

```



```

    }
}
}

```

3 Misc

3.1 Dsu_dynconn

```

struct dsu_state{
    int v, u, rnk_v, rnk_u;
    dsu_state() {}
    dsu_state(int v, int u, int rnk_v, int rnk_u)
        : v(v), u(u), rnk_v(rnk_v), rnk_u(rnk_u) {}
};

struct dsuRoll{
    vector<int> par, rnk;
    stack<dsu_state> st;
    int comps;
    dsuRoll() {}
    dsuRoll(int n){
        par.resize(n + 1), rnk.resize(n + 1, 0);
        for(int i = 1; i <= n; i++){
            par[i] = i;
            rnk[i] = 0;
        }
        comps = n;
    }
    int find(int v){
        return (v == par[v]) ? v : find(par[v]);
    }
    bool unite(int x, int y){
        x = find(x), y = find(y);
        if(x == y) return false;
        if(rnk[x] > rnk[y]) swap(x, y);
        st.push(dsu_state(x, y, rnk[x], rnk[y]));
        par[x] = y;
        if(rnk[x] == rnk[y]) rnk[y]++;
        comps--;
        return true;
    }
    void rollback(){
        if(st.empty()) return;
        auto cur = st.top(); st.pop();
        comps++;
        par[cur.v] = cur.v;
        par[cur.u] = cur.u;
        rnk[cur.v] = cur.rnk_v;
        rnk[cur.u] = cur.rnk_u;
    }
};

struct qry{
    int v, u;
    bool f;
    qry() {}
    qry(int v, int u) : v(v), u(u) {}
};

struct dynCon{
    int n, sz;
    vector<vector<qry>> seg;
    dsuRoll dsu;
    dynCon(int _n, int _q) : n(_n), sz(_q) {
        dsu = dsuRoll(_n);
        seg.resize(4 * _q + 5);
    }
    void add(int idx, int st, int en, int ql, int qr, qry& q){
        if(st > qr || en < ql) return;
        if(st >= ql && en <= qr){
            seg[idx].push_back(q);
            return;
        }
        int md = (st + en) >> 1;
        add(idx << 1, st, md, ql, min(qr, md), q);
        add(idx << 1 | 1, md + 1, en, max(md + 1, ql), qr, q);
    }
};

```

```

void add(int l, int r, qry q){
    add(1, 0, sz, l, r, q);
}

void run(int v, int l, int r, vector<int>& ans){
    for(auto &q : seg[v]) q.f = dsu.unite(q.v, q.u);
    if(l == r) { /* do something */ }
    else{
        int md = (l + r) >> 1;
        run(v << 1, l, md, ans);
        run(v << 1 | 1, md + 1, r, ans);
    }
    for(auto &q : seg[v]) if(q.f) dsu.rollback();
}

vector<int> solve(){
    vector<int> ans(sz + 1);
    run(1, 0, sz, ans);
    return ans;
}

};

int n, q;
fscanf(in, "%d %d", &n, &q);
map<pair<int, int>, int> mp;
vector<int> ans(q + 1);
dynCon dc(n, q);
for(int i = 0; i < q; i++){
    char c; fscanf(in, "%c", &c);
    if(c == '?'){
        ans[i] = 1;
    }
    else{
        int v, u;
        fscanf(in, "%d %d", &v, &u);
        if(v > u) swap(v, u);
        if(c == '+'){
            mp[{v, u}] = i;
        }
        else{
            dc.add(mp[{v, u}], i - 1, qry(v, u));
            mp.erase({v, u});
        }
    }
}

for(auto [p, start] : mp){
    dc.add(start, q, qry(p.first, p.second));
}

auto f = dc.solve();

```

3.2 IntervalContainer

```

/* Description: Add and remove intervals from a set of disjoint
↪ intervals.
Will merge the added interval with any overlapping intervals in
↪ the set when
adding. Intervals are [inclusive, exclusive). */
set<pii>::iterator addInterval(set<pii>& is, int L, int R) {
    if (L == R) return is.end();
    auto it = is.lower_bound({L, R}), before = it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second);
        is.erase(it);
    }
    return is.insert(before, {L, R});
}

void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
}

```

```

    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}

```

3.3 2SAT_Shrey

```

struct two_sat
{
    int n;
    vector<vector<int>> g, gr; // gr is the
    ↪ reversed graph
    vector<int> comp, topological_order, answer; // comp[v]: ID
    ↪ of the SCC containing node v
    vector<bool> vis;

    two_sat() {}

    two_sat(int _n) { init(_n); }

    void init(int _n)
    {
        n = _n;
        g.assign(2 * n, vector<int>());
        gr.assign(2 * n, vector<int>());
        comp.resize(2 * n);
        vis.resize(2 * n);
        answer.resize(2 * n);
    }

    void add_edge(int u, int v)
    {
        g[u].push_back(v);
        gr[v].push_back(u);
    }

    // For the following three functions
    // int x, bool val: if 'val' is true, we take the variable
    ↪ to be x. Otherwise we take it to be x's complement.

    // At least one of them is true
    void add_clause_or(int i, bool f, int j, bool g)
    {
        add_edge(i + (f ? n : 0), j + (g ? 0 : n));
        add_edge(j + (g ? n : 0), i + (f ? 0 : n));
    }

    // Only one of them is true
    void add_clause_xor(int i, bool f, int j, bool g)
    {
        add_clause_or(i, f, j, g);
        add_clause_or(i, !f, j, !g);
    }

    // Both of them have the same value
    void add_clause_and(int i, bool f, int j, bool g)
    {
        add_clause_xor(i, !f, j, g);
    }

    // Topological sort
    void dfs(int u)
    {
        vis[u] = true;

        for (const auto &v : g[u])
            if (!vis[v])
                dfs(v);

        topological_order.push_back(u);
    }

    // Extracting strongly connected components
    void scc(int u, int id)
    {
        vis[u] = true;
        comp[u] = id;
    }
}

```

```

        for (const auto &v : gr[u])
            if (!vis[v])
                scc(v, id);
    }

    // Returns true if the given proposition is satisfiable and
    ↪ constructs a valid assignment
    bool satisfiable()
    {
        fill(vis.begin(), vis.end(), false);

        for (int i = 0; i < 2 * n; i++)
            if (!vis[i])
                dfs(i);

        fill(vis.begin(), vis.end(), false);
        reverse(topological_order.begin(),
            ↪ topological_order.end());

        int id = 0;
        for (const auto &v : topological_order)
            if (!vis[v])
                scc(v, id++);

        // Constructing the answer
        for (int i = 0; i < n; i++)
        {
            if (comp[i] == comp[i + n])
                return false;
            answer[i] = (comp[i] > comp[i + n] ? 1 : 0);
        }

        return true;
    }
};

```

3.4 BoilerPlate_Shrey

```

// Jaane wo kaise, log the jinke, pyaar ko pyaar milaaaaa
// Hamme to jab kaliyan maangi, kaaton ka haaar milaaaaa

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
typedef long long ll;
typedef long double ld;
using namespace std;
using namespace __gnu_pbds;
typedef tree<ll, null_type, less<ll>, rb_tree_tag,
    ↪ tree_order_statistics_node_update> indexed_set;
typedef tree<ll, null_type, less_equal<ll>, rb_tree_tag,
    ↪ tree_order_statistics_node_update> indexed_multiset;
#pragma GCC optimize("O3")
#pragma GCC target("avx2,bmi,bmi2,popcnt,lzcnt")
mt19937
    ↪ rng(chrono::steady_clock::now().time_since_epoch().count());

void __print(int x) {cerr << x;}
void __print(long x) {cerr << x;}
void __print(long long x) {cerr << x;}
void __print(unsigned x) {cerr << x;}
void __print(unsigned long x) {cerr << x;}
void __print(unsigned long long x) {cerr << x;}
void __print(float x) {cerr << x;}
void __print(double x) {cerr << x;}
void __print(long double x) {cerr << x;}
void __print(char x) {cerr << '\'' << x << '\'';}
void __print(const char *x) {cerr << '\"' << x << '\"';}
void __print(const string &x) {cerr << '\"' << x << '\"';}
void __print(bool x) {cerr << (x ? "true" : "false");}

template<typename T, typename V>
void __print(const pair<T, V> &x) {cerr << '{';
    ↪ __print(x.first); cerr << ','; __print(x.second); cerr <<
    ↪ '}';}
template<typename T>

```

```

    }
    x *= x;
    x %= p;
    y >>= 1;
}
return res;
}

const int NUM = 1e6 + 7;
const ll INF = 1e18 + 5;
vp moves = {{0, 1}, {1, 0}, {-1, 0}, {0, -1}};

void solve()
{
}

// clear all data structures between test cases
// handle all corner cases
// confusing between n and m , i and j?
// uninitialized variables?

int main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);
    // freopen("input.txt", "r", stdin);
    // freopen("output.txt", "w", stdout);
    // memset(dp, -1, sizeof(dp));
    ll t = 1;
    cin >> t;
    while (t--)
    {
        solve();
    }
    return 0;
}

```

```
// ans[i] = j means ith worker is assigned jth task
// O(n^3) time complexity
// It finds the assignment where the sum of costs is the lowest
// possible value.

void hungarian(vector<vector<long double>> &a, vll &ans)
{
    ll n = a.size();
    vector<ld> u(n + 1, 0), v(n + 1, 0);
    vll p(n + 1, 0), way(n + 1, 0);

    for (ll i = 1; i <= n; ++i)
    {
        vector<ld> minv(n + 1, INF);
        vector<bool> used(n + 1, false);
        ll j0 = 0;
        p[0] = i;
        do
        {
            used[j0] = true;
            ll i0 = p[j0], j1;
            long double delta = LDBL_MAX;
            for (ll j = 1; j <= n; ++j)
            {
                if (!used[j])
                {
                    long double cur = a[i0 - 1][j - 1] - u[i0]
                    ↪ - v[j];
                    if (cur < minv[j])
                    {
                        minv[j] = cur;
                        way[j] = j0;
                    }
                    if (minv[j] < delta)
                    {
                        delta = minv[j];
                        j1 = j;
                    }
                }
            }
        }
    }
}
```

```

    }
}
for (ll j = 0; j <= n; ++j)
{
    if (used[j])
    {
        u[p[j]] += delta;
        v[j] -= delta;
    }
    else
    {
        minv[j] -= delta;
    }
}
j0 = j1;
} while (p[j0] != 0);
do
{
    ll j1 = way[j0];
    p[j0] = p[j1];
    j0 = j1;
} while (j0);

for (ll j = 1; j <= n; ++j)
{
    ans[p[j] - 1] = j - 1;
}
}

```

3.6 MEX_DS

```

template <class T>
int calcMex(vector<T> v)
{
    sort(v.begin(), v.end());
    v.erase(unique(v.begin(), v.end()), v.end());
    int n = int(v.size());
    for (int i = 0; i < n; ++i)
        if (v[i] != i)
            return i;
    return n;
}

//

class Mex {
private:
    map<int, int> frequency;
    set<int> missing_numbers;
    vector<int> A;

public:
    Mex(vector<int> const& A) : A(A) {
        for (int i = 0; i <= A.size(); i++)
            missing_numbers.insert(i);

        for (int x : A) {
            ++frequency[x];
            missing_numbers.erase(x);
        }
    }

    int mex() {
        return *missing_numbers.begin();
    }

    void update(int idx, int new_value) {
        if (--frequency[A[idx]] == 0)
            missing_numbers.insert(A[idx]);
        A[idx] = new_value;
        ++frequency[new_value];
        missing_numbers.erase(new_value);
    }
};

```

3.7 VeniceSet

```

// This can be applied to all Data Structures that support (add,
// remove and query) and only need the operation (updateAll).

class VeniceSet
{
public:
    multiset<ll> ice;
    ll level = 0;
    void add(ll x)
    {
        ice.insert(x + level);
    }
    void remove(ll x)
    {
        ice.erase(ice.find(x + level));
    }
    void decrement_all(ll x) // update all
    {
        level += x;
    }
    ll get_min() // query
    {
        return *ice.begin() - level;
    }
    ll get_size()
    {
        return ice.size();
    }
};

```

3.8 OrderedSet

```

// Remember to change define int long long
#include "ext/pb_ds/assoc_container.hpp"
#include "ext/pb_ds/tree_policy.hpp"
using namespace __gnu_pbds;
template<class T>
using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
// tree_order_statistics_node_update>;
template<class key, class value, class cmp = std::less<key>>
using ordered_map = tree<key, value, cmp, rb_tree_tag,
// tree_order_statistics_node_update>;
// find_by_order(k) returns iterator to kth element starting
// from 0;
// order_of_key(k) returns count of elements strictly smaller
// than k;
template<class T>
using min_heap = priority_queue<T, vector<T>, greater<T>>;

```

3.9 Twosat

```

struct twoSAT{
    int n, m;
    vector<vector<int>> adj, adjT;
    vector<int> val, order, comp, vis;
    twoSAT(int n) : n(n), m(2 * n), adj(2 * n), adjT(2 * n),
    // val(n), comp(2 * n, -1), vis(2 * n) {
        order.reserve(2 * n);
    }
    void dfs1(int v){
        vis[v] = 1;
        for(auto u : adj[v]){
            if(!vis[u]) dfs1(u);
        }
        order.push_back(v);
    }
    void dfs2(int v, int cl){
        comp[v] = cl;
        for(auto u : adjT[v]){
            if(comp[u] == -1) dfs2(u, cl);
        }
    }
    void add_f(int a, bool na, int b, bool nb){

```

```

    a = (2 * a) ^ na;
    b = (2 * b) ^ nb;
    adj[a ^ 1].push_back(b);
    adj[b ^ 1].push_back(a);
    adjT[b].push_back(a ^ 1);
    adjT[a].push_back(b ^ 1);
}
bool solver(){
    order.clear();
    fill(vis.begin(), vis.end(), 0);
    for(int i = 0; i < m; i++){
        if(!vis[i]) dfs1(i);
    }
    comp.assign(m, -1);
    for(int i = 0, j = 0; i < m; i++){
        int v = order[m - i - 1];
        if(comp[v] == -1) dfs2(v, j++);
    }
    val.assign(n, 0);
    for(int i = 0; i < m; i += 2){
        if(comp[i] == comp[i + 1]) return false;
        val[i >> 1] = comp[i] > comp[i + 1];
    }
    return true;
}
};

```

3.10 Fast

```

namespace fast {
    char B[1 << 18], *S = B,*T = B;
    #define getc() (S == T && (T = (S = B) + fread(B, 1, 1 <<
    ↪ 18, stdin), S == T) ? 0 : *S++)
    long long read() {
        long long ret = 0; char c;
        int f = 0;
        while (c = getc(), (c != '-') && (c < '0' || c > '9'));
        for (; (c >= '0' && c <= '9') || c == '-'; c = getc()){
            if(c == '-') f = 1;
            else ret = ret * 10 + c - '0';
        }
        return f ? -ret : ret;
    }
}

```

3.11 Template

```

#include<bits/stdc++.h>
#ifdef ONLINE_JUDGE
#include "template.cpp"
#else
#define dbg(...) ;
#define debugArr(...) ;
#endif
using namespace std;
#define int long long
#define endl "\n"
#define al(v) v.begin(), v.end()
#define set_bits __builtin_popcountll
const int N = 1e9 + 7;
//const int N = 998244353;
const int inf = 0x3f3f3f3f3f3f3f3f;
const int MAXN = 2e5 + 7;
mt19937_64 rng(chrono::steady_clock::now()
    ↪ .time_since_epoch().count());
void solve(){
}
int t = 1;
int32_t main(){
    ios::sync_with_stdio(0);
    cin.tie(0);
    int t; cin>>t;
    while(t--){
        solve();
    }
}

```

```

}
#pragma GCC optimize ("Ofast")
#pragma GCC target ("avx2")

```

3.12 Basis

```

struct basis{
    array<int, 20> b;
    int sz = 0;
    basis(){
        b.fill(0);
        sz = 0;
    }
    void insert(int x){
        for(int i = 19; i >= 0; i --){
            if((x >> i) & 1){
                if(!b[i]){
                    b[i] = x;
                    sz ++;
                    return;
                }
                x ^= b[i];
            }
        }
    }
    bool query(int x){
        for(int i = 19; i >= 0; i --){
            if(x == 0) return true;
            if((x >> i) & 1){
                if(!b[i]) return false;
                x ^= b[i];
            }
        }
        return x == 0;
    }
}
};

```

3.13 ConvexHullTrick

```

template<class T>
using min_heap = priority_queue<T,vector<T>,greater<T>>;
// When lines are added in increasing order of slopes
// Queries minimum
struct CHT {
    struct Line {
        int m, c;
        Line () {}
        Line (int _m, int _c) : m(_m), c(_c) {}

        double intersect(const Line &other) const {
            return (double)(other.c - c) / (m - other.m);
        }

        int operator()(int x) const {
            return m * x + c;
        }
    };
    vector<double> points;
    vector<Line> lines;
    void init(Line l){
        points.push_back(-inf);
        lines.push_back(l);
    }
    void add_line(Line l){
        while(lines.size() >= 2 &&
            ↪ l.intersect(lines[lines.size() - 2]) <=
            ↪ points.back()){
            points.pop_back();
            lines.pop_back();
        }
        if(!lines.empty()){
            points.push_back(l.intersect( lines.back()));
        }
        if(!lines.empty() && lines.back().m == l.m){
            if(lines.back().c >= l.c) return;
        }
    }
}

```

```

        lines.pop_back();
        points.pop_back();
    }
    lines.push_back(1);
}
int query(int x){
    int idx = upper_bound(al(points), x) - points.begin() -
    ↪ 1;
    return lines[idx](x);
}
};
void solve(){
    int n, c; cin>>n>>c;
    vector<int> a(n + 1), dp(n + 1);
    for(int i = 1; i <= n; i++){
        cin>>a[i];
    }

    CHT cht;
    cht.init(CHT::Line(-2 * a[1], a[1] * a[1]));
    for(int i = 2; i <= n; i++){
        dp[i] = cht.query(a[i]) + a[i] * a[i] + c;
        cht.add_line(CHT::Line(-2 * a[i], dp[i] + a[i] *
        ↪ a[i]));
    }
    cout<<dp[n]<<endl;
}

// Anyhow works, Queries Maximum
struct Line {
    mutable int k, m, p;
    bool operator<(const Line& o) const { return k < o.k; }
    bool operator<(int x) const { return p < x; }
};

struct CHT : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    int div(int a, int b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;
        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
        else x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(int k, int m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y =
        ↪ erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    int query(int x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};

```

4 Strings

4.1 Hash

```

void go_hsh(string s){
    hsh[0] = s[0];
    ppow[0] = 1;
    for(int i = 1; i < s.size(); i++){
        hsh[i] = (((hsh[i - 1] * p) % mod) + s[i]) % mod;
        ppow[i] = (ppow[i - 1] * p) % mod;
    }
}
int get(int l, int r){
    if(!l) return hsh[r];
    return (hsh[r] - (hsh[l - 1] * ppow[r - l + 1]) % mod +
    ↪ mod) % mod;
}

```

```

}

```

4.2 Manacher

```

// Finds all palindromic substrings in O(n) time
// Returns a vector where the ith element represents the length
↪ of the longest palindromic substring
// centered at index i (for odd-length palindromes) or between
↪ indices i and i+1 (for even-length palindromes)
vector<int> manacher_odd(string s){
    int n = s.size();
    s = ('$' + s + '^');
    vector<int> ans(n + 2);
    int l = 1, r = 1;
    for(int i = 1; i <= n; i++){
        ans[i] = max(OLL, min(r - i, ans[l + (r - i)]));
        while(s[i + ans[i]] == s[i - ans[i]]){
            ans[i]++;
        }
        if(i + ans[i] > r){
            l = i - ans[i];
            r = i + ans[i];
        }
    }
    vector<int> res;
    // we get answer as
    // even lengthed palindrome between i & i+1 as
    ↪ (ans[i+1]-1)/2
    // odd centered at i as ans[i]/2
    return vector<int>(ans.begin()+1, ans.end()-1);
}

vector<int> manacher(string s){
    string t = "";
    for(auto x : s){
        t += "#";
    }
    t += "#";
    // cout<<t<<endl;
    auto res = manacher_odd(t);
    return vector<int>(res.begin() + 1, res.end() - 1);
}

Manacher.h
Description: For each position in a string, computes p[0][i] =
↪ half length
of longest even palindrome around pos i, p[1][i] = longest odd
↪ (half rounded
down).
Time: O (N)
e7ad79, 13 lines
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi, 2> p = {vi(n+1), vi(n)};
    rep(z, 0, 2) for (int i=0, l=0, r=0; i < n; i++) {
        int t = r-i+!z;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
        int L = i-p[z][i], R = i+p[z][i]-!z;
        while (L>=1 && R+1<n && s[L-1] == s[R+1])
            p[z][i]++, L--, R++;
        if (R>r) l=L, r=R;
    }
    return p;
}

```

4.3 SuffixArray

```

struct SuffixArray {
    vector<int> sa, lcp;

    // Append 0 to s in case s is a vector
    SuffixArray(string &s, int lim = 256){
        int n = s.size() + 1, k = 0, a, b;
        vector<int> x(n), y(n), ws(max(n, lim)), rank(n);
        for(int i = 0; i < n - 1; i++) x[i] = s[i];
    }
}

```

```

sa = lcp = y, iota(sa.begin(), sa.end(), 0);
for(int j = 0, p = 0; p < n; j = max(1LL, j * 2), lim =
↪ p){
    p = j, iota(y.begin(), y.end(), n - j);
    for(int i = 0; i < n; i++) if (sa[i] >= j) y[p++]
↪ = sa[i] - j;
    fill(ws.begin(), ws.end(), 0);
    for(int i = 0; i < n; i++) ws[x[i]]++;
    for(int i = 1; i < lim; i++) ws[i] += ws[i - 1];
    for(int i = n; i --;) sa[--ws[x[y[i]]]] = y[i];
    swap(x, y), p = 1, x[sa[0]] = 0;
    for(int i = 1; i < n; i++) a = sa[i - 1], b =
↪ sa[i], x[b] =
        (y[a] == y[b] && y[a + j] == y[b + j])
↪ ? p - 1 : p++;
}
for(int i = 1; i < n; i++) rank[sa[i]] = i;
for(int i = 0, j; i < n - 1; lcp[rank[i++]] = k) {
    for(k && k--, j = sa[rank[i] - 1]; s[i + k] == s[j]
↪ + k);
    k++;
}
}
};

```

4.4 Trie

```

const int MAXB = 30;
struct node{
    int cnt;
    int t[2];
    set<int> id;
    node (){
        cnt = 0;
        t[0] = t[1] = -1;
    }
};
struct btrie{
    vector<node> trie;
    btrie() {
        trie.resize(1);
    }
    int new_node(){
        trie.push_back(node());
        return (int)trie.size() - 1;
    }
    void insert(int x, int id){
        int cur = 0;
        trie[cur].cnt++;
        for(int i = MAXB; i >= 0; i --){
            int b = (x >> i) & 1;
            if(trie[cur].t[b] == -1){
                trie[cur].t[b] = new_node();
            }
            cur = trie[cur].t[b];
            trie[cur].cnt++;
        }
        trie[cur].id.insert(id);
    }
    void remove(int x, int id){
        int cur = 0;
        trie[cur].cnt--;
        for(int i = MAXB; i >= 0; i --){
            int b = (x >> i) & 1;
            cur = trie[cur].t[b];
            trie[cur].cnt--;
        }
        assert(trie[cur].id.count(id));
        trie[cur].id.erase(id);
    }
    pair<int, int> min_xor(int x){
        int cur = 0, res = 0, idx = -1;
        for(int i = MAXB; i >= 0; i --){
            int b = ((x >> i) & 1);
            if(trie[cur].t[b] != -1 &&
↪ trie[trie[cur].t[b]].cnt > 0){
                cur = trie[cur].t[b];

```

```

        }
        else{
            res |= (1LL << i);
            cur = trie[cur].t[b ^ 1];
            if(cur == -1) return {res, -1};
        }
    }
    assert(!trie[cur].id.empty());
    idx = *trie[cur].id.begin();
    return {res, idx};
}
};
auto get = [&](int x){
    // I need y such that x ^ y is maximum;
    // if x has 0 then find 1 then 0;
    // if x has 1 then find 0 then 1;
    int curr = 0;
    int ans = 0;
    for(int i = 29; i >= 0; i --){
        int bit = (x >> i) & 1;
        if(bit){
            if(trie[curr][0]){
                ans += (1 << i);
                curr = trie[curr][0];
            } else {
                curr = trie[curr][1];
            }
        } else {
            if(trie[curr][1]){
                ans += (1 << i);
                curr = trie[curr][1];
            } else {
                curr = trie[curr][0];
            }
        }
    }
    return ans;
};

```

4.5 Kmp

```

// p[i] = length of the longest proper prefix of s[0..i]
// which is also a suffix of s[0..i]
vector<int> prefix_function(string s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}

```

5 Mathematics

5.1 Sieve

```

int low[MAXN]; // smallest prime factor
int phi[MAXN]; // Euler Totient Function
int mu[MAXN]; // Mobius function
vector<int> primes;
void sieve() {
    for (int i = 1; i < MAXN; i++) {
        phi[i] = i;
        mu[i] = 1;
    }
    for (int i = 2; i < MAXN; i++) {
        if (low[i] == 0) { // i is prime

```



```

primes.push_back(i);
phi[i] = i - 1;
mu[i] = -1;

for (int j = i; j < MAXN; j += i) {
    if (low[j] == 0) low[j] = i;
    phi[j] -= phi[j] / i;
    if ((j / i) % i == 0)
        mu[j] = 0;
    else
        mu[j] *= -1;
}
}
}
}

```

5.2 SOSDp

```

int dpOr[MAXN], dpAnd[MAXN], A[MAXN];
for(int i = 0; i < n; i++){
    dpOr[A[i]] ++, dpAnd[A[i]] ++;
}
for(int bit = 0; bit < 20; bit++){
    for(int msk = 0; msk < MAXN; msk++){
        if((msk >> bit) & 1){
            dpOr[msk] += dpOr[msk ^ (1 << bit)];
        }
        else{
            dpAnd[msk] += dpAnd[msk | (1 << bit)];
        }
    }
}
}

```

5.3 Bits

```

mask &= ~(1LL << i); // Clear i-th bit
mask &= (mask - 1); // Turn off lowest set bit
bool is_pow2 = (mask > 0 && (mask & (mask - 1)) == 0); // Is
↳ power of two
int leading_zeros = __builtin_clzll(mask); // Count leading
↳ zeros
int trailing_zeros = __builtin_ctzll(mask); // Count trailing
↳ zeros
int lsb = mask & (-mask); // Isolate least significant bit
mask &= (mask - 1); // Turn off least significant bit

// Iterate over all subsets of a bitmask
for(int sub = mask; sub; sub = (sub - 1) & mask){
    // sub is a non-empty subset
}

```

5.4 Euler_Totient

```

int phi(int n) { // O(sqrt(n))
    int result = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            result -= result / i;
        }
    }
    if (n > 1)
        result -= result / n;
    return result;
}

void phi_1_to_n(int n) { // O(n log log n)
    vector<int> phi(n + 1);
    for (int i = 0; i <= n; i++)
        phi[i] = i;

    for (int i = 2; i <= n; i++) {

```

```

        if (phi[i] == i) {
            for (int j = i; j <= n; j += i)
                phi[j] -= phi[j] / i;
        }
    }
}

```

5.5 Comb_mint

```

struct mint {
    int val;
    mint(long long v = 0) {
        if (v < 0) {
            v = v % N + N;
        }
        if (v >= N) {
            v %= N;
        }
        val = v;
    }
    static int mod_inv(int a, int m = N) {
        int g = m, r = a, x = 0, y = 1;
        while (r != 0) {
            int q = g / r;
            g %= r; swap(g, r);
            x -= q * y; swap(x, y);
        }
        return x < 0 ? x + m : x;
    }
    explicit operator int() const {
        return val;
    }
    mint& operator+=(const mint &other) {
        val += other.val;
        if (val >= N) val -= N;
        return *this;
    }
    mint& operator-=(const mint &other) {
        val -= other.val;
        if (val < 0) val += N;
        return *this;
    }
    typedef unsigned long long ull;
    ull fast_N(ull a, ull b, ull M = N) {
        long long ret = a * b - M * ull(1.L / M * a * b);
        return ret + M * (ret < 0) - M * (ret >= (long long)M);
    }
    mint& operator*=(const mint &other) {
        val = fast_N((ull) val, other.val);
        return *this;
    }
    mint& operator/=(const mint &other) {
        return *this *= other.inv();
    }
    friend mint operator+(const mint &a, const mint &b) {
        ↳ return mint(a) += b;
    }
    friend mint operator-(const mint &a, const mint &b) {
        ↳ return mint(a) -= b;
    }
    friend mint operator*(const mint &a, const mint &b) {
        ↳ return mint(a) *= b;
    }
    friend mint operator/(const mint &a, const mint &b) {
        ↳ return mint(a) /= b;
    }
    mint& operator++() {
        val = val == N - 1 ? 0 : val + 1;
        return *this;
    }
    mint& operator--() {
        val = val == 0 ? N - 1 : val - 1;
        return *this;
    }
    mint operator++(int32_t) { mint before = *this; ++*this;
        ↳ return before;
    }
    mint operator--(int32_t) { mint before = *this; --*this;
        ↳ return before;
    }
    mint operator-() const {
        return val == 0 ? 0 : N - val;
    }
}

```

```

bool operator==(const mint &other) const { return val ==
    ⇨ other.val; }
bool operator!=(const mint &other) const { return val !=
    ⇨ other.val; }
mint inv() const {
    return mod_inv(val);
}
mint pow(long long p) const {
    assert(p >= 0);
    mint a = *this, result = 1;

    while (p > 0) {
        if (p & 1)
            result *= a;

        a *= a;
        p >>= 1;
    }
    return result;
}
friend ostream& operator<<(ostream &stream, const mint &m)
    ⇨ {
    return stream << m.val;
}
friend istream& operator >> (istream &stream, mint &m) {
    return stream >> m.val;
}
};
template<typename T, const int P>
class comb {
public:
    int n;
    vector<T> fac, ifac, inv, pow;
    comb(int n) : n(n), fac(n), ifac(n), inv(n), pow(n) {
        fac[0] = ifac[0] = inv[0] = pow[0] = T(1);
        for(int i = 1; i <= n; i++){
            inv[i] = T(1) / T(i);
            fac[i] = fac[i - 1] * T(i);
            ifac[i] = ifac[i - 1] * inv[i];
            pow[i] = pow[i - 1] * T(P);
        }
    }

    T ncr(int n, int r){
        if(n < r) return T(0);
        if(n < 0 || r < 0) return T(0);
        return fac[n] * ifac[r] * ifac[n - r];
    }
};
comb<mint, 2> com(MAXN);

```

5.6 NCr_Shrey

```

const ll MAXN = 1e7;
const ll MOD = 1e9 + 7;

vector<ll> fac(MAXN + 1);
vector<ll> inv(MAXN + 1);

/** Computes x^y modulo p in O(log p) time. */
ll exp(ll x, ll y, ll p)
{
    ll res = 1;
    x %= p;
    while (y)
    {
        if (y & 1)
        {
            res *= x;
            res %= p;
        }
        x *= x;
        x %= p;
        y >>= 1;
    }
    return res;
}

```

```

void factorial() {
    fac[0] = 1;
    for (ll i = 1; i <= MAXN; i++) {
        fac[i] = ( fac[i - 1] * i ) % MOD;
    }
}

void inverses() {
    inv[MAXN] = exp(fac[MAXN], MOD - 2, MOD);
    for (ll i = MAXN; i >= 1; i--) {
        inv[i - 1] = (inv[i] * i) % MOD;
    }
}

ll choose(int n, int r) {
    return fac[n] * inv[r] % MOD * inv[n - r] % MOD;
}

```

5.7 Matrix

```

template<typename T>
struct Matrix{
    vector<vector<T>> mat;
    int n, m;
    Matrix() {}
    Matrix(int _n, int _m, bool ident = false) {
        n = _n; m = _m;
        mat.assign(n, vector<T>(m, 0));
        if (ident) {
            for (int i = 0; i < n; i++)
                mat[i][i] = 1;
        }
    }
    Matrix(const vector<vector<T>> &v) {
        n = v.size();
        m = v[0].size();
        mat = v;
    }
    Matrix operator*(const Matrix &b) const {
        Matrix res(n, b.m);
        for (int i = 0; i < n; i++) {
            for (int k = 0; k < m; k++) {
                if (mat[i][k].val == 0) continue;
                for (int j = 0; j < b.m; j++) {
                    res.mat[i][j] += mat[i][k] * b.mat[k][j];
                }
            }
        }
        return res;
    }
};

template<typename T>
Matrix<T> mat_pow(Matrix<T> a, long long p) {
    Matrix<T> res(a.n, a.n, true);
    while (p) {
        if (p & 1) res = res * a;
        a = a * a;
        p >>= 1;
    }
    return res;
}

```

5.8 Extended_GCD

```

ll extended_gcd(ll a, ll b, ll &x, ll &y)
{
    if (b == 0)
    {
        x = 1;
        y = 0;
        return a;
    }
    ll x1, y1;
    ll d = extended_gcd(b, a % b, x1, y1);

```

```

x = y1;
y = x1 - y1 * (a / b);
return d;
}

```

5.9 Segmented Sieve

```

// 1. Standard Sieve to generate primes up to sqrt(MaxR)
// MaxR = 10^12 usually, so limit = 10^6
void simpleSieve(int limit, vector<int> &primes)
{
    vector<bool> is_prime(limit + 1, true);
    is_prime[0] = is_prime[1] = false;

    for (int p = 2; p * p <= limit; p++)
    {
        if (is_prime[p])
        {
            for (int i = p * p; i <= limit; i += p)
                is_prime[i] = false;
        }
    }

    for (int p = 2; p <= limit; p++)
    {
        if (is_prime[p])
        {
            primes.push_back(p);
        }
    }
}

// 2. Segmented Sieve for range [L, R]
vector<long long> segmentedSieve(long long L, long long R)
{
    // A. Generate small primes up to sqrt(R)
    int lim = sqrt(R);
    vector<int> small_primes;
    simpleSieve(lim, small_primes);

    // B. Create a boolean array for the range [L, R]
    // is_prime[i] corresponds to number (L + i)
    vector<bool> is_prime(R - L + 1, true);

    // C. Mark multiples of small primes
    for (int p : small_primes)
    {
        // Find the first multiple of p that is >= L
        // Formula: (L + p - 1) / p * p gives ceil(L/p) * p
        long long start = (L + p - 1) / p * p;

        // Corner case: If start is the prime itself, move to
        // next multiple
        // (We don't want to mark the prime itself as
        // composite)
        if (start == p)
            start += p;

        // Mark all multiples in range
        // Index conversion: number x maps to index (x - L)
        for (long long i = start; i <= R; i += p)
        {
            // Check bounds just in case (start could be > R if
            // p > R)
            if (i >= L)
            {
                is_prime[i - L] = false;
            }
        }
    }
}

```

```

}

// D. Collect primes
vector<long long> primes;
for (long long i = 0; i <= R - L; i++)
{
    if (is_prime[i])
    {
        long long num = L + i;
        if (num > 1)
        { // 1 is not prime
            primes.push_back(num);
        }
    }
}

return primes;
}

```

5.10 Miller Rabin

```

using u64 = uint64_t;
using u128 = __uint128_t;

u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1;
    base %= mod;
    while (e) {
        if (e & 1)
            result = (u128)result * base % mod;
        base = (u128)base * base % mod;
        e >>= 1;
    }
    return result;
}

bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1)
        return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
        if (x == n - 1)
            return false;
    }
    return true;
};

bool MillerRabin(u64 n) { // returns true if n is prime, else
    ↪ returns false.
    if (n < 2)
        return false;

    int r = 0;
    u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1;
        r++;
    }

    for (int a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37})
    {
        if (n == a)
            return true;
        if (check_composite(n, a, d, r))
            return false;
    }
    return true;
}

```